

## Crimping Press TH 8E-530, TH 8E-535-BM

- Strong crimping machine for all Parker *No-Skive* hose up to size-32
- Easy installation on the workbench in the workshop area or in the van
- For die sets series 239L and 266 (adapter die set PB266.239L required)

### Primary Applications

Hose assembly workshops with small series production and services at certified distributors, ParkerStores and hose workshops in the maintenance areas at OEM customers



### Restrictions

Not for ParLock hose assemblies in size -20, -24 and -32 (fittings series V4 and V6).

#### All TH 8E-530 and TH 8E-535 with

- adapter die set PB266.239L
- die set packet (14 mm – 74 mm) PBSET-TH8E-53X
- quick change tool QDC239.3

#### TH 8E-530

Crimp force	200 t
Crimp range	94 mm
Noise level	69 dBA
Colour	black/silver

Electrical power	400 V / 50 Hz / 3 PH / 4 kW
Control system	micrometer
Dimensions	L 700 x W 600 x H 735 mm
Oil quantity	50 l
Weight	248 kg

**Part Number TH8E-530**

#### TH 8E-530-BM

Electrical power	400 V / 50 Hz / 3 PH / 4 kW
Control system	B-Touch
Dimensions	L 700 x W 600 x H 735 mm
Oil quantity	50 l
Weight	255 kg

**Part Number TH8E-530-BM**

#### TH 8E-530-12VDC

Electrical power	12 V DC
Control system	micrometer

**Part Number TH8E-530-12VDC**

#### TH 8E-535-BM

Electrical power	400 V / 50 Hz / 3 PH / 5.5 kW
Control system	B-Touch
Dimensions	L 690 x W 600 x H 1053 mm
Oil quantity	55 l
Weight	375 kg

**Part Number TH8E-535-BM**

#### Adapter die set

**Part Number PB266.239L**

#### Die rack

**Part Number QDS239S**

#### Die set packet, diameter from 14 – 74 mm

**Part Number PBSET-TH8E-53X**

#### Quick change tool

**Part Number QDC239.3**