




Parker Legris: Connection Solutions for Industrial Fluids

aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



ENGINEERING YOUR SUCCESS.



Serving as a true shop window for Parker Legris' knowledge and expertise, this new catalogue strives to provide the day-to-day support you need when designing your industrial equipment.

This new edition has been written in an informative style and describes our entire range of products and services. We have developed the content, structure and layout to enable you to find the products and information you require as quickly as possible.

Many new products have been introduced, widening the choice of solutions available in order to meet your requirements more effectively.

For advice or more information, please do not hesitate to contact us. Visit our web site today: www.parkerlegris.com.



A Century of Dedication and Enthusiasm...

Inventor of the push-in fitting, Legris joined the Parker Hannifin Corporation, world leader in motion and control technologies, in October 2008.

3 Industrial Activities

Optimising the transport and control of many fluids (compressed air, liquids, gas) through innovative product design has been the motto of our teams for more than 100 years.

Today, Parker Legris' expertise is divided into three business activities:

Legris Connectic: fittings, couplers, function fittings, valves, tubing and accessories for industrial applications.

Legris Transair: air and fluid distribution systems for industrial buildings.


Legris Autoline: push-in connection solutions for automobile fuel lines.

150 Years of History

Our experience and expertise in the design, manufacturing and marketing of high-quality connectors allow us to provide our customers with solutions adapted to a variety of applications.

- 1848** Legris, a small valve manufacturer in France
- 1969** Invention of LF 3000®, the first push-in fitting for compressed air
- 1988** Legris becomes a division of the Legris Industries Group

- 1996** Launch of Transair®
- 1997** Launch of Autoline
- 2008** Acquisition of Legris by the Parker Hannifin Corporation
- 2009** Legris becomes Parker Legris, a division of the Parker group



...Supporting Industrial Connectivity

Parker Legris Sites

Parker Legris has 9 locations distributed across Europe.

France: Annemasse, Baillé, Guer, Guichen, Malestroit, Muzillac, Rennes

Belgium: Herstal

Spain: Terrassa

Industrial Applications

Our products are used everywhere fluid control is required.

Our knowledge and expertise are deployed in a variety of sectors: production automation, packaging, transport, food process, and the medical industry.

Parker Legris is also involved in innovative sectors such as renewable energy, information and communication technologies.


Our Distribution Network

We encourage local support and long-term partnerships with our customers.

Through our many sales outlets, professionals are on hand to provide you with technical advice and to offer you a wide choice of products local to your sites.

Do not hesitate to contact them for further information and advice.

1940



2012



Your Applications Inspire Our Innovation

Innovation is Parker-Legris' number one priority in order to provide solutions that meet your technological, energy reduction and environmental challenges.

Our expertise is continually improving

We continually invest in our tools in order to anticipate market requirements in terms of industrial efficiency. Furthermore, our long-term partnerships with the most qualified organisations (universities, skills hubs, etc.) enable us to incorporate the latest technological advances in our product development. Lastly, constantly incorporating your needs into the design of our products keeps us at the forefront of the new industrial challenges.

Together, we can build advanced and unique connector solutions

Here are a few examples:

To increase the efficiency of your systems

The new LIQUIfit+, with its ecological design, combines full flow and quick connection to stainless steel tubes without grooving. This range guarantees the quality and non-contamination of the fluids conveyed, plus reduced operating costs.

To prolong the life of your equipment

Developed for railway applications and demanding industrial markets, our new high strength flame-resistant tubing combines unequalled flame resistance with very high mechanical strength and ease of installation.

To limit energy costs

The new range of energy-saving blowguns allows you to reduce the air flow, thus limiting its energy consumption while maintaining blowing efficiency.

This catalogue also contains details of our latest products:

LF 3000® 16 mm, LIQUIfit®, PFA tubing, piloted non-return valve, adjustable non-return valve, blowgun kits and many other components.



Quality and Safety, the Basis of Our Commitment

Our target is to provide our customers with the best solution and the highest quality. Certified ISO/TS 16949, Parker Legris includes customer quality at the heart of its processes.

Invest in quality for increased productivity

The cost of a production stoppage due to a defective part is greater than the cost of all the connectors in the machine. Choosing the quality of the components in your machine is thus of primary importance; it also guarantees the safety of your employees. Furthermore, investing in quality increases your productivity over the long term and contributes to maintaining your brand image.

We guarantee the quality and traceability of our solutions


Our products are fully inspected and dated individually during production in order to ensure quality and traceability.
We commit our name and our image to yours through the quality of our products.

We protect your connectors to give you peace of mind

Our company exceeds its statutory responsibilities with regard to the safety of individuals and systems.
Certification and qualification processes are integrated upstream of our developments.

We ensure the performance of your installations

Our product ranges are designed with a high safety factor and comply with quality management processes.



Our Services Contribute to Your Performance

Our services integrate easily into your processes. Whether during the design phase, for promotion, or for administrative, business, or stock management of your components, our skills are here for you to use.

Customised Products

We can help you develop customised solutions: fittings, manifolds, valves, etc.



EDI Transmission

Implementation of computerised data exchange.



Improved Stock Management

Packaging, bar codes and customised labels according to your needs.




Technical Specifications

All the technical data for our products is available on-line.



2D and 3D Drawings

The CAD drawings of our products are available on-line in the 21 main formats used by the industry (Solidworks, Autocad, Pro/E, etc.).




Certificates and Regulations

Certificates of conformity for our products are available on our web site. Contact us for any further information you require.



e-Tools

Requests for quotations, stock availability, energy-saving calculators, searching for cross-references, etc. are available on-line.



Communication Tools

We can provide you with any promotional sales material you require: brochures, flash animations, sample kits, etc.



e-Catalogue

Integration of our product data into your information systems (e-procurement, e-commerce site, etc.).




Parker Legris

Industrial Connector Systems



Directives and Regulations: the Parker Legris Offer

Parker Legris complies with the directives and regulations listed below and goes beyond its statutory obligations for the ranges in question.

	European RoHS directives: 2011/65/EC Relating to the limitation of the use of 6 hazardous substances in electrical and electronic equipment (mercury, lead, cadmium, hexavalent chromium, PBB and PBDE).		NSF 61: NSF / ANSI-61 Fittings and tubes complying with this standard are tested and approved by NSF for contact with drinking water.
	REACH regulation: no. 1907/2006 As product manufacturer, we are subject to article 33 of the regulation which defines a duty to inform when a candidate substance is present at more than 0.1% weight for weight.		NSF 42 and 58: NSF/ANSI-42/58 Tubes complying with this standard are tested and approved by NSF for drinking water treatment systems.
	Pressurised equipment directive: 97/23/EC This directive regulates the design, manufacture and assessment of pressurised equipment to ensure operating safety.		ACS: Attestation de Conformité Sanitaire (France) Official approval issued by the Direction générale de la Santé Française (French Health Directorate), applies to constituent materials of equipment in contact with water intended for human consumption.
	ATEX directive: 94/9/EC mandatory since 01/07/2003 This directive is mandatory for electrical and non-electrical equipment used in explosive gaseous or dusty atmospheres. The use of our products in these areas must be determined in accordance with the ATEX environment.	KTW	KTW: Kunststoffe und Trinkwasser (Germany) Guidelines for the health evaluation of equipment in contact with drinking water, assessment and certification carried out by the TZW.
	Regulation 1935/2004 This framework regulation relates to materials and objects designed to come into contact with foodstuffs. It describes specific measures per product group (Art. 5).	W270	W270: Food contact standard (Germany) Standard describing a test method for determining the microbial growth on non-metal materials designed to come into contact with drinking water. Test and certification carried out by the TZW.
	CFR 21: Code of Federal Regulation Title 21: Food and Drugs This code consists of lists of prohibited substances for materials intended to come into contact with foodstuffs.		WRAS: Water Regulations Advisory Scheme (UK) Fittings approved by this programme are declared compliant for water supply by WRc - NSF.
	NSF 51: NSF / ANSI-51 Fittings and tubes complying with this standard are tested and approved by NSF for contact with drinks and foodstuffs.		DM 174: Ministerial decree (Italy) Declaration of hygiene compliance for equipment used for drinking water, tested and certified by the TIFQ.

The Parker Legris product range offers compliance with numerous European standards associated in particular with the directives and regulations referred to above. The official texts of these directives are available on the site: <http://eur-lex.europa.eu>.



Together, We Can Build Sustainable Development

Parker Legris, ISO 14001 certified, has made the conservation of resources and protection of the environment a major priority. We have incorporated improved environmental management as a permanent feature in the vision and mission of the company, aiming to benefit nature, technology and mankind.



Protecting natural resources

By saving energy through the performance of our production facilities.

Improving performance

By changing habits in order to promote new materials and concepts.

Asserting our values for the protection of the environment

By having all our sites ISO 14001 certified in order to unify all our employees around clear objectives regarding the management of the environment.

Our actions are coupled with your environmental process

Reducing the impact on industrial sites

Parker Legris has integrated environmental protection management into the operation of its industrial sites. This approach has enabled 85% of waste to be recovered and has reduced energy consumption by 15%.

Offering ecologically responsible products

Under its continuous improvement process, Parker Legris has integrated ecological design as an input parameter to innovation and uses Life Cycle Assessment (LCA) to optimise the environmental impact of its products.

Providing information on the PEP (Product Environmental Profile)

This communication tool is common to all industries and professions and delivers a reliable and clear message for promoting ecological advances and incorporating this data within the LCA equipment.

Getting ahead of regulations

Parker Legris goes beyond its statutory obligations and endeavours to find a good match between choice of materials, limitation of hazardous substances, selection of recycling channels and industrial performance to encourage the recycling of products at end of life.

Using our technology reduces the environmental impact


LIQUIfit®

Tube-to-Tube Connector




Market Standard

Tube-to-Tube Connector




- Parker Legris
- Market Standard in PP
- Market Standard in POM

Stud Elbow




- RWD: Raw Material Depletion
- ED: Energy Depletion
- WD: Water Depletion
- GW: Global Warming

Tube-to-Tube Connector



- OZ: Ozone Depletion
- AT: Air Toxicity
- POC: Photochemical Ozone Creation
- AA: Air Acidification

Stud Fitting



- WT: Water Toxicity
- WE: Water Eutrophication
- HWP: Hazardous Waste Production




Technical Guidelines

Compressed Air Flow and Pressure Drop

Flow represents the quantity of compressed air passing through a section per unit time. It is expressed in l/min, m³/min or m³/h, at the value expressed in free air, under Standard Reference Atmospheric conditions (ANR) namely: **+20°C, 65 % relative humidity, 1.013 bar**, according to standards NFE 48100 and ISO R554, R558.

When in open position and subject to a supply pressure (**P**), the pneumatic component provides a flow (**d**) which generates a pressure drop at the outlet. The pressure difference therefore between the inlet orifice (upstream pressure) and the outlet orifice (downstream pressure), is called the **pressure drop** and is designated by **ΔP** (pressure differential).



The **maximum allowable working pressure** of a component is the effective pressure to which this component may be subjected in a given installation.

The **upstream pressure** is the compressed air pressure at the component inlet.

The **downstream pressure** is the outlet pressure from the component.

The **differential pressure (ΔP)** is the pressure difference between the upstream and downstream pressures.

In order to have simple and usable values available for carrying out calculations and comparing the performances of pneumatic components, we use a flow factor called **Kv**. This experimental factor characterises the flow capacity of a component. It equates to the practical value of the flow of water in litres/minute under a Δp of 1 bar with bore fully open.

The flow factor Kv equates to a coefficient of conductivity - the higher its value, the better the flow provided by the component.

The Kv and pressure drop are linked by the following relationship:

$$Q_v = 26.7 K_v \sqrt{\Delta p \times P_{\text{upstream}}}$$

Q_v = flow in l/min (ANR)

K_v = flow factor

Δp = in bar

P_{upstream}: in bar absolute


C_v is a flow factor equivalent to Kv, but expressed in US gallons per minute under a Δp of 1 PSI. Kv and Cv are therefore linked by the following relationships:

$$K_v = 14.3 C_v \quad - \quad C_v = 0.07 K_v$$

The flow indicated for certain products in the Parker Legris catalogue is the average flow at 6 bar expressed in NI/min of depressurised air at the Standard Reference Atmosphere (ANR).

Pressure

The normal atmospheric pressure of the air is 1.013 bar at sea level (0 m altitude). It is generally used as a reference for pressure measurements but varies with altitude. For tests and measurements, it is preferable to use absolute bar which relates to an absolute pressure.



$$P_{\text{abs}} = P_{\text{atm}} + P_{\text{rel}}$$

P_{abs} : absolute pressure

P_{rel} : relative pressure

P_{atm} : atmospheric pressure

The pressure is expressed in bar according to industrial practice. It is the result of a force of daN applied to a surface area in cm².

$$1 \text{ bar} = \frac{1 \text{ daN}}{1 \text{ cm}^2} = 10^5 \text{ pascal}$$

Vacuum and Vacuum Levels

Vacuum appears when the atmosphere is rarefied. By removing the air from an enclosed space, a depression (or vacuum) is created relative to atmospheric pressure.

Vacuum therefore relates to the state of a fluid where the pressure is less than atmospheric pressure.

The vacuum level may be expressed as:

depression level = relative pressure value compared to atmospheric pressure

vacuum level in absolute value (defined in comparison with absolute zero)

The common unit of vacuum is the millimetre of mercury (**mm Hg**).

Classification of vacuum

• medium vacuum	1013	to	10 mbar absolute
• primary vacuum	10	to	10 ⁻³ mbar absolute
• secondary vacuum	10 ⁻³	to	10 ⁻⁶ mbar absolute
• molecular vacuum	10 ⁻⁶	to	10 ⁻⁹ mbar absolute
• ultra-vacuum			< 10 ⁻⁹ mbar absolute

Conversion Tables

Units Used in this Catalogue

Symbol	Unit
A	ampere
bar	bar
°C	degree Celsius
dBA	decibel
Hz	hertz
kg	kilogram
m	metre
m²	square metre
m³/h	cubic metres per hour
min	minute
mm	millimetre
mm Hg	millimetres of mercury
N	Newton
NI	litres at standard reference atmospheric pressure (ANR)*
V	volt

* Parker Legris carries out its tests under normal pressure and temperature conditions (1013 mbar, +20°C). All flows mentioned in this catalogue are therefore expressed in NI/min.

Units of Flow

L/min	Cfm	m³/h
600	21	36
1200	43	72
1800	64	108
2400	85	144
3000	106	180
3600	128	216
4200	149	252
4800	170	288
5400	191	324
6000	213	360
6600	234	396
7200	255	432
7800	277	468

Units of Vacuum

Depression (mm Hg)	Vacuum (%)	Absolute Pressure (mbar)	Depression (mbar)
0	0	1000	0
-75	10	900	-100
-100	13.3	867	-133
-150	20	800	-200
-200	26.7	733	-267
-225	30	700	-300
-300	40	600	-400
-375	50	500	-500
-400	53.3	467	-533
-450	60	400	-600
-500	66.7	333	-667
-525	70	300	-700
-600	80	200	-800
-675	90	100	-900
-690	92	80	-920

Units of Pressure

1 bar = 100.000 Pa = 100 kPa = 14.5 psi
1 Pa = 0.00001 bar = 0.000145 psi
1 psi = 0.069 bar = 6897.8 Pa


Units of Temperature

0 °C = +23 °F
0 °F = -17.8 °C

bar	kPa	psi	psi	kPa	bar
0.0005	0.05	0.0073	0.007	0.05	0.0005
0.001	0.10	0.0145	0.015	0.1	0.0010
0.005	0.5	0.0725	0.070	0.48	0.0048
0.01	1	0.145	0.150	1.04	0.0104
0.05	5	0.725	0.700	4.83	0.0483
0.069	6.9	1.000	1.000	6.90	0.0690
0.1	10	1.450	1.500	10.35	0.1035
0.25	25	3.625	3.000	20.70	0.2070
0.5	50	7.250	7.000	48.30	0.4830
0.75	75	10.875	10.000	69.00	0.690
1.0	100	14.500	15.000	103.50	1.0350
1.5	150	21.750	20.000	138.00	1.380
2.0	200	29.000	25.000	172.50	1.725
2.5	250	36.250	30.000	207.00	2.070
3.0	300	43.500	35.000	241.50	2.415
3.5	350	50.750	40.000	276.00	2.760
4.0	400	58.000	50.000	345.00	3.450
4.5	450	65.250	60.000	414.00	4.140
5.0	500	72.500	70.000	483.00	4.830
5.5	550	79.750	80.000	552.00	5.520
6.0	600	87.000	90.000	621.00	6.210
7.0	700	101.500	100.000	690.00	6.900
8.0	800	116.000	110.000	759.00	7.590
9.0	900	130.500	125.000	862.50	8.625
10.0	1000	145.000	150.000	1035	10.350
12.0	1200	174.000	175.000	1207.5	12.075
14.0	1400	203.000	200.000	1380	13.800
16.0	1600	232.000	225.000	1552.5	15.525
18.0	1800	261.000	250.000	1725	17.250
20.0	2000	290.000	300.000	2070	20.700

°F	°C	°C	°F
-40	-40.0	-40	-40
-30	-34.4	-30	-22
-20	-28.9	-20	-4
-10	-23.3	-10	+14
0	-17.8	0	+32
+10	-12.2	+10	+50
+20	-6.7	+20	+68
+30	-1.1	+30	+86
+40	+4.4	+40	+104
+50	+10.0	+50	+122
+60	+15.6	+60	+140
+70	+21.1	+70	+158
+80	+26.7	+80	+176
+90	+32.2	+90	+194
+100	+37.8	+100	+212
+110	+43.3	+110	+230
+120	+48.9	+120	+248
+130	+54.4	+130	+266
+140	+60.0	+140	+284
+150	+65.6	+150	+302
+160	+71.1	+160	+320
+170	+76.7	+170	+338
+180	+82.2	+180	+356
+190	+87.8	+190	+374
+200	+93.3	+200	+392
+210	+98.9	+210	+410
+220	+104.4	+220	+428
+230	+110.0	+230	+446
+240	+115.6	+240	+464
+250	+121.1	+250	+482

Fitting Threads



BSP Threads (British Standard Pipe)

NPT Threads (National Pipe Thread)

There are two types of "Pipe" profile threads:

- **Parallel (BSPP):** these threads fit in matching parallel ports. Sealing is provided by an O-ring gasket or a sealing washer.
- **Taper (BSPT):** these threads fit in matching parallel or taper ports. Sealing is provided by a pre-coating on the thread.

Thread designation

- **BSP Parallel (BSPP):**
G followed by the denomination, according to standard ISO 228-1.
Example: 1/8 BSP parallel thread = G1/8
- **BSP Taper (BSPT):**
R followed by the denomination, according to standard ISO 7-1.
Example: 1/8 BSP parallel (BSPP) thread = R1/8
- **Female threads:**
BSP parallel: G followed by the designation
BSP taper: R followed by the designation

This is an American standard taper thread which fits into the matching taper port. Sealing is provided by a pre-coating on the thread.
Example: 1/8 NPT thread = 1/8 NPT

Metric Threads

These ISO-profile threads are parallel and are fit into the matching parallel port. Sealing is provided by an O-ring or a sealing washer.

Thread designation

- M depending on the diameter and pitch in millimetres, separated by a multiplication sign, in accordance with standards ISO 68-1 and ISO 965-1.
Example: metric thread diameter 7 with a pitch of 1 mm = M7x1

Thread Identification

BSP Thread	Code	NPT Thread	Code	Metric Thread	Code	Metric Thread	Code	Metric Thread	Code
1/8	10	1/16	08	M3x0.5	09	M12x1.25	66	M22x1.5	82
1/4	13	1/8	11	M5x0.8	19	M12x1.5	67	M24x1.5	83
3/8	17	1/4	14	M6x1	52	M13x1.25	68	M27x1.5	85
1/2	21	3/8	18	M7x1	55	M14x1.25	70	M30x2	88
3/4	27	1/2	22	M8x1	56	M14x1.5	71	M33x1.5	90
1"	34	3/4	28	M8x1.25	57	M16x1.25	74	M39x1.5	36
1 1/4"	42	1"	35	M10x1	60	M16x1.5	75	M42x1.5	37
1 1/2"	49	1 1/4"	43	M10x1.5	62	M18x1.5	78	M42x2	96
2"	48	1 1/2"	50	M12x1	65	M20x1.5	80	M48x2	98
		2"	44						

Principle and Advantages of Our Coupling Systems

A very large number of technical solutions exist for connecting two pipes together. Leader in industrial connection systems, Parker Legris offers a very wide range of technologies and materials to cover all requirements.

<div>Push-In Fittings</div> <div>Tube retention with gripping ring</div>  <div>Tube retention with collet</div>  <div>Tube retention with reversed collet</div> 

Product Selection Table

Push-In Fittings	Materials	Fluids	Maximum Pressure (bar)	Temperature		Performance in Aggressive Environments	
				Min.	Max.	Mechanical	Chemical
LF 3000®	Technical polymer/brass/NBR	Compressed air	20	-20°C	+80°C	Good	Moderate
LIQUIfit®	Bio-sourced polymer/EPDM	Liquids	16	-10°C	+95°C	Moderate	Good
LF 3200	Nickel-plated brass/NBR	Compressed air	20	-15°C	+80°C	Excellent	Moderate
LF 3600	Chemical nickel-plated brass FDA/FKM	All brass-compatible fluids	30	-20°C	+150°C	Excellent	Good
LF 6100	Brass/NBR	Oil, analytical gases	60	-40°C	+120°C	Excellent	Moderate
LF 3800 / LF 3900	316L - 303 stainless steel/FKM	All fluids	30	-20°C	+150°C	Excellent	Excellent

Cartridges and Customised Products

LF 3000®	Technical polymer/brass or chemical nickel-plated brass/NBR	Compressed air	20	-20°C	+80°C	Good	Moderate
LIQUIfit®	Bio-sourced polymer/EPDM	Liquids	16	-10°C	+95°C	Moderate	Good
LF 3600	Chemical nickel-plated brass FDA/FKM	All brass-compatible fluids	30	-20°C	+150°C	Excellent	Good
LF 3800 / LF 3900	316L - 303 stainless steel/FKM	All fluids	30	-20°C	+150°C	Excellent	Excellent
TL	Brass/NBR	Compressed air	16	-25°C	+80°C	Good	Moderate

Technical Tubing and Hose

Semi-Rigid PA	Semi-rigid bio-sourced polyamide	Compressed air, industrial fluids	50	-40°C	+100°C	Good	Good
Rigid PA	Rigid polyamide	Compressed air, industrial fluids	58	-40°C	+80°C	Good	Good
Fireproof High Resistance PA	Polyamide with flame-retardant additive	Coolants, industrial fluids (lubricants), compressed air	50	-40°C	+100°C	Excellent	Moderate
Anti-Spark PA and PU with or without PVC sheath	Semi-rigid polyamide with PVC sheath Polyurethane ether with PVC sheath Single-layer polyurethane ester with flame-retardant additive	Compressed air, coolants, industrial fluids	36 (PA) 14 (PU)	-20°C	+70°C +80°C	Excellent	Good
PU single and multi-tube	Polyurethane ester Polyurethane ether "Crystal" food-quality polyurethane ether	Compressed air, industrial fluids (water) or food industry fluids	12	-20°C	+70°C	Excellent	Moderate Good Good
Antistatic PU	Polyurethane filled with conductive particles	Compressed air	10	-20°C	+70°C	Excellent	Moderate
Advanced PE	Polyethylene, 50% reticulated	All fluids	16	-40°C	+95°C	Good	Excellent
FEP	Fluoropolymer: fluorinated ethylene-propylene	All fluids	28	-40°C	+150°C	Good	Excellent
PFA	Fluoropolymer: high purity and coloured perfluoroalkoxy FDA	All fluids	36	-196°C	+260°C	Excellent	Excellent
Antistatic PFA	Fluoropolymer: perfluoroalkoxy filled with conducting particles	All fluids	36	-196°C	+260°C	Excellent	Good
Self-Fastening NBR	NBR with polyamide braid	Compressed air, coolants	16	-20°C	+100°C	Excellent	Good
Braided PU	Polyurethane with polyester braid	Compressed air, industrial fluids	15	-40°C	+75°C	Excellent	Good

Function Fittings

Polymer Flow Regulators	Technical polymer/nickel-plated brass	Compressed air	10	0°C	+70°C	Good	Moderate
Metal Flow Regulators	Treated brass/nickel-plated brass	Compressed air	10	0°C	+70°C	Excellent	Moderate
Stainless Steel Flow Regulators	316L stainless steel	Compressed air	40	-15°C	+120°C	Excellent	Excellent
Blocking Fittings	Nickel-plated brass	Compressed air	10	-20°C	+70°C	Excellent	Good
Piloted Non-Return Valve	Technical polymer/nickel-plated brass	Compressed air	10	-5°C	+60°C	Good	Moderate
Non-Return Fitting	Technical polymer/nickel-plated brass	Compressed air	10	0°C	+70°C	Good	Moderate
Silencers	Polymer, sintered bronze, nickel-plated brass, 316L stainless steel	Compressed air	12	-20°C	+180°C	Good	Moderate

Compression Fittings	Materials	Fluids	Maximum Pressure (bar)	Temperature		Performance in Aggressive Environments	
				Min.	Max.	Mechanical	Chemical
Brass Fittings	Brass	Compressed air, industrial fluids	550 (depending on the type of tubing used)	-40°C	+250°C	Excellent	Good
Stainless Steel Fittings	316L stainless steel	All fluids	400 (80 bar in aggressive environment)	-40°C	+250°C	Excellent	Excellent
PL Spigot Fittings	Nickel-plated brass	Compressed air, industrial fluids	40	-40°C	+100°C	Good	Good

Industrial Valves

Universal and Customised Series Ball Valves	Nickel-plated brass	Compressed air, industrial fluids	40	-20°C	+100°C	Excellent	Good
Mini Series Ball Valves	Technical polymer/nickel-plated brass	Compressed air	10	-20°C	+80°C	Good	Moderate
DVGW Series Ball Valves	Nickel-plated brass	Gas, water	40	-40°C	+170°C	Excellent	Good
LIQUIfit® Ball Valves	Polypropylene	Drinking water, treated water, beverages	10	-15°C	+100°C	Moderate	Good
Standard Series Ball Valves	Nickel- or chromium-plated brass	All industrial fluids	30	-20°C	+130°C	Excellent	Good
Stainless Steel Series Ball Valves	316L stainless steel	All fluids	65	-20°C	+150°C	Excellent	Excellent
Axial Valves	Nickel-plated brass	Compressed air	10	-20°C	+135°C	Excellent	Good

Industrial Blowguns

Polymer	Technical polymer	Compressed air	10	-20°C	+50°C	Good	Moderate
Metal	Aluminium or nickel-plated brass	Industrial fluids	20	-20°C	+100°C	Excellent	Good

Quick-Acting Couplers

C 9000 Safety Couplers	Technical polymer	Compressed air	16	-20°C	+60°C	Good	Moderate
Metal Quick-Acting Couplers	Nickel-plated brass	Compressed air, compatible fluids	20	-20°C	+100°C	Excellent	Good
Metal Quick-Acting Couplers	316L stainless steel	Industrial fluids	35	-15°C	+200°C	Excellent	Excellent
Injection Mould Couplers	Nickel-plated brass	Water, oil	10	-15°C	+90°C	Excellent	Good

Adaptors and Manifolds

Brass Adaptors with sealing washer	Brass	Compressed air	200	-20°C	+80°C	Good	Moderate
Brass Adaptors without sealing washer	Brass	Compressed air	200	-40°C	+150°C	Good	Moderate
Nickel-Plated Brass Adaptors	Nickel-plated brass	Compressed air	60	-10°C	+80°C	Good	Moderate
Stainless Steel Adaptors	316L stainless steel	All fluids	200	-20°C	+180°C	Excellent	Excellent
Manifolds	Anodised aluminium, brass	Compressed air	20	-10°C	+80°C	Excellent	Good

This table is not exhaustive; you will find additional technical information in the various chapters of this catalogue which will enable you to select the product you need.

Part Number Identification

The part numbers used for our product ranges are coded in such a way as to make it easy to identify any particular item. Detailed explanations of these part numbers can be found in the corresponding chapters.

Fittings and Valves

The part numbers are selected using a technical mnemonic code.

Each fitting and valve is identified by:

- model series (4 digits)
- nominal diameter (2 digits)
- thread or 2nd nominal diameter (2 digits)
- a suffix, if applicable

Fittings	Valves
<div><div>3101</div><div>06</div><div>10</div><div>Item type</div><div>Nominal diameter</div><div>Thread code</div></div>	<div><div>0402</div><div>13</div><div>21</div><div>22</div><div>Item type</div><div>Nominal diameter DN</div><div>Thread</div><div>Suffix defining the customised series selected</div></div>

Nominal diameter code: equates to the outside diameter of the tube.
Thread code: see tables page 12.

Nominal diameter code: equates to the bore diameter of the valve.
Thread code: see tables page 12.

When the product does not have a thread, the code used is: 00.

Technical Tubing and Hose

The part numbers are selected using a technical mnemonic code.

Each tube and hose is identified by:

- model series (4 digits and a letter)
- nominal diameter (2 digits)
- colour (2 digits)
- inside diameter, if applicable

Tubing	Hose
<div><div>1025U08</div><div>06</div><div>Item type</div><div>Nominal diameter</div><div>Colour</div></div>	<div><div>1040H56</div><div>04</div><div>Item type</div><div>Nominal diameter</div><div>Colour</div></div>

Nominal diameter code: equates to the outside diameter.
Colour code: see table below.

Nominal diameter code: equates to the inside diameter code.
Colour code: see table below.

00 =  01 =  02 =  03 =  04 =  05 =  06 =  07 =  08 = 

For other colours, refer to chapter "Technical Tubing and Hose".

Push-In Fittings

Chapter 1

LF 3000®
LF 3200: 3 mm
LIQUIfit®
LF 3600
LF 3800/LF 3900
LF 6100



Cartridges and Customised Products

Chapter 2

Polymer: Carstick® & Quick Fitting
Metal: LF Cartridges & TL Fittings
Customised Products



Technical Tubing and Hose

Chapter 3

Flexible Calibrated Tubing
Calibrated Multi-Tubing
Recoil Tubing and Hose
Calibrated Braided Hose
Accessories



Function Fittings

Chapter 4

Flow Control Regulators
Piloted Function Fittings
Non-Return Valves & LIQUIfit®
Pressure Fittings
Other Function Fittings
Silencers



Compression Fittings

Chapter 5

Brass Compression Fittings
Stainless Steel Compression Fittings
PL Nickel-Plated Brass Spigot Fittings



Industrial Valves

Chapter 6

Ball Valves & LIQUIfit®
Needle & Butterfly Valves
Axial Valves



Industrial Blowguns

Chapter 7

Polymer
Metal
Kits



Quick-Acting Couplers

Chapter 8

Polymer: C 9000 Safety
Metal: Nickel-Plated Brass and Stainless Steel



Adaptors and Manifolds

Chapter 9

Adaptors: Brass, Nickel-Plated Brass, Stainless Steel
Manifolds



Push-In Fittings

LF 3000®

LF 3200: 3 mm

LIQUIfit®

LF 3600

LF 3800/ LF 3900

LF 6100







Principle and Advantages of the Push-In Fitting

The **push-in fitting** is the most intuitive way of connecting tubes to a fitting in order to create a fluid distribution network. Thanks to its **quick installation**, versatility and **exceptional lifespan**, the push-in fitting contributes to improving machine efficiency. Moreover, the advanced patented design of the LF 3000® contributes to reducing **total cost of use**.

Connection

- Manual connection and disconnection without the use of tools
- Release button available in 5 colours, to identify different circuits



Assembly

All straight connectors are fitted with an internal hexagon for ease of assembly with the use of an Allen spanner. This enables assembly in restricted spaces.

Threads




BSPP
and metric



BSPT, NPT
and NPTF

Close Porting Assembly



Our fittings are designed for internal (above) or external assembly.

Sealing and 100 % Leak-Tested

The quality of the sealing material, selected specifically for the application, ensures excellent longevity of the fitting. In this way, Parker Legris offers the best return on investment on the market.

Quality of Design


- Unique and patented sealing technology
- Rigorous selection of materials:
NBR: ideally suited for compressed air
EPDM: perfectly suited for food and beverage
FKM: all fluids and high temperatures
- 100 % leak-tested in the production process

Benefits of Use

- The lowest leak rate on the market, whatever the temperature and length of use
- Perfectly suited to primary vacuum
- Full bore for optimum flow
- Optimum gripping of tube guaranteed


Gripping Ring Technology

- Ideal for polymer tubing, even for soft tubing
- Excellent tube guidance
- No tube movement under pressure
- Very compact solution




Gripping with Collet

- For polymer and grooved metal tubing (groove drawings available on request)
- Resistant to high pressure, excellent lifespan
- Robust solution for harsh environments



Gripping with Reversed Collet

- For rigid polymer and grooved metal tubing
- Resistant to high pressure
- Excellent durability
- Optimum sealing



Push-In Fittings

LF 3000® Push-In Fittings

[P. 1-4]



Fluids: compressed air

Materials: technical polymer, nickel-plated brass, NBR

Pressure: 20 bar

Temperature: -20°C to +80°C

Ø metric: 3 mm to 16 mm

Ø inch: 1/8" to 1/2"

LF 3200 3 mm Push-In Fittings

[P. 1-39]



Fluids: compressed air, non-corrosive fluids

Materials: chemical nickel-plated brass, NBR

Pressure: 20 bar

Temperature: -15°C to +80°C

Ø metric: 3 mm

LIQUIfit® Push-In Fittings

[P. 1-44]



Fluids: water, beverages, coolants, inert gases

Materials: biopolymer, EPDM

Pressure: 16 bar

Temperature: -10°C to +95°C

Ø metric: 4 mm to 12 mm

Ø inch: 5/32" to 1/2"

LF 3600 Push-In Fittings

[P. 1-65]



Fluids: compressed air, slightly corrosive industrial fluids

Materials: high phosphorus nickel-plated brass, FKM

Pressure: 30 bar

Temperature: -20°C to +150°C

Ø metric: 4 mm to 14 mm

LF 3800/LF 3900 Push-In Fittings

[P. 1-77]



Fluids: industrial fluids, chemicals, medical fluids, beverages

Materials: stainless steel, FKM

Pressure: 30 bar

Temperature : -20°C to +150°C

Ø metric: 4 mm to 12 mm

Ø inch: 3/16" to 1/2"

LF 6100 Push-In Fittings

[P. 1-89]



Fluids: compressed air, oil, water

Materials: brass, NBR

Pressure: 60 bar

Temperature: -40°C to +120°C

Ø metric: 4 mm to 10 mm

For more details on these ranges, you will find a selection guide in the "Introduction" section of this catalogue.

LF 3000® Push-In Fittings Range

Stud Fittings

Straights

3175
BSPT/NPT
Page 1-7



3101
BSPP/Metric
Page 1-8



3181
Metric
Page 1-8



3114
BSPP/Metric
Page 1-9



3121
BSPT/NPT
Page 1-9



3131
BSPP/Metric
Page 1-10



Straights - Inch

3175
NPT/BSPT
Page 1-7/8



3121
NPT
Page 1-9



Elbows

3109
BSPT/NPT
Page 1-10



3199
BSPP/Metric
Page 1-11



3192
BSPP
Page 1-12



3129
BSPT
Page 1-12



3169
BSPP/Metric
Page 1-13



3113
BSPT
Page 1-13



3133
BSPP/Metric
Page 1-13



Elbows - Inch

3109
NPT/BSPT
Page 1-11



Tees

3108
BSPT
Page 1-14



3198
BSPP/Metric
Page 1-14



3103
BSPT
Page 1-14



3193
BSPP/Metric
Page 1-15



Y

3148
BSPT
Page 1-15



3158
BSPP/Metric
Page 1-15



3112
BSPT
Page 1-16



3132
BSPP
Page 1-16



Cartridge

3100
Carstick®
Page 1-16



Cartridge - Inch

3100
Carstick®
Page 1-16



Tube-to-Tube Fittings

Straight

3106
Page 1-17



Straight - Inch

3106
Page 1-17



Elbow

3102
Page 1-17



Elbow - Inch

3102
Page 1-17



Tee

3104
Page 1-18



Tee - Inch

3104
Page 1-18



Y

3140
Page 1-18



Cross

3107
Page 1-19



Bulkhead Connector Fittings

Straights

3116
Page 1-20



3146
Page 1-20



3136
Page 1-20



Elbow

3139
Page 1-20



Multiple Fittings

Y

3144
Page 1-21



Tee

3304
Page 1-21



Elbow

3306
Page 1-21



Manifold

3310
Page 1-21



LF 3000® Push-In Fittings Range

LF 3000®

Push-In Fittings

Plug-In Fittings and Accessories

Elbows

3182
Page 1-22



3184
Page 1-22



3180
Page 1-22



Tees

3183
Page 1-23



3188
Page 1-23



Y

3142
Page 1-23



3143
Page 1-23



Elbows - Inch

3182
Page 1-22



Accessories

3120
Page 1-24



3166
Page 1-24



3168
Page 1-24



3126
Page 1-25



3122
Page 1-25



3151
Page 1-25



Accessories - Inch

3166
Page 1-24



3168
Page 1-24



3126
Page 1-25



Banjo Fittings

Banjo Fittings

3118
BSPP/Metric
Page 1-27



3018
BSPT
Page 1-27



3124
BSPP/Metric
Page 1-27



3149
BSPP/Metric
Page 1-27



3119
BSPP/Metric
Page 1-27



Modular Banjo Fittings

3538
Single Body
Page 1-28



3539
Double Body
Page 1-28



3549
Y Body
Page 1-28



3527
BSPP/Metric
Page 1-29



3528
BSPP/Metric
Page 1-29



3529
BSPP
Page 1-29



3524
BSPP/Metric
Page 1-29



Multi-Connectors

3300
Page 1-31



3320
Page 1-31



3321
Page 1-31



3329
Page 1-31



3379
Page 1-32



3381
Page 1-32



Self-Sealing and Oscillating Fittings

Self-Sealing Fittings

3391
BSPP
Page 1-35



3091
BSPT
Page 1-35



3160
Page 1-35



Oscillating Fittings

3159
BSPT
Page 1-35



3189
BSPP/Metric
Page 1-35



Accessories for Push-In Fittings

3130
Page 1-37



Clip
Page 1-37



3000 70
Page 1-37



3110
Page 1-37



0178
BSPP/Metric
Page 1-37



0222
BSPP/Metric
Page 1-37



LF 3000® Push-In Fittings

The LF 3000® range, with its wide variety of shapes and configurations, allows you to find **the perfect product to meet your needs** and thus **optimise the use** of your equipment.

Product Advantages

World-Class Performance

- 40 years of expertise
- Full bore for optimum flow
- Ideal for vacuum or pressure applications
- Automatic sealing guaranteed, in both static and dynamic applications
- Materials with high resistance
- Durability of product and equipment

Optimal Design

- 100% leak-tested in production
- Date coding to guarantee quality and traceability
- Compact and aesthetic design: reduced dimensions for space-saving
- Tube fixed during connection, preventing leakage
- Conforms to ISO 14743
- Excellent vacuum performance thanks to the patented sealing technology
- Lightweight: reduced energy consumption of operating systems
- Parallel threaded fitting with a patented captive O-ring seal
- Maximum flexibility due to the wide product range



Robotics
Automotive Process
Pneumatics
Semi-Conductors
Textile
Packaging
Vacuum

Applications


Technical Characteristics

Compatible Fluids	Compressed air Other fluids: please consult us
Working Pressure	Vacuum to 20 bar
Working Temperature	-20°C to +80°C

Tightening Torque (daN.m)	Threads								
	M3 x0.5	M5 x0.8	M7 x1	M10 x1	M12 x1.5	G1/8	G1/4	G3/8	G1/2
	0.06	0.16	0.8	0.8	1.1	0.8	1.2	3	3.5

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Regulations

ISO 14743: Pneumatic fluid power, push-in connectors for thermoplastic tubes
DI: 97/23/EC (PED)

DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 1907/2006 (REACH)

Stud Fittings

3175 Stud Fitting, Male BSPT Thread

ØD	C		F1	F2	H	kg
4	R1/8	3175 04 10	10	3	9.5	0.005
	R1/4	3175 04 13	14	3	6.5	0.012
	R3/8	3175 04 17	17	3	8	0.024
6	R1/8	3175 06 10	10	4	11.5	0.005
	R1/4	3175 06 13	14	4	8.5	0.011
	R3/8	3175 06 17	17	4	8.5	0.022
8	R1/2	3175 06 21	21	4	9	0.043
	R1/8	3175 08 10	13	5	20	0.011
	R1/4	3175 08 13	14	6	17	0.014
10	R3/8	3175 08 17	17	6	13	0.021
	R1/2	3175 08 21	21	6	12	0.040
12	R1/8	3175 10 10	16	5	22.5	0.017
	R1/4	3175 10 13	16	7	20	0.017
	R3/8	3175 10 17	17	8	16.5	0.019
14	R1/2	3175 10 21	21	8	14	0.037
	R1/4	3175 12 13	19	7	26.5	0.029
	R3/8	3175 12 17	19	9	24	0.028
16	R1/2	3175 12 21	21	10	19.5	0.036
	R3/8	3175 14 17	22	9	28.5	0.043
	R1/2	3175 14 21	24	10	23.5	0.047
16	R3/8	3175 16 17	27	9	32.5	0.068
	R1/2	3175 16 21	27	12	32.5	0.079

Pre-coated thread

3175 Stud Fitting, Male NPT Thread

ØD	C		F1	F2	H	kg
6	NPT1/8	3175 06 11	11	4	11.5	0.006
	NPT1/4	3175 06 14	14	4	8.5	0.012
	NPT1/4	3175 10 14	16	7	20	0.018
10	NPT3/8	3175 10 18	18	8	16.5	0.023
	NPT1/2	3175 10 22	22	8	14	0.037
12	NPT3/8	3175 12 18	19	9	24	0.030
	NPT1/2	3175 12 22	22	10	19.5	0.037

Pre-coated thread

3175 Stud Fitting, Male NPT Thread

Inch

ØD	C		F1	F2	H	kg
1/8	NPT1/8	3175 53 11	11	2	7.2	0.006
	NPT1/4	3175 53 14	14	2	8	0.016
1/4	NPT1/8	3175 56 11	11	4	11.9	0.006
	NPT1/4	3175 56 14	14	4	9.4	0.013
	NPT3/8	3175 56 18	18	5	7.6	0.024
3/8	NPT1/8	3175 60 11	16	4	22.7	0.019
	NPT1/4	3175 60 14	16	7	20.5	0.019
	NPT3/8	3175 60 18	18	7	17.5	0.026
1/2	NPT3/8	3175 62 18	22	9.5	25.9	0.047
	NPT1/2	3175 62 22	24	9.5	22.1	0.064

Pre-coated thread


Other products are available upon request; please do not hesitate to consult us.

Stud Fittings


3175


Stud Fitting, Male BSPT Thread

Inch



Nickel-plated brass, NBR




	ØD	C		F1	F2	H	kg
1/8	3/16	R1/8	3175 53 10	11	3	8.5	0.005
		R1/8	3175 55 10	11.1	3.2	15.5	0.009
		R1/4	3175 55 13	14.3	4	15	0.020
1/4	3/8	R1/8	3175 56 10	11	4	12	0.006
		R1/4	3175 56 13	14	4	9.5	0.021
		R1/4	3175 60 13	18	5	7.5	0.017
3/8	1/2	R3/8	3175 60 17	13	5	20	0.019
		R1/2	3175 60 21	14	6	16.8	0.061
		R1/4	3175 62 13	22	6	26.9	0.044
1/2		R3/8	3175 62 17	22	7	25.9	0.048
		R1/2	3175 62 21	24	7	20.5	0.049

Pre-coated thread

Pre-coated thread

3101


Stud Fitting, Male BSPP and Metric Thread

	ØD	C						kg
				E	F1	F2	H	
	3	M3x0.5	3101 03 09*	2.5	8	-	12.5	0.003
		M5x0.8	3101 03 19	3.5	8	2.5	12.5	0.004
	4	M3x0.5	3101 04 09*	2.5	8	-	14.5	0.003
		M5x0.8	3101 04 19	3	9	2.5	14	0.003
	6	M7x1	3101 04 55	5	10	2.5	14	0.004
		G1/8	3101 04 10	5	13	3	11.5	0.007
	8	G1/4	3101 04 13	5.5	16	3	10.5	0.011
		M5x0.8	3101 06 19	3	11	2.5	16	0.005
	10	M7x1	3101 06 55	5	10	3	16	0.006
		M10x1	3101 06 60	5	13	4	13	0.007
	12	M12x1.5	3101 06 67	5.5	15	4	13	0.009
		G1/8	3101 06 10	5	13	4	13	0.007
	14	G1/4	3101 06 13	5.5	16	4	12.5	0.011
		G3/8	3101 06 17	5.5	20	4	13	0.020
	16	G1/2	3101 06 21	7.5	24	4	20	0.040
		M10x1	3101 08 60	5	13	5	21	0.011
	18	M12x1.5	3101 08 67	5.5	15	5	21	0.015
		G1/8	3101 08 10	4.5	13	5	20.5	0.011
	20	G1/4	3101 08 13	5.5	16	6	19.5	0.016
		G3/8	3101 08 17	5.5	20	6	18	0.022
	22	G1/2	3101 08 21	7.5	24	6	16.5	0.039
		G1/4	3101 10 13	5.5	16	7	23	0.018
	24	G3/8	3101 10 17	5.5	20	8	19.5	0.021
		G1/2	3101 10 21	7.5	24	8	18.5	0.033
	26	G1/4	3101 12 13	5.5	19	7	27.5	0.027
		G3/8	3101 12 17	5.5	20	9	27	0.029
	28	G1/2	3101 12 21	7	24	11	22.5	0.035
		G3/8	3101 14 17	5.5	22	9	29.5	0.041
	30	G1/2	3101 14 21	7	24	11	28	0.047
		G3/8	3101 16 17	7.5	27	9	32.5	0.061
		G1/2	3101 16 21	9	27	12	32.5	0.066


* Bi-material O ring seal

3181

Stud Fitting Round Body, Male Metric Thread

	ØD	C						kg
				E	F	G	H	
	4	M5x0.8	3181 04 19	3.5	2.5	8.5	14.5	0.005
		M7x1	3181 04 55	5	3	10	14	0.004
	6	M5x0.8	3181 06 19	3.5	2.5	11	16	0.007
		M7x1	3181 06 55	5	3	10	16	0.005

The internal hexagon and circular external shape ensure that model 3181 provides highly compact assembly.
They can be easily installed with an Allen key without the need of a spanner.



Stud Fittings

LF 3000®

Push-In Fittings

3114 Stud Fitting, Female BSPP and Metric Thread

ØD	C					
			E	F	H	kg
4	M5x0.8	3114 04 19	6.5	8	19.5	0.005
	G1/8	3114 04 10	9.5	13	22.5	0.010
	G1/4	3114 04 13	13.5	16	26.5	0.015
6	G1/8	3114 06 10	9.5	13	24.5	0.011
	G1/4	3114 06 13	13.5	16	28.5	0.017
8	G1/8	3114 08 10	9.5	13	29	0.015
	G1/4	3114 08 13	13.5	16	33	0.021
10	G3/8	3114 08 17	14	19	34	0.025
	G1/4	3114 10 13	13.5	16	36	0.027
	G3/8	3114 10 17	14	19	36	0.027
12	G1/2	3114 10 21	19.5	24	41.5	0.048
	G3/8	3114 12 17	14	19	40	0.033
14	G1/2	3114 12 21	19.5	24	45.5	0.052
	G3/8	3114 14 17	14	22	42.5	0.057
16	G1/2	3114 16 21	15	27	49	0.096

3121 Stud Standpipe, Male BSPT Thread

ØD	C		F	H	H1	kg
4	R1/8	3121 04 10	10	26	14	0.005
	R1/4	3121 04 13	14	26.5	14.5	0.014
6	R1/8	3121 06 10	10	28	14	0.005
	R1/4	3121 06 13	14	28.5	14.5	0.014
8	R1/8	3121 08 10	10	29.5	11	0.006
	R1/4	3121 08 13	14	28.5	10	0.012
10	R3/8	3121 08 17	17	28.5	10	0.015
	R1/4	3121 10 13	15	36	15.5	0.012
	R3/8	3121 10 17	17	36	15.5	0.017
12	R1/2	3121 10 21	21	36	15.5	0.028
	R3/8	3121 12 17	17	36.5	12	0.018
14	R1/2	3121 12 21	21	36.5	12	0.028
	R1/2	3121 14 21	21	41	13.5	0.042

Pre-coated thread

3121 Stud Standpipe, Male NPT Thread

ØD	C		F	H	H1	kg
4	NPT1/8	3121 04 11	11	25.9	14.5	0.007
	NPT1/4	3121 04 14	14	26.4	15	0.017
8	NPT1/8	3121 08 11	11	29.5	10.9	0.008
	NPT1/4	3121 08 14	14	28.4	9.9	0.014

Pre-coated thread
5/32" (4 mm) and 5/16" (8 mm) are also available

3121 Stud Standpipe, Male NPT Thread

Inch


ØD	C		F	H	H1	kg
1/4	NPT1/8	3121 56 11	11	30	15.5	0.001
	NPT1/4	3121 56 14	14	28.4	14.5	0.001
3/8	NPT1/8	3121 60 11	15	44.4	16.5	0.013
	NPT1/4	3121 60 14	15	36.1	17	0.014
1/2	NPT3/8	3121 60 18	18	36.1	15.5	0.023
	NPT3/8	3121 62 18	17	36.6	9.4	0.026
	NPT1/2	3121 62 22	21	37.1	9.9	0.046

Pre-coated thread
5/32" (4 mm) and 5/16" (8 mm) are also available

Stud Fittings

3131 Stud Standpipe, Male BSPP and Metric Thread

Technical polymer, nickel-plated
brass, NBR

ØD	C		E	F	H	H1	kg
4	M5x0.8	3131 04 19	3.5	8	31	16	0.002
	G1/8	3131 04 10	5	13	30	13.5	0.005
	G1/4	3131 04 13	5.5	16	31	13.5	0.010
6	G1/8	3131 06 10	5	13	32	13.5	0.005
	G1/4	3131 06 13	5.5	16	33	13.5	0.010
8	G1/8	3131 08 10	5	13	35.5	12.5	0.008
	G1/4	3131 08 13	5.5	16	34.5	10.5	0.010
	G3/8	3131 08 17	5.5	20	34.5	10.5	0.015
10	G1/4	3131 10 13	5.5	16	43.5	17.5	0.012
	G3/8	3131 10 17	5.5	20	41.5	15.5	0.015
	G1/2	3131 10 21	7.5	24	41.5	15.5	0.024
12	G3/8	3131 12 17	5.5	20	42	12	0.015
	G1/2	3131 12 21	7	24	43.5	12	0.025
14	G3/8	3131 14 17	5.5	20	46.5	14	0.018
	G1/2	3131 14 21	7	24	48	13.5	0.025

3109 Stud Elbow, Male BSPT Thread

ØD	C						kg
			F	G	H	L	
4	R1/8	3109 04 10	10	8.5	13.5	14	0.006
	R1/4	3109 04 13	14	8.5	14	14	0.015
	R3/8	3109 04 17	17	8.5	13.5	14	0.018
6	R1/8	3109 06 10	10	10.5	15.5	16	0.006
	R1/4	3109 06 13	14	10.5	16	16	0.015
	R3/8	3109 06 17	17	10.5	16	16	0.019
8	R1/2	3109 06 21	21	10.5	16.5	16	0.034
	R1/8	3109 08 10	10	13.5	19	23	0.007
	R1/4	3109 08 13	14	13.5	18	23	0.014
10	R3/8	3109 08 17	17	13.5	18	23	0.018
	R1/2	3109 08 21	21	13.5	19.5	23	0.033
	R1/8	3109 10 10	15	16	23	26.5	0.012
12	R1/4	3109 10 13	15	16	22	26.5	0.014
	R3/8	3109 10 17	17	16	22	26.5	0.019
	R1/2	3109 10 21	21	16	22	26.5	0.031
14	R1/4	3109 12 13	15	19	25	31	0.016
	R3/8	3109 12 17	17	19	25	31	0.022
	R1/2	3109 12 21	21	19	25	31	0.033
16	R3/8	3109 14 17	20	22	30.5	35.5	0.031
	R1/2	3109 14 21	24	22	28.5	35.5	0.041
	R3/8	3109 16 17	27	27	53	39	0.106
	R1/2	3109 16 21	27	27	53	39	0.104

Pre-coated thread
The body swivels for positioning purposes.

3109 Stud Elbow, Male NPT Thread

ØD	C						kg
			F	G	H	L	
4	NPT1/8	3109 04 11	11	8.4	13.5	14	0.007
	NPT1/4	3109 04 14	14	8.4	14	14	0.016
6	NPT1/8	3109 06 11	11	10.5	15.5	16	0.007
	NPT1/4	3109 06 14	14	10.5	16	16	0.017
8	NPT1/8	3109 08 11	11	13.5	19	23.1	0.009
	NPT1/4	3109 08 14	14	13.5	18	23.1	0.015
10	NPT1/4	3109 10 14	15	16	23	26.5	0.017
	NPT3/8	3109 10 18	18	16	22	26.5	0.024
	NPT1/2	3109 10 22	22	16	23	26.5	0.045
12	NPT3/8	3109 12 18	18	19	25	31	0.050
	NPT1/2	3109 12 22	22	19	26	31	0.092

Pre-coated thread
The body swivels for positioning purposes.

Stud Fittings

3109

Stud Elbow, Male NPT Thread

Inch

Technical polymer, nickel-plated
brass, NBR

ØD	C		F	G	H	L	kg
1/8	NPT1/8	3109 53 11	11	8.5	13.5	14.5	0.007
	NPT1/4	3109 53 14	14	8.5	14	14.5	0.015
1/4	NPT1/8	3109 56 11	11	10.9	17	18	0.007
	NPT1/4	3109 56 14	14	10.9	16	18	0.014
	NPT3/8	3109 56 18	18	10.9	16.5	18	0.021
	NPT1/8	3109 60 11	15	16	23.1	27.4	0.014
3/8	NPT1/4	3109 60 14	15	16	23.1	27.4	0.017
	NPT3/8	3109 60 18	18	16	22.1	27.4	0.023
1/2	NPT3/8	3109 62 18	20	22.1	31	35.1	0.041
	NPT1/2	3109 62 22	24	22.1	28.4	35.1	0.054


Pre-coated thread - 5/32" (4 mm) and 5/16" (8 mm) are also available.
The body swivels for positioning purposes.

3109

Stud Elbow, Male BSPT Thread

Inch

Technical polymer, nickel-plated
brass, NBR

ØD	C		F	G	H	L	kg
1/8	R1/8	3109 53 10	10	8.5	13.5	14.5	0.011
3/16	R1/8	3109 55 10	11	10.9	17	21.6	0.010
	R1/4	3109 55 13	14	8.4	14	14	0.016
1/4	R1/8	3109 56 10	10	10.9	17	18	0.006
	R1/4	3109 56 13	14	10.9	17	18	0.013
3/8	R1/4	3109 60 13	15	16	22.1	26.4	0.016
	R3/8	3109 60 17	17	16	22.1	26.4	0.054
1/2	R1/4	3109 62 13	20	22.1	31	35.1	0.064
	R3/8	3109 62 17	20	22.1	31	35.1	0.067
	R1/2	3109 62 21	24	22.1	28.4	35.1	0.046

Pre-coated thread

The body swivels for positioning purposes.

5/32" (4 mm) and 5/16" (8 mm) are also available.

3199

Stud Elbow, Male BSPP and Metric Thread

Technical polymer, nickel-plated
brass, NBR



ØD	C		E	F	G	H	L	kg
3	M3x0.5	3199 03 09*	2.5	8	8.5	15	14.5	0.003
	M5x0.8	3199 03 19	3.5	8	8.5	13.5	14.5	0.003
4	M3x0.5	3199 04 09*	2.5	8	8.5	15	14.5	0.002
	M5x0.8	3199 04 19	3.5	8	8.5	13.5	14	0.002
	M7x1	3199 04 55	4.5	10	8.5	15	14	0.005
	G1/8	3199 04 10	5	13	8.5	13	14	0.006
	G1/4	3199 04 13	5.5	16	8.5	13	14	0.011
	M5x0.8	3199 06 19	3.5	8	10.5	15.5	16	0.003
6	M7x1	3199 06 55	4.5	10	10.5	17.5	16	0.006
	M10x1	3199 06 60	5	13	10.5	15	14	0.006
	M12x1.5	3199 06 67	5.5	15	10.5	15	16	0.009
	G1/8	3199 06 10	5	13	10.5	15	16	0.006
	G1/4	3199 06 13	5.5	16	10.5	15	16	0.011
	G3/8	3199 06 17	5.5	20	10.5	15.5	16	0.022
	G1/2	3199 06 21	7	24	10.5	16	16	0.027
	M10x1	3199 08 60	5	13	13.5	20.5	23	0.009
8	M12x1.5	3199 08 67	5.5	15	13.5	19.5	23	0.009
	G1/8	3199 08 10	4.5	13	13.5	20.5	23	0.009
	G1/4	3199 08 13	5.5	16	13.5	18.5	23	0.012
	G3/8	3199 08 17	5.5	20	13.5	18.5	23	0.017
	G1/2	3199 08 21	7	24	13.5	19	23	0.027
	G1/4	3199 10 13	5.5	16	16	23.5	26.5	0.014
10	G3/8	3199 10 17	5.5	20	16	22	26.5	0.017
	G1/2	3199 10 21	7.5	24	16	22	26.5	0.026
12	G1/4	3199 12 13	5.5	16	19	26.5	31	0.016
	G3/8	3199 12 17	5.5	20	19	25	31	0.019
14	G1/2	3199 12 21	7	24	19	25	31	0.029
	G3/8	3199 14 17	5.5	20	22	32.5	35.5	0.029
16	G1/2	3199 14 21	7	24	22	27	35.5	0.028
	G3/8	3199 16 17	7.5	27	27	54.5	39	0.101
	G1/2	3199 16 21	9	27	27	54.5	39	0.097

The body swivels for positioning purposes.
*Bi-material seal

Stud Fittings


3192

Stud Elbow, Female BSPP Thread

	ØD	C		E	F	G	H	L	kg
	4	G1/8	3192 04 10	8.5	13	8.5	23	14	0.010
		G1/4	3192 04 13	11.5	16	8.5	27	14	0.017
	6	G1/8	3192 06 10	8.5	13	10.5	25	16	0.010
		G1/4	3192 06 13	11.5	16	10.5	29	16	0.017
	8	G1/8	3192 08 10	8.5	13	13.5	28	23	0.012
		G1/4	3192 08 13	11.5	16	13.5	32	23	0.020
		G3/8	3192 08 17	12	19	13.5	33	23	0.026
		G1/4	3192 10 13	11	16	16	34.5	26.5	0.020
	10	G3/8	3192 10 17	12	19	16	35	26.5	0.025
		G1/2	3192 10 21	16	24	16	41	26.5	0.049
	12	G1/4	3192 12 13	11	16	19	38	30.5	0.023
		G3/8	3192 12 17	12	19	19	38.5	30.5	0.027
		G1/2	3192 12 21	16	24	19	43.5	30.5	0.050



The body swivels for positioning purposes.

Technical polymer, nickel-plated brass, NBR




3129

Extended Stud Elbow, Male BSPT Thread

	ØD	C		F	G	H	L	kg
	4	R1/8	3129 04 10	10	8.5	23	19	0.008
		R1/4	3129 04 13	14	8.5	23.5	19	0.018
	6	R1/8	3129 06 10	10	10.5	27	22.5	0.010
		R1/4	3129 06 13	14	10.5	27.5	22.5	0.020
	8	R1/8	3129 08 10	13	13.5	34.5	29.5	0.018
		R1/4	3129 08 13	14	13.5	32.5	29.5	0.022
		R3/8	3129 08 17	17	13.5	33	29.5	0.032
		R1/4	3129 10 13	15	16	39.5	34.5	0.031
	10	R3/8	3129 10 17	17	16	39.5	34.5	0.041
		R1/2	3129 10 21	21	16	39.5	34.5	0.060
	12	R1/4	3129 12 13	19	19	45.5	40.5	0.035
		R3/8	3129 12 17	19	19	45.5	40.5	0.051
		R1/2	3129 12 21	21	19	45.5	40.5	0.065
		R3/8	3129 14 17	21	22	51.5	46.5	0.064
	14	R1/2	3129 14 21	21	22	51.5	46.5	0.070

Pre-coated thread
The body swivels for positioning purposes.

Technical polymer, nickel-plated brass, NBR



Parker Legris offers the solution to enable many types of configuration options.



Stud Fittings

3169

Extended Stud Elbow, Male BSPP and Metric Thread

ØD	C		E	F	G	H	L	kg
4	M5x0.8	3169 04 19	3.5	8	8.5	23	19	0.005
	M7x1	3169 04 55	4.5	10	8.5	22.5	19	0.008
	G1/8	3169 04 10	5	13	8.5	22.5	19	0.009
	G1/4	3169 04 13	5.5	16	8.5	22.5	19	0.014
6	M5x0.8	3169 06 19	3.5	10	10.5	27.5	23	0.008
	M7x1	3169 06 55	4.5	10	10.5	26	23	0.012
	G1/8	3169 06 10	5	13	10.5	27	23	0.011
	G1/4	3169 06 13	5.5	16	10.5	27	23	0.016
8	G1/8	3169 08 10	5	13	13.5	36	29.5	0.018
	G1/4	3169 08 13	5.5	16	13.5	33	29.5	0.020
	G3/8	3169 08 17	5.5	20	13.5	33	29.5	0.028
	G1/4	3169 10 13	5.5	16	16	40.5	34.5	0.029
10	G3/8	3169 10 17	5.5	20	16	40.5	34.5	0.037
	G1/2	3169 10 21	7.5	24	16	40.5	34.5	0.042
	G1/4	3169 12 13	5.5	19	19	44.5	40.5	0.049
	G3/8	3169 12 17	5.5	20	19	42	40.5	0.040
12	G1/2	3169 12 21	7.5	24	19	42	40.5	0.049
	G3/8	3169 14 17	5.5	22	22	51	46.5	0.059
	G1/2	3169 14 21	7.5	24	22	48.5	46.5	0.063
	G3/8	3169 16 17	7.5	27	27	82.5	52	0.220
16	G1/2	3169 16 21	9	27	27	82.5	52	0.206

The body swivels for positioning purposes.

3113

45° Elbow, Male BSPT Thread

ØD	C		F	G	H	L	kg
4	R1/8	3113 04 10	10	9	21	13	0.006
6	R1/8	3113 06 10	10	11	24.5	14.5	0.006
	R1/4	3113 06 13	14	11	25	14.5	0.015
8	R1/8	3113 08 10	10	13.5	30	19.5	0.008
	R1/4	3113 08 13	14	13.5	28.5	19.5	0.015
	R3/8	3113 08 17	17	13.5	28.5	19.5	0.020
10	R1/4	3113 10 13	15	16	33.5	23	0.014
	R3/8	3113 10 17	17	16	33.5	23	0.019
	R1/2	3113 10 21	21	16	34	23	0.100
12	R1/4	3113 12 13	15	19	39	26	0.016
	R3/8	3113 12 17	17	19	39	26	0.022
	R1/2	3113 12 21	21	19	39	26	0.040

Pre-coated thread
The body swivels for positioning purposes.
This model prevents distortion of the tube.

3133

45° Elbow, Male BSPP and Metric Thread

ØD	C		E	F	G	H	L	kg
4	M5x0.8	3133 04 19	3.5	8	9	23	13	0.003
	G1/8	3133 04 10	4.5	13	9	20.5	13	0.006
6	M5x0.8	3133 06 19	3.5	8	11	28	14.5	0.003
	G1/8	3133 06 10	4.5	13	11	24	14.5	0.006
	G1/4	3133 06 13	5.5	16	11	24	14.5	0.011
8	G1/8	3133 08 10	4.5	13	13.5	31	19.5	0.011
	G1/4	3133 08 13	5.5	16	13.5	29	19.5	0.012
	G3/8	3133 08 17	5.5	20	13.5	29	19.5	0.020
10	G1/4	3133 10 13	5.5	16	16	35	23	0.014
	G3/8	3133 10 17	5.5	20	16	33.5	23	0.017
	G1/2	3133 10 21	7	24	16	33.5	23	0.026
12	G1/4	3133 12 13	5.5	16	19	40.5	26	0.016
	G3/8	3133 12 17	5.5	20	19	39	26	0.019
	G1/2	3133 12 21	7	24	19	39	26	0.028

The body swivels for positioning purposes.
This model prevents distortion of the tube.

Stud Fittings

3108

Stud Branch Tee, Male BSPT Thread

Technical polymer, nickel-plated
brass, NBR

ØD	C		F	G	H	L/2	kg
4	R1/8	3108 04 10	10	8.5	15.5	14	0.006
	R1/4	3108 04 13	14	8.5	16	14	0.015
6	R1/8	3108 06 10	10	10.5	17.5	16	0.007
	R1/4	3108 06 13	14	10.5	18	16	0.016
8	R1/8	3108 08 10	10	13.5	22	23	0.009
	R1/4	3108 08 13	14	13.5	21	23	0.016
10	R3/8	3108 08 17	17	13.5	21	23	0.020
	R1/4	3108 10 13	15	16	24	26.5	0.017
12	R3/8	3108 10 17	17	16	24	26.5	0.022
	R1/2	3108 10 21	21	16	24	26.5	0.033
14	R1/4	3108 12 13	15	19	27	31	0.021
	R3/8	3108 12 17	17	19	27	31	0.026
16	R1/2	3108 12 21	21	19	27	31	0.037
	R3/8	3108 14 17	20	22	30.5	35	0.038
16	R1/2	3108 14 21	24	22	28.5	35	0.048
	R3/8	3108 16 17	27	27	53	38.5	0.128
	R1/2	3108 16 21	27	27	53	38.5	0.124

Pre-coated thread

The body swivels for positioning purposes.

3198

Stud Branch Tee, Male BSPP and Metric Thread

Technical polymer, nickel-plated
brass, NBR


ØD	C		E	F	G	H	L/2	kg
4	M5x0.8	3198 04 19	3.5	8	8.5	17.5	14	0.003
	G1/8	3198 04 10	5	13	8.5	15	14	0.006
	G1/4	3198 04 13	5.5	16	8.5	15	14	0.011
6	M5x0.8	3198 06 19	3.5	8	10.5	19.5	16	0.004
	G1/8	3198 06 10	5	13	10.5	17	16	0.007
	G1/4	3198 06 13	5.5	16	10.5	17	16	0.012
8	G1/8	3198 08 10	4.5	13	13.5	23.5	23	0.011
	G1/4	3198 08 13	5.5	16	13.5	21.5	23	0.014
	G3/8	3198 08 17	5.5	20	13.5	21.5	23	0.019
10	G1/4	3198 10 13	5.5	16	16	26	26.5	0.017
	G3/8	3198 10 17	5.5	20	16	24	26.5	0.020
	G1/2	3198 10 21	7.5	24	16	24	26.5	0.029
12	G1/4	3198 12 13	5.5	16	19	29	31	0.021
	G3/8	3198 12 17	5.5	20	19	27	31	0.024
	G1/2	3198 12 21	7	24	19	27	31	0.033
14	G3/8	3198 14 17	5.5	20	22	32.5	35.5	0.036
	G1/2	3198 14 21	7	24	22	27	35.5	0.036
	G3/8	3198 16 17	7.5	27	27	54.5	38.5	0.121
16	G1/2	3198 16 21	9	27	27	54.5	38.5	0.117

The body swivels for positioning purposes.

3103

Stud Run Tee, BSPT Thread

Technical polymer, nickel-plated
brass, NBR


ØD	C		F	G	H	H1	L	kg
4	R1/8	3103 04 10	10	8.5	23.5	9	14.5	0.006
	R1/4	3103 04 13	14	8.5	24	9.5	14.5	0.015
6	R1/8	3103 06 10	10	10.5	27.5	10	17.5	0.007
	R1/4	3103 06 13	14	10.5	28	10.5	17.5	0.016
8	R1/8	3103 08 10	10	13.5	35	12	23	0.009
	R1/4	3103 08 13	14	13.5	34	11	23	0.015
10	R3/8	3103 08 17	17	13.5	34	11	23	0.020
	R1/4	3103 10 13	15	16	40.5	14	26.5	0.017
12	R3/8	3103 10 17	17	16	40.5	14	26.5	0.022
	R1/2	3103 10 21	21	16	40.5	14	26.5	0.033
14	R1/4	3103 12 13	15	19	46.5	15.5	31	0.028
	R3/8	3103 12 17	17	19	46.5	15.5	31	0.026
16	R1/2	3103 12 21	21	19	46.5	15.5	31	0.037
	R3/8	3103 14 17	20	22	55	19.5	35.5	0.037
18	R1/2	3103 14 21	24	22	52.5	17.5	35.5	0.048
	R3/8	3103 16 17	27	27	78	27	38.5	0.126
20	R1/2	3103 16 21	27	27	78	27	38.5	0.124

Pre-coated thread


The body swivels for positioning purposes.


Stud Fittings

3193 Stud Run Tee, Male BSPP and Metric Thread



Technical polymer, nickel-plated
brass, NBR



ØD	C		E	F	G	H	H1	L	kg
4	M5x0.8	3193 04 19	3.5	8	8.5	26	11.5	14.5	0.003
	G1/8	3193 04 10	5	13	8.5	23	8.5	14.5	0.006
	G1/4	3193 04 13	5.5	16	8.5	23	8.5	14.5	0.011
6	M5x0.8	3193 06 19	3.5	8	10.5	29.5	12.5	17.5	0.004
	G1/8	3193 06 10	5	13	10.5	27	10	17.5	0.007
	G1/4	3193 06 13	5.5	16	10.5	27	10	17.5	0.012
8	G1/8	3193 08 10	4.5	13	13.5	36.5	14	23	0.011
	G1/4	3193 08 13	5.5	16	13.5	34.5	12	23	0.014
	G3/8	3193 08 17	5.5	20	13.5	34.5	12	23	0.019
10	G1/4	3193 10 13	5.5	16	16	42	15.5	26.5	0.017
	G3/8	3193 10 17	5.5	20	16	40.5	14	26.5	0.020
	G1/2	3193 10 21	7.5	24	16	40.5	14	26.5	0.029
12	G1/4	3193 12 13	5.5	16	19	48	17	31	0.021
	G3/8	3193 12 17	5.5	20	19	46.5	15.5	31	0.024
	G1/2	3193 12 21	7	24	19	46.5	15.5	31	0.038
14	G3/8	3193 14 17	5.5	20	22	56.5	21.5	35.5	0.107
	G1/2	3193 14 21	7	24	22	51	16	35.5	0.120
16	G3/8	3193 16 17	7.5	27	27	79.5	41	38.5	0.121
	G1/2	3193 16 21	9	27	27	79.5	41	38.5	0.117

The body swivels for positioning purposes.

3148 Y Piece, Male BSPT Thread


Technical polymer, nickel-plated brass, NBR

ØD	C		F	H	K	L	N	kg
4	R1/8	3148 04 10	10	32.5	8.5	17.5	9	0.010
	R1/4	3148 04 13	14	33	8.5	17.5	9	0.019
6	R1/8	3148 06 10	10	39.5	10.5	21.5	11	0.011
	R1/4	3148 06 13	14	40	10.5	21.5	11	0.021
8	R1/8	3148 08 10	13	56.5	13.5	28	14.5	0.020
	R1/4	3148 08 13	14	55.5	13.5	28	14.5	0.025
10	R3/8	3148 08 17	16	48.5	13.5	28	14.5	0.034
	R1/4	3148 10 13	14	60	19	39	20	0.033
	R3/8	3148 10 17	16	60.5	19	39	20	0.042
12	R1/2	3148 10 21	24	61	19	39	20	0.062
	R3/8	3148 12 17	19	66	19	39	20	0.054
	R1/2	3148 12 21	21	66	19	39	20	0.059

Pre-coated thread
The body swivels for positioning purposes.

3158 Y Piece, Male BSPP and Metric Thread




Technical polymer, nickel-plated
brass, NBR

ØD	C		E	F	H	K	L	N	kg
4	M5x0.8	3158 04 19	3.5	8	32.5	8.5	17.5	9	0.006
	G1/8	3158 04 10	5	13	32	8.5	17.5	9	0.009
	G1/4	3158 04 13	5.5	16	32.5	8.5	17.5	9	0.014
6	M5x0.8	3158 06 19	3.5	10	39.5	10.5	21.5	11	0.009
	G1/8	3158 06 10	5	13	39	10.5	21.5	11	0.012
	G1/4	3158 06 13	5.5	16	39.5	10.5	21.5	11	0.017
8	G1/8	3158 08 10	5	13	49	13.5	28	14.5	0.020
	G1/4	3158 08 13	5.5	16	49.5	13.5	28	14.5	0.023
	G3/8	3158 08 17	6	19	48	13.5	28	14.5	0.030
10	G1/4	3158 10 13	5.5	16	58	16	33	17	0.031
	G3/8	3158 10 17	6	20	57.5	16	33	17	0.039
	G1/2	3158 10 21	7	24	58	16	33	17	0.053
12	G3/8	3158 12 17	6	20	62	19	39	20	0.044
	G1/2	3158 12 21	7	24	63	19	39	20	0.049

The body swivels for positioning purposes.




Tube-to-Tube Fittings

3106 Equal and Unequal Tube-to-Tube Connector




	Technical polymer, NBR 	ØD	ØD1		G	L	kg
		3	3	3106 03 00	8.5	25	0.002
			4	3106 03 04	8.5	25	0.002
			1/4	3106 04 56	11	29.5	0.010
		4	4	3106 04 00	8.5	25	0.001
			6	3106 04 06	11	28	0.002
			8	3106 04 08	13.5	38	0.005
			1/4	3106 06 56	13.5	36	0.009
		6	6	3106 06 00	10.5	28.5	0.002
			8	3106 06 08	13.5	38	0.005
			10	3106 06 10	16	42	0.007
		8	8	3106 08 00	13.5	38	0.004
			10	3106 08 10	16	42	0.008
			12	3106 08 12	19	50.5	0.026
		10	10	3106 10 00	16	42	0.006
			12	3106 10 12	19	50.5	0.022
			1/2	3106 12 62	22	56.5	0.024
		12	12	3106 12 00	19	50.5	0.009
			14	3106 12 14	22	56	0.026
			16	3106 12 16	27	61	0.066
		14	14	3106 14 00	22	56	0.014
		16	16	3106 16 00	27	60.5	0.041

3106 Equal and Unequal Tube-to-Tube Connector

Inch




	Technical polymer, NBR 	ØD	ØD1		G	L	kg
		1/4	1/4	3106 56 00	10.9	29.5	0.002
			3/8	3106 60 00	16	42	0.006
		3/8	10	3106 60 10	12	50.5	0.029
			1/4	3106 60 56	16	41	0.016
		1/2	1/2	3106 62 00	22	55	0.015
		5/32" (4 mm) and 5/16" (8 mm) also available					

3102 Equal and Unequal Elbow

	Technical polymer, NBR 	ØD	ØD1		G	L	kg
		4	4	3102 04 00	8.5	19	0.001
			6	3102 04 06	10.5	22.5	0.004
		6	6	3102 06 00	10.5	22.5	0.002
			8	3102 06 08	13.5	29.5	0.009
		8	8	3102 08 00	13.5	29.5	0.004
			10	3102 08 10	16	34.5	0.031
		10	10	3102 10 00	16	34.5	0.006
			12	3102 10 12	19	40.5	0.022
		12	12	3102 12 00	19	40.5	0.010
		14	14	3102 14 00	22	46.5	0.015
		16	16	3102 16 00	27	52	0.043

3102 Equal Elbow

Inch

	Technical polymer, NBR 	ØD	ØD1		G	L	kg
		1/4	1/4	3102 56 00	11	23.5	0.002
		3/8	3/8	3102 60 00	16	34	0.006
		1/2	1/2	3102 62 00	22	35	0.018
		5/32" (4 mm) and 5/16" (8 mm) also available					


Tube-to-Tube Fittings

3104

Equal and Unequal Tee



Technical polymer, NBR



ØD	ØD1		G	H	L/2	kg
3	3	3104 03 00	8.5	19	14.5	0.004
4	4	3104 04 00	8.5	19	14.5	0.002
	6	3104 04 06	10.5	22.5	17.5	0.007
6	4	3104 06 04	10.5	22.5	17.5	0.005
	6	3104 06 00	10.5	22.5	17.5	0.003
8	8	3104 06 08	13.5	29.5	23	0.015
	4	3104 08 04	13.5	29	22.5	0.114
8	6	3104 08 06	13.5	29.5	23	0.010
	8	3104 08 00	13.5	29.5	23	0.006
10	10	3104 08 10	16	34.5	26.5	0.021
	4	3104 10 04	16	39	31	0.027
10	8	3104 10 08	16	34.5	26.5	0.014
	10	3104 10 00	16	34.5	26.5	0.009
12	12	3104 10 12	19	40.5	31	0.036
	4	3104 12 04	19	39	31	0.034
12	10	3104 12 10	19	40.5	31	0.024
	12	3104 12 00	19	40.5	31	0.014
14	8	3104 14 08	22	46	35.5	0.054
	14	3104 14 00	22	46	35.5	0.023
16	12	3104 16 12	27	52.5	39	0.088
	16	3104 16 00	27	52	39	0.063


3104

Equal and Unequal Tee

Inch



Technical polymer, NBR



ØD	ØD1		G	H	L/2	kg
5/32	1/4	3104 04 56	11	23.5	18	0.014
1/8	1/8	3104 53 00	8.4	19	14.5	0.003
	1/4	3104 53 56	11	23.5	18	0.011
3/16	3/16	3104 55 00	10.9	27.2	21.6	0.015
1/4	5/32	3104 56 04	11	23.5	18.5	0.014
	1/4	3104 56 00	11	23	24	0.003
1/4	1/8	3104 56 53	11	23.5	18.5	0.007
	3/8	3104 56 60	16	33.5	24.5	0.017
3/8	1/4	3104 60 56	16	32.5	25.5	0.019
	1/2	3104 60 62	22	46	35	0.070
3/8	3/8	3104 60 00	16	34	26	0.009
	1/2	3104 62 00	22	46	35	0.026
1/2	1/4	3104 62 56	22.1	45.2	35.3	0.021
	3/8	3104 62 60	22	46	35	0.060


5/32" (4 mm) and 5/16" (8 mm) also available

3140

Equal and Unequal Single Y Piece



Technical polymer, NBR



ØD	ØD1		H	K	L	N	kg
4	4	3140 04 00	17.5	8.5	28.5	9	0.002
	6	3140 04 06	17.5	10.5	33	9	0.003
6	6	3140 06 00	21.5	10.5	35	11	0.003
	8	3140 06 08	22.5	13.5	41	11.5	0.005
8	8	3140 08 00	28	13.5	45	14.5	0.007
	10	3140 08 10	28	16	47	14.5	0.011
10	10	3140 10 00	33	16	53	17	0.010
	12	3140 10 12	33	19	57	17	0.018
12	12	3140 12 00	39	19	57	17	0.028

Tube-to-Tube Fittings

LF 3000®


Push-In Fittings

3107

Equal and Unequal Cross



Technical polymer, NBR



ØD	ØD1	ØD2		G	H	N	ØT	kg
4	4	4	3107 04 00	11	36	20	4.2	0.013
6	4	6	3107 04 06	11	36	20	4.2	0.010
4	4	6	3107 06 04	11	36	20	4.2	0.011
6	6	6	3107 06 00	11	36	20	4.2	0.005
8	6	8	3107 06 08	11	46	22.5	4.2	0.018
6	6	8	3107 08 06	13.5	46	22.5	4.2	0.023
8	8	8	3107 08 00	13.5	46	22.5	4.2	0.020




Boxes protect the contents and are designed to meet your requirements:

- part numbers and corresponding product pictures allow for immediate visual identification
- bar codes
- easy storage
- tamper-proof system of opening/closing
- recyclable material






Bulkhead Connector Fittings

3116 Equal Bulkhead Connector




	Technical polymer, NBR 	ØD		F	K _{max}	L1	L2	ØT _{min}	kg
		4	3116 04 00	13	5.5	15	10	10.5	0.003
		6	3116 06 00	15	8.5	18	10.5	12.5	0.004
		8	3116 08 00	18	14.5	25	13.5	15.5	0.007
		10	3116 10 00	22	14.5	27.5	15.5	18.5	0.015
		12	3116 12 00	26	18.5	33	18	22.5	0.019
		14	3116 14 00	29	20.5	37.5	20.5	25.5	0.028

3146 Equal Mixed Bulkhead Connector




	Nickel-plated brass, NBR 	ØD		F1	F2	F3	K _{max}	L1	L2	ØT _{min}	kg
		4	3146 04 00	13	13	10	7	17.5	17.5	10.5	0.018
		6	3146 06 00	15	17	13	8	19	18	12.5	0.029
		8	3146 08 00	18	19	14	8	20.5	20.5	15.5	0.036
		10	3146 10 00	22	22	19	8.5	23	24.5	18.5	0.065
		12	3146 12 00	26	25	22	8.5	27	25	22.5	0.096
		14	3146 14 00	29	29	24	10.5	27	27	25.5	0.125

Push-in connection with compression fitting

3136 Bulkhead Connector, Female BSPP Thread

	Nickel-plated brass, NBR 	ØD	C		E	F1	F2	K _{max}	L1	L2	ØT _{min}	kg
		4	G1/8	3136 04 10	9.5	13	13	7	17	11.5	10.5	0.015
			G1/4	3136 04 13	13.5	13	16	7	17	15.5	10.5	0.021
		6	G1/8	3136 06 10	9.5	15	15	8	19	10.5	12.5	0.020
			G1/4	3136 06 13	13.5	15	17	7	19	15.5	12.5	0.027
		8	G3/8	3136 06 17	12	15	22	8	19	16	12.5	0.041
			G1/8	3136 08 10	9.5	18	17	8	20.5	10.5	15.5	0.029
		10	G1/4	3136 08 13	13.5	18	17	8	20.5	14.5	15.5	0.029
			G3/8	3136 10 17	14	22	22	8.5	23	16	18.5	0.051
		12	G3/8	3136 12 17	14	26	24	8.5	27	16	22.5	0.078
			G1/2	3136 12 21	19.5	26	27	8.5	27	21.5	22.5	0.097
		16	G3/8	3136 16 17	12	29	29	10.5	30	15	27.5	0.125
			G1/2	3136 16 21	15	29	29	10.5	30	19.5	27.5	0.126




3139 Equal Bulkhead Elbow

	Technical polymer, nickel-plated brass, NBR 	ØD		F	G	H	K _{max}	L	ØT _{min}	kg
		4	3139 04 00	13	8.5	17	6.5	14.5	10.5	0.014
		6	3139 06 00	15	10.5	19.5	7	17.5	12.5	0.021
		8	3139 08 00	18	13.5	24	8	23	15.5	0.032
		10	3139 10 00	22	16	28	8.5	26	18.5	0.050
		12	3139 12 00	26	19	33	8.5	31	22.5	0.086
		14	3139 14 00	29	25.5	37.5	10.5	36	25.5	0.116




The body swivels for positioning purposes.

Multiple Fittings




3144 Equal and Unequal Multiple Y Piece

	Technical polymer, NBR		ØD	ØD1		K	K1	L	N	N1	ØT	kg
			4	4	3144 04 04	25.5	21	30.5	10	8.5	3.7	0.015
				6	3144 04 06	26	21	30.5	10	10	3.7	0.013
			6	6	3144 06 06	31.5	26.5	37.5	12	8.5	3.7	0.034
				8	3144 06 08	31.5	26.5	38	12	10	3.7	0.026




3304 Multiple Tee

	Technical polymer, NBR		ØD1	ØD2		H	L	L/2	N	ØT	kg
			6	4	3304 06 04	24.5	34	37	11.5	4.2	0.015
			8	4	3304 08 04	24.5	34	37	11.5	4.2	0.012
				6	3304 08 06	24.5	34	37	11.5	4.2	0.010
			10	6	3304 10 06	36	44	40.5	14.5	4.2	0.019
				8	3304 10 08	36	44	40.5	15.5	4.2	0.015

3306 90° Multiple Elbow

	Technical polymer, NBR		ØD1	ØD2		G	G1	H	L/2	N	N1	ØT	kg
			6	4	3306 06 04	13.5	11	18.5	36	43	11.5	4.2	0.034
			8	4	3306 08 04	13.5	11	18.5	36.5	43	11.5	4.2	0.025
				6	3306 08 06	13.5	11	18.5	36.5	43	11.5	4.2	0.022
			10	6	3306 10 06	16	13.5	23	42	52	14.5	4.2	0.048
				8	3306 10 08	16	13.5	23.5	42	52	14.5	4.2	0.036


3310 In-Line Manifold

	Treated aluminium, NBR		ØD	C		Number of Outlets	E	H	L	L1	N	kg
			4	G1/4	3310 04 13	8	10	33	114	104	11.5	0.175
			6	G1/4	3310 06 13	8	10	33	114	104	12.5	0.170
			8	G3/8	3310 08 17	6	12	33	114	104	15	0.157
			10	G1/2	3310 10 21	6	16	48	145.5	135.5	17	0.348
			12	G1/2	3310 12 21	6	16	45	158	148	20.5	0.370

Plug-In Fittings and Accessories

3182


Equal and Unequal Plug-In Elbow

	Technical polymer, NBR			G	H	H1	H2	L	kg
	ØD1	ØD2							
	4	4	3182 04 00	8.5	23	6	15.5	14	0.001
		6	3182 04 06	10.5	26.5	7	17	16	0.003
6	4	6	3182 06 04	10.5	24.5	7	15.5	16	0.001
	6	6	3182 06 00	10.5	26.5	7	17	16	0.001
8	8	8	3182 08 00	13.5	33.5	8	21.5	23	0.007
	8	8	3182 08 00	13.5	33.5	8	21.5	23	0.003
10	10	10	3182 10 00	16	39	10	24.5	26.5	0.010
	10	12	3182 10 12	19	44.5	10.5	27.5	31	0.017
12	12	12	3182 12 00	19	45.5	10.5	27.5	31	0.007

3182

Equal Plug-In Elbow


Inch

	Technical polymer, NBR			G	H	H1	H2	L	kg
	ØD1	ØD2							
	1/4	1/4	3182 56 00	11	27.5	7.5	18	18.5	0.002
	3/8	3/8	3182 60 00	16	38.5	9	24	26	0.010
1/2	1/2	1/2	3182 62 00	22	51	13	28	35	0.030

5/32" (4 mm) and 5/16" (8 mm) also available


3184

Extended Equal and Unequal Plug-In Elbow

	Technical polymer, NBR			G	H	H1	H2	L	kg
	ØD1	ØD2							
	4	4	3184 04 00	8.5	32.5	15.5	25	14	0.004
		6	3184 04 06	10.5	38.5	19	29	16	0.004
6	6	6	3184 06 00	10.5	38.5	19	29	16	0.002
	8	8	3184 06 08	13.5	49	23.5	37	23	0.010
8	8	8	3184 08 00	13.5	49	23.5	37	23	0.003
	10	10	3184 08 10	16	56	26.5	41.5	26.5	0.013
10	10	10	3184 10 00	16	56	26.5	41.5	26.5	0.010
	12	12	3184 10 12	19	62.5	28	45.5	31	0.020
12	12	12	3184 12 00	19	62.5	28	45.5	31	0.014



3180

45° Plug-In Equal Elbow



	Technical polymer, NBR			G	H	H1	H2	L	kg
	ØD1	ØD2							
	4	4	3180 04 00	9	33.5	19	21	13	0.001
	6	6	3180 06 00	11	39	21	25	14.5	0.003
8	8	8	3180 08 00	13.5	44	21.5	25.5	19.5	0.005
10	10	10	3180 10 00	16	53	27	32.5	23	0.004
12	12	12	3180 12 00	19	58.5	27.5	34	26.5	0.007

Plug-In Fittings and Accessories



3183 Equal and Unequal Plug-In Run Tee

	Technical polymer, NBR	ØD1	ØD2		G	H	H1	H2	L	kg
		4	4	3183 04 00	8.5	33	6	15.5	14.5	0.002
			6	3183 04 06	10.5	38.5	7	17	17.5	0.006
		6	6	3183 06 00	10.5	38.5	7	17	17	0.002
			8	3183 06 08	13.5	48.5	8	21.5	23	0.014
		8	8	3183 08 00	13.5	49	8	21.5	23	0.004
			10	3183 08 10	16	56.5	10.5	24.5	26.5	0.018
		10	10	3183 10 00	16	57	10.5	24.5	26.5	0.007
			12	3183 10 12	19	65.5	10.5	27.5	31	0.034
		12	12	3183 12 00	19	65.5	10.5	27.5	31	0.011



3188 Equal and Unequal Plug-In Branch Tee

	Technical polymer, NBR	ØD1	ØD2		G	H	H1	H2	L/2	kg
		4	4	3188 04 00	8.5	25	8	15.5	14.5	0.002
			6	3188 04 06	10.5	28.5	9	17	16	0.007
		6	6	3188 06 00	10.5	28.5	9	17	16	0.002
			8	3188 06 08	13.5	36.5	11	21.5	22	0.014
		8	8	3188 08 00	13.5	36.5	11	21.5	23	0.005
			10	3188 08 10	16	41	12.5	24.5	26.5	0.018
		10	10	3188 10 00	16	41	12.5	24.5	26.5	0.007
			12	3188 10 12	19	46.5	12.5	27.5	31	0.034
		12	12	3188 12 00	19	46.5	12.5	27.5	31	0.020

3142 Equal and Unequal Plug-In Single Y Piece

	Technical polymer, NBR	ØD1	ØD2		L	L1	L2	N	kg
		4	4	3142 04 00	34	21.5	17.5	9	0.002
			6	3142 04 06	35.5	21.5	17.5	9	0.004
		6	6	3142 06 00	39.5	25.5	21.5	11	0.004
			8	3142 06 08	44	25.5	21.5	11	0.015
		8	8	3142 08 00	50.5	32	28	14.5	0.007
			10	3142 08 10	53.5	32	28	14.5	0.024
		10	10	3142 10 00	57.5	36	33	17	0.010
			12	3142 10 12	60	35	33	17	0.037
		12	12	3142 12 00	66	41	39	20	0.017

3143 Multiple Plug-In Y Piece

	Technical polymer, nickel-plated brass, NBR	ØD1	ØD2		K	K1	L	L1	N	N1	kg
		4	6	3143 04 06	26	21.5	49.5	35.5	11	8.5	0.012
			8	3143 04 08	26	21.5	51	32	11	8.5	0.021
		6	8	3143 06 08	31.5	26.5	57.5	39	12	10	0.035


Plug-In Fittings and Accessories

3120

Stem Connector



Technical polymer



ØD



L

L1

kg

4	3120 04 00	34.5	12	0.001
6	3120 06 00	38.5	14	0.001
8	3120 08 00	41	18.5	0.001
10	3120 10 00	51.5	20.5	0.002
12	3120 12 00	60	24.5	0.004
14	3120 14 00	69.5	25.5	0.007


This model is available in nickel-plated brass; please use suffix 85. Example: 3120 04 00 85.
Only compatible with Parker Legris fittings.
Drawing available upon request.

3166

Plug-In Reducer



Technical polymer, NBR



ØD1

ØD2



G

L

L1

kg

3	4	3166 03 04	8.5	37.5	23.5	0.002
	6	3166 04 06	8.5	37.5	23.5	0.001
4	8	3166 04 08	8.5	37.5	19	0.001
	10	3166 04 10	12	44	22.5	0.003
	8	3166 06 08	10.5	37.5	20	0.001
	10	3166 06 10	10.5	38	17.5	0.002
6	12	3166 06 12	14.5	46	23	0.005
	14	3166 06 14	14.5	48	23	0.006
	10	3166 08 10	13.5	49	28.5	0.003
8	12	3166 08 12	13.5	49	24.5	0.004
	14	3166 08 14	17	48	23	0.007
	12	3166 10 12	21.5	56.5	33.5	0.006
10	14	3166 10 14	21.5	58.5	33.5	0.007
12	14	3166 12 14	23.5	58.5	33.5	0.010


3166

Plug-In Reducer

Inch



Technical polymer, NBR



ØD1

ØD2



G

L

L1

kg


1/4	5/16	3166 56 08	11	41	23	0.002
	3/8	3166 56 60	11	41	21	0.002

3168

Plug-In Increaser



Technical polymer, NBR



ØD1

ØD2



G

L

L1

kg

6	4	3168 06 04	10.5	35	23	0.001
	6	3168 08 06	13.5	45	31.5	0.003
8	1/4	3168 08 56	16	40	25.5	0.008
10	8	3168 10 08	16	42.5	21	0.009
12	10	3168 12 10	19	49	24.5	0.012


3168

Plug-In Increaser

Inch



Technical polymer, NBR



ØD1

ØD2



G

L

L1

kg


1/4	5/32	3168 56 04	11	41	29	0.001
	3/16	3168 56 55	20.5	41	25	0.003

Plug-In Fittings and Accessories


LF 3000®


Push-In Fittings

3126 Blanking Plug



Technical polymer






ØD		G	L	L1	kg
3	3126 03 00	6	25	13.5	0.001
4	3126 04 00	4	30	15.5	0.001
6	3126 06 00	8	33	16.5	0.001
8	3126 08 00	10	35	17.5	0.001
10	3126 10 00	12	42	21	0.002
12	3126 12 00	14	45	22	0.003
14	3126 14 00	16	49	23.5	0.005
16	3126 16 00*	19	57	30	0.063




*Nickel-plated brass

3126 Blanking Plug




Inch

	Technical polymer 	ØD		G	L	L1	kg
		1/4	3126 56 00	8	36.5	22	0.001
		3/8	3126 60 00	12	42	22	0.002
		1/2	3126 62 00	15	48.5	21.5	0.003
		5/32" (4 mm) and 5/16" (8 mm) also available					

3122 Plug-In Barb Connector

	Technical polymer 	ØD1	ØD2		ØD3	L	L1	L2	kg
		4	3.2	3122 04 53	5	37	25	17	0.004
			5	3122 04 05	7	37	25	17	0.005
		6	5	3122 06 05	7	39	25	17	0.001
		8	6.3	3122 08 56	8.5	39.5	21	17	0.001
			8	3122 08 08	10	44.5	26	22	0.001
		10	6.3	3122 10 56	8	45	24.5	17	0.002
			8	3122 10 08	10	50	29.5	22	0.002
			8	3122 12 08	10	50	26	22	0.002
		12	10	3122 12 10	12	48.5	25.5	22.5	0.002
			12.5	3122 12 62	14.5	57	34	22.5	0.004
		14	12.5	3122 14 62	14.5	59.5	34.5	22.5	0.022

3151 End Cap

	Technical polymer, NBR 	ØD		G	H	kg
		4	3151 04 00	8.5	14.7	0.001
		6	3151 06 00	10.5	16.9	0.001
		8	3151 08 00	13.5	21.9	0.002
		10	3151 10 00	16	22.2	0.003
		12	3151 12 00	19	27.7	0.006
		14	3151 14 00	22	28	0.014

Other products are available upon request; please do not hesitate to consult us.

Banjo Fittings

This range of fittings is ideal when access is only possible from above and **orientation of the tube** is required. This range of modular fittings includes single and multiple configurations, allowing **wide flexibility of design**.

Product Advantages

- Compact**
- Compact design with minimum space between fittings
 - Banjo bolt designed for maximum flow
 - Easy access, even when fittings are close together
 - Easy assembly and automatic sealing:
 - with pre-coating on taper threads
 - with an integral O-ring seal on parallel threads
 - Safe operation: orientation of tube is ensured
 - 100% leak-tested in production
 - Date coding to guarantee quality and traceability

- Modular**
- Effortless stacking of banjo bodies to allow construction of 2 to 6 outlets
 - Orientable (360°) for perfect alignment
 - Modular: tube diameters may be different



Applications

- Robotics
- Automotive Process
- Pneumatics
- Semi-Conductors
- Textile
- Packaging


Technical Characteristics

Compatible Fluids	Compressed air Other fluids: please consult us
Working Pressure	Vacuum to 20 bar
Working Temperature	-20°C to +80°C

Tightening Torque (daN.m)	Threads					
	M3 x0.5	M5 x0.8	G1/8	G1/4	G3/8	G1/2
	0.05	0.1	0.4	0.5	0.6	0.7

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Regulations


ISO 14743: Pneumatic fluid power, push-in connectors for thermoplastic tubes
DI: 97/23/EC (PED)

DI: 2002/95/EC (RoHS)
2011/65/EC


DI: 1907/2006 (REACH)

Installation Configurations

Thread and bore diameters for part numbers 3524 - 3527 - 3528 - 3529:



Thread (C)	M5x0.8	G1/8	G1/4	G3/8	G1/2
DN	2.5	5.5	8.5	11	13



Banjo Fittings

LF 3000®

Push-In Fittings

3118 Single Banjo, Male BSPP and Metric Thread

ØD	C		E	F	G	H	L1	L2	kg
3	M3x0.5	3118 03 09*	3	-	8.5	13	5	16	0.005
	M5x0.8	3118 03 19*	4	-	8.5	13	5	16	0.005
4	M5x0.8	3118 04 19*	4	-	8.5	13	5	16.5	0.004
	G1/8	3118 04 10	4	13	8.5	17	7	18.5	0.012
6	M5x0.8	3118 06 19*	4	-	10.5	13	7	18.5	0.004
	G1/8	3118 06 10	4	13	10.5	17	7	20	0.013
8	G1/4	3118 08 10	4	13	13.5	16.5	7	25	0.013
	G1/4	3118 08 13	5.5	17	13.5	21	9	27	0.024
10	G3/8	3118 08 17	5.5	20	13.5	24.5	11	29	0.038
	G1/4	3118 10 13	5.5	17	16	21	9.5	29	0.025
12	G3/8	3118 10 17	5.5	20	16	24.5	11	31	0.039
	G1/2	3118 10 21	8	25	19	27.5	13.5	36.5	0.083
12	G3/8	3118 12 17	5.5	20	19	24.5	11	34.5	0.044
	G1/2	3118 12 21	8	25	19	27.5	13.5	36.5	0.074

*With screwdriver slot

3018 Single Banjo, Male BSPT Thread

ØD	C		F	G	H	L	L1	kg
4	R1/8	3018 04 10	13	8.5	18.5	18.5	7	0.015
6	R1/8	3018 06 10	13	10.5	18.5	20	7	0.015
	R1/4	3018 06 13	17	10.5	22.5	22	9.5	0.029
8	R1/8	3018 08 10	13	13.5	18.5	25	7	0.016
	R1/4	3018 08 13	17	13.5	22.5	27	9.5	0.030
10	R3/8	3018 08 17	21	13.5	26.5	29	11	0.047
	R1/4	3018 10 13	17	16	22.5	29	9.5	0.032
12	R3/8	3018 10 17	21	16	26.5	31	11	0.048
	R1/4	3018 12 13	21	19	26.5	34.5	11	0.052
12	R3/8	3018 12 17	21	19	26.5	34.5	11	0.050
	R1/2	3018 12 21	25	19	30	37	13.5	0.086

Pre-coated thread

3124 Single Banjo, Male/Female BSPP and Metric Thread

ØD	C		E	F	G	H	L	L1	kg
4	M5x0.8	3124 04 19	4	8	8.5	19	16	5	0.006
	G1/8	3124 04 10	4	13	8.5	25.5	18.5	7	0.015
6	G1/4	3124 06 13	5.5	17	10.5	33	22	9	0.030
8	G3/8	3124 08 17	5.5	20	13.5	37.5	29	11	0.056

This product family was developed to allow assembly of a function fitting on a cylinder.

3149 Twin Banjo, Male BSPP and Metric Thread

ØD	C		E	F	G	H	L	L1	N	kg
4	M5x0.8	3149 04 19*	4	-	8.5	13	16	4.5	9	0.005
	G1/8	3149 04 10	4	13	10.5	16.5	18.5	7	11.5	0.018
6	G1/8	3149 06 10	4	13	10.5	16.5	18.5	7	11.5	0.014
	G1/4	3149 06 13	5.5	17	13.5	21	27	9.5	14.5	0.035
8	G1/4	3149 08 13	5.5	17	13.5	21	27	9.5	14.5	0.026
	G3/8	3149 08 17	5.5	20	16	24.5	31	11	17	0.053
10	G3/8	3149 10 17	5.5	20	16	24.5	31	11	17	0.042

*With screwdriver slot

3119 Double Banjo, BSPP and Metric Thread

ØD	C		E	F	G	H	L/2	kg
4	M5x0.8	3119 04 19*	4	-	8.5	13	8	0.005
	G1/8	3119 04 10	4	13	11	17	20	0.021
6	G1/8	3119 06 10	4	13	11	17	20	0.024
	G1/4	3119 06 13	5.5	17	13.5	21	26.5	0.031
8	G1/4	3119 08 13	5.5	17	13.5	21	27	0.033
	G3/8	3119 08 17	5.5	20	16	24.5	30.5	0.053
10	G3/8	3119 10 17	5.5	20	16	24.5	31	0.045

*With screwdriver slot


Banjo Fittings

3538

Single Banjo Bodies



Technical polymer, NBR




ØD	C		G	H	L	L1	kg
3	M5x0.8	3538 03 19	8.5	13	16	5	0.003
4	M5x0.8	3538 04 19	8.5	13	16	5	0.001
	G1/8	3538 04 10	10.5	14.5	18.5	7	0.002
	M5x0.8	3538 06 19	11	13	18.5	5	0.001
6	G1/8	3538 06 10	10.5	14.5	20	7	0.002
	G1/4	3538 06 13	13.5	18	22	9.5	0.003
	G1/8	3538 08 10	13.5	14.5	25	7	0.003
8	G1/4	3538 08 13	13.5	18	27	9.5	0.004
	G3/8	3538 08 17	13.5	21.5	29	11.5	0.009
	G1/4	3538 10 13	16	18	29	9.5	0.005
10	G3/8	3538 10 17	16	21.5	31	11.5	0.006
	G1/2	3538 10 21	19	22.5	36.5	13.5	0.019
12	G3/8	3538 12 17	19	21.5	34.5	11.5	0.011
	G1/2	3538 12 21	19	22.5	36.5	13.5	0.015

3539

Double Banjo Bodies



Technical polymer, NBR




ØD	C		G	H	L/2	kg
4	M5x0.8	3539 04 19	8.5	13	16	0.002
	G1/8	3539 04 10	10.5	14.4	20	0.008
6	G1/8	3539 06 10	10.5	14.4	20	0.011
	G1/4	3539 06 13	13.5	18	26	0.014
8	G1/4	3539 08 13	13.5	18	27	0.013
	G3/8	3539 08 17	16	21.5	30.5	0.020
10	G3/8	3539 10 17	16	21.5	31	0.016

3549

Twin Banjo Bodies






Technical polymer, NBR



ØD	C		G	K	L	N	kg
4	M5x0.8	3549 04 19	10	17.5	15.5	9	0.003
	G1/8	3549 04 10	14	22.5	20	12	0.007
	G1/4	3549 04 13	18.5	28	25	14.5	0.019
	G1/8	3549 06 10	14	22.5	20.5	12	0.003
6	G1/4	3549 06 13	18.5	28	25	14.5	0.017
	G3/8	3549 06 17	22.5	33	28.5	17	0.013
	G1/4	3549 08 13	18.5	28	26	14.5	0.010
8	G3/8	3549 08 17	22.5	33	29.5	17	0.020
10	G3/8	3549 10 17	22.5	33	29.5	17	0.016




Modular Banjo Fittings

3527 Single Banjo Bolts, Male BSPP and Metric Thread

	Nickel-plated brass, NBR		C		F	H	H1	kg
			M5x0.8	3527 00 19*	-	17	7.5	0.003
			G1/8	3527 00 10	13	17	7.5	0.011
			G1/4	3527 00 13	17	21	9.5	0.020
			G3/8	3527 00 17	20	24.5	11	0.033
			G1/2	3527 00 21	25	27.5	11.5	0.063




*With screwdriver slot
Full bore

3528 Stacking Banjo for 2 Body High Modules, Male BSPP and Metric Thread

	Nickel-plated brass, NBR		C		F	H	H1	H2	kg
			M5x0.8	3528 00 19*	-	24.5	7.5	18.5	0.005
			G1/8	3528 00 10	13	31	7.5	22	0.017
			G1/4	3528 00 13	17	39	9.5	27.5	0.031
			G3/8	3528 00 17	20	46	11	32.5	0.053




*With screwdriver slot
Full bore
Designed for use with 2 banjo bodies

3529 Stacking Banjo for 3 Body High Modules, Male BSPP Thread

	Nickel-plated brass, NBR		C		F	H	H1	H2	H3	kg
			G1/8	3529 00 10	13	45.5	7.5	22	36	0.023
			G1/4	3529 00 13	17	54	9.5	27.5	45.5	0.042
			G3/8	3529 00 17	20	67.5	11	32.5	54	0.069

Full bore
Designed for use with 3 banjo bodies


3524 Threaded Banjo Bolts, Male/Female BSPP and Metric Thread


	Nickel-plated brass, NBR		C		F	H	H1	kg
			M5x0.8	3524 00 19	8	17	7.5	0.005
			G1/8	3524 00 10	13	24.5	7.5	0.013
			G1/4	3524 00 13	17	33	9.5	0.027
			G3/8	3524 00 17	20	37.5	11	0.038
			G1/2	3524 00 21	26	42	11.5	0.067

Full bore

Banjo bolts 3527, 3528, 3529 and 3524 are only usable in association with the corresponding bodies for modular construction 3538, 3539 and 3549.

Thread and passage size for part numbers 3527, 3528, 3529 and 3524.

Thread	M5x0.8	G1/8	G1/4	G3/8	G1/2
	2.5	5.5	8.5	11	13



Modular Plug-In Connectors

These connectors allow a **maximum number of tube connections** in a **minimum of space**. Parker Legris offers an **ergonomic solution** to enable quick connection for the most complex installations.

Product Advantages

Panel-Mounted

- Panel mounted to a machine or bulkhead
- Reduced risk of incorrect assembly
- Possible to connect in-line
- Plated metal joiners and clips for reinforcement

In-Line

- Locating pin prevents incorrect assembly
- Cap guides the tubes and protects connections
- Aluminium and technical polymer components
- Bulkhead mountable
- Customised multi-connectors upon request

DIN Rail

- Used alongside electrical connectors
- Pressure indication
- Can be clipped side-by-side into a DIN rail profile [or Ω
- Channels or slots for labels for tube identification



Robotics
Automotive Process
Pneumatics
Semi-Conductors
Textile
Packaging

Applications

Technical Characteristics

Compatible Fluids	Compressed air Other fluids: please consult us
Working Pressure	Vacuum to 10 bar
Working Temperature	-20°C to +80°C

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials

- Multi-connectors:
- panel-mounted: zinc-plated steel, technical polymer
 - in-line: aluminium, technical polymer
 - DIN rail: technical polymer



Connections: LF 3000®



Silicone-free

Installation Configurations

Panel-Mounted



Standard assembly Customised assembly

A box contains:

- 10 units
- 20 joining clips and 4 end pins
- 4 mounting brackets
- 4 coupling clips
- 1 dismantling tool

The module is constructed from a number of symmetrical components connected by joining clips. A coupling clip locks the module closed. A dismantling tool allows disconnection.

Maximum 5 modules recommended for the mating module; the fixed module is not limited.


In-Line



Regulations

ISO 14743: Pneumatic fluid power, push-in connectors for thermoplastic tubes
DI: 97/23/EC (PED)
DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 1907/2006 (REACH)




DIN Rail Connector



Modular Plug-In Connectors

3300




Modular Plug-In Connector

	Technical polymer, NBR 	ØD		B	H	H1	K	K1	L	L1	L2	N	kg
		4	3300 04 00	21	40.5	29.5	32	20	55	22	6	11	0.078
		6	3300 06 00	28	48	38.5	39	27.5	70	28	7.5	14	0.213
		8	3300 08 00	28	50	39	39	27.5	70	28	7.5	14	0.025

Clearance hole for Ø3 mm screw

3320




Multi-Connector Male Screw Body

	Technical polymer, NBR 	ØD	C	C1		Number of Outlets	G	kg
		4	M38x1.5	M32x1.5	3320 04 00 02	2	42	0.046
			M46x1.5	M40x1.5	3320 04 00 04	4	50	0.070
			M46x1.5	M40x1.5	3320 04 00 07	7	50	0.072
			M65x1.5	M58x1.5	3320 04 00 12	12	70	0.136
		6	M38x1.5	M32x1.5	3320 06 00 02	2	42	0.050
			M46x1.5	M40x1.5	3320 06 00 04	4	50	0.070
			M46x1.5	M40x1.5	3320 06 00 07	7	50	0.070
			M38x1.5	M32x1.5	3320 08 00 02	2	45	0.050

The number of male body outlets must correspond to the same number of outlets on the female body.

3321




Multi-Connector Female Screw Body

	Technical polymer, NBR 	ØD	C	C1		Number of Outlets	G	kg
		4	M38x1.5	M32x1.5	3321 04 00 02	2	45	0.040
			M46x1.5	M40x1.5	3321 04 00 04	4	55	0.065
			M46x1.5	M40x1.5	3321 04 00 07	7	55	0.063
			M65x1.5	M58x1.5	3321 04 00 12	12	75	0.124
		6	M38x1.5	M32x1.5	3321 06 00 02	2	45	0.043
			M46x1.5	M40x1.5	3321 06 00 04	4	55	0.066
			M46x1.5	M40x1.5	3321 06 00 07	7	55	0.064
			M38x1.5	M32x1.5	3321 08 00 02	2	45	0.039


The number of female body outlets must correspond to the same number of outlets on the male body.

3329

Multi-Connector Screw Cap

	Technical polymer 	C		Number of Outlets	G	G1	L	kg
		M32x1.5	3329 00 01	2	32	42	50	0.043
		M40x1.5	3329 00 02	4-7	35	50	55	0.058
		M58x1.5	3329 00 03	12	34	70	70	0.139

Overall Dimensions for Bulkhead Mounting



Number of Outlets	L	ØD1
2	17	32.5
4-7	21	40.5
12	30.3	58.5


Modular Plug-In Connectors

3379

DIN Rail Connector for 2 Tubes



Technical polymer, NBR



ØD



H K L kg

4	3379 04 00	34.5	11	39.5	0.016
6	3379 06 00	34.5	11	39.5	0.026
8	3379 08 00	46	13	44.5	0.034


Start pressure test point on the system

3381

DIN Rail Connector for 3 Tubes



Technical polymer, NBR




ØD



H K L N kg

4	3381 04 00	36.5	11	39.5	11.5	0.012
6	3381 06 00	36.5	11	39.5	11.5	0.008
8	3381 08 00	46	13	44.5	14.5	0.013

Start pressure test point on the system



Self-Sealing and Oscillating Fittings

Parker Legris has developed these two **innovative** push-in fittings in order to integrate various functions and allow **quick installation** on pneumatic circuits.

Product Advantages

Self-Sealing Fittings

Prevents fluid flow when there is no tube connected
Circuits may remain pressurised when being checked and maintained
When connected, the compressed air flow is restored in both directions

Oscillating Fittings

Rotation matched to cylinder rod stroke
Prevents tube wear due to excessive flexing
Optimum reliability and durability
Simplifies circuit assembly



Applications

- Robotics
- Automotive Process
- Pneumatics
- Semi-Conductors
- Textile
- Packaging


Technical Characteristics

Compatible Fluids	Compressed air Other fluids: please consult us
Working Pressure	Vacuum to 20 bar (10 bar: self-sealing fitting)
Working Temperature	-20°C to +80°C

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials

Swivel Fitting



Silicone-free


Regulations

ISO 14743: Pneumatic fluid power, push-in connectors for thermoplastic tubes
DI: 97/23/EC (PED)

DI: 2002/95/EC (RoHS),
2011/65/EC
DI: 1907/2006 (REACH)


Installation Configurations

Self-Sealing Fitting



Oscillating Fitting


Tube O.D. (mm)	Torque (daN.m)	Max. Rotation Speed (turn/min.)
4	$<2.5 \cdot 10^{-3}$	190
6	$<4 \cdot 10^{-3}$	160
8	$<7 \cdot 10^{-3}$	120
10	$<11 \cdot 10^{-3}$	90
12	$<16 \cdot 10^{-3}$	80



Self-Sealing and Oscillating Fittings


3391 Self-Sealing Stud Fitting, Male BSPP Thread

Nickel-plated brass, NBR


ØD	C		E	F	H	H1	H2	ØT	kg
4	G1/8	3391 04 10	5	13	18	7.5	6	5	0.017
6	G1/8	3391 06 10	5	14	19.5	9	6	7.5	0.019
8	G1/8	3391 08 10	5	14	29.5	10	6	7.5	0.025
	G1/4	3391 08 13	5.5	16	25.5	11	8	9	0.032
10	G3/8	3391 10 17	5.5	20	27.5	13	11	10	0.055


Maximum working pressure: 10 bar

3091 Self-Sealing Stud Fitting, Male BSPT Thread






Nickel-plated brass, NBR




ØD	C		E	F	H	H1	ØT	kg
4	R1/8	3091 04 10	7.5	12	18	9.5	5	0.015
6	R1/8	3091 06 10	7.5	13	19.5	9.5	7.5	0.015
8	R1/8	3091 08 10	6.5	14	25	10.5	7.5	0.024
	R1/4	3091 08 13	11	14	25.5	13.5	9	0.021
10	R3/8	3091 10 17	11.5	17	27.5	14	10	0.035

Maximum working pressure: 10 bar
Pre-coated thread


3160 Self-Sealing Plug-In Fitting


	<p>Technical polymer, NBR</p> 	ØD		L	L1	kg
		4	3160 04 00	46	33.5	0.006
		6	3160 06 00	53.5	31	0.009
		8	3160 08 00	58	31	0.014

3159 Oscillating Elbow, Male BSPT Thread






Technical polymer, nickel-plated brass, NBR



ØD	C		F	G	H	L	kg
4	R1/8	3159 04 10	12	11	22	17.5	0.012
6	R1/8	3159 06 10	14	14	26.5	20.5	0.014
	R1/4	3159 06 13	14	14	23.5	20.5	0.022
8	R1/8	3159 08 10	17	16	32	23.5	0.036
	R1/4	3159 08 13	17	16	29	23.5	0.037
	R3/8	3159 08 17	17	16	25	23.5	0.033
10	R1/4	3159 10 13	19	19.5	37.5	29	0.053
	R3/8	3159 10 17	19	19.5	33.5	29	0.045
12	R1/4	3159 12 13	21	22	44.5	33.5	0.080
	R3/8	3159 12 17	21	22	41	33.5	0.070

Pre-coated thread

3189 Oscillating Elbow, Male BSPP and Metric Thread

	Technical polymer, nickel-plated brass, NBR 	ØD	C		E	F	G	H	L	kg
		4	M5x0.8	3189 04 19	3	12	11	24.5	17.5	0.012
			G1/8	3189 04 10	5	13	11	23	17.5	0.013
			M5x0.8	3189 06 19	3	12	14	27.5	20.5	0.017
		6	G1/8	3189 06 10	5	14	14	27	20.5	0.019
			G1/4	3189 06 13	5.5	16	14	25.5	20.5	0.023
			G1/8	3189 08 10	5	17	16	33.5	23.5	0.034
		8	G1/4	3189 08 13	5.5	17	16	31	23.5	0.034
			G3/8	3189 08 17	5.5	20	16	29.5	23.5	0.042
			G1/4	3189 10 13	5.5	19	19.5	39	29	0.058
		10	G3/8	3189 10 17	5.5	20	19.5	37	29	0.050
			G1/4	3189 12 13	5.5	21	22	46.5	33.5	0.074
			G3/8	3189 12 17	5.5	21	22	45.5	33.5	0.072

Accessories for Push-In Fittings

Parker Legris has designed these different accessories to improve **safety** and circuit **identification**.

Product Advantages

Safety

- Protection of operators and equipment
- Prevents accidental disconnection
- Disconnection only possible with tooling
- Resistance to grease and cleaning agents

Ergonomic

- Colour-coding for fluid circuit identification (6 colours)
- Setting and fixing of your circuits thanks to clips and release button covers
- Easy disconnection with tool where access is difficult
- Adapted to meet all installation configurations



Applications

- Robotics
- Automotive Process
- Pneumatics
- Semi-Conductors
- Textile
- Water Treatment
- Beverage Dispensers

Technical Characteristics

Compatible Ranges	LF 3000®, LIQUIfit®
Working Temperature	-20°C to +95°C
Materials	Tamper-proof safety clip, release button cover, clip: technical polymer Reducer and plug: nickel-plated brass

Installation Process

Tamper-Proof Safety Clip



Coloured Release Button Covers


Coloured release button covers can be mounted on LF 3000® and LIQUIfit® fittings, supplied fitted with manual release buttons.

5 colours are available and allows colour coding to be used throughout circuits.



Disconnection Tool

In cases where access is difficult, this tool can be particularly useful.



Clip Strips

Clips are also designed to fix LF 3000® fittings in series within a minimum of space.



The complete range of accessories can be found in Chapter 9.

Accessories for Push-In Fittings




LF 3000®

Push-In Fittings

3130 Tamper-Proof Safety Clip



Technical polymer	ØD							H	K	kg
	4	3130 04 01	3130 04 02	3130 04 03	3130 04 04	3130 04 05	3130 04 10	6.6	3	0.001
	6	3130 06 01	3130 06 02	3130 06 03	3130 06 04	3130 06 05	3130 06 10	7.8	3.1	0.001
	8	3130 08 01	3130 08 02	3130 08 03	3130 08 04	3130 08 05	3130 08 10	9.5	4.3	0.001
	10	3130 10 01	3130 10 02	3130 10 03	3130 10 04	3130 10 05	3130 10 10	10.8	4.2	0.002
	12	3130 12 01	3130 12 02	3130 12 03	3130 12 04	3130 12 05	3130 12 10	12.5	5.1	0.003
	14	3130 14 01	3130 14 02	3130 14 03	3130 14 04	3130 14 05	3130 14 10	15	6	0.004

CLIP Clip Strip for Tubes and Fittings

Technical polymer	ØD		H	K	N	kg
	4	CLIP 04 00	9	13.5	10.5	0.007
	6	CLIP 06 00	10.5	13	10.5	0.004
	8	CLIP 08 00	12.5	10.5	12	0.007
	10	CLIP 10 00	14	12	15	0.005
	12	CLIP 12 00	16.5	14	16.5	0.009
	14	CLIP 14 00	18	16	20.5	0.008







Delivered in boxes of 10 strips of the same diameter (complete with selftapping screws of 95 mm length)

3000 Disconnection Tool




Treated steel	H	H1	L	kg
	25	20	96	0.021
	3000 70 00			

For disconnecting LF 3000® tubing/fittings where access is difficult, we recommend the use of this disconnection tool.

3110 Coloured Release Button Covers




Technical polymer	ØD						kg
	4	3110 04 00	3110 04 02	3110 04 03	3110 04 04	3110 04 05	0.001
	6	3110 06 00	3110 06 02	3110 06 03	3110 06 04	3110 06 05	0.001
	8	3110 08 00	3110 08 02	3110 08 03	3110 08 04	3110 08 05	0.001
	10	3110 10 00	3110 10 02	3110 10 03	3110 10 04	3110 10 05	0.001
	12	3110 12 00	3110 12 02	3110 12 03	3110 12 04	3110 12 05	0.001
	14	3110 14 00	3110 14 02	3110 14 03	3110 14 04	3110 14 05	0.002

0178 Reducer, Male/Female BSPP and Metric Thread

Nickel-plated brass, NBR	C1	C2		E	F	L	kg
	M7x1	M5x0.8	0178 55 19	5	10	12	0.005
	G1/8	M5x0.8	0178 10 19	5	13	9	0.006
	G1/4	G1/8	0178 13 10	5.5	16	9.5	0.006
	G3/8	G1/8	0178 17 10	5.5	20	10.5	0.016
		G1/4	0178 17 13	5.5	20	10.5	0.011
	G1/2	G1/4	0178 21 13	7.5	24	12.5	0.024
		G3/8	0178 21 17	7.5	24	12.5	0.016
	G3/4	G1/2	0178 27 21	7.5	32	13.5	0.035

With integrated O-ring seal

0222 Internal Hex Plug, Male BSPP and Metric Thread

Nickel-plated brass, NBR	C		E	F	F1	H	kg
	M5x0.8	0222 19 00	3.5	8	2.5	7	0.002
	M7x1	0222 55 00	5	10	3	8.5	0.003
	G1/8	0222 10 00	5	13	5	8.5	0.006
	G1/4	0222 13 00	5.5	16	6	9.5	0.010
	G3/8	0222 17 00	5.5	20	8	10.5	0.019
	G1/2	0222 21 00	7.5	24	10	12	0.030

With integrated O-ring seal



LF 3200 (3 mm) Push-In Fittings Range

Stud Fittings

- 3281**
Metric
Page 1-41
- 3299**
Metric
Page 1-41
- 3229**
Metric
Page 1-41
- 3298**
Metric
Page 1-41
- 3293**
Metric
Page 1-41
- 3218**
Metric
Page 1-42

Tube-to-Tube Fittings and Accessories

- 3206**
Straight
Page 1-43
- 3202**
Elbow
Page 1-43
- 3204**
Tee
Page 1-43
- 3266**
Reducer
Page 1-43
- 3226**
Plug
Page 1-43

LF 3200: 3 mm

Push-In Fittings

LF 3200 Push-In Fittings (3 mm)

Miniature pneumatic installations are very precise and sensitive systems, having specific operating characteristics. Consequently, Parker Legris has developed this **ergonomic** range of brass push-in fittings for its **mechanical robustness** and **compactness**.

Product Advantages

Compact & Lightweight	25% smaller than other fittings on the market for optimum actuator dimensions Minimum weight for maximum efficiency Reduces energy consumption and limits actuator wear
Resistance & Performance	All brass components for excellent impact resistance Gripping system with collet for increased robustness and service life Excellent resistance to high operating pressures
Reliability	100% leak-tested in production Date coding to guarantee quality and traceability Ideal for very sensitive applications Corrosion-resistant



Applications


- Pneumatic Panels
- Robotics
- Semi-Conductors
- Textile
- Pneumatics
- Vacuum

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	Vacuum to 20 bar
Working Temperature	-15°C to +80°C
Tightening Torque (daN.m)	0.01 to 0.1

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials




Silicone-free

Regulations

ISO 14743 ISO 14743: Pneumatic fluid power, push-in connectors for thermoplastic tubes

DI: 97/23/EC (PED)
DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 94/9/EC (ATEX)
RG: 1907/2006 (REACH)

Installation Configurations





The LF 3200 fitting, connected with a 3 mm polyurethane or antistatic polyurethane tube, is the perfect solution for compact installations:



- which are highly stressed
- whose reliability is critical

Stud Fittings



3281 Stud Fitting, Male Metric Thread

	Nickel-plated brass, NBR		ØD	C		F	G	H	kg
			3	M3x0.5	3281 03 09	1.5	6	9.5	0.001
				M5x0.8	3281 03 19	1.5	8	9.5	0.002



3299 Compact Stud Elbow, Male Metric Thread

	Nickel-plated brass, NBR		ØD	C		F	G	H	J	L	kg
			3	M3x0.5	3299 03 09	6	6	13.5	6	13.5	0.004
				M5x0.8	3299 03 19	8	6	13	6	13.5	0.005



3229 Extended Stud Elbow, Male Metric Thread

	Nickel-plated brass, NBR		ØD	C		F	G	H	J	L	kg
			3	M3x0.5	3229 03 09	6	6	16	6	13.5	0.004
				M5x0.8	3229 03 19	8	6	17	6	13.5	0.005

3298 Stud Branch Tee, Male Metric Thread

	Nickel-plated brass, NBR		ØD	C		F	G	H	J	L	kg
			3	M3x0.5	3298 03 09	6	6	13.5	6	20.5	0.004
				M5x0.8	3298 03 19	8	6	13	6	20.5	0.005

3293 Stud Run Tee, Male Metric Thread




	Nickel-plated brass, NBR		ØD	C		F	G	H	J	L	kg
			3	M3x0.5	3293 03 09	6	6	20	6	13.5	0.004
				M5x0.8	3293 03 19	8	6	20	6	13.5	0.005

LF 3200: 3 mm

Stud Fittings




3218

Single Banjo, Male Metric Thread




		Nickel-plated brass, NBR 	ØD	C			G	H	H1	J	L	kg
3				M3x0.5	3218 03 09		6	9.5	4	6	12.5	0.002
				M5x0.8			6	10.5	4.5	8	15	0.005

Tube-to-Tube Fittings and Accessories




3206 Equal Tube-to-Tube Connector

	Nickel-plated brass, NBR		ØD		G	L	kg
			3	 3206 03 00	6	17	0.002




3202 Equal Elbow

	Nickel-plated brass, NBR		ØD		G	J	L	kg
			3	 3202 03 00	6	6	13.5	0.003




3204 Equal Tee

	Nickel-plated brass, NBR		ØD		G	H	J	L	L1	kg
			3	 3204 03 00	6	13.5	6	20.5	10.25	0.004

3266 Plug-In Reducer

	Nickel-plated brass, NBR, technical polymer		ØD	ØD1		G	L	L1	kg
			3	4	 3266 03 04	6	28	19	0.001

3226 Blanking Plug

	Nickel-plated brass		ØD			L	L1	kg
			3	 3226 03 00		20	10	0.001

LF 3200: 3 mm

Range of LIQUIfit® Push-In Fittings

Stud Fittings

Straights

6505
BSPT
Page 1-48



6315
BSPT
Page 1-48



6353
BSPP
Page 1-49



6521
BSPT
Page 1-50



Straights - Inch

6505
NPTF/BSPT
Page 1-48



6315
NPTF
Page 1-49



6353
BSPP
Page 1-49



6352
BSPP
Page 1-49



6325
UNS
Page 1-49



6521
NPTF/BSPT
Page 1-50



Carstick®

6300
Page 1-50



Carstick® - Inch

6300
Page 1-50



Elbows

6579
BSPT
Page 1-51



6509
BSPT
Page 1-51



Elbows - Inch

6579
BSPT/NPTF
Page 1-51



6509
BSPT/NPTF
Page 1-52



Tees

6508
BSPT
Page 1-52



6503
BSPT
Page 1-53



Tees - Inch

6508
BSPT/NPTF
Page 1-53



6503
BSPT/NPTF
Page 1-53



Plugs

6355
BSPT
Page 1-53



Tube-to-Tube Fittings

Straight

6306
Page 1-54



Straight - Inch

6306
Page 1-54



Elbow

6302
Page 1-54



Elbow - Inch

6302
Page 1-54



Tee

6304
Page 1-55



Tee - Inch

6304
Page 1-55



Y

6340
Page 1-55



Y - Inch

6340
Page 1-55



Cross

6307
Page 1-56



Cross - Inch

6307
Page 1-56



Bulkhead Connectors

Straight

6316
Page 1-56



Straight - Inch

6316
Page 1-56



Plug-In Fittings and Accessories

Elbows

6382
Page 1-57



6380
Page 1-57



6382
Page 1-57



Tees

6383
Page 1-57



6388
Page 1-57



6388
Page 1-58



Accessories

6366
Page 1-58



6326
Page 1-58



6322
Page 1-59



6351
Page 1-59



Accessories - Inch

6366
Page 1-58



6368
Page 1-58



6326
Page 1-59



6322
Page 1-59



6351
Page 1-59



Range of LIQUIfit+ Push-In Fittings

Stud Fittings

Straight - Inch

6333

Page 1-63



Tube-to-Tube Fittings

Straight - Inch

6336

Page 1-63



Elbow - Inch

6332

Page 1-63



Plug-In Fittings

Elbow - Inch

6331

Page 1-63



LIQUIfit® and LIQUIfit+ Accessories

3130

Page 1-60

3110

Page 1-60


0605

Page 1-60



Part Number Construction

Example: 6505 08 17WP2



LIQUIfit® Push-In Fittings

This "eco-designed" range proposes an **innovative alternative** for water applications; **no fluid contamination** occurs and **environmental protection is guaranteed**. These fittings ensure **reliable and compact** connections for **liquid transfer** applications.

Product Advantages

Innovative Technology & Concept

- Ergonomic and aesthetic design
- The most compact product on the market for water, beverages and liquid foodstuffs
- Easy-to-clean external surfaces
- Push-in connection and disconnection
- Full flow
- Use with a pre-prepared metallic tubing
- Gripping system preventing any pumping effect
- Eco-designed (materials, manufacturing process, weight, dimensions and performance)

Optimal Performance

- Patented sealing technology
- 100% leak-tested in production
- Date coding to guarantee quality and traceability
- Wide range of shapes and numerous configurations

High Performance Material

- Bio-sourced polymer meeting the most severe food process regulations
- Suitable for contact with water and beverages
- Excellent chemical and mechanical resistance, even at high temperature
- Free of bisphenol A and phthalates, conforming with regulations



Hot & Cold Drinks Dispensers
Neutral Gases
Cooling Systems
Food Process
Water Purification Systems
Water Dispensers
Medical


Applications

Technical Characteristics

Compatible Fluids	Water, beverages, CO ₂ (inert use) Chemical fluids: please consult us		
Working Pressure	Vacuum to 16 bar		
Working Temperature	-10°C to +95°C		
Tightening Torques (BSPT/NPTF)	Thread	1/8" and 1/4"	3/8" and 1/2"
	daN.m	0.15	0.30

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Regulations

DI: 2002/95/EC (RoHS), 2011/65/EC
RG: 1935/2004/EC
FDA: 21 CFR
NSF 51 at 95°C
NSF/ANSI 61 - C HOT

DM 174
KTW: fittings, on request
WRAS
ACS

Pressure and Temperature of the Different Diameters and Related Products of the LIQUIfit® Range

-10°C		Pressure (bar)	
mm Ø	inch Ø	Fittings	Tubing
4	5/32	16	16
6	1/4	16	16
8	5/16	16	16
10	3/8	13	15
12	1/2	11	11

+1°C		Pressure (bar)	
mm Ø	inch Ø	Fittings	Tubing
4	5/32	16	16
6	1/4	16	16
8	5/16	16	16
10	3/8	13	15
12	1/2	11	11

+20°C		Pressure (bar)	
mm Ø	inch Ø	Fittings	Tubing
4	5/32	16	16
6	1/4	16	16
8	5/16	16	16
10	3/8	13	15
12	1/2	11	11


+40°C		Pressure (bar)	
mm Ø	inch Ø	Fittings	Tubing
4	5/32	16	16
6	1/4	16	16
8	5/16	16	16
10	3/8	13	15
12	1/2	11	11

+65°C		Pressure (bar)	
mm Ø	inch Ø	Fittings	Tubing
4	5/32	10	10
6	1/4	10	10
8	5/16	10	10
10	3/8	7	7
12	1/2	7	7

+95°C		Pressure (bar)	
mm Ø	inch Ø	Fittings	Tubing
4	5/32	4	4
6	1/4	4	4
8	5/16	4	4
10	3/8	4	4
12	1/2	4	4

Environmental Footprint

Example: representation of the environmental footprint of an equal tube-to-tube connector



Double Union


- Market Standard in POM
- Market Standard in PP
- PARKER LEGRIS

LIQUIfit® Tube-to-Tube Connector



Market Standard

Tube-to-Tube Connector



Environmental Approach

The Life Cycle Analysis (LCA) offers a true alternative in terms of environmental differentiation.

We carried out a comparative LCA on the market of drinking water between 3 Parker Legris fittings and the standard products on the market.

This analysis relies on ISO 14020, ISO 14025 and IEC PAS 62545 standards and the results are presented in a report approved by an ethics committee (Bureau Veritas).



RWD: Raw Material Depletion
ED: Energy Depletion
WD: Water Depletion
GW: Global Warming
OZ: Ozone Depletion
AT: Air Toxicity

POC: Photochemical Ozone Creation
AA: Air Acidification
WT: Water Toxicity
WE: Water Eutrophication
HWP: Hazardous Waste Production

Stud Fittings

6505

Stud Fitting, Male BSPT Thread

	Bio-based polymer, EPDM		F	F1	H	kg
	ØD	C				
4	R1/8	6505 04 10WP2	11	3	18	0.003
	R1/4	6505 04 13WP2	14	3	18	0.004
6	R1/8	6505 06 10WP2	11	4	18	0.002
	R1/4	6505 06 13WP2	14	4	18	0.004
8	R1/8	6505 08 10WP2	17	6	20	0.004
	R1/4	6505 08 13WP2	14	6	20	0.004
10	R3/8	6505 08 17WP2	17	6	20	0.005
	R1/4	6505 10 13WP2	17	7	21.5	0.005
12	R3/8	6505 10 17WP2	19	7	21.5	0.007
	R1/2	6505 10 21WP2	22	7	21.5	0.010
12	R3/8	6505 12 17WP2	19	9	24.5	0.008
	R1/2	6505 12 21WP2	22	9	24.5	0.012

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating.

6505

Stud Fitting, Male NPTF Thread

Inch

	Bio-based polymer, EPDM		F	F1	H	kg
	ØD	C				
1/4	NPT1/8	6505 56 11WP2	1/2	5/32	17	0.002
	NPT1/4	6505 56 14WP2	9/16	5/32	17	0.003
3/8	NPT3/8	6505 56 18WP2	3/4	1/4	21,5	0,004
	NPT1/8	6505 60 11WP2	3/4	5/32	22,1	0,005
1/2	NPT1/4	6505 60 14WP2	3/4	1/4	22	0.006
	NPT3/8	6505 60 18WP2	3/4	1/4	22	0.007
1/2	NPT1/2	6505 60 22WP2	15/16	1/4	27	0,012
	NPT3/8	6505 62 18WP2	15/16	3/8	28	0.012
1/2	NPT1/2	6505 62 22WP2	15/16	3/8	28	0.013

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating.
6505 56 18WP3, 6505 60 11WP3 and 6505 60 22WP3 are also available.

6505

Stud Fitting, Male BSPT Thread

Inch

	Bio-based polymer, EPDM		F	F1	H	kg
	ØD	C				
1/4	R1/8	6505 56 10WP2	11	5	17	0.002
	R1/4	6505 56 13WP2	14	5	17	0.003
3/8	R1/4	6505 60 13WP2	17	7	22	0.006
	R3/8	6505 60 17WP2	19	7	22	0.006
1/2	R1/2	6505 60 21WP2	22	7	28	0.012
	R3/8	6505 62 17WP2	24	9	28	0.014
1/2	R1/2	6505 62 21WP2	24	9	28	0.017

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
5/32" (4 mm) and 5/16" (8 mm) also available.
Thread without pre-coating.

6315




Stud Fitting, Female BSPT Thread

	Bio-based polymer, EPDM		F	H	kg
	ØD	C			
6	R1/8	6315 06 10WP2	13	32	0.003
	R1/4	6315 06 13WP2	16	33	0.004
8	R1/4	6315 08 13WP2	16	33.5	0.004
	R3/8	6315 08 17WP2	20	36	0.009




These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

Stud Fittings




6315
Stud Fitting, Female NPTF Thread
Inch

		Bio-based polymer, EPDM						
		ØD	C		F	H	kg	
		1/4	NPT1/4	6315 56 14WP2	11/16	30	0.003	
		3/8	NPT3/8	6315 60 18WP2	13/16	36	0.007	
These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).								




6353
Tap Connector Cone Type, Female BSPP Thread

	<p>Bio-based polymer, EPDM</p> 	ØD	C		E	F	H	kg
		6	G3/4	6353 06 27WP2	10	32	32	0.011
		8	G3/4	6353 08 27WP2	10	32	40.5	0.017
		10	G1/2	6353 10 21WP2	12	27	36	0.011
		These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).						




6353
Tap Connector Cone Type, Female BSPP Thread
Inch

	<p>Bio-based polymer, EPDM</p> 	ØD	C		E	F	H	kg
		1/4	G3/4	6353 56 27WP2	10	32	31	0.006
		3/8	G1/2	6353 60 21WP2	12	27	36	0.011
			G3/4	6353 60 27WP2	10	32	41	0.018
		1/2	G3/4	6353 62 27WP2	10	32	44.5	0.014
<p>These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).</p>								

6352
Stud Fitting Flat Type, Female BSPP Thread
Inch

	<p>Bio-based polymer, EPDM</p> 	ØD	C		E	F	H	kg
		5/16	G1/2	6352 08 21WP2	10.5	27	37	0.009
			G5/8	6352 08 23WP2	10.5	29	32	0.013
		3/8	G3/8	6352 60 17WP2	12	22	36	0.008
			G1/2	6352 60 21WP2	12	27	36	0.011
		1/2	G5/8	6352 62 23WP2	10.5	29	32	0.013
These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).								

6325
Faucet Connector, Female UNS Thread
Inch

	<p>Bio-based polymer, EPDM</p> 					E	F	H	kg
		1/4	UNS7/16-24	6325 56 133WP2	7	9/16	31	0.002	
		3/8	UNS7/16-24	6325 60 133WP2	7	9/16	32	0.004	
		These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).							

Stud Fittings

6521 Stud Standpipe, Male BSPT Thread

	Bio-based polymer	ØD	C		F	H	kg
6		R1/8	6521 06 10WP2		13	19	0.002
		R1/4	6521 06 13WP2		14	19	0.003
		R3/8	6521 06 17WP2		17	19	0.004
8		R1/8	6521 08 10WP2		19	23	0.003
		R1/4	6521 08 13WP2		19	23	0.004
		R3/8	6521 08 17WP2		19	23	0.004
10		R1/4	6521 10 13WP2		19	25	0.004
		R3/8	6521 10 17WP2		19	25	0.005
		R1/2	6521 10 21WP2		22	25	0.008
12		R3/8	6521 12 17WP2		22	28	0.005
		R1/2	6521 12 21WP2		22	28	0.007

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating.

6521 Stud Standpipe, Male NPTF Thread Inch

	Bio-based polymer	ØD	C		F	H	kg
1/4		NPT1/8	6521 56 11WP2		1/2	19	0.001
		NPT1/4	6521 56 14WP2		1/2	19	0.002
		NPT3/8	6521 56 18WP2		3/4	19.5	0.004
3/8		NPT1/4	6521 60 14WP2		3/4	25	0.004
		NPT3/8	6521 60 18WP2		3/4	25	0.004
1/2		NPT3/8	6521 62 18WP2		15/16	31	0.010
		NPT1/2	6521 62 22WP2		15/16	32.5	0.013

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating.

6521 Stud Standpipe, Male BSPT Thread Inch

	Bio-based polymer	ØD	C		F	H	kg
1/4		R1/8	6521 56 10WP2		14	19	0.001
		R1/4	6521 56 13WP2		14	19	0.002
		R3/8	6521 56 17WP2		17	19	0.004
3/8		R1/4	6521 60 13WP2		19	25	0.004
		R3/8	6521 60 17WP2		19	25	0.004
1/2		R3/8	6521 62 17WP2		24	31.5	0.006
		R1/2	6521 62 21WP2		24	31.5	0.009

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32" (4 mm) and 5/16" (8 mm) also available.
Thread without pre-coating.

6300 LIQUIfit® Cartridge

	Brass, EPDM	ØD		G	H	kg
4			6300 04 00	8	10	0.002
6			6300 06 00	10	11.5	0.002
8			6300 08 00	13	15	0.003
10			6300 10 00	15.5	17	0.005
12			6300 12 00	18.5	19.5	0.010

50 cartridges per Carstick®
Cavity dimensions are available in Chapter 2.




6300 LIQUIfit® Cartridge Inch

	Brass, EPDM	ØD		G	H	kg
1/4			6300 56 00	10.5	12.5	0.002
3/8			6300 60 00	15.5	17	0.005
1/2			6300 62 00	22	23	0.011

50 cartridges per Carstick®
5/32" (4 mm) and 5/16" (8 mm) also available.
Cavity dimensions are available in Chapter 2.

Stud Fittings




6579 Fixed Elbow, Male BSPT Thread

		ØD	C		G	H	J	L	kg
6			R1/8	6579 06 10WP2	11	14	10	19	0.002
			R1/4	6579 06 13WP2	11	14	10	19	0.003
			R3/8	6579 06 17WP2	11	14	10	19	0.004

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating.

6579 Fixed Elbow, Male NPTF Thread




Inch

		ØD	C		G	H	J	L	kg
1/4			NPT1/8	6579 56 11WP2	11	22	3/8	18	0.009
			NPT1/4	6579 56 14WP2	11	26	3/8	18	0.003
			NPT3/8	6579 56 18WP2	11	26.5	3/8	18	0.004
3/8			NPT1/4	6579 60 14WP2	16	32	1/2	26	0.006
			NPT3/8	6579 60 18WP2	16	32	1/2	26	0.006

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating.




6579 Fixed Elbow, Male BSPT Thread

Inch

		ØD	C		G	H	J	L	kg
1/4			R1/8	6579 56 10WP2	11	22	10	18	0.002
			R1/4	6579 56 13WP2	11	26	10	18	0.003
			R3/8	6579 56 17WP2	11	26	10	18	0.004
3/8			R1/4	6579 60 13WP2	16	31.5	13	26	0.006
			R3/8	6579 60 17WP2	16	32	13	26	0.006

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating.

6509 Stud Elbow, Male BSPT Thread

		ØD	C		F	G	H	L	kg
6			R1/8	6509 06 10WP2	13	10.5	28	24	0.037
			R1/4	6509 06 13WP2	14	10.5	28	24	0.007
			R3/8	6509 06 17WP2	17	10.5	28	24	0.008
8			R1/8	6509 08 10WP2	19	13.5	34	29.5	0.010
			R1/4	6509 08 13WP2	19	13.5	34	29.5	0.011
			R3/8	6509 08 17WP2	19	13.5	34	29.5	0.011
10			R1/4	6509 10 13WP2	19	16	38	34.5	0.019
			R3/8	6509 10 17WP2	19	16	38	34.5	0.020
			R1/2	6509 10 21WP2	22	16	38	34.5	0.023
12			R3/8	6509 12 17WP2	22	19	44	40	0.022
			R1/2	6509 12 21WP2	22	19	44	40	0.024

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating; the body swivels for positioning purposes.

Complementary LIQUIfit® Range Products

The other LIQUIfit® range products are presented in the corresponding chapters of this catalogue:

Technical Tubing and Hose

Advanced PE

P. 3-26



Function Fittings

Non-Return Valves

P. 4-44



Industrial Ball Valves

LIQUIfit® Ball Valves

P. 6-34



Stud Fittings


6509

Elbow, Male NPTF Thread

Inch



Bio-based polymer, EPDM



ØD	C		F	G	H	L	kg
1/4	NPT1/8	6509 56 11WP2	1/2	11	28	23.5	0.003
	NPT1/4	6509 56 14WP2	9/16	11	28	23.5	0.004
	NPT3/8	6509 56 18WP2	3/4	11	28.5	23.5	0.006
3/8	NPT1/4	6509 60 14WP2	3/4	16	38	34	0.010
	NPT3/8	6509 60 18WP2	3/4	16	38	34	0.011
1/2	NPT3/8	6509 62 18WP2	15/16	22	50.5	46.5	0.024
	NPT1/2	6509 62 22WP2	15/16	22	51.5	46.5	0.027

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

Thread without pre-coating; the body swivels for positioning purposes.


6509

Elbow, Male BSPT Thread

Inch



Bio-based polymer, EPDM



ØD	C		F	G	H	L	kg
1/4	R1/8	6509 56 10WP2	14	11	28	23.5	0.003
	R1/4	6509 56 13WP2	14	11	28	23.5	0.004
	R3/8	6509 56 17WP2	17	11	28	23.5	0.006
3/8	R1/4	6509 60 13WP2	19	16	38	34	0.010
	R3/8	6509 60 17WP2	19	16	38	34	0.011
1/2	R3/8	6509 62 17WP2	24	22	50.5	46.5	0.024
	R1/2	6509 62 21WP2	24	22	50.5	46.5	0.027

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32" (4 mm) and 5/16" (8 mm) also available.


Thread without pre-coating; the body swivels for positioning purposes.

6508

Branch Tee, Male BSPT Thread



Bio-based polymer, EPDM



ØD	C		F	G	H	L/2	kg
6	R1/8	6508 06 10WP2	13	10.5	28	18	0.008
	R1/4	6508 06 13WP2	14	10.5	28	18	0.009
	R3/8	6508 06 17WP2	17	10.5	28	18	0.010
8	R1/8	6508 08 10WP2	19	13.5	34	23	0.012
	R1/4	6508 08 13WP2	19	13.5	34	23	0.013
	R3/8	6508 08 17WP2	19	13.5	34	23	0.013
10	R1/4	6508 10 13WP2	19	16	38	26.5	0.018
	R3/8	6508 10 17WP2	19	16	38	26.5	0.019
	R1/2	6508 10 21WP2	22	16	38	26.5	0.022
12	R3/8	6508 12 17WP2	22	19	44	31	0.024
	R1/2	6508 12 21WP2	22	19	44	31	0.026

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

Thread without pre-coating; the body swivels for positioning purposes.


6508

Branch Tee, Male NPTF Thread

Inch



Bio-based polymer, EPDM



ØD	C		F	G	H	L/2	kg
1/4	NPT1/8	6508 56 11WP2	1/2	11	28	18	0.004
	NPT1/4	6508 56 14WP2	9/16	11	28	18	0.005
	NPT3/8	6508 56 18WP2	3/4	11	29	18	0.007
3/8	NPT1/4	6508 60 14WP2	3/4	16	38	26	0.013
	NPT3/8	6508 60 18WP2	3/4	16	38	26	0.013
1/2	NPT3/8	6508 62 18WP2	15/16	22	50	35.5	0.031
	NPT1/2	6508 62 22WP2	15/16	22	51	35.5	0.034

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

Thread without pre-coating; the body swivels for positioning purposes.

Stud Fittings

6508

Branch Tee, Male BSPT Thread

Inch

	ØD	C		F	G	H	L/2	kg
1/4	R1/8	6508 56 10WP2		13	11	28	18	0.004
	R1/4	6508 56 13WP2		14	11	28	18	0.005
	R3/8	6508 56 17WP2		17	11	28	18	0.007
3/8	R1/4	6508 60 13WP2		19	16	38	26	0.013
	R3/8	6508 60 17WP2		19	16	38	26	0.013
1/2	R3/8	6508 62 17WP2		24	22	50	35.5	0.032
	R1/2	6508 62 21WP2		24	22	50	35.5	0.032

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32" (4 mm) and 5/16" (8 mm) also available.
Thread without pre-coating; the body swivels for positioning purposes.

6503

Run Tee, Male BSPT Thread

	ØD	C		F	G	H	H1	L	kg
6	R1/8	6503 06 10WP2		13	10.5	40	22	18.5	0.008
	R1/4	6503 06 13WP2		14	10.5	40	22	18.5	0.009
	R3/8	6503 06 17WP2		17	10.5	40	22	18.5	0.010
8	R1/8	6503 08 10WP2		19	13.5	50	27	23	0.012
	R1/4	6503 08 13WP2		19	13.5	50	27	23	0.013
	R3/8	6503 08 17WP2		19	13.5	50	27	23	0.013
10	R1/4	6503 10 13WP2		19	16	56.5	30	26.5	0.018
	R3/8	6503 10 17WP2		19	16	56.5	30	26.5	0.019
	R1/2	6503 10 21WP2		22	16	56.5	30	26.5	0.022
12	R3/8	6503 12 17WP2		22	19	65.5	34.5	31	0.024
	R1/2	6503 12 21WP2		22	19	65.5	34.5	31	0.026

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating; the body swivels for positioning purposes.

6503

Run Tee, Male NPTF Thread

Inch

	ØD	C		F	G	H	H1	L	kg
1/4	NPT1/8	6303 56 11WP2		1/2	11	40.5	22.5	18	0.004
	NPT1/4	6503 56 14WP2		9/16	11	40.5	22.5	18	0.005
	NPT3/8	6503 56 18WP2		3/4	11	41.5	23	18	0.007
3/8	NPT1/4	6503 60 14WP2		3/4	16	56	30	26	0.013
	NPT3/8	6503 60 18WP2		3/4	16	56	30	26	0.013
1/2	NPT3/8	6503 62 18WP2		15/16	22	75	39.5	35.5	0.031
	NPT1/2	6503 62 22WP2		15/16	22	76	40.5	35.5	0.035

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Thread without pre-coating; the body swivels for positioning purposes.

6503

Run Tee, Male BSPT Thread

Inch

	ØD	C		F	G	H	H1	L	kg
1/4	R1/8	6503 56 10WP2		13	11	41.5	22.5	18	0.004
	R1/4	6503 56 13WP2		14	11	41.5	22.5	18	0.005
	R3/8	6503 56 17WP2		17	11	41.5	23	18	0.007
3/8	R1/4	6503 60 13WP2		19	16	56	30	26	0.013
	R3/8	6503 60 17WP2		19	16	56	30	26	0.013
1/2	R3/8	6503 62 17WP2		24	22	75	39.5	35.5	0.032
	R1/2	6503 62 21WP2		24	22	75	39.5	35.5	0.035

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32" (4 mm) and 5/16" (8 mm) also available.
Thread without pre-coating; the body swivels for positioning purposes.

6355

Unequal Connector, Female BSPP Thread


	C	C1		E	F	H	kg
G3/4	G1/4	6355 13 27WP2		10	32	23.5	0.050

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

Tube-to-Tube Fittings

6306

Equal and Unequal Tube-to-Tube Connector


	ØD	ØD1		G	L	kg
	4	4	6306 04 00WP2	8.5	26.5	0.002
		6	6306 04 06WP2	10.5	29	0.002
		8	6306 04 08WP2	13.5	37	0.005
	6	6	6306 06 00WP2	10.5	30	0.004
		8	6306 06 08WP2	13.5	37	0.005
		10	6306 06 10WP2	16	42	0.007
	8	8	6306 08 00WP2	13.5	37	0.004
		10	6306 08 10WP2	16	42	0.007
		12	6306 08 12WP2	19	50	0.012
	10	10	6306 10 00WP2	16	42	0.009
		12	6306 10 12WP2	19	50	0.013
	12	12	6306 12 00WP2	19	50.5	0.009

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6306

Equal and Unequal Tube-to-Tube Connector


Inch

	ØD	ØD1		G	L	kg
	5/16	3/8	6306 08 60WP2	16	42	0.008
		1/2	6306 08 62WP2	22	55	0.018
		1/4	6306 56 00WP2	11	30	0.002
	1/4	5/16	6306 56 08WP2	13.5	37	0.007
		3/8	6306 56 60WP2	16	41	0.007
	3/8	3/8	6306 60 00WP2	16	42	0.006
		1/2	6306 60 62WP2	22	56	0.020
	1/2	1/2	6306 62 00WP2	22	57	0.016
	1/2	3/8	6306 60 00WP2	16	42	0.006
		1/2	6306 60 62WP2	22	56	0.020
		1/2	6306 62 00WP2	22	57	0.016
	1/2	1/2	6306 62 00WP2	22	57	0.016

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6302

Equal and Unequal Elbow


	ØD	ØD1		G	L	kg
	4	4	6302 04 00WP2	8.5	19	0.002
		6	6302 04 06WP2	10.5	24	0.004
	6	6	6302 06 00WP2	10.5	24	0.004
		8	6302 06 08WP2	13.5	29.5	0.006
	8	8	6302 08 00WP2	13.5	29	0.004
		10	6302 08 10WP2	16	34.5	0.008
	10	10	6302 10 00WP2	16	34.5	0.005
		12	6302 10 12WP2	19	40.5	0.013
	12	12	6302 12 00WP2	19	40.5	0.010
	12	12	6302 12 00WP2	19	40.5	0.010
		12	6302 12 00WP2	19	40.5	0.010
	12	12	6302 12 00WP2	19	40.5	0.010

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6302

Equal and Unequal Elbow

Inch





	ØD	ØD1		G	L	kg
	5/16	3/8	6302 08 60WP2	16	34	0.009
		1/4	6302 56 00WP2	11	24	0.005
	1/4	5/16	6302 56 08WP2	13.5	29.5	0.006
		3/8	6302 56 60WP2	16	34	0.008
	3/8	3/8	6302 60 00WP2	16	34	0.006
		1/2	6302 60 62WP2	22	46.5	0.011
	1/2	1/2	6302 62 00WP2	22	46.5	0.017
	1/2	3/8	6302 60 00WP2	16	34	0.006
		1/2	6302 60 62WP2	22	46.5	0.011
	1/2	1/2	6302 62 00WP2	22	46.5	0.017
		1/2	6302 62 00WP2	22	46.5	0.017
	1/2	1/2	6302 62 00WP2	22	46.5	0.017

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

Tube-to-Tube Fittings

6304

Equal Tee




 	Bio-based polymer, EPDM 	ØD	ØD1		G	H	L/2	kg
		4	4	6304 04 00WP2	8.5	20	15.5	0.004
		6	6	6304 06 00WP2	10.5	23	18	0.006
		8	8	6304 08 00WP2	13.5	29	22.5	0.006
		10	10	6304 10 00WP2	16	34.5	26.5	0.009
		12	12	6304 12 00WP2	19	40	31	0.014
		These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).						

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6304

Equal and Unequal Tee




Inch

		Bio-based polymer, EPDM							
		ØD	ØD1			G	H	L/2	kg
		1/4	1/4	6304 56 00WP2		11	24	18	0.002
		3/8	3/8	6304 60 00WP2		16	34	26	0.009
			1/4	6304 60 56WP2		16	34	26	0.011
		1/2	1/2	6304 62 00WP2		22	47	36	0.027
			3/8	6304 62 60WP2		22	47	36	0.009
<p>These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).</p> <p>5/32" (4 mm) and 5/16" (8 mm) also available.</p>									

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
5/32" (4 mm) and 5/16" (8 mm) also available.

6340

Equal Single Y Piece




 	Bio-based polymer, EPDM								
	ØD	ØD1		H	K	L	N	kg	
	4	4		6340 04 00WP2	17.5	8.5	30	9	0.004
	6	6		6340 06 00WP2	21.5	10.5	36.5	11	0.008
	8	8		6340 08 00WP2	28	13.5	44.5	14.5	0.007
	10	10		6340 10 00WP2	33	16	53	17	0.010
	12	12		6340 12 00WP2	39	19	60.5	20	0.025
These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).									

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6340





Equal Single Y Piece

Inch

		Bio-based polymer, EPDM								
		ØD	ØD1		H	K	L	N	kg	
		1/4	1/4	6340 56 00WP2	22	11	36	11.5	0.010	
		3/8	3/8	6340 60 00WP2	33	16	53	17	0.011	
		1/2	1/2	6340 62 00WP2	45	22	67	23	0.028	
These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32" (4 mm) and 5/16" (8 mm) also available.										





Tube-to-Tube and Bulkhead Connectors

6307 Equal Cross

 	Bio-based polymer, EPDM		ØD		G	H	N	ØT	kg
			6	6307 06 00WP2	11	36	20	4.2	0.005
			8	6307 08 00WP2	13.5	45	22.5	4.2	0.020
			These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).						


6307 Equal Cross

Inch

 	Bio-based polymer, EPDM								
			ØD		G	H	N	ØT	kg
			1/4	6307 56 00WP2	11	36	20	4.2	0.010
			These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32" (4 mm) and 5/16" (8 mm) also available.						

6316 Equal Bulkhead Union


Bio-based polymer, EPDM


ØD		F	K _{max}	L	L1	ØT _{min}	kg
4	6316 04 00WP2	13	5.5	15.5	10.5	10.5	0.018
6	6316 06 00WP2	15	8.5	20	10	12.5	0.004
8	6316 08 00WP2	18	14.5	27	10.5	15.5	0.007
10	6316 10 00WP2	22	14.5	30	13	18.5	0.012
12	6316 12 00WP2	26	18.5	35	15.5	22.5	0.020

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).


6316 Equal Bulkhead Union

Inch





Bio-based polymer, EPDM






ØD		F	K _{max}	L	L1	ØT _{min}	kg
1/4	6316 56 00WP2	15	8.5	20	10	12.5	0.004
3/8	6316 60 00WP2	22	14.5	29.5	12.5	18.5	0.012
1/2	6316 62 00WP2	29	20.5	40.5	17	25.5	0.030

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

5/32" (4 mm) and 5/16" (8 mm) also available.

Plug-In Fittings and Accessories




6382 Equal and Unequal Plug-In Elbow

	ØD	ØD1		G	H	H1	H2	L	kg
	4	4	6382 04 00WP2	8.5	23	6	15.5	15	0.003
		6	6382 04 06WP2	10.5	26.5	7	17	16.5	0.002
	6	6	6382 06 00WP2	10.5	26.5	7	17	17	0.003
		4	6382 06 04WP2	10.5	25	7	15.5	17	0.001
	8	8	6382 08 00WP2	13.5	33.5	8	21.5	22.5	0.004
		8	6382 08 00WP2	13.5	33.5	8	21.5	22.5	0.004
	10	10	6382 10 00WP2	16	39	9.5	24.5	26	0.007
		10	6382 10 00WP2	16	39	9.5	24.5	26.5	0.004
	12	12	6382 12 00WP2	19	44.5	10	27	30	0.011
		12	6382 12 00WP2	19	44.5	10	27	31	0.012

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).




6382 Equal and Unequal Plug-In Elbow

Inch

	ØD	ØD1		G	H	H1	H2	L	kg
	5/16	3/8	6382 08 60WP2	16	39	10	24.5	26	0.009
		1/4	6382 56 00WP2	11	30.5	11	18	18	0.002
	1/4	3/8	6382 56 60WP2	16	39	9	24.5	25.5	0.006
		3/8	6382 60 00WP2	16	39	9	24.5	26.5	0.005
	1/2	1/2	6382 62 00WP2	22	49	13	28.5	36	0.011




These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).
Equal plug-in elbow: 5/32" (4 mm) and 5/16" (8 mm) also available.

6380 Plug-In 45° Equal Elbow

	ØD	ØD1		G	H	H1	H2	L	kg
	4	4	6380 04 00WP2	8.5	33.5	19	21	13	0.001
		6	6380 06 00WP2	11	39	21	25	14.5	0.002
	8	8	6380 08 00WP2	13.5	44	21.5	25.5	19.5	0.006
		10	6380 10 00WP2	16	53	27	32.5	23	0.004
	12	12	6380 12 00WP2	19	58	27	34	26	0.012




These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6383 Plug-In Equal Run Tee

	ØD	ØD1		G	H	H1	H2	L	kg
	4	4	6383 04 00WP2	8.5	33	6	15.5	15	0.002
		6	6383 06 00WP2	10.5	38.5	7	17	18	0.002
	8	8	6383 08 00WP2	13.5	49	8	21.5	23	0.005
		10	6383 10 00WP2	16	57	10.5	25.5	26.5	0.012
	12	12	6383 12 00WP2	19	65	36.5	27	31	0.016

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6388 Plug-In Equal Branch Tee

	ØD	ØD1		G	H	H1	H2	L/2	kg
	4	4	6388 04 00WP2	8.5	25	6	15.5	15	0.005
		6	6388 06 00WP2	10.5	28.5	7	17	16	0.006
	8	8	6388 08 00WP2	13.5	33.5	8	21.5	23	0.005
		10	6388 10 00WP2	16	41	9.5	24.5	26.5	0.007
	12	12	6388 12 00WP2	19	46.5	10	27	31	0.016




These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

Plug-In Fittings and Accessories

6388

Plug-In Equal Branch Tee


Inch

 	Bio-based polymer, EPDM											
	ØD	L/2	L/2				G	H	H1	H2	L/2	kg
	1/4	1/4		6388 56 00WP2			11	30.5	11	20	18	0.002
	3/8	3/8		6388 60 00WP2			16	42	12	25	25	0.008
	1/2	1/2		6388 62 00WP2			22	51	13	29	32	0.020
These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32" (4 mm) and 5/16" (8 mm) also available.												

6366

Plug-In Reducer

Bio-based polymer, EPDM




ØD	ØD1		G	L	L1	kg
4	6	6366 04 06WP2	8.5	38	23.5	0.004
	8	6366 04 08WP2	8.5	38	19	0.004
6	8	6366 06 08WP2	10.5	38	20	0.004
	10	6366 06 10WP2	10.5	39	17.5	0.002
8	10	6366 08 10WP2	13.5	48.5	28.5	0.009
	12	6366 08 12WP2	13.5	48.5	24.5	0.004
10	12	6366 10 12WP2	16	52	33.5	0.005
	14	6366 10 14WP2	16	53	33.5	0.005
12	14	6366 12 14WP2	19	55.5	33.5	0.023

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6366

Plug-In Reducer




Inch

		Bio-based polymer, EPDM			ØD	ØD1		G	L	L1	kg
		1/4	5/16	6366 56 08WP2	11	41	22.5	0.015			
			3/8	6366 56 60WP2	11	41	20.5	0.002			
		5/16	3/8	6366 08 60WP2	13.5	48.5	29	0.003			
			1/2	6366 08 62WP2	16	48.5	22	0.007			
		3/8	1/2	6366 60 62WP2	16	51	30	0.011			
<p>These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).</p>											

6368



Plug-In Increaser

Inch


		Bio-based polymer, EPDM						
		ØD	ØD1		G	L	L1	kg
		3/8	5/16	6368 60 08WP2	16	44	25.5	0.004
		These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).						


6326

Blanking Plug



Bio-based polymer



ØD		G	L	L1	kg
4	6326 04 00WP2	6	30	15.5	0.001
6	6326 06 00WP2	8	33	16.5	0.001
8	6326 08 00WP2	10	35	17.5	0.002
10	6326 10 00WP2	12	42	21	0.003
12	6326 12 00WP2	14	45	22	0.004





These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

Plug-In Fittings and Accessories

6326

Blanking Plug

Inch


		Bio-based polymer 	ØD		G	L	L1	kg
			1/4	6326 56 00WP2	8	36.5	22	0.001
			3/8	6326 60 00WP2	11.6	42.5	22	0.002
			1/2	6326 62 00WP2	14.7	48.5	21.5	0.004
			These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32 (4 mm) and 5/16 (8 mm) also available					

6322

Plug-In Barb Connector Inch

Bio-based polymer

Technical drawing of the bio-based polymer connector. The drawing shows a tapered, ribbed connector with a central hole. Dimensions are indicated: L (total length), L1 (length of the tapered section), L2 (length of the cylindrical section), ØD (outer diameter of the cylindrical section), ØD2 (outer diameter of the tapered section), and ØD1 (inner diameter of the central hole).




ØD	ØD1	ØD2		L	L1	L2	kg
6	4	7	6322 06 04WP2	39	25	17	0.004
8	6	8.5	6322 08 06WP2	43	25	17	0.005
10	7	8	6322 10 07WP2	50	29.5	22	0.006
12	12.5	15.5	6322 12 62WP2	56	32	27.5	0.004

These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).

6322




Plug-In Barb Connector Inch

Inch

	<p>Bio-based polymer</p> 	ØD	ØD1	ØD2		L	L1	L2	kg
		1/4	0.28	0.32	6322 56 56WP2	39	24.5	17	0.001
			0.33	0.38	6322 60 08WP2	50	29.5	22	0.001
		3/8	0.28	0.32	6322 60 56WP2	45	24.5	17	0.008
			0.40	0.45	6322 60 60WP2	50	29	22	0.002
		1/2	0.40	0.45	6322 62 60WP2	58	37.5	30	0.005
<p>These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).</p>									

6351




End Cap

	<p>Bio-based polymer, EPDM</p> 	ØD		G	H	kg
		4	6351 04 00WP2	8.5	15	0.001
		6	6351 06 00WP2	10.5	17	0.002
		8	6351 08 00WP2	13.5	21.5	0.003
		10	6351 10 00WP2	16	22	0.003
		12	6351 12 00WP2	19	27.5	0.006
		These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters).				

6351


End Cap

Inch

	<p>Bio-based polymer, EPDM</p> 	ØD		G	H	kg
		1/4	6351 56 00WP2	11	16	0.001
		3/8	6351 60 00WP2	16	22.5	0.003
		These part numbers are also available in WP3 = high volumes (number of parts per bag: 40, 50 or 100, depending on the diameters). 5/32" (4 mm) and 5/16" (8 mm) also available.				








Accessories

3130 Tamper-Proof Safety Clip







Technical Polymer	ØD							H	K	kg
	4	3130 04 01	3130 04 02	3130 04 03	3130 04 04	3130 04 05	3130 04 10	6.60	3.00	0.001
	6	3130 06 01	3130 06 02	3130 06 03	3130 06 04	3130 06 05	3130 06 10	7.80	3.10	0.001
	8	3130 08 01	3130 08 02	3130 08 03	3130 08 04	3130 08 05	3130 08 10	9.50	4.30	0.001
	10	3130 10 01	3130 10 02	3130 10 03	3130 10 04	3130 10 05	3130 10 10	10.80	4.20	0.002
	12	3130 12 01	3130 12 02	3130 12 03	3130 12 04	3130 12 05	3130 12 10	12.50	5.10	0.003
	14	3130 14 01	3130 14 02	3130 14 03	3130 14 04	3130 14 05	3130 14 10	12.50	5.10	0.004

3130 Tamper-Proof Safety Clip

Inch







Technical Polymer	ØD							H	K	kg
	1/4	3130 56 01	3130 56 02	3130 56 03	3130 56 04	3130 56 05	3130 56 10	7.80	3.10	0.001
	3/8	3130 60 01	3130 60 02	3130 60 03	3130 60 04	3130 60 05	3130 60 10	10.80	4.20	0.002
	1/2	3130 62 01	3130 62 02	3130 62 03	3130 62 04	3130 62 05	3130 62 10	12.50	5.10	0.003
	5/32" (4 mm) and 5/16" (8 mm) also available.									

3110 Coloured Release Button Covers



Technical Polymer	ØD						kg
	4	3110 04 00	3110 04 02	3110 04 03	3110 04 04	3110 04 05	0.001
	6	3110 06 00	3110 06 02	3110 06 03	3110 06 04	3110 06 05	0.001
	8	3110 08 00	3110 08 02	3110 08 03	3110 08 04	3110 08 05	0.001
	10	3110 10 00	3110 10 02	3110 10 03	3110 10 04	3110 10 05	0.001
	12	3110 12 00	3110 12 02	3110 12 03	3110 12 04	3110 12 05	0.001
	14	3110 14 00	3110 14 02	3110 14 03	3110 14 04	3110 14 05	0.002

3110 Coloured Release Button Covers

Inch

Technical Polymer	ØD						kg
	1/4	3110 56 00	3110 56 02	3110 56 03	3110 56 04	3110 56 05	0.001
	3/8	3110 60 00	3110 60 02	3110 60 03	3110 60 04	3110 60 05	0.001
	1/2	3110 62 00	3110 62 02	3110 62 03	3110 62 04	3110 62 05	0.001
	5/32" (4 mm) and 5/16" (8 mm) also available						

0605 Fluoropolymer Tape

FKM		kg
	0605 12 12 Can be used for temperatures from - 250°C to +260°C. Chemically inert and resistant to gases, acids, solvents, hydrocarbons, oils, alkalines, steam, etc. Non-toxic, waterproof, self-lubricating. In accordance with CFR21. Can be used on all materials. Used to facilitate the preparation of leak-free threaded joints. Supplied on a reel: length = 12 m; width = 12.7 mm; thickness = 0.08 mm.	0.012

LIQUIfit+ Push-In Fittings

For the transfer of sensitive fluids, the LIQUIfit+ range **reduces the growth of bacteria** in your circuits **for 100% cleanliness after cleaning**, and can be **directly** connected to stainless steel tubing, without grooving.

Product Advantages

Zero Retention for 100% Cleanliness

- Up to 10 times less microbial growth within the fitting
- Elimination of 99.9% of bacteria during cleaning operations
- No degradation of the beverage taste
- Preservation of the integrity of sensitive or industrial fluids
- Extension of the fitting's life due to the absence of bacteria after cleaning

Quality & Reliability

- 100% leak-tested in production
- Date coding to guarantee quality and traceability
- Quality approved for contact with food
- Excellent chemical resistance (chlorine, cleaning agents, UV...)
- Excellent long-term mechanical resistance
- Safety clip to avoid any untimely disconnection

Innovative Technology

- Patented push-in connection, unique on stainless steel tubing (without preparation) and on polymer tubing
- Extremely compact
- 100% bio-based material
- Patented sealing technology (FR29461418)
- No tube movement after connection



Applications

- Food Process
- Medical
- Beverage Dispensers
- Pharmaceutical
- Chemical
- Brewing


Technical Characteristics

Compatible Fluids	Beer, water, beverages, industrial fluids
Working Pressure	Vacuum to 16 bar
Working Temperature	-10°C to +95°C (see LIQUIfit® chart p. 1-47)

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
The use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Cleaning Efficiency


Comparison of the contamination by micro-organisms before and after cleaning operations (cfu/surface)*



* Tests carried out by an independent laboratory

Component Materials

Release button: technical polymer
Body: bio-polymer
Seal: EPDM
Gripping ring: stainless steel






Silicone-free

Regulations

DI: 2002/95/EC (RoHS), 2011/65/EC
RG: 1935/2004/EC
FDA: 21 CFR
NSF51
NSF/ANSI 61 - C HOT

6333 Stud Fitting, Female BSPP Thread




Inch

		ØD	C		E	F	H	kg
		3/8	G1/2	6333 60 21WP3	14	11	30	0.010
		3/8	G5/8	6333 60 23WP3	14	13	36	0.016

WP3 suffix = high volume (number of parts per bag: 40, 50 or 100 depending on the diameters).

6336 Equal and Unequal Tube-to-Tube Connector




Inch

		ØD	ØD1		ØG	L	kg
		5/16		6336 08 00WP3	13.5	37	0.004
		3/8		6336 08 60WP3	16	42	0.008
		1/2		6336 08 62WP3	22	55	0.016
		3/8	3/8	6336 60 00WP3	16	42	0.006
		1/2		6336 60 62WP3	22	56	0.020
		1/2	1/2	6336 62 00WP3	22	57	0.016

WP3 suffix = high volume (number of parts per bag: 40, 50 or 100 depending on the diameters).

6332 Equal and Unequal Elbow




Inch

		ØD	ØD1		ØG	L	kg
		5/16	5/16	6332 08 00WP3	13.5	29	0.004
		3/8		6332 08 60WP3	16	34	0.009
		3/8	3/8	6332 60 00WP3	16	34	0.006
		1/2		6332 60 62WP3	22	46.5	0.011
		1/2	1/2	6332 62 00WP3	22	46.5	0.017

WP3 suffix = high volume (number of parts per bag: 40, 50 or 100 depending on the diameters).

6331 Equal Plug-In Elbow

Inch

		ØD	ØD1		ØG	H	H1	H2	L	kg
		5/16	5/16	6331 08 00WP3	13.5	33.5	8	21.5	22.5	0.004
		3/8	3/8	6331 60 00WP3	16	39	9	24.5	26.5	0.005

WP3 suffix = high volume (number of parts per bag: 40, 50 or 100 depending on the diameters).

Use with Stainless Steel Tubing

- These fittings are approved for use with 304 and 316L stainless steel tubing, 160 Hv, with tolerances on the external diameter +0.05/-0.10 mm.
- Carefully deburr the stainless steel tube end.
- For easy disconnection, press firmly on the release button.
- After 5 connections/disconnections, we recommend that you change the fitting.





LF 3600 Push-In Fittings Range

Stud Fittings

Straights

3675 BSPT Page 1-67	3601 BSPP/Metric Page 1-67	3681 Metric Page 1-67	3614 BSPP/Metric Page 1-68	3621 BSPT Page 1-68	3631 BSPP/Metric Page 1-68	3600 Page 1-68
----------------------------------	---	------------------------------------	---	----------------------------------	---	--------------------------



Elbows

3609 BSPT Page 1-69	3629 BSPT Page 1-69	3699 BSPP/Metric Page 1-69	3669 BSPP/Metric Page 1-70
----------------------------------	----------------------------------	---	---



Tees

3608 BSPT Page 1-70	3603 BSPT Page 1-70	3698 BSPP/Metric Page 1-70	3693 BSPP/Metric Page 1-71
----------------------------------	----------------------------------	---	---



Banjo

3618 BSPP/Metric Page 1-71



Tube-to-Tube Fittings

Straight

3606 Page 1-72



Elbow

3602 Page 1-72



Tee

3604 Page 1-72



Bulkhead Connector Fittings

Straights

3616 Page 1-73	3636 BSPP Page 1-73
--------------------------	----------------------------------



Elbow

3639 Page 1-73



Plug-In Accessories

3666 Page 1-74	3667 Page 1-74	3668 Page 1-74	3622 Page 1-74	3620 Page 1-74	3626 Page 1-75
--------------------------	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------



Accessories

0605 Page 1-75	3000 70 Page 1-75	3610 Page 1-75
--------------------------	-----------------------------	--------------------------



LF 3600 Push-In Fittings

In order to meet your **technical and environment requirements**, Parker Legris designed this range of metal fittings, offering **robustness**, **reliability** and **resistance to industrial fluids** for the most demanding environments.

Product Advantages

High Performance

Resistant up to +150°C at 30 bar
Excellent mechanical performance
Long threads to resist shock and vibration
Excellent abrasion and corrosion resistance due to high phosphorus chemical nickel plating
Full flow, minimal pressure drop

Versatility

Materials conform to FDA standards
Spring collet gripping system suitable for both metal (grooved) and polymer tubing
Excellent resistance to high pressure and vacuum
Excellent chemical compatibility
More than 250 part numbers
One fitting for numerous applications: stock optimisation
Manual connection and disconnection
Compact and ergonomic

Reliability

High performance brass for increased lifespan
100% leak-tested in production
Date coding to guarantee quality and traceability



Food Process
Coffee Machines
In-Plant Automotive
Medical Equipment
Printing
Misting
Welding Robots

Applications


Technical Characteristics

Suitable Fluids	Compressed air, grease, lubricant, water...
Working Pressure	Vacuum to 30 bar (20 bar: 3699, 3609)
Working Temperature	-20°C to +150°C

Maximum Tightening Torque (daN.m)	Thread							
	M5 x0.8	M6 x1	M8 x1	M10 x1	G1/8	G1/4	G3/8	G1/2
	0.16	0.18	0.6	0.8	0.8	1.2	3	3.5

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Regulations

Industrial
ISO 14743: pneumatic transmissions, push-in fittings for thermoplastic tubing
DI: 97/23/EC (PED)
DI: 2002/95/EC (RoHS), 2011/65/EC
RG: 1907/2006 (REACH)
DI: 94/9/EC (ATEX)
UL94 V-0: please consult us

Food
RG: 21CFR (FDA)
RG: 1935/2004/EC (minimum flow 0.02 l/h)
USDA NSF H1: grease
ASTM B733-04: autocatalytic (electroless) nickel-phosphorus coatings

Stud Fittings

3675

Stud Fitting, Male BSPT Thread

ØD	C					F1	F2	H	kg
4	R1/8	3675 04 10				10	3	15	0.009
	R1/4	3675 04 13				14	3	15	0.017
6	R1/8	3675 06 10				13	4	17	0.011
	R1/4	3675 06 13				14	4	17	0.018
8	R1/8	3675 08 10				15	5	19	0.015
	R1/4	3675 08 13				16	6	18	0.019
	R3/8	3675 08 17				17	6	18.5	0.027
10	R1/4	3675 10 13				18	7	23	0.026
	R3/8	3675 10 17				18	8	22.5	0.031
	R1/2	3675 10 21				22	8	22.5	0.056
12	R1/4	3675 12 13				20	7	25.5	0.033
	R3/8	3675 12 17				20	9	24	0.035
14	R1/2	3675 12 21				22	10	23	0.051
	R3/8	3675 14 17				22	9	27	0.042
	R1/2	3675 14 21				24	11	26	0.057

3601

Stud Fitting, Male BSPP and Metric Thread

ØD	C		E	F1	F2	H	kg
4	M5x0.8	3601 04 19	3.5	10	2.5	15.5	0.006
	M6x1	3601 04 52	4.5	10	3	16	0.006
	M8x1	3601 04 56	5	11	3	14.5	0.007
	G1/8	3601 04 10	5.5	13	3	14.5	0.009
	G1/4	3601 04 13	6.5	16	3	14.5	0.015
6	M5x0.8	3601 06 19	3.5	13	2.5	19	0.010
	M10x1	3601 06 60	5.5	13	4	17.5	0.011
	G1/8	3601 06 10	5.5	13	4	17.5	0.011
	G1/4	3601 06 13	6.5	16	4	17	0.015
8	G1/8	3601 08 10	5.5	16	5	20	0.014
	G1/4	3601 08 13	6.5	16	6	18	0.016
	G3/8	3601 08 17	7.5	20	6	19	0.028
10	G1/4	3601 10 13	6.5	18	7	25	0.025
	G3/8	3601 10 17	7.5	20	8	22.5	0.028
	G1/2	3601 10 21	9	24	8	22.5	0.043
12	G1/4	3601 12 13	6.5	20	7	26.5	0.030
	G3/8	3601 12 17	7.5	20	9	26	0.034
	G1/2	3601 12 21	9	24	10	23.5	0.042
14	G3/8	3601 14 17	7.5	22	9	28	0.038
	G1/2	3601 14 21	9	24	11	26.5	0.045

3681

Stud Fitting with Internal Hexagon, Male Metric Thread

ØD	C		E	F	G	H	kg
4	M5x0.8	3681 04 19	3.5	2.5	10	16	0.005




Related Products

- Polyurethane Tubing
- Polyamide Tubing
- Polyethylene Tubing
- Fluoropolymer Tubing
- Anti-Spark Tubing
- Fireproof PA Tubing
- Brass Flow Control Regulators

Stud Fittings




3614

Stud Fitting, Female BSPP and Metric Thread

	FDA chemical nickel-plated brass, FKM		ØD	C		E	F	H	kg
4				M5x0.8	3614 04 19	5	10	22	0.009
				G1/8	3614 04 10	7.5	14	25	0.016
				G1/4	3614 04 13	11	17	29	0.026
6				G1/8	3614 06 10	7.5	14	27.5	0.019
				G1/4	3614 06 13	11	17	31.5	0.028
8				G1/8	3614 08 10	9.5	15	28.5	0.022
				G1/4	3614 08 13	13.5	17	32.5	0.028
10				G3/8	3614 10 17	14	22	38	0.052
				G3/8	3614 12 17	14	22	39	0.055
12				G1/2	3614 12 21	18.5	24	43.5	0.062




3621

Stud Standpipe, Male BSPT Thread

	FDA chemical nickel-plated brass		ØD	C		F	H	H1	kg
4				R1/8	3621 04 10	10	21	7	0.006
				R1/4	3621 04 13	14	21	7	0.014
6				R1/8	3621 06 10	10	23.5	6.5	0.008
				R1/4	3621 06 13	14	23.5	6.5	0.016
8				R1/8	3621 08 10	10	24	6.5	0.009
				R1/4	3621 08 13	14	24	6.5	0.017
10				R1/4	3621 10 13	14	22	6.5	0.018
				R3/8	3621 10 17	17	30	7.5	0.022
12				R3/8	3621 12 17	17	31	7.5	0.023
				R1/2	3621 12 21	22	31	7.5	0.041
14				R1/2	3621 14 21	22	33	8	0.042




3631

Stud Standpipe, Male BSPP and Metric Thread

	FDA chemical nickel-plated brass, FKM		ØD	C		E	F	H	H1	kg
4				M5x0.8	3631 04 19	3.5	13	21.5	7	0.003
				G1/8	3631 04 10	5.5	13	20	7	0.007
				G1/4	3631 04 13	6.5	8	20	7.5	0.011
6				G1/8	3631 06 10	5.5	13	22.5	6.5	0.009
				G1/4	3631 06 13	6.5	16	22.5	6.5	0.012
8				G1/8	3631 08 10	5.5	13	22.5	6.5	0.010
				G1/4	3631 08 13	6.5	16	23	6.5	0.013
				G3/8	3631 08 17	7.5	20	23	7.5	0.018
10				G1/4	3631 10 13	6.5	16	28	6.5	0.015
				G3/8	3631 10 17	7.5	20	28	7.5	0.022
				G1/2	3631 10 21	9	24	28	7.5	0.028
12				G3/8	3631 12 17	7.5	20	29	7.5	0.023
				G1/2	3631 12 21	9	24	29	7.5	0.033
14				G1/2	3631 14 21	9	24	31	8	0.033

3600

Cartridge

	FDA chemical nickel-plated brass, FKM		ØD		G	G1	H	H1	H2	N	kg
4					9.8	8	17	8.5	8.5	11	0.006
6					12.1	10	19	10.5	8.5	13.5	0.009
8					14.8	13	21	12.5	8.5	16	0.012
10					17.5	15	24.5	14	10.5	20	0.019
12					20	17	25	14.5	10.5	22.5	0.023
14					22	20	28.5	16.5	12	25	0.031

Cavity dimensions available in Chapter 2

Stud Fittings

3609

Stud Elbow, Male BSPT Thread

ØD	C		F	G	H	J	L	kg
4	R1/8	3609 04 10	13	10	15	7	18	0.014
	R1/4	3609 04 13	14	10	17	7	18	0.020
6	R1/8	3609 06 10	13	12	17.5	8	21.5	0.018
	R1/4	3609 06 13	14	12	19	8	21.5	0.025
8	R1/8	3609 08 10	13	15	19.5	10	23.5	0.023
	R1/4	3609 08 13	14	15	21	10	23.5	0.029
10	R3/8	3609 08 17	17	15	21	10	23.5	0.035
	R1/4	3609 10 13	15	17.5	23.5	12	29	0.037
12	R3/8	3609 10 17	17	17.5	25.5	12	29	0.043
	R1/4	3609 12 13	15	19.5	26	15	31	0.049
14	R3/8	3609 12 17	17	19.5	28.5	15	31	0.055
	R1/2	3609 12 21	21	19.5	28.5	15	31	0.072
14	R3/8	3609 14 17	19	21.5	29	16	34	0.063
	R1/2	3609 14 21	22	21.5	30	16	34	0.072

The body swivels for positioning purposes.

3629

Extended Stud Elbow, Male BSPT Thread

ØD	C		F	G	H	J	L	kg
4	R1/8	3629 04 10	10	10	24.5	7	18	0.025
	R1/8	3629 06 10	13	12	29.5	8	21.5	0.024
6	R1/4	3629 06 13	14	12	30.5	8	21.5	0.031
8	R1/8	3629 08 10	14	15	32.5	10	23.5	0.031
	R1/4	3629 08 13	14	15	34	10	23.5	0.037
10	R1/4	3629 10 13	18	17.5	39	12	29	0.054

The body swivels for positioning purposes.

3699

Compact Elbow, Male BSPP and Metric Thread




ØD	C		E	F	G	H	J	L	kg
4	M5x0.8	3699 04 19	3.5	10	10	18	7	18	0.011
	M6x1	3699 04 52	4.5	10	10	18	7	18	0.011
	M8x1	3699 04 56	5	11	10	18	7	18	0.013
	G1/8	3699 04 10	5.5	13	10	17	7	18	0.014
	G1/4	3699 04 13	6.5	16	10	17.5	7	18	0.019
6	M10x1	3699 06 60	5.5	13	12	19	8	21.5	0.017
	G1/8	3699 06 10	5.5	13	12	19	8	21.5	0.018
	G1/4	3699 06 13	6.5	16	12	19.5	8	21.5	0.022
8	G1/8	3699 08 10	5.5	13	15	20.5	10	23.5	0.021
	G1/4	3699 08 13	6.5	16	15	21.5	10	23.5	0.027
	G3/8	3699 08 17	7.5	20	15	21.5	10	23.5	0.033
10	G1/4	3699 10 13	6.5	16	17.5	27	12	29	0.037
	G3/8	3699 10 17	7.5	20	17.5	25.5	12	29	0.043
	G1/4	3699 12 13	6.5	16	19.5	29.5	15	31	0.050
12	G3/8	3699 12 17	7.5	20	19.5	28.5	15	31	0.057
	G1/2	3699 12 21	9	24	19.5	28.5	15	31	0.065
14	G3/8	3699 14 17	7.5	20	21.5	29	16	34	0.059
	G1/2	3699 14 21	9	24	21.5	29.5	16	34	0.062

The body swivels for positioning purposes.

Stud Fittings

3669




Extended Stud Elbow, Male BSPP and Metric Thread

	FDA chemical nickel-plated brass, FKM			ØD	C		E	F	G	H	J	L	kg
				4	M5x0.8	3669 04 19	3.5	10	10	27.5	7	18	0.014
					G1/8	3669 04 10	5.5	13	10	25.5	7	18	0.017
				6	G1/8	3669 06 10	5.5	13	12	31	8	21.5	0.024
					G1/4	3669 06 13	6.5	16	12	30.5	8	21.5	0.028
				8	G1/8	3669 08 10	5.5	14	15	33.5	10	23.5	0.031
					G1/4	3669 08 13	5.5	16	15	34	10	23.5	0.035
				10	G1/4	3669 10 13	6.5	18	17.5	42	12	29	0.052
					G3/8	3669 10 17	7.5	20	17.5	41	12	29	0.056
				12	G1/4	3669 12 13	6.5	20	19.5	47	15	31	0.070
					G3/8	3669 12 17	7.5	20	19.5	46	15	31	0.072
				14	G1/2	3669 14 21	9	24	21.5	49	16	34	0.094

The body swivels for positioning purposes.

3608




Stud Branch Tee, Male BSPT Thread

	FDA chemical nickel-plated brass, FKM			ØD	C		F	G	H	J	L/2	kg
				4	R1/8	3608 04 10	10	10	24.5	7	18	0.020
					R1/8	3608 06 10	13	12	29.5	8	21.5	0.031
				6	R1/4	3608 06 13	14	12	30.5	8	21.5	0.038
					R1/8	3608 08 10	14	15	32.5	10	23.5	0.040
				8	R1/4	3608 08 13	14	15	34	10	23.5	0.047
					R1/4	3608 10 13	18	17.5	39	12	29	0.067
				10	R3/8	3608 10 17	18	17.5	41	12	29	0.070
					R3/8	3608 12 17	20	19.5	46.5	15	31	0.094
				14	R1/2	3608 14 21	22	21.5	50.5	16	34	0.125

The body swivels for positioning purposes.

3603




Stud Run Tee, Male BSPT Thread

	FDA chemical nickel-plated brass, FKM			ØD	C		F	G	H	H1	J	L	kg
				4	R1/8	3603 04 10	10	10	19.5	18	7	23	0.018
					R1/8	3603 06 10	13	12	23.5	21.5	8	28	0.031
				6	R1/4	3603 06 13	14	12	24.5	21.5	8	28	0.037
					R1/8	3603 08 10	14	15	25	23.5	10	31	0.041
				8	R1/4	3603 08 13	14	15	26.5	23.5	10	31	0.044
					R1/4	3603 10 13	18	17.5	30.5	29	12	37.5	0.067
				10	R3/8	3603 10 17	18	17.5	32.5	29	12	37.5	0.069
					R3/8	3603 12 17	20	19.5	36.5	31	15	40.5	0.103
				14	R1/2	3603 14 21	22	21.5	40	34	16	45	0.147

The body swivels for positioning purposes.

3698

Stud Branch Tee, Male BSPP and Metric Thread



	FDA chemical nickel-plated brass, FKM			ØD	C		E	F	G	H	J	L/2	kg
				4	M5x0.8	3698 04 19	3.5	10	10	27.5	7	18	0.018
					G1/8	3698 04 10	5.5	13	10	25.5	7	18	0.021
				6	G1/8	3698 06 10	5.5	13	12	31	8	21.5	0.031
					G1/4	3698 06 13	6.5	16	12	30.5	8	21.5	0.035
				8	G1/8	3698 08 10	5.5	14	15	33.5	10	23.5	0.041
					G1/4	3698 08 13	6.5	16	15	34	10	23.5	0.045
				10	G1/4	3698 10 13	6.5	18	17.5	42	12	29	0.066
					G3/8	3698 12 17	7.5	20	19.5	46	15	31	0.088
				14	G1/2	3698 14 21	9	24	21.5	49	16	34	0.111

The body swivels for positioning purposes.

Stud Fittings

3693

Stud Run Tee, Male BSPP and Metric Thread

FDA chemical nickel-plated brass, FKM



ØD	C		E	F	G	H	H1	J	L	kg
4	M5x0.8	3693 04 19	3.5	10	10	22.5	18	7	23	0.019
	G1/8	3693 04 10	5.5	13	10	20.5	18	7	23	0.021
6	G1/8	3693 06 10	5.5	13	12	25	21.5	8	28	0.031
	G1/4	3693 06 13	6.5	16	12	24.5	21.5	8	28	0.035
8	G1/8	3693 08 10	5.5	14	15	26.5	23.5	10	31	0.041
	G1/4	3693 08 13	6.5	16	15	26.5	23.5	10	31	0.044
10	G1/4	3693 10 13	6.5	18	17.5	33	29	12	37.5	0.066
12	G3/8	3693 12 17	7.5	20	19.5	36.5	31	15	40.5	0.090
14	G1/2	3693 14 21	9	24	21.5	38.5	34	16	45	0.112

The body swivels for positioning purposes.

The body swivels for positioning purposes.

3618

Single Banjo, Male BSPP and Metric Thread

 	FDA chemical nickel-plated brass, FKM									
	ØD	C		F	H	H1	J	L1	L2	kg
	4	M5x0.8	3618 04 19	8	14.5	6.5	10	6	18.5	0.011
		G1/8	3618 04 10	14	23	9.5	17	10	20.5	0.029
	6	M5x0.8	3618 06 19	8	15	7	10	6	22.5	0.015
		G1/8	3618 06 10	14	23	9.5	17	10	23.5	0.031
	8	G1/4	3618 06 13	17	22	9	22	13	25.5	0.049
		G1/8	3618 08 10	14	23	9.5	17	10	26	0.033
	8	G1/4	3618 08 13	17	22	9	22	13	27.5	0.051
		G3/8	3618 10 17	22	33	14	22	13	32	0.105




Maximum temperature: +80°C

Each model has been designed to meet specific requirements: compactness due to small overall dimensions, with inter-connectability for customised configurations.






Tube-to-Tube Fittings




3606 Equal Tube-to-Tube Connector

 	FDA chemical nickel-plated brass, FKM 	ØD			G	L	kg
		4	3606 04 00		10	30.5	0.010
		6	3606 06 00		12	36.5	0.016
		8	3606 08 00		15	37.5	0.021
		10	3606 10 00		17.5	47.5	0.034
		12	3606 12 00		19.5	50	0.042
		14	3606 14 00		21.5	52.5	0.050

3602 Equal Elbow

 	FDA chemical nickel-plated brass, FKM 	ØD			G	L	kg
		4	3602 04 00		10	23	0.010
		6	3602 06 00		12	28	0.016
		8	3602 08 00		15	31	0.023
		10	3602 10 00		17.5	37.5	0.033
		12	3602 12 00		19.5	40.5	0.045
		14	3602 14 00		21.5	45	0.056



3604 Equal Tee

 	FDA chemical nickel-plated brass, FKM 	ØD			G	H	L/2	kg
		4	3604 04 00		10	23	18	0.014
		6	3604 06 00		12	28	21.5	0.023
		8	3604 08 00		15	31	23.5	0.032
		10	3604 10 00		17.5	37.5	29	0.048
		12	3604 12 00		19.5	40.5	31	0.063
		14	3604 14 00		21.5	45	34	0.078

Bulkhead Connector Fittings



3616

Equal Bulkhead Connector

	<p>FDA chemical nickel-plated brass, FKM</p> 	ØD		F1	F2	K	L1	L2	ØT min	kg
		4	3616 04 00	13	14	14	14	20	12.5	0.018
		6	3616 06 00	16	17	17.5	17	22	15	0.028
		8	3616 08 00	18	19	19.5	18.5	23.5	17	0.035
		10	3616 10 00	22	27	24	21.5	26.5	21	0.063
		12	3616 12 00	24	24	26	23	27	23	0.062
		14	3616 14 00	27	27	29.5	25.5	29.5	25	0.079



3636

Bulkhead Connector, Female BSPP Thread

	<p>FDA chemical nickel-plated brass, FKM</p> 	ØD	C		E	F1	F2	H	H1	K	ØT min	kg
		4	G1/8	3636 04 10	8.5	14	14	30.5	11	15	13	0.020
		6	G1/8	3636 06 10	8.5	17	17	33	11	18.5	15	0.033
			G1/4	3636 06 13	11.5	17	17	37	15	18.5	15	0.033
		8	G1/8	3636 08 10	8.5	19	19	34	10.5	21	17	0.044
			G1/4	3636 08 13	11.5	19	19	38	14.5	21	17	0.044
		10	G3/8	3636 10 17	12	22	27	42.5	16	24	21	0.073
		12	G3/8	3636 12 17	12	24	24	43	16	26	23	0.077
			G1/2	3636 12 21	16	27	24	48.5	21.5	29.5	23	0.133

3639

Equal Bulkhead Elbow




	<p>FDA chemical nickel-plated brass, FKM</p> 	ØD		F1	F2	G	H	K	L	ØT min	kg
		4	3639 04 00	13	14	10	35	14	18	12.5	0.023
		6	3639 06 00	16	17	12	40.5	17.5	21.5	15	0.035
		8	3639 08 00	18	19	15	44	19.5	23.5	17	0.046
		10	3639 10 00	22	27	17.5	51	24	29	21	0.080
		12	3639 12 00	24	24	19.5	55	26	31	23	0.086
		14	3639 14 00	27	27	21.5	59	29.5	34	25	0.144

The body swivels for positioning purposes.

Plug-In Accessories




3666

Plug-In Reducer

	FDA chemical nickel-plated brass, FKM								
	ØD1	ØD2		G	L	L1	L2	kg	
	4	6	3666 04 06	10	35	19.5	18	0.008	
		8	3666 04 08	10	35.5	20	18	0.009	
	6	8	3666 06 08	12	38	20	20.5	0.012	
		10	3666 06 10	12	43.5	25	21	0.015	
	8	10	3666 08 10	15	44	25	21.5	0.016	
		12	3666 08 12	15	44	26	20.5	0.018	
	10	12	3666 10 12	17.5	50	26	27	0.026	
	12	14	3666 12 14	19.5	53	28	28.5	0.032	




3667

Plug-In Metric/Inch Adaptor

	FDA chemical nickel-plated brass, FKM								
	ØD1	ØD2		G	L	L1	L2	kg	
	6	1/4	3667 06 56	12.5	38.5	19.5	21	0.012	
	10	3/8	3667 10 60	17	49.5	25	27	0.026	
	12	1/2	3667 12 62	20	51	26	27.5	0.030	




3668

Plug-In Increaser

	FDA chemical nickel-plated brass, FKM								
	ØD1	ØD2		G	L	L1	L2	kg	
	6	4	3668 06 04	12	36	17	21.5	0.010	




3622

Plug-In Barb Connector

	FDA chemical nickel-plated brass								
	ØD1	ØD2		ØD3	L	L1	L2	kg	
	4	3.2	3622 04 53	5	40.5	27	22.5	0.003	
		5	3622 04 05	7	40.5	27	22.5	0.005	
	6	5	3622 06 05	7	43	27	22.5	0.006	
		6.3	3622 06 56	8.3	42	25	22.5	0.008	
	8	8	3622 08 08	10	44	27	22.5	0.010	
		6.3	3622 10 56	8.3	47.5	25.5	22.5	0.011	
	10	8	3622 10 08	10	47.5	25.5	22.5	0.011	
		8	3622 12 08	10	48.5	25.5	22.5	0.015	
	12	10	3622 12 10	10	48.5	25.5	22.5	0.014	
		12.5	3622 12 62	14.5	57	34	29.5	0.019	
	14	12.5	3622 14 62	16	57.5	33	29.5	0.023	
		14	3622 14 14	16	59.5	35	29.5	0.023	

3620




Male Stem Connector

	FDA chemical nickel-plated brass						
	ØD			L	L1	kg	
	4		3620 04 00	31	14	0.002	
	6		3620 06 00	36.5	17	0.005	
	8		3620 08 00	37.5	17.5	0.007	
	10		3620 10 00	47.5	22.5	0.011	
	12		3620 12 00	49.5	23.5	0.015	
	14		3620 14 00	53	25	0.016	

Plug-In Accessories



3626

Blanking Plug

		FDA chemical nickel-plated brass							
		ØD	G		L	L1	L2	kg	
		4	3626 04 00		6	25.5	17.5	11.5	0.004
		6	3626 06 00		8	30.5	19.5	13.5	0.009
		8	3626 08 00		10	33	20	16	0.009
		10	3626 10 00		12	40	25	18	0.015
		12	3626 12 00		14	43	26	20	0.021
14	3626 14 00	16	47	28	22.5	0.029			

0605



Fluoropolymer Tape

	FKM		kg
		0605 12 12	0.012

Can be used for temperatures from - 250°C to +260°C.
Chemically inert and resistant to gases, acids, solvents, hydrocarbons, oils, alkalines, steam etc.
Non-toxic, waterproof, self-lubricating.
In accordance with CFR21.
Can be used on all materials.
Used to facilitate the preparation of leak-free threaded joints.
Supplied on a reel, length = 12 m; width = 12.7 mm; thickness 0.08 mm.

3000 70 00




Disconnection Tool

	Treated steel		H	H1	L	kg
		3000 70 00	25	20	96	0.021

For disconnecting LF 3000® fittings/tubing where access is difficult, we recommend the use of this disconnection tool.

3610

Coloured Release Button Covers

	Anodised aluminium	ØD			kg
		6	3610 06 00	3610 06 04	0.004
		8	3610 08 00	3610 08 04	0.007
		10	3610 10 00	3610 10 04	0.011
		12	3610 12 00	3610 12 04	0.013
		14	3610 14 00	3610 14 04	0.016
		Red and green colours are available upon request Coloured release buttons covers help the identification of circuits and will protect your connections against spark projections.			

LF 3800/LF 3900 Push-In Fittings Range

Stud Fittings

Straights

3805
3905
BSPT
Page 1-79



3805
NPT
Page 1-79



3801
3901
BSPP/Metric
Page 1-79



3821
3921
BSPT
Page 1-80



3821
3921
NPT
Page 1-80



3831
3931
BSPP/Metric
Page 1-80



3800
3900
Page 1-81



Straights - Inch

3805
NPT
Page 1-79



3821
NPT
Page 1-80



Elbows

3809
3909
BSPT
Page 1-81



3809
NPT
Page 1-81



3899
3999
BSPP/Metric
Page 1-81



3889
3989
BSPT
Page 1-82



3889
NPT
Page 1-82



3879
3979
BSPP
Page 1-82



3889
NPT
Page 1-82



Elbow - Inch

Tees

3803
3903
BSPT
Page 1-83



3803
NPT
Page 1-83



3893
3993
BSPP/Metric
Page 1-83



3808
3908
BSPT
Page 1-83



3808
NPT
Page 1-84



3898
3998
BSPP/Metric
Page 1-84



Tube-to-Tube Fittings

Straight

3806
3906
Page 1-85



Straight - Inch

3806
3906
Page 1-85



Elbow

3802
3902
Page 1-85



Elbow - Inch

3802
3902
Page 1-85



Tee

3804
3904
Page 1-85



Tee - Inch

3804
Page 1-86



Bulkhead Connector Fittings

Straight

3816
3916
Page 1-86



Straight - Inch

3816
3916
Page 1-86



Plug-In Fittings and Accessories

3866
3966
Reducer
Page 1-87



3826
Plug
Page 1-87



Accessories

3800 70
Page 1-87



0605
Page 1-87



3000 70
Page 1-87



LF 3800/LF 3900 Push-In Fittings

Parker Legris has developed two ranges of **stainless steel fittings** (LF 3800 or LF 3900 in full 316L) for conveying corrosive fluids in **aggressive environments**. These ranges provide two complementary levels of corrosion resistance and a **hygienic external design**.

Product Advantages

High Resistance to Aggressive Environments

LF 3800: excellent for conveying aggressive fluids
LF 3900: maximum chemical resistance to internal and external corrosion
Hygienic external design for reducing retention zones
Easy cleaning in situ
Proven gripping technology

Wide Range of Applications

Perfect for permanent contact with foodstuffs
Compatible with frequent sterilization
Excellent in saline environments and outdoor applications
Resistant to industrial cleaning agents and detergents
Compatible with polymer and grooved stainless steel tubing
One fitting for many applications: optimised stock management

Reliability & Safety

All-metal product allowing detection of all components
Full bore, with minimal pressure drop
Resistant to hammering, mechanical shock and impulse
Manual connection and disconnection, no tools required
100% leak-tested in production
Date coding to guarantee quality and traceability
IP 51 bulkhead: complete protection against ingress in food and non-food zones




Applications
Food Process
Paper Industry
Petrochemical
Pharmaceutical
Chemical
Medical

Technical Characteristics

Compatible Fluids	All fluids compatible with the fitting and tubing component materials					
Working Pressure	Vacuum to 30 bar (20 bar: 3879/3979 and 3889/3989)					
Working Temperature	-20° to +150°C					
Adaptor Tightening Torque	Threads	M5x0.8	G1/8	G1/4	G3/8	G1/2
	daN.m	0.16	0.8	1.2	3	3.5
Bulkhead Tightening Torque	Ø (mm)	4	6	8	10	12
	daN.m min. max.	0.5 0.9	0.5 0.9	0.6 1	0.6 1	0.6 1

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Regulations

ISO 14743 Pneumatic transmissions, push-in fittings for thermoplastic tubing
DI: 97/23/EC (PED)
DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 94/9/EC (ATEX)

RG: 1907/2006 (REACH)
UL94 V-0: Seal
RG: 21CFR (FDA)
RG: 1935/2004/EC
USDA NSF H1: Grease

Stud Fittings

3805/3905

Stud Fitting, Male BSPT Thread

ØD	C			F	F1	H	kg
4	R1/8	3805 04 10	3905 04 10	10	3	14.5	0.008
	R1/4	3805 04 13	3905 04 13	14	3	14.5	0.016
6	R1/8	3805 06 10	3905 06 10	13	4	18	0.012
	R1/4	3805 06 13	3905 06 13	14	4	16.5	0.018
8	R1/8	3805 08 10	3905 08 10	15	5	19	0.015
	R1/4	3805 08 13	3905 08 13	15	6	18	0.018
	R3/8	3805 08 17	3905 08 17	17	6	18.5	0.025
10	R1/4	3805 10 13	3905 10 13	19	6	24	0.029
	R3/8	3805 10 17	3905 10 17	19	6	22.5	0.031
12	R1/4	3805 12 13	3905 12 13	22	7	25	0.035
	R3/8	3805 12 17	3905 12 17	22	8	24	0.038
	R1/2	3805 12 21	3905 12 21	22	10	23	0.046

3805

Stud Fitting, Male NPT Thread

ØD	C		F	F1	H	kg
4	NPT1/8	3805 04 11	11	3	14.5	0.009
6	NPT1/8	3805 06 11	13	4	18	0.012
	NPT1/4	3805 06 14	14	4	16.5	0.017
8	NPT1/8	3805 08 11	15	5	19	0.015
	NPT1/4	3805 08 14	15	6	18	0.019
10	NPT1/4	3805 10 14	19	6	24	0.028
	NPT3/8	3805 10 18	19	7	22.5	0.031
	NPT1/2	3805 12 14	22	7	25	0.035
12	NPT3/8	3805 12 18	22	8	24	0.039
	NPT1/2	3805 12 22	22	10	23	0.045

3805

Stud Fitting, Male NPT Thread

Inch

ØD	C		F	F1	H	kg
3/16	NPT1/8	3805 55 11	10	3	15.5	0.010
	NPT1/4	3805 55 14	14	3	15.5	0.016
1/4	NPT1/8	3805 56 11	13	4	19	0.012
	NPT1/4	3805 56 14	14	4	17.5	0.017
3/8	NPT1/4	3805 60 14	19	6	25	0.029
	NPT3/8	3805 60 18	19	7	24	0.032
	NPT1/2	3805 62 14	22	7	26	0.039
1/2	NPT3/8	3805 62 18	22	8	25	0.042
	NPT1/2	3805 62 22	22	10	25	0.050

5/32" (4 mm) and 5/16" (8 mm) also available

3801/3901

Stud Fitting, Male BSPP and Metric Thread






ØD	C		F	F1	H	kg
4	M5x0.8	3801 04 19	10	2.5	17	0.006
	G1/8	3801 04 10	13	3	16.5	0.009
	M5x0.8	3801 06 19	13	2.5	20.5	0.010
6	G1/8	3801 06 10	13	4	18	0.010
	G1/4	3801 06 13	17	4	18	0.015
	G1/8	3801 08 10	15	5	19	0.013
8	G1/4	3801 08 13	17	5	20.5	0.017
	G3/8	3801 08 17	21	6	20	0.027
10	G1/4	3801 10 13	19	7	25	0.025
	G3/8	3801 10 17	21	7	25	0.035
12	G1/4	3801 12 13	21	7	27	0.030
	G3/8	3801 12 17	21	9	26.5	0.034

Other products are available upon request; please do not hesitate to consult us.

Stud Fittings





3821/3921

Stud Standpipe, Male BSPT Thread

	Stainless steel 316L	ØD	C			F	H	kg
4		R1/8	3821 04 10		3921 04 10	10	21	0.006
			3821 06 10		3921 06 10	10	23	0.007
6		R1/4	3821 06 13		3921 06 13	14	24	0.015
			3821 08 10		3921 08 10	11	24	0.008
8		R1/4	3821 08 13		3921 08 13	14	25	0.015
			3821 10 13		3921 10 13	19	30	0.020
10		R3/8	3821 10 17		3921 10 17	19	30	0.022
			3821 12 13		3921 12 13	19	31	0.017
12		R3/8	3821 12 17		3921 12 17	19	31	0.022
			3821 12 21		3921 12 21	22	32	0.040

3821/3921




Stud Standpipe, Male NPT Thread

	Stainless steel 316L	ØD	C			F	H	kg
4		R1/8	3821 04 11		3921 04 11	10	21	0.006
			3821 06 11		3921 06 11	10	23	0.008
6		R1/4	3821 06 14		3921 06 14	14	24	0.016
			3821 08 11		3921 08 14	14	24	0.010
8		R1/4	3821 08 14		3921 08 14	14	25	0.016
			3821 10 14		3921 10 14	14	30	0.016
10		R3/8	3821 10 18		3921 10 18	17	30	0.022
			3821 12 14		3921 12 14	14	31	0.022
12		R3/8	3821 12 18		3921 12 18	17	31	0.026
			3821 12 22		3921 12 22	22	32	0.052

3821

Stud Standpipe, Male NPT Thread



Inch

	Stainless steel 316L	ØD	C			F	H	kg
3/16		NPT1/8	3821 55 11			9.9	24.9	0.009
			3821 56 11			9.9	25.9	0.009
1/4		NPT1/4	3821 56 14			14	26.9	0.018
			3821 60 14			19	32	0.018
3/8		NPT3/8	3821 60 18			19	32	0.029
			3821 62 14			19	36.1	0.033
1/2		NPT3/8	3821 62 18			19	37.1	0.037
			3821 62 22			22.1	37.1	0.055

5/32" (4 mm) and 5/16" (8 mm) also available

3831/3931

Stud Standpipe, Male BSPP and Metric Thread



	Stainless steel 316L, FKM	ØD	C			F	H	K	kg
4		G1/8	3831 04 19		3931 04 19	7	23.5	8	0.005
			3831 04 10		3931 04 10	13	22	14	0.008
6		G1/4	3831 04 13		3931 04 13	17	22	18.5	0.016
			3831 06 10		3931 06 10	13	24	14	0.009
8		G1/4	3831 06 13		3931 06 13	17	24	18.5	0.015
			3831 08 10		3931 08 10	13	25	14	0.010
10		G1/4	3831 08 13		3931 08 13	17	27	18.5	0.018
			3831 10 13		3931 10 13	17	32	18.5	0.020
12		G3/8	3831 10 17		3931 10 17	21	27	23	0.026
			3831 12 13		3931 12 13	17	33	18.5	0.022
12		G3/8	3831 12 17		3931 12 17	21	33	23	0.028
			3831 12 21		3931 12 21	24	36	26	0.043

LF 3800 : full 316L stainless steel (body) with 303 stainless steel collet, FKM seals
LF 3900 : full 316L, FKM seals

Stud Fittings



3800/3900

Cartridge

	Stainless steel 316L, FKM		ØD			L	G	G1	H	H1	H2	kg
			4			9.8	8	17	8.5	8.5	11	0.006
			6			12.1	10	19	10.5	8.5	13.5	0.008
			8			14.8	13	21	12.5	8.5	16	0.012
			10			17.5	15	24.5	14	10.5	20	0.019
			12			20	17	25	14.5	10.5	22.5	0.023
			Cavity dimensions are available in Chapter 2. 3800: collet in stainless steel 303 3900: collet in stainless steel 316L									



3809/3909

Stud Elbow, Male BSPT Thread

	Stainless steel 316L, FKM		ØD	C			F	G	H	L	kg
			4	R1/8			10	10	23.5	16.5	0.020
			6	R1/8			13	12	27.5	20	0.031
			6	R1/4			14	12	27.5	25	0.036
			8	R1/8			14	15	32	25	0.041
			8	R1/4			14	14.5	34	25	0.046
			10	R1/4			19	17.5	37.5	27.5	0.068
			10	R3/8			19	17.5	37.5	27.5	0.069
	The body swivels for positioning purposes.										



3809

Stud Elbow, Male NPT Thread

	Stainless steel 316L, FKM		ØD	C			F	G	H	L	kg
			4	NPT1/8			11	10	25.5	18.5	0.021
			6	NPT1/8			13	12.5	29	22.5	0.025
			6	NPT1/4			14	12.5	29	22.5	0.030
			8	NPT1/8			14	15	34	24	0.041
			8	NPT1/4			14	15	34	24	0.046
			10	NPT1/4			19	17.5	39.5	30	0.057
			10	NPT3/8			19	17.5	39.5	30	0.071
	The body swivels for positioning purposes.										


3899/3999

Stud Elbow, Male BSPP and Metric Thread

	Stainless steel 316L, FKM		ØD	C			F	G	H	L	kg
			4	M5x0.8			10	10	26	18	0.019
			4	G1/8			13	10	27	19	0.021
			4	G1/4			17	10	27	19	0.018
			6	M5x0.8			13	12	33	24	0.031
			6	G1/8			6	12	33	24	0.031
			6	G1/4			17	12	32	24	0.035
			8	G1/8			14	15	35	25	0.039
			8	G1/4			17	15	35	25	0.044
			8	G3/8			21	15	34.5	25	0.048
			10	G1/4			19	17	43	31	0.068
			10	G3/8			21	17	42	31	0.072
	The body swivels for positioning purposes.										

Stud standpipe 3821, 3921, 3831, 3931 can be used as illustrated, allowing:

- stock optimisation
- installation of tees and elbows where required



Stud Fittings

3889/3989

Compact Stud Elbow, Male BSPT Thread

	ØD	C			F	G	H	L	kg
4	R1/8	3889 04 10	3989 04 10		13	10	18	17	0.018
	R1/4	3889 04 13	3989 04 13		17	10	19.5	16.5	0.025
6	R1/8	3889 06 10	3989 06 10		13	12	21.5	20.5	0.026
	R1/4	3889 06 13	3989 06 13		14	12	21.5	20.5	0.032
8	R1/8	3889 08 10	3989 08 10		14	15	24	22	0.036
	R1/4	3889 08 13	3989 08 13		14	15	24	22	0.041
10	R1/4	3889 10 13	3989 10 13		17	17.5	28.5	27.5	0.057
	R3/8	3889 10 17	3989 10 17		19	17.5	28.5	27.5	0.062
12	R1/4	3889 12 13	3989 12 13		22	20	33.5	30	0.086
	R3/8	3889 12 17	3989 12 17		22	20	33.5	30	0.088
	R1/2	3889 12 21	3989 12 21		22	20	33.5	33	0.095

The body swivels for positioning purposes.
Max. 20 bar

3889

Compact Stud Elbow, Male NPT Thread

	ØD	C			F	G	H	L	kg
4	NPT1/8	3889 04 11			13	10	17.5	19	0.019
	NPT1/8	3889 06 11			13	12.5	20	22.5	0.020
6	NPT1/4	3889 06 14			14	12.5	20	22.5	0.033
	NPT1/8	3889 08 11			13	15	25	24	0.037
8	NPT1/4	3889 08 14			14	15	24	24	0.037
	NPT1/8	3889 10 14			17	17.5	27.5	27.5	0.058
10	NPT3/8	3889 10 18			19	17.5	28.5	26.5	0.067
	NPT1/4	3889 12 14			22	20	31.5	32.5	0.070
12	NPT3/8	3889 12 18			22	20	32.5	32.5	0.087
	NPT1/2	3889 12 22			22	20	27.5	32.5	0.072

The body swivels for positioning purposes.
Max. 20 bar

3889

Compact Stud Elbow, Male NPT Thread

Inch

	ØD	C			F	G	H	L	kg
3/16	NPT1/8	3889 55 11			10	9.9	20.6	19.6	0.019
	NPT1/4	3889 55 14			14	9.9	20.6	19.6	0.022
1/4	NPT1/8	3889 56 11			13	11.9	21.6	23.1	0.026
	NPT1/4	3889 56 14			14	11.9	21.6	23.1	0.031
3/8	NPT1/4	3889 60 14			17	17.5	28.4	30.5	0.059
	NPT3/8	3889 60 18			19	17.5	28.4	30.5	0.062
1/2	NPT1/4	3889 62 14			22	20.1	34	33	0.086
	NPT3/8	3889 62 18			22	20.1	34	33	0.088
	NPT1/2	3889 62 22			22	20.1	27.2	33	0.091

The body swivels for positioning purposes; 5/32" (4 mm) and 5/16" (8 mm) also available.
Max. 20 bar

3879/3979

Compact Stud Elbow, Male BSPP Thread

	ØD	C			F	G	H	L	kg
4	G1/8	3879 04 10	3979 04 10		10	11	22	19	0.021
	G1/4	3879 04 13	3979 04 13		17	11	20	19	0.026
6	G1/8	3879 06 10	3979 06 10		13	12	24	24	0.029
	G1/4	3879 06 13	3979 06 13		17	12	22	24	0.034
8	G1/8	3879 08 10	3979 08 10		13	15	25	25	0.035
	G1/4	3879 08 13	3979 08 13		17	15	25	25	0.040
10	G3/8	3879 08 17	3979 08 17		21	15	23	25	0.048
	G1/4	3879 10 13	3979 10 13		18	17	43	31	0.056
12	G3/8	3879 10 17	3979 10 17		21	17	40	31	0.067
	G1/4	3879 12 13	3979 12 13		17	20	33	33	0.075
12	G3/8	3879 12 17	3979 12 17		21	20	33	33	0.082
	G1/2	3879 12 21	3979 12 21		24	20	30	33	0.094



The body swivels for positioning purposes.
Max. 20 bar

Stud Fittings

3803/3903

Stud Run Tee, Male BSPT Thread


Stainless steel 316L, FKM

ØD	C			F	G	H	H1	L	kg
4	R1/8	3803 04 10	3903 04 10	10	10	19	17	22	0.020
6	R1/8	3803 06 10	3903 06 10	13	12	22	20	26.5	0.038
	R1/4	3803 06 13	3903 06 13	14	15	22	20	27	0.035
8	R1/8	3803 08 10	3903 08 10	14	15	24	23	31	0.050
	R1/4	3803 08 13	3903 08 13	14	15	24	23	31	0.055
10	R1/4	3803 10 13	3903 10 13	19	17.5	30	29	38	0.070
	R3/8	3803 10 17	3903 10 17	19	17.5	30	29	38	0.084


The body swivels for positioning purposes.


3803

Stud Run Tee, Male NPT Thread



Stainless steel 316L, FKM





ØD	C		F	G	H	H1	L	kg
4	NPT1/8	3803 04 11	11	10	21	19	25	0.020
6	NPT1/8	3803 06 11	13	12	24	21	27	0.031
	NPT1/4	3803 06 14	14	12	24	21	27.5	0.037
8	NPT1/8	3803 08 11	14	15	26.5	24	30.5	0.050
	NPT1/4	3803 08 14	14	15	26.5	24	30.5	0.048
10	NPT1/4	3803 10 14	19	17.5	31	29.5	37.5	0.084

The body swivels for positioning purposes.

3893/3993

Stud Run Tee, Male BSPP and Metric Thread

Stainless steel 316L, FKM



ØD	C			F	G	H	H1	L	kg
4	M5x0.8	3893 04 19	3993 04 19	10	11	21.5	19	24.5	0.023
	G1/8	3893 04 10	3993 04 10	13	11	21.5	19	24.5	0.026
	G1/4	3893 04 13	3993 04 13	17	11	22	19	28	0.033
6	G1/8	3893 06 10	3993 06 10	13	12	26.5	24	30	0.038
	G1/4	3893 06 13	3993 06 13	17	12	26	24	32	0.044
8	G1/8	3893 08 10	3993 08 10	14	15	27.5	25	32	0.049
	G1/8	3893 08 13	3993 08 13	17	15	28	25	33.5	0.054
	G3/8	3893 08 17	3993 08 17	21	15	27	25	35.5	0.094
10	G1/4	3893 10 13	3993 10 13	19	17	35.5	31	39.5	0.081
	G3/8	3893 10 17	3993 10 17	21	17	35.5	31	39.5	0.082

The body swivels for positioning purposes.

3808/3908

Stud Branch Tee, Male BSPT Thread

Stainless steel 316L, FKM

ØD	C			F	G	H	L/2	kg
4	R1/8	3808 04 10	3908 04 10	10	10	23.5	19	0.020
	R1/8	3808 06 10	3908 06 10	13	12	27.5	24	0.038
6	R1/4	3808 06 13	3908 06 13	14	12	27.5	24	0.043
	R1/8	3808 08 10	3908 08 10	14	15	32	25	0.049
8	R1/4	3808 08 13	3908 08 13	14	15	32	25	0.048
	R3/8	3808 08 17	3908 08 17	19	15	33	25	0.068
10	R1/4	3808 10 13	3908 10 13	19	17.5	37.5	31	0.081
	R3/8	3808 10 17	3908 10 17	19	17.5	37.5	31	0.070



The body swivels for positioning purposes.

These models enable compact connection for elbow outlets, thus allowing space saving.

Stud Fittings

3808



Stud Branch Tee, Male NPT Thread

	Stainless steel 316L, FKM		ØD	C		F	G	H	L/2	kg
			4	NPT1/8	3808 04 11	11	10	22	19	0.021
			6	NPT1/8	3808 06 11	13	12.5	30	24	0.031
				NPT1/4	3808 06 14	14	12.5	30	24	0.044
			8	NPT1/8	3808 08 11	14	15	34	25	0.042
				NPT1/4	3808 08 14	14	15	34	25	0.048
			10	NPT1/4	3808 10 14	19	17.5	40	31	0.069
				NPT3/8	3808 10 18	19	17.5	40	31	0.084

The body swivels for positioning purposes.

3898/3998

Stud Branch Tee, Male BSPP and Metric Thread

	Stainless steel 316L, FKM		ØD	C			F	G	H	L/2	kg
			4	M5x0.8	3898 04 19	3998 04 19	10	11	27	19	0.024
				G1/8	3898 04 10	3998 04 10	13	11	27	19	0.026
				G1/4	3898 04 13	3998 04 13	17	11	27	19	0.032
			6	M5x0.8	3898 06 19	3998 06 19	13	12	33.5	24	0.038
				G1/8	3898 06 10	3998 06 10	13	12	33	24	0.038
				G1/4	3898 06 13	3998 06 13	17	12	32	24	0.043
			8	G1/8	3898 08 10	3998 08 10	14	15	35	25	0.051
				G1/4	3898 08 13	3998 08 13	17	15	35	25	0.054
				G3/8	3898 08 17	3998 08 17	21	15	34.5	25	0.058
			10	G1/4	3898 10 13	3998 10 13	19	17	43	31	0.082
				G3/8	3898 10 17	3998 10 17	21	17	41	31	0.087





The body swivels for positioning purposes.

LF 3800 : full 316L stainless steel (body) with 303 stainless steel collet, FKM seals
 LF 3900 : full 316L, FKM seals

Tube-to-Tube Fittings

3806/3906





Equal Straight Connector

	Stainless steel 316L, FKM		ØD			G	L	kg
			4	3806 04 00	3906 04 00	10	29	0.009
			6	3806 06 00	3906 06 00	12	34	0.015
			8	3806 08 00	3906 08 00	15	36	0.019
			10	3806 10 00	3906 10 00	17.5	45	0.032
			12	3806 12 00	3906 12 00	20	46.5	0.041

3806/3906





Equal Straight Connector

Inch

	Stainless steel 316L, FKM		ØD			G	L	kg
			3/16	3806 55 00	3906 55 00	9.9	30	0.010
			1/4	3806 56 00	3906 56 00	11.9	35.1	0.015
			3/8	3806 60 00	3906 60 00	17.5	46	0.030
			1/2	3806 62 00	3906 62 00	20.1	48	0.040
			5/32" (4 mm) and 5/16" (8 mm) also available					

3802/3902





Equal Stud Elbow

	Stainless steel 316L, FKM		ØD			G	L	kg
			4	3802 04 00	3902 04 00	10	21.5	0.015
			6	3802 06 00	3902 06 00	12	26.5	0.024
			8	3802 08 00	3902 08 00	15	29.5	0.031
			10	3802 10 00	3902 10 00	17.5	36.5	0.051
			12	3802 12 00	3902 12 00	20	40	0.069

3802/3902





Equal Stud Elbow

Inch

	Stainless steel 316L, FKM		ØD			G	L	kg
			3/16	3802 55 00	3902 55 00	9.9	24.4	0.011
			1/4	3802 56 00	3902 56 00	11.9	29	0.023
			3/8	3802 60 00	3902 60 00	17.5	39.6	0.042
			1/2	3802 62 00	3902 62 00	20.1	40.9	0.070
			5/32" (4 mm) and 5/16" (8 mm) also available					

3804/3904

Equal Tee

	Stainless steel 316L, FKM		ØD			G	L	L/2	kg
			4	3804 04 00	3904 04 00	10	22	19	0.015
			6	3804 06 00	3904 06 00	12	26	24	0.031
			8	3804 08 00	3904 08 00	15	29.5	25	0.041
			10	3804 10 00	3904 10 00	17.5	36.5	31	0.064
			12	3804 12 00	3904 12 00	20	40	33	0.064

Bulkhead Connector Fittings


3804/3904

Equal Tee

Inch



Stainless steel 316L, FKM



ØD			G	H	L/2	kg
3/16	3804 55 00	3904 55 00	9.9	22.6	19	0.017
1/4	3804 56 00	3904 56 00	11.9	26.9	22	0.031
3/8	3804 60 00	3904 60 00	17.5	37.6	30	0.059
1/2	3804 62 00	3904 62 00	20.1	40.9	32	0.090


5/32" (4 mm) and 5/16" (8 mm) also available

3816/3916

Equal Bulkhead Connector



Stainless steel 316L, FKM



ØD			F	F1	L1	L2	ØT	kg
4	3816 04 00	3916 04 00	13	14	13.5	19.5	13	0.017
6	3816 06 00	3916 06 00	17	17	16.5	21.5	14	0.027
8	3816 08 00	3916 08 00	19	19	18	24	16	0.034
10	3816 10 00	3916 10 00	22	22	21.5	27.5	21	0.049
12	3816 12 00	3916 12 00	24	24	24	29	23	0.059

IP51 sealing


3816/3916

Equal Bulkhead Connector

Inch



Stainless steel 316L, FKM



ØD			F	F1	L1	L2	ØT	kg
3/16	3816 55 00	3916 55 00	17	13	15	21.1	12.4	0.019
1/4	3816 56 00	3916 56 00	19	17	17	22.6	14.5	0.027
3/8	3816 60 00	3916 60 00	27	22	22.1	27.4	20.6	0.052
1/2	3816 62 00	3916 62 00	27	27	20	29	20.1	0.076

IP51 sealing
5/32" (4 mm) and 5/16" (8 mm) also available


LF 3800/LF 3900 push-in fittings allow connection with several types of Parker Legris tubing shown in Chapter 3 of this catalogue, "Technical Tubing and Hose":

- PFA tubing
- Fluoropolymer tubing
- Polyethylene tubing
- Semi-rigid polyamide and flexible Crystal polyurethane tubing


Plug-In Fittings and Accessories


3866/3966



Push-In Reducer



Stainless steel 316L, FKM








ØD1	ØD2			G	L	L1	L2	L3	kg
4	6	3866 04 06	3966 04 06	10	35	19	19	16	0.009
	8	3866 04 08	3966 04 08	10	34	17	20	14	0.011
6	8	3866 06 08	3966 06 08	12	42	24	23	19	0.015
	10	3866 06 10	3966 06 10	12	41	19	25	16	0.019
8	10	3866 08 10	3966 08 10	15	45	22.5	25	20	0.021
	12	3866 08 12	3966 08 12	15	43	20	26	17	0.025
10	12	3866 10 12	3966 10 12	17	50	23	26	24	0.029




3826



Blanking Plug

	Stainless steel 316L			ØD1	ØD2		L	L1	L2	kg
	4	6		3826 04 00	25	17	11	0.003		
	6	8		3826 06 00	30.4	19.5	13.5	0.007		
	8	10		3826 08 00	33	20	14	0.014		
	10	12		3826 10 00	40	25	17	0.025		
	12	14		3826 12 00	43	26	19	0.038		

3800/3900



Pre-Grooving Tool for Stainless Steel Tubing

	Treated steel						G	H	H1	K	L	kg
			3800 70 00		3900 70 00		25	51	13	36	70	0.326
	This tool correctly pre-grooves 4-12 mm O.D. and 3/16"-1/2" O.D. stainless steel tubing, to ensure that the LF 3800/LF 3900 collet grips the tube securely.											

H		H1
L		
ØG		K



0605

Fluoropolymer Tape

	FKM		kg
		0605 12 12	0.012
	<p>Can be used for temperatures from - 250°C to +260°C.</p> <p>Chemically inert and resistant to gases, acids, solvents, hydrocarbons, oils, alkalines, steam, etc.</p> <p>Non-toxic, waterproof, self-lubricating.</p> <p>In accordance with CFR21.</p> <p>Can be used on all materials.</p> <p>Used to facilitate the preparation of leak-free threaded joints.</p> <p>Supplied on a reel: length = 12 m; width = 12.7 mm; thickness = 0.08 mm.</p>		

3000

Disconnection Tool

	Treated steel		H	H1	L	kg
		3000 70 00	25	20	96	0.021
		For disconnecting push-in tubing/fittings where access is difficult, we recommend the use of this disconnection tool.				

LF 6100 Push-In Fittings Range

Stud Fittings

Straights

6105

BSPT/Metric Taper
Page 1-91

6101

Metric Parallel
Page 1-91

6114

Metric Parallel
Page 1-91



Elbow

6179

BSPT Metric Taper
Page 1-91



Tube-to-Tube Fittings

Straight

6106

Page 1-92



Tee

6104

Page 1-92



Accessory

0138

Page 1-92



LF 6100 Push-In Fittings

This fittings range dedicated to **lubrication and vacuum systems**, combines very high performance and manual connection. This technology **secures the connection** and sealing performance, even at high pressure.

Product Advantages

- Robust**
 - Designed for mechanically demanding environments
 - Excellent pressure and temperature resistance
 - Stamped brass forgings for increased service life
- Secure & Reliable**
 - Perfect sealing guaranteed by the three rings
 - The two sealing O-rings positioned before the gripping ring endure no scratching on the tube in the sealing area
 - Manual connection for time-saving
 - No fluid loss
 - Tube cannot be disconnected without the use of a spanner
 - Up to 60 bar with rigid polymer or grooved metal tubing
 - 100% leak-tested in production



Construction Equipment
Lubrication
Transportation
Measurement Systems
Industrial Machines
Industrial Vacuum

Applications


Technical Characteristics

Compatible Fluids	Lubricants, compressed air, vacuum, other fluids and compatible gases							
Working Pressure	Vacuum to 60 bar							
Working Temperature	-20° to +120°C							

Max./Min. Tightening Torques (daN.m)	Thread	M6 x1	M8 x1	M8 x1.25	M10 x1	M12 x1	M14 x1.5	R 1/8	R 1/4
	Taper	0.2/ 0.6	0.2/ 1.2	0.2/ 1	0.2/ 1.2	0.2/ 2	0.5/ 1.5	0.2/ 1.0	0.5/ 1.5
	Parallel	-	0.6/ 1	-	0.6/ 1	1.8/ 2.2	-	-	-

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Regulations

DI: 97/23/EC (PED)
DI: 2002/95/EC (RoHS),
2011/65/EC

DI: 94/9/EC (ATEX)
RG: 1907/2006 (REACH)

Performance



Working Pressure / Temperature According to the Tubing Used

O.D. of Tube	-20°C to +20°C		+20°C to +30°C		+30°C to +50°C		+50°C to +80°C		+80°C to 120°C
	Semi-Rigid PA	Rigid PA	Semi-Rigid PA	Rigid PA	Semi-Rigid PA	Rigid PA	Semi-Rigid PA	Rigid PA	FEP
2x4	40	-	33	-	25.5	-	19	-	-
2.5x4	-	52	-	43	-	32	-	24.5	7
2.7x4	23	-	19	-	15	-	11	-	-
4x6	24	45	20	37	15.5	29	11	21	6
5x8	-	52	-	43	-	33	-	24	-
6x8	17	32	14	27	11	21	8	15	4
6x10	-	57	-	47	-	37	-	27	-
7.5x10	17	-	14	-	11	-	8	-	-
8x10	14	-	12	-	9	-	7	-	3



Should your requirement not be covered by our standard range, please consult us for customised fittings.

Stud Fittings



6105 Stud Fitting, Male BSPT and Taper Metric Thread

	Brass, NBR	ØD	C		F1	F2	H	kg
		4	M6x1	6105 04 52	13	11	16.5	0.013
		4	M8x1	6105 04 56	13	11	14.5	0.012
		4	M8x1.25	6105 04 57	13	11	14.5	0.012
		4	M10x1	6105 04 60	13	11	14.5	0.014
		4	R1/8	6105 04 10	13	11	14.5	0.014
		4	R1/4	6105 04 13	14	11	12.5	0.018
		6	M10x1	6105 06 60	17	14	16.5	0.024
		6	R1/8	6105 06 10	17	14	17.5	0.026
		6	M14x1.5	6105 06 71	17	14	16.5	0.028
		6	R1/4	6105 06 13	17	14	16.5	0.030
		8	M12x1	6105 08 65	19	21	24	0.041
		10	M14x1.5	6105 10 71	22	24	26	0.005



6101 Stud Fitting, Male Parallel and Metric Thread

	Brass, NBR	ØD	C		F1	F2	H	kg
		4	M10x1	6101 04 60	13	11	14	0.014
		6	M10x1	6101 06 60	17	14	17.5	0.026
			M12x1	6101 06 65	17	14	16.5	0.025

6114 Stud Fitting, Female Metric Parallel Thread



	Brass, NBR	ØD	C		E	F1	F2	H	kg
		4	M8x1	6114 04 56	8	13	11	25.5	0.021
		6	M8x1	6114 06 56	8	17	14	28.5	0.043

6179 Stud Elbow, Male BSPT and Taper Metric Thread



	Brass, NBR	ØD	C		F	G	H	J	L	kg
		4	M6x1	6179 04 52	11	12.5	14.5	6	20	0.014
			M8x1	6179 04 56	11	12.5	15	6	20	0.015
			M8x1.25	6179 04 57	11	12.5	15	6	20	0.015
			M10x1	6179 04 60	11	12.5	15.5	6	20	0.016
			R1/8	6179 04 10	11	12.5	15.5	6	20	0.017
			R1/4	6179 04 13	11	12.5	17	6	20	0.022
		6	M10x1	6179 06 60	14	16	18	8	25.5	0.030
			M12x1	6179 06 65	14	16	18	8	25.5	0.030
			R1/8	6179 06 10	14	16	18	8	25.5	0.030
		8	R1/4	6179 06 13	14	16	19	8	25.5	0.035
			M12x1	6179 08 65	17	19	21	10	30	0.047

Tube-to-Tube Fittings



6106 Tube-to-Tube Connector

	Brass, NBR		ØD		F1	F2	L	kg
			4	6106 04 00	13	11	34	0.025
			6	6106 06 00	17	14	39	0.044
			8	6106 08 00	19	17	46	0.069

6104 Equal Tee

	Brass, NBR		ØD		F	G	H	L/2	kg
			4	6104 04 00	11	12.5	26.5	20	0.032
			6	6104 06 00	14	16	32.5	25.5	0.066
			8	6104 08 00	17	19	38	30	0.103

0138 Copper Washer

	Copper		C		G1	G2	K	kg
			M8	0138 08 00	8.3	11	1	0.001
			M10	0138 10 00	10.3	13.5	1	0.001
			M12	0138 12 00	12.3	15.5	1.3	0.072

DIN 7603
ISO 65061

Related Products

The Parker Legris push-in system for centralised lubrication is designed for use with various polymer tubing found in Chapter 3, "Technical Tubing and Hose":

- Fireproof High Resistance PA Tubing
- Rigid and Semi-Rigid Calibrated Polyamide Tubing
- Fluoropolymer Tubing



Cartridges and Customised Products





Cartridges

Polymer Cartridges

Compressed Air							Fluids and Gases	
3100 Carstick® Page 2-8	3086 Quick Fitting Page 2-8	3089 Quick Fitting Page 2-8	3082 Quick Fitting Page 2-8	3081 Quick Fitting Page 2-9	3088 Quick Fitting Page 2-9	3100 - Inch Carstick® Page 2-8	6300 Carstick® LIQUIfit® Page 2-10	6300 - Inch Carstick® LIQUIfit® Page 2-10
								

Metal Cartridges

Fluids and Gases			
3600 Page 2-13	3800 3900 Page 2-13	TL Page 2-13	TLT Disconnection Tool Page 2-13
			

Polymer Cartridges: LF 3000® and LIQUIfit® Carstick®, Quick Fitting

Parker Legris has developed the range of patented **Carstick®** cartridges guaranteeing **the integrity of the sealing system** before and after assembly in non-threaded cavities. The **compact design** of the one-piece Carstick® cartridge enables **automation** of your manufacturing process and improves the **reliability** of your system.

Product Advantages

Time-Saving	<ul style="list-style-type: none"> No thread to be machined for inserting the fitting into its cavity Seal pre-assembled, greased and protected Self-centring of the cartridge in the cavity Product protected against contamination, from manufacture to installation Possible to have several diameters of tube in the same cavity (Quick Fitting)
Proven Technology	<ul style="list-style-type: none"> Technical performances of the LF 3000® Push-in connection Full flow Optimum flow at pressure and vacuum LIQUIfit® Carstick® compatible with drinking water and food fluids
Automated Installation	<ul style="list-style-type: none"> Ensures that the product will be correctly assembled Connection fully integrated in the cavity Carstick® packaging designed for an automatic assembly process




Applications

- Robotics
- Automotive Process
- Pneumatics
- Semi-Conductors
- Water & Beverage
- Packaging
- Vacuum



Technical Characteristics

	LF 3000® Carstick® and Quick Fitting	LIQUIfit® Carstick®
Compatible Fluids	Compressed air	Food fluids, inert gases
Working Pressure	Vacuum to 20 bar	Vacuum to 16 bar*
Working Temperature	-20°C to +80°C	-10°C to +95°C*

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used. Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum). *The pressure/temperature information is shown in Chapter 1, in the "LIQUIfit®" section.



Component Materials



Silicone-free

Regulations

LF 3000® Carstick® and Quick Fitting

ISO 14743: Pneumatic fluid power, push-in fittings for thermoplastic tubes
 DI: 2002/95/CE (RoHS), 2011/65/CE
 DI: 97/23/CE (PED)

LIQUIfit® Carstick®

RG: 1935/2004/CE
 FDA: 21 CFR 177.1550
 NSF 51 to 95°C
 ACS
 DM 174 (Italy)

DI: 2002/95/CE (RoHS), 2011/65/CE
 DI: 97/23/CE (PED)
 WRAS
 NSF/ANSI 61 - C HOT
 KTW: cartridges on request

Assembly Options

Cartridge solutions quickly pay for themselves when they enable production to be rationalised:

Threaded Fittings

For small quantities or non-standard assembly operations:
The threaded solution remains the most advantageous.




Carstick®: Manual Assembly

For medium quantities:
Assembly by manually-operated press offers the most economic solution.




Carstick®: Automated Assembly

For repetitive operations and large quantities:
Investment in an automated manufacturing solution is quickly recovered, providing significant long-term savings.



Installation


Carstick® Installation



Assembly tool:
For details on the assembly tool, please contact us.



Quick Fitting Installation



Assembly tool:
For details on the assembly tool, please contact us.



1. Self-centering of the cartridge in the cavity.
2. The seal protection is broken.
The seal slides into the cavity.
The cartridge is in place.







3. Tube connection.

Polymer Cartridges for Compressed Air

3100





Carstick® Cartridge

	Brass, NBR		ØD		G	G1	H	L	kg
			4	3100 04 00	8	11	10	554	0.001
			6	3100 06 00	10	14.5	11.5	629	0.002
			8	3100 08 00	13	15	15	794	0.002
			10	3100 10 00	15.5	19.5	17	930	0.005
			12	3100 12 00	19.5	21	19.5	1038	0.010
			50 cartridges per Carstick®						
									

3100




Carstick® Cartridge

Inch

	<p>Nickel-plated brass, NBR</p> 	ØD		G	G1	H	L	kg
		1/8	3100 53 00 99	7	10	9	508	0.002
		1/4	3100 56 00 99	10.5	14.5	12	600	0.003
		3/8	3100 60 00 99	15.5	19	16.5	930	0.006
		50 cartridges per Carstick® 5/32" (4 mm) and 5/16" (8 mm) also available						
								




3086

Quick Fitting Reducer

	<p>Nickel-plated brass, NBR</p> 	ØD		Cavity	G	H	kg
		4	3086 04 06	6	12.5	7	0.005
		6	3086 06 08	8	14	7.5	0.008
		Available on request					


3089

Quick Fitting Elbow


	Technical polymer, nickel-plated brass, NBR		ØD		Cavity	G	G1	H	L	kg
			4	3089 04 04	4	9	12.5	11.5	15	0.004
				3089 04 06	6	9	12.5	11.5	15	0.005
			6	3089 06 04	4	11	12.5	14	17	0.004
				3089 06 06	6	11	12.5	12.5	17	0.006
				3089 06 08	8	11	14.5	13	17	0.010
			8	3089 08 08	8	13.5	14.5	16	23	0.011
				3089 08 10	10	13.5	19	16	23	0.021
			10	3089 10 10	10	16	19	19	26.5	0.017
				3089 10 12	12	16	20	19	26.5	0.028
			12	3089 12 12	12	19	20	22	31	0.030


3082

Quick Fitting Extended Elbow



Technical polymer, nickel-plated brass, NBR



ØD		Cavity	G	G1	H	L	kg
4	3082 04 04	4	9	12.5	16	15	0.006
	3082 04 06	6	9	12.5	15	15	0.009
6	3082 06 06	6	9	12.5	23	19	0.010
	3082 06 08	8	10.5	14	29	18.5	0.014
8	3082 08 08	8	13.5	17	29.5	22.5	0.021
	3082 08 10	10	13.5	19	29	23	0.025
10	3082 10 10	10	16	20	33	26	0.029
	3082 10 12	12	16	20	33	26	0.040
12	3082 12 12	12	19	23	39	31	0.056

Available on request


Polymer Cartridges for Compressed Air

3081

Quick Fitting 45° Elbow



Technical polymer, nickel-plated brass, NBR



ØD		Cavity	G	G1	H	L	kg
4	3081 04 04	4	9	12.5	19	13	0.004
6	3081 06 06	6	11	12.5	22	14.5	0.006
8	3081 08 08	8	13.5	14.5	26	19	0.011
10	3081 10 10	10	16	19	30	22	0.017
12	3081 12 12	12	19	20	35.5	26	0.031


Available on request

3088

Quick Fitting Tee





Technical polymer, nickel-plated brass, NBR



ØD		Cavity	G	G1	H	L	kg
4	3088 04 04	4	9	12.5	14	30	0.005
	3088 04 06	6	8.6	12.5	12.5	29.5	0.006
6	3088 06 06	6	11	12.5	14.5	34	0.007
	3088 06 08	8	10.6	14.5	15	33.5	0.011
8	3088 08 08	8	14	14.5	19	46	0.013
	3088 08 10	10	14	19	19	46	0.023
10	3088 10 10	10	16	19	21	53	0.020
	3088 10 12	12	16	20	21	53	0.031
12	3088 12 12	12	19	20	24	61	0.035

Cavity Dimensions



Carstick® et Quick Fitting

Metric

Cavity	ØD3	H	H1	H2
4	4.1	10	6	8.15
6	6.1	12	7.5	9.65
8	8.15	15.5	9.9	12.45
10	10.25	19	11.7	14.35
12	12.17	22	13.9	16.75

Carstick®

Inch

Cavity	ØD3	H	H1	H2
1/8	3.25	7.45	5.3	9.5
5/32*	4.1	8.15	6	10
1/4	6.45	10.15	8	12.5
5/16*	8.15	12.45	9.9	15.5
3/8	9.65	14.35	11.7	19

Polyamide Cavity

Cavity	ØD1	ØD2	N*	N**	K
4	8.25	7.05	9.8	12.3	1.5
6	10.2	9.15	12.2	12.3	2
8	12.15	10.85	14.2	14.3	2
10	14.8	13.2	16.8	19	2
12	17.5	15.5	20	20.2	2.5

Cavity	ØD1	ØD2	N	K
1/8	7.05	6.02	8.6	1.5
5/32*	8.25	7.05	9.75	1.5
1/4	10.55	9.35	12.6	2
5/16*	12.15	10.85	14.2	2
3/8	14.8	13.1	16.8	2

Aluminium Cavity

Cavity	ØD1	ØD2	N*	N**	K*	K**
4	8.25	7.5	11.5	12.3	3	1.5
6	10.3	9.15	13.5	12.3	3	2
8	12.2	10.85	15.2	15.2	3	2
10	15.05	13.2	17.1	19	2	2
12	17.5	15.5	20	20.2	2.5	2.5

Cavity	ØD1	ØD2	N	K
1/8	7.1	6.2	8.6	1.5
5/32*	8.25	7.05	11.25	3
1/4	10.6	9.35	12.65	2
5/16*	12.2	10.85	15.2	3
3/8	15.05	13.1	17.1	2

Brass Cavity

Cavity	ØD1	ØD2	N*	N**	K*	K**
4	8.25	7.05	10.25	12.3	2	1.5
6	10.25	9.1	12.25	12.3	2	2
8	12.2	10.85	14.25	14.3	2	2
10	15.05	13.2	17.1	19	2	2
12	17.65	15.5	20	20.2	2.5	2.5

Cavity	ØD1	ØD2	N	K
1/8	7.1	6.2	8.6	1.5
5/32*	8.25	7.05	10.25	2
1/4	10.6	9.35	12.65	2
5/16*	12.2	10.85	14.25	2
3/8	10.05	13.1	17.1	2

Please consult us for detailed drawings of cavity dimensions and tolerances.

All our dimensions are in millimeters.





*Carstick® / **Quick Fitting

*5/32" = 4 mm and 5/16" = 8 mm

Polymer Cartridges for Fluids and Gases

6300






LIQUIfit® Cartridge

		Laiton, EPDM											
			ØD						G	G1	H	L	kg
			4	6300 04 00					8	11	10	554	0.002
			6	6300 06 00					10	14.5	11.5	629	0.002
			8	6300 08 00					13	15	15	794	0.003
			10	6300 10 00					15.5	19.5	17	930	0.005
			12	6300 12 00					18.5	21	19.5	1038	0.010
50 cartridges per Carstick®													
													


6300

LIQUIfit® Cartridge

Inch

	Laiton, EPDM		ØD		G	G1	H	L	kg
			1/4	6300 56 00	10.5	14.5	12.5	600	0.002
			3/8	6300 60 00	15.5	19	17	930	0.005
			1/2	6300 62 00	22	25	23	1038	0.011
			50 cartridges per Carstick® 5/32" (4 mm) and 5/16" (8 mm) also available						
									

LIQUIfit® Cavity Dimensions



LIQUIfit® Carstick®

Metric

Cavity	ØD3	H	H1	H2
4	4.1	10	6	8.15
6	6.1	12	7.5	9.65
8	8.15	15.5	9.9	12.45
10	10.25	19	11.7	14.35
12	12.17	22	13.9	16.75

LIQUIfit® Carstick®

Inch

Cavity	ØD3	H	H1	H2
1/8	3.25	7.45	5.3	9.5
5/32*	4.1	8.15	6	10
1/4	6.45	10.15	8	12.5
5/16*	8.15	12.45	9.9	15.5
3/8	9.65	14.35	11.7	19

Polyamide Cavity

Cavity	ØD1	ØD2	K	N
4	8.25	7.05	9.8	1.5
6	10.2	9.15	12.2	2
8	12.15	10.85	14.2	2
10	14.8	13.2	16.8	2
12	17.5	15.5	20	2.5

Cavity	ØD1	ØD2	K	N
1/8	7.05	6.02	8.6	1.5
5/32*	8.25	7.05	9.75	1.5
1/4	10.55	9.35	12.6	2
5/16*	12.15	10.85	14.2	2
3/8	14.8	13.1	16.8	2

Aluminium Cavity

Cavity	ØD1	ØD2	K	N
4	8.25	7.5	11.5	3
6	10.3	9.15	13.5	3
8	12.2	10.85	15.2	3
10	15.05	13.2	17.1	2
12	17.5	15.5	20	2.5

Cavity	ØD1	ØD2	K	N
1/8	7.1	6.2	8.6	1.5
5/32*	8.25	7.05	11.25	3
1/4	10.6	9.35	12.65	2
5/16*	12.2	10.85	15.2	3
3/8	15.05	13.1	17.1	2

Brass Cavity

Cavity	ØD1	ØD2	K	N
4	8.25	7.05	10.25	2
6	10.25	9.1	12.25	2
8	12.2	10.85	14.25	2
10	15.05	13.2	17.1	2
12	17.65	15.5	20	2.5

Cavity	ØD1	ØD2	K	N
1/8	7.1	6.2	8.6	1.5
5/32*	8.25	7.05	10.25	2
1/4	10.6	9.35	12.65	2
5/16*	12.2	10.85	14.25	2
3/8	10.05	13.1	17.1	2

*5/32" = 4 mm and 5/16" = 8 mm

Please consult us for detailed drawings of cavity dimensions and tolerances.

All our dimensions are in millimeters.



Metal Cartridges

For full **compatibility** with **many fluids** and severe conditions **(+150°C)**, Parker Legris has developed two types of patented cartridges. Using our metal cartridges allows for **optimisation of installation configurations** and for the TL, the possibility of removal.

Product Advantages

LF Cartridges	LF 3600	All the advantages of the LF 3600, LF 3800 and LF 3900 fittings applied to cartridge technology
	LF 3800	All-metal product to provide the greatest mechanical strength and chemical resistance
	LF 3900	Resistant at high temperatures (+150°C)
		Can be installed in either polymer or metal housings
TL Cartridge		Possibility to have several tubing diameters in the same cavity
		Visible retention and sealing system, can be disassembled using the dedicated tool



Robotics
Automotive Process
Pneumatics
Semi-Conductors
Refrigeration
Packaging
Vacuum

Applications

Technical Characteristics



LF Cartridges		TL Cartridge		Regulations
Compatible Fluids	Fluids: see corresponding chapters	Compatible Fluids	Compressed air	LF 3600, LF 3800, LF 3900 DI: 97/23/CE (PED) RG: 21CFR (FDA) RG: 1935/2004/CE (minimum flow 0.02 l/hr) DI: 2011/65/CE (RoHS) USDA NSF H1: grease ASTM B733-04: self-catalytic nickel coating DI: 94/9/CE (ATEX)
Working Pressure	Vacuum to 30 bar	Working Pressure	0.01 to 16 bar	
Working Temperature	-20°C to +150°C	Working Temperature	-25°C to +80°C	
Component Materials	See corresponding chapters	Component Materials	Body: brass Release button: technical polymer Gripping ring: stainless steel Seals: NBR	
				TL DI: 97/23/CE (PED) DI: 2011/65/CE (RoHS)

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).


Metal Cartridges for Fluids and Gases

3600

One-Piece Cartridge




FDA chemical nickel-plated brass, FKM



ØD		G	G1	H	H1	H2	N	kg
4	3600 04 00	9.8	8	17	8.5	8.5	11	0.006
6	3600 06 00	12.1	10	19	10.5	8.5	13.5	0.009
8	3600 08 00	14.8	13	21	12.5	8.5	16	0.012
10	3600 10 00	17.5	15	24.5	14	10.5	20	0.019
12	3600 12 00	20	17	25	14.5	10.5	22.5	0.023
14	3600 14 00	22	20	28.5	16.5	12	25	0.031



3800/3900

One-Piece Cartridge

 	<p>Stainless steel 316L, FKM</p> 	ØD			G	G1	H	H1	H2	N	kg
		4	3800 04 00	3900 04 00	9.8	8	17	8.5	8.5	11	0.006
		6	3800 06 00	3900 06 00	12.1	10	19	10.5	8.5	13.5	0.008
		8	3800 08 00	3900 08 00	14.8	13	21	12.5	8.5	16	0.012
		10	3800 10 00	3900 10 00	17.5	15	24.5	14	10.5	20	0.019
		12	3800 12 00	3900 12 00	20	17	25	14.5	10.5	22.5	0.023
		3800: collet in 303 stainless steel 3900: collet in 316L stainless steel									

TL



Cartridge

	<p>Brass, NBR</p> 	ØD	Cavity		G	G1	H	H1	H1*	kg
		4	4	FTL4	8	8	14.5	4.5	7.5	0.003
		4	6	FTL4-6	8	10	17	4.5	9.5	0.003
		6	6	FTL6	10.5	10	17	4.5	9.5	0.004
		4	8	FTL8-4	8	12	17.5	5	10.5	0.008
		6	8	FTL8-6	10.5	12	18	5.5	11	0.008
		8	8	FTL8	13.5	12	19	6.5	12	0.005

*Can be mounted in a short hole with extremely close porting


TLT

Disconnection Tool

			G	L	kg
		TLT	28	156	0.235

Only for use with TL cartridges

Cavity Dimensions



TL Cartridge

Cavity	ØD1	ØD2	ØD3	H2	H3
4	9	8	5.5	9	1.5
6	11	10	8	11	1.5
8	13	12	8.5	11.5	1.5
4C*	9	8	5.5	6	1.5
6C*	11	10	8	6	1.5
8C*	13	12	8.5	6	1.5

*Can be mounted in a short hole with extremely close porting

Customised Solutions

Parker Legris has made **the development of customised products** one of its specialities. These dedicated products provide our customers with a **technical and economic solution** which fully meets their needs.

Customised Solution Development Process

- 1. Define the Function Parameters**

Specify the pressure, temperature, environment, fluids, materials and product function you need.

Estimate the quantity requirements.

Our product engineers are available to help you refine your requirements.
- 2. Send Your Request to our Technical Department**

Complete the online request form at www.parkerlegris.com, "Special Products".

Specify your quantities, technical and commercial requirements.
- 3. Request Analysis**

We assess the feasibility of the product based on the information you have sent us.

We carry out a technical study and produce drawings (prototypes and testing as necessary).
- 4. Parker Legris Proposes the Customised Solution**

We submit the optimum technical and commercial proposal.

If our proposal is accepted, we launch the production process.
- 5. Serial Production**

We will continually update you as to the status of your order and delivery date.

Customised Products

Cartridges




Fittings




Function Fittings



Multi-Connectors and Manifolds




Tubing and Blowguns



Valves



Skilled and Dedicated People Provide You with the Best Solution



More than 40 years' experience in the design of push-in fittings also means more than 40 years spent in producing customised solutions for our customers.

We have a team of motivated and experienced engineers skilled in using the latest design tools: calculation and digital simulation tools, CAD, rheology (plastic injection modelling), quick prototyping and performance measuring in the laboratory.

Customised Fittings

To meet your needs, we can re-engineer the design of our fittings.

To complement our wide range of fittings, we can offer customised products.

Longer threads, different types of seal, special grease, specific cleaning processes, colours, packaging, etc. are all parameters which we can easily modify.



Low Temperature Carstick®

Resistant at -40°C



Metal Cartridges

Cartridges adapted to the client's dimensional and environmental requirements

Combination of the patented Carstick® system (seal protection) and LF 3600 performance levels



Fitting for Breathable Air

Specific gripping feature, cleanliness, oxygen-compatible grease

Reinforced leak testing

Coloured release button for fluid identification

Special packaging



Fitting for the Transmission of Deionised Cooling Water in Frequency Inverters

Water-resistant materials

Stainless steel threads

Special seals



Fitting for the Transmission of Water in Ceiling-Mounted Air Conditioning Systems

Brass body

Double seal

Crimped to hose



Orifice Fitting

Allows accurate flow regulation

Minimum orifice diameter: 0.5 mm




Non-Return Valve

Developed for systems carrying breathable air
Low cracking threshold
Oxygen-compatible grease, cleanliness



Compact Flow Regulator with Recessed Screw and FKM Seals

Improved external chemical resistance
Custom logo



Multi-Connector

Allows disconnection of up to 16 tubes in a single operation
Compact design suitable for the operating environment



Polymer Body with Integrated Fittings

For connection of pneumatic lines between the truck cab and chassis




Polymer Manifold

Reinforced integrated connections
Dedicated to the distribution of compressed air for truck auxiliary systems e.g. cab seat, air horn, gauges...

Customised Tubing and Blowguns

We can adapt the formulation of polymers and customise tubing or blowguns to suit your requirements.

We can offer custom modifications such as: special additives and materials, non-standard diameters, customised marking, specific packaging, custom colours, custom tube cutting, pre-formed tubing, packaged solutions (tubes + fittings or couplers, blowgun kits).



Tube marked with customer's name
Tubes cut to specific lengths



Marked with the customer's logo and part number
In lengths of 5 m, 10 m, 25 m, 50 m and 100 m, depending on the tube material
For flexible or semi-rigid tubing
Optimised tube packaging
Easy identification of the tube type
Integrated reel for easy handling



Marked with the customer's logo and part number
Up to 1000 m lengths
Immediate identification of the tube for easy handling
Suitable for workshop hose reels



Blowgun customised in customer's colours
Specific logo
Customised packaging



Production of a "tube + coupler + blowgun" assembly in dedicated and customised packaging

Customised Valves

Over and above our range of standard valves, Parker Legris can supply application-specific valves adapted to our customers' environment.

We offer custom modifications such as:
longer threads, different types of seal, special grease, lever options, specific cleaning process, materials and surface treatments, assemblies, etc.



Transport Valve

Mounted on the wheel rims of armoured vehicles
For managing tyre pressures through an integrated inflation valve



Auto-Process Valve

Designed to simultaneously control both the inlet and outlet of a cooling line
Also allows one of the lines to be closed independently



Valve for Breathable Air

Dedicated to the transmission of oxygen-enriched air in hospital networks
Special seals, cleanliness, specific grease, very high reliability

Technical Tubing and Hose

Flexible Calibrated Tubing

Calibrated Multi-Tubing

Recoil Tubing and Hose

Calibrated Braided Hose

Accessories





Technical Tubing and Hose

PA Tubing

(P. 3-10)



Fluids: Compressed air, industrial fluids

Materials:

- 2 polyamide grades (semi-rigid and rigid)
- 7 colours

Pressure: 58 bar

Temperature: -40°C to +100°C

O.D. metric: 3 mm to 16 mm

O.D. inch: on request

Fireproof High Resistance PA Tubing

(P. 3-14)



Fluids: compressed air, coolants, lubricants

Materials:

- Polyamide with flame retardant additive
- 5 colours

Pressure: 50 bar

Temperature: -40°C to +100°C

O.D. metric: 4 mm to 12 mm

Anti-Spark PA or PU Tubing, with or without PVC Sheath (P. 3-16 & 24)



Fluids : compressed air, coolants, industrial fluids

Materials :

- Semi-rigid polyamide with PVC sheath
- Polyurethane ether with PVC sheath
- Single layer polyurethane ether
- 4 colours

Pressure: 36 bar max.

Temperature: -20°C to +80°C

O.D. metric: 4 mm to 12 mm

PU Tubing

(P. 3-18)



Fluids: compressed air and food industry fluids ("crystal")

Materials:

- Polyurethane ester or ether
- Polyurethane food-grade "crystal"
- 7 colours

Pressure: 12 bar

Temperature: -20°C to +70°C

O.D. metric: 3 mm to 16 mm

O.D. inch: on request

Antistatic PU Tubing

(P. 3-22)



Fluids: compressed air

Materials:

- Polyurethane with conductive particles
- Black ($10^2 \Omega.m$)

Pressure: 10 bar

Temperature: -20°C to +70°C

O.D. metric: 3 mm to 12 mm

PE Tubing

(P. 3-26)



Fluids: many fluids

Materials:

- Low density polyethylene
- 50% reticulated polyethylene, food-grade
- 7 colours

Pressure: 20 bar

Temperature: -40°C to +95°C

O.D. metric: 4 mm to 14 mm

O.D. inch: 1/8" to 1/2"

FEP Tubing

(P. 3-28)



Fluids: many fluids

Materials:

- Fluoropolymer: fluorinated ethylene propylene, food-grade
- Transparent

Pressure: 28 bar

Temperature: -40°C to +150°C

O.D. metric: 4 mm to 12 mm

PFA Tubing

(P. 3-30)



Fluids: many fluids

Materials:

- 3 grades of perfluoroalkoxy
- High purity food-grade, clear
- Standard food-grade, 3 "crystal" colours
- Antistatic ($0.2 \Omega.m$), black

Pressure: 36 bar

Temperature: -196°C to +260°C

O.D. metric: 4 mm to 12 mm

PA Multi-Tubing

(P. 3-32)



Fluids: compressed air, industrial fluids

Materials:

- Semi-rigid polyamide with PVC sheath
- 6 colours

Pressure: 24 bar

Temperature: -40°C to +80°C

O.D. metric: 4 mm to 8 mm

Technical Tubing and Hose

Twin PU Tubing

(P. 3-32)



Fluids: compressed air

Materials:

- Polyurethane ester
- 1 to 2 colours

Pressure: 14 bar

Temperature: -20°C to +70°C

O.D. metric: 4 mm to 8 mm

Recoil PA Tubing

(P. 3-34)



Fluids: compressed air, industrial fluids

Materials:

- Semi-rigid polyamide
- 2 colours
- Recoil tubing with fittings

Pressure: 20 bar

Temperature: -20°C to +80°C

O.D. metric: 6 mm and 8 mm

Recoil PU Tubing

(P. 3-36)



Fluids: compressed air

Materials:

- Polyurethane ester or ether
- 3 colours
- With or without fittings

Pressure: 10 bar

Temperature: -20°C to +70°C

O.D. metric: 4 mm to 12 mm

I.D. inch: 3/8" and 19/32"

Braided PU Recoil Hose

(P. 3-40)



Fluids: compressed air, industrial fluids

Materials:

- Translucent blue polyurethane, reinforced with a polyester braid
- Assembled with threaded fittings

Pressure: 15 bar

Temperature: -40°C to +75°C

I.D. inch: 1/4" and 5/16"

Braided PVC Hose

(P. 3-42)



Fluids: compressed air, non-corrosive or alimentary fluids (translucent PVC)

Materials:

- Polyvinyl chloride with braided polyester
- Translucent (food-grade) or blue (industrial)


Pressure: 15 bar

Temperature: -25°C to +70°C

I.D. metric: 4 mm to 19 mm

Self-Fastening NBR Hose

(P. 3-44)



Fluids: compressed air, coolants

Materials:

- Nitrile butadiene rubber reinforced with a polyamide braid
- 4 colours

Pressure: 16 bar

Temperature: -20°C to +100°C

I.D. inch: 1/4" to 3/4"

Technical Tubing and Hose Range

Flexible Calibrated Tubing

Polyamide Tubing

Semi-Rigid PA



1025P
1100P
2005P
2010P
Page 3-11

Rigid PA



1025L
Page 3-12

Fireproof PA



1025P..R
1100P..R
2005P..R
2010P..R
Page 3-15

Anti-Spark PA with PVC Sheath



1025P..V
1100P..V
Page 3-17

Polyurethane Tubing

PU Ester



1025U
1100U
2003U
2005U
2010U
Page 3-19

PU Ether PU Ether Food-Grade "Crystal"



1025U..R
1100U..R
2003U..R
2005U..R
2010U..R
Page 3-20

Antistatic PU



1025U..A
1100U..A
Page 3-23

PU Ether, Anti-Spark, Single Layer PU Ether, Anti-Spark with PVC Sheath



1025U..V
1100U..V
Page 3-25
1025U..K
1100U..K
Page 3-25

Polyethylene Tubing

Advanced PE



1015Y..F
1030Y..F
1075Y..F
1096Y..F
1098Y..F
1099Y..F
Page 3-27

Low Density PE



1025Y
1100Y
Page 3-27

Fluoropolymer Tubing

FEP



1005T
1025T
Page 3-29

PFA



1010T..P
1050T..P
1100T..P
Page 3-31

Antistatic PFA



1010T..A
1050T..A
Page 3-31

Calibrated Multi-Tubing

Polyamide Tubing with PVC Sheath

Semi-Rigid PA



1010P..M
1050P..M
Page 3-33

Twin Polyurethane Tubing

Twin PU Ester



1420U
Page 3-33

Technical Tubing and Hose Range

Calibrated Recoil Tubing

Semi-Rigid PA

Assembled with Fittings



1470P
1471P
1472P

Page 3-35

PU Ester and Ether Tubing

Assembled with Fittings,
Metallic Spring Guard



1470U
1471U
1472U

Page 3-37

Assembled with Fittings,
Plastic Spring Guard



1445U..R
1441U..R
1442U..R
1447U..R

Page 3-38

Coiled without Fittings



1460U
1461U
1462U

Page 3-37

Braided PU Hose

Assembled with Fittings,
Plastic Spring Guard



1445U..E
1442U..E
1447U..E

Page 3-41

Calibrated Braided Hose

Clear Food-Grade PVC



1025V
1050V

Page 3-43

Blue PVC



1025V..C
1050V..C

Page 3-43

Self-Fastening NBR



1040H
1080H
1100H

Page 3-45

Accessories

0694

Page 3-46

0695

Page 3-46

3000 71 11

Page 3-46

3000 71

Page 3-46

6000 71

Page 3-46

0127

Page 3-47

1827

Page 3-47

Clip

Page 3-47

0697

Page 3-47



Packaging for Technical Tubing and Hose

Tubepack®

- 5 m, 10 m, 25 m and 100 m lengths
- For polyamide, polyurethane, fluoropolymer, polyethylene and anti-spark tubing
- Optimisation of tubing storage
- Immediate identification of the type of tubing
- Integrated winder for easy handling



Drums

- Up to 1000 m long
- For polyamide, polyurethane, fluoropolymer tubing, etc.
- Immediate identification of the tubing for easy handling
- Adapted to workshop reels



Reels

- Up to 100 m
- Supplied with protective plastic film
- For braided tubing, special tubing (e.g. multi-tubing)



Plastic Bags

- Ideal for merchandising
- Promotional tools
- Recoil tubing or tubing cut to the required length



Tube Marking (except for Fluoropolymer, PFA and FEP)

- Length indicated every metre:
 - time saved when cutting to exact length
 - remaining quantity is immediately identifiable (PA and PU)
- Custom marking upon request (marking, fluid identification, customer part number...)
- Traceability with marking of manufacturing batch



Tube Cutting to the Required Length

- Upon request, cutting of your tube to the required length, from 5 cm to 3 m
- Precision +/- 3 mm
- Ideal for optimising your installation costs




Product Codes of Parker Legris Tubing and Hose

Material		Type of Tubing	
H	= Self-Fastening NBR	P..A	= Antistatic PA
L	= Rigid Polyamide	P..R	= Fireproof PA
P	= Semi-Rigid Polyamide	P..V	= Anti-Spark PA with PVC Sheath
T	= Fluoropolymer	T..A	= Antistatic PFA
U	= Polyurethane	T..P	= PFA
V	= PVC	U..A	= Antistatic PU
Y	= Polyethylene	U..K	= Anti-Spark Single Layer PU
		U..R	= PU Ether
		U..V	= Anti-Spark PU with PVC Sheath
		Y..F	= Advanced PE (LIQUIfit®)

2 0 1 0 P 0 4 R 0 0 2 7				
Packaging Code	Length	O.D. Code	Colour	Special I.D.
1 = Tubepack® or LIQUIfit® Drum	015 = 150 m 020 = 20 m 025 = 25 m 030 = 300 m 040 = 40 m 075 = 75 m 080 = 80 m 100 = 100 m	03 = 3 mm 04 = 4 mm 06 = 6 mm 08 = 8 mm .../... 1/4 = 56 mm .../...	00 = clear 01 = black 02 = green 03 = red 04 = blue 05 = yellow 06 = grey 07 = orange 08 = crystal clear 09 = purple 10 = white 12 = crystal green 13 = crystal red 14 = crystal blue 17 = crystal orange	18 = 1.8 mm 27 = 2.7 mm 33 = 3.3 mm 75 = 7.5 mm 95 = 9.5 mm
2 = Long Length on Drum	003 = 300 m 005 = 500 m 010 = 1000 m	10 = 10 mm 04 = 4 mm 06 = 6 mm 08 = 8 mm 10 = 10 mm 04 = 4 mm 06 = 6 mm		

How to Read the Graphs

- In the graphs in this chapter, each curve represents the acceptable maximum pressure at a given temperature, by diameter.
- Technical characteristics of Parker Legris tubing depend on the type of connection used.
- The vacuum capability of all tubing is 755 mm Hg (99% vacuum).



PA Tubing

Tried-and-tested for industrial or vehicle applications, PA tubing guarantees **excellent durability** due to its stable long-term mechanical properties.

Parker Legris' special grade of semi-rigid polyamide is manufactured according to our **Eco-Design** approach for higher performance.

Product Advantages

Tried-&-Tested Material

- Good chemical and humidity resistance
- Excellent material stability (mechanical and chemical)
- Continuous calibration during production for excellent reliability
- Two material grades: rigid and semi-rigid
- Bio-based semi-rigid material

Versatility & Performance

- Wide range of working pressure and temperature
- Good vibration absorption
- Abrasion-resistant
- Remaining length marking
- Large choice of colours to facilitate circuit identification
- Silicone-free



Applications

- Packaging
- Tooling
- Compressed Air
- Motion Technologies
- Robotics
- Industrial Machinery

Technical Characteristics

Tubing	Semi-Rigid PA	Rigid PA
Compatible Fluids	Compressed air, other fluids	Compressed air, lubricants, other fluids
Working Pressure	Vacuum to 50 bar	Vacuum to 60 bar
Working Temperature	-40°C to +100°C	-40°C to +80°C
Component Materials	Bio-based polyamide (68 shore D)	Polyamide (65 shore D)

Regulations

Industrial

DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)

Transportation

Chemical performance and resistance tested according to DIN 74324 -1 / DIN 73378 / ISO 7628


Packaging

TubePack®: 25 m, 100 m
Drum: 500 m, 1 000 m


Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Performance of PA Tubing

Semi-Rigid



Rigid











Tube O.D.	Tube O.D. Tolerance
3 to 5 mm	+0.05 / -0.08
6 to 16 mm	+0.05 / -0.10

Connected to Parker Legris push-in fittings, the calibration of Parker Legris tubing ensures perfect sealing in accordance with NF E49-100.

1025P Semi-Rigid Polyamide (PA) Tubing









Tubepack® 25 m

O.D. (mm)	I.D. (mm)									kg
3	1.8	6	1025P03 00 18				1025P03 04 18			0.020
4	2	10	1025P04 00	1025P04 01	1025P04 02	1025P04 03	1025P04 04	1025P04 05	1025P04 06	0.318
4	2.7	10	1025P04 00 27	1025P04 01 27	1025P04 02 27	1025P04 03 27	1025P04 04 27	1025P04 05 27	1025P04 06 27	0.254
5	3.3	15	1025P05 00 33	1025P05 01 33			1025P05 04 33			0.420
6	4	15	1025P06 00	1025P06 01	1025P06 02	1025P06 03	1025P06 04	1025P06 05	1025P06 06	0.535
8	6	25	1025P08 00	1025P08 01	1025P08 02	1025P08 03	1025P08 04	1025P08 05	1025P08 06	0.748
10	7.5	42	1025P10 00 75	1025P10 01 75			1025P10 04 75			1.135
10	8	50	1025P10 00	1025P10 01	1025P10 02	1025P10 03	1025P10 04	1025P10 05	1025P10 06	0.989
12	9	47	1025P12 00 09	1025P12 01 09			1025P12 04 09			1.769
12	10	90	1025P12 00	1025P12 01			1025P12 04			1.345
14	11	80	1025P14 00 11	1025P14 01 11			1025P14 04 11			2.226
14	12	116	1025P14 00	1025P14 01			1025P14 04			1.734
16	13	90	1025P16 00 13	1025P16 01 13	1025P16 02 13	1025P16 03 13	1025P16 04 13			2.500

Inch version tubing available upon request

1100P Semi-Rigid Polyamide (PA) Tubing









Tubepack® 100 m

O.D. (mm)	I.D. (mm)									kg
4	2	10	1100P04 00	1100P04 01	1100P04 02	1100P04 03	1100P04 04	1100P04 05	1100P04 06	1.152
4	2.7	10	1100P04 00 27	1100P04 01 27	1100P04 02 27	1100P04 03 27	1100P04 04 27	1100P04 05 27	1100P04 06 27	0.893
5	3.3	15	1100P05 00 33	1100P05 01 33			1100P05 04 33			1.274
6	4	15	1100P06 00	1100P06 01	1100P06 02	1100P06 03	1100P06 04	1100P06 05	1100P06 06	1.799
8	6	25	1100P08 00	1100P08 01	1100P08 02	1100P08 03	1100P08 04	1100P08 05	1100P08 06	2.898
10	7.5	42	1100P10 00 75	1100P10 01 75			1100P10 04 75			4.400
10	8	50	1100P10 00	1100P10 01	1100P10 02	1100P10 03	1100P10 04	1100P10 05		3.667
12	9	47	1100P12 00 09	1100P12 01 09			1100P12 04 09			5.600
12	10	90	1100P12 00	1100P12 01			1100P12 04		1100P12 06	5.052
14	11	80	1100P14 00 11	1100P14 01 11			1100P14 04 11			5.200
14	12	116	1100P14 00	1100P14 01			1100P14 04			4.800
16	13	90	1100P16 00 13	1100P16 01 13	1100P16 02 13	1100P16 03 13	1100P16 04 13			7.800

Inch version tubing available upon request









2005P Semi-Rigid Polyamide (PA) Tubing

Drum 500 m

O.D. (mm)	I.D. (mm)									kg
8	6	25	2005P08 00	2005P08 01	2005P08 02	2005P08 03	2005P08 04	2005P08 05	2005P08 06	12.100
10	8	50	2005P10 00	2005P10 01	2005P10 02	2005P10 03	2005P10 04	2005P10 05		15.600

2010P Semi-Rigid Polyamide (PA) Tubing

Drum 1000 m

O.D. (mm)	I.D. (mm)									kg
4	2.7	10	2010P04 00 27	2010P04 01 27	2010P04 02 27	2010P04 03 27	2010P04 04 27	2010P04 05 27	2010P04 06 27	7.630
6	4	15	2010P06 00	2010P06 01	2010P06 02	2010P06 03	2010P06 04	2010P06 05	2010P06 06	16.600

Tube Cutting to the Required Length



- Cutting of your tubing upon request, from 5 cm to 3 m
- Precision +/- 3 mm
- Ideal for optimising your installation costs



PA Tubing

1025L Rigid Polyamide (PA) Tubing

Tubepack® 25 m

O.D. (mm)	I.D. (mm)	 R		kg
4	2.5	35	1025L04 01 25	0.190
6	4	45	1025L06 01	0.400
8	5	70	1025L08 01 05	0.760
8	6	65	1025L08 01	0.760
10	6	85	1025L10 01 06	1.330

PA tubing can be connected to various fittings shown throughout this catalogue.

Tubing

Semi-Rigid PA



Rigid PA



Push-In Fittings

LF 3000* P. 1-4



LF 3600 P. 1-65



LF 3800/LF 3900 P. 1-77



LF 6100 P. 1-89



Compression Fittings

Brass P. 5-5




Stainless Steel P. 5-31



Ferrules P. 5-5





Fireproof High Resistance PA Tubing

This **single layer fireproof** tubing not only combines excellent resistance to pressure, temperature and flame, but also guarantees **non-toxic smoke** resulting from burn-off. This tubing eliminates the need for a stripping tool, thus preventing the risk of tube damage prior to connection.

Product Advantages

Safety for On-Board Railway Equipment

Designed for on-board equipment
Excellent flame-resistance: self-extinguishing
Very little smoke generation
Non-toxic combustion gases
UV-resistant
Extremely resistant to high pressure and temperature

Innovative Single-Layer Solution

Developed for demanding industrial applications
Excellent spark resistance
Economical alternative to PA tubing with PVC sheath
Combines technical advantages of rigid and semi-rigid PA tubing
5 colours available
Flow direction marking
Silicone-free



Applications
Railway
Air Horns
Industrial Machinery
Pneumatic Doors
Step-Units
Centralised Lubrication
Welding

Technical Characteristics

Compatible Fluids	Compressed air, lubricants Other fluids: please consult us
Working Pressure	Vacuum to 50 bar
Working Temperature	-40°C to +100°C
Component Materials	Polyamide (63 shore D)

Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Regulations


Railway

Pr EN 45545-2: HL3, R22, R24, R25
NF F16101: I3 F2,
DIN 5510-2: S4, SR2, ST2
ISO 4892

Industrial

DI: 97/23/EC (PED)
DI: 2002/95/EC (RoHS), 2011/65/EC
RG: 1907/2006/EC (REACH)
UL94 V-0 (Fire resistance)

Performance of Fireproof High Resistance PA Tubing



Tube O.D.	Tube O.D. Tolerance
4 mm	+0.05 / -0.08
6 to 12 mm	+0.05 / -0.10

Connected to Parker Legris push-in fittings, the calibration of PA tubing ensures perfect sealing based on NF E49-100.







Packaging

Tubepack®: 25 m, 100 m
Drum: 500 m, 1000 m

To calculate burst pressure, the values in this graph should be multiplied by 3.







1025P..R Fireproof High Resistant Polyamide (PA)

Tubepack® 25 m

O.D. (mm)	I.D. (mm)		 Clear					kg
4	2	17	1025P04R00	1025P04R01	1025P04R02	1025P04R03	1025P04R04	0.367
6	4	29	1025P06R00	1025P06R01	1025P06R02	1025P06R03	1025P06R04	0.554
8	6	40	1025P08R00	1025P08R01	1025P08R02	1025P08R03	1025P08R04	0.554
10	8	77	1025P10R00	1025P10R01	1025P10R02	1025P10R03	1025P10R04	0.721
12	9	92	1025P12R00	1025P12R01	1025P12R02		1025P12R04	1.345







1100P..R Fireproof High Resistant Polyamide (PA)

Tubepack® 100 m

O.D. (mm)	I.D. (mm)		 Clear					kg
4	2	17	1100P04R00	1100P04R01	1100P04R02	1100P04R03	1100P04R04	1.308
6	4	29	1100P06R00	1100P06R01	1100P06R02	1100P06R03	1100P06R04	1.308
8	6	40	1100P08R00	1100P08R01	1100P08R02	1100P08R03	1100P08R04	2.122
10	8	77	1100P10R00	1100P10R01	1100P10R02	1100P10R03	1100P10R04	2.725
12	9	92	1100P12R00	1100P12R01			1100P12R04	5.052







2005P..R Fireproof High Resistant Polyamide (PA)

Drum 500 m

O.D. (mm)	I.D. (mm)		 Clear					kg
8	6	40	2005P08R00	2005P08R01	2005P08R02	2005P08R03	2005P08R04	17.500
10	8	77	2005P10R00	2005P10R01	2005P10R02	2005P10R03	2005P10R04	22.800

2010P..R Fireproof High Resistant Polyamide (PA)

Drum 1000 m

O.D. (mm)	I.D. (mm)		 Clear					kg
4	2	17	2010P04R00	2010P04R01	2010P04R02	2010P04R03	2010P04R04	14.300
6	4	29	2010P06R00	2010P06R01	2010P06R02	2010P06R03	2010P06R04	23.000

Related Products

Fireproof high resistance tubing can be connected to various fittings presented in this catalogue in Chapter 1.

Push-In Fittings

LF 3000*

P. 1-4

LF 3600

P. 1-65

LF 3800/LF 3900

P. 1-77

LF 6100

P. 1-89



Compression Fittings

Brass

P. 5-5

Brass Tube Support

P. 5-5



Anti-Spark PA Tubing with PVC Sheath

A range of **flame and spark-resistant** PA tubing with superior resistance to impact and abrasion, improving equipment **durability**, particularly in areas subject to weld spatter.

Product Advantages

Spark Resistance | Flame-retardant PVC jacket protects inner tubing
Non-adhesive jacket facilitates sheath removal
Excellent pressure resistance at high temperature

Robustness & Durability | Highly kink and crush-resistant
Excellent compatibility with coolants
Flow direction marking
Silicone-free



Industrial Machinery
Welding Robots
Cooling
Aggressive Environments

Applications

Technical Characteristics

Compatible Fluids	Hot and cold water, refrigerated fluids, compressed air
Working Pressure	0 to 36 bar
Working Temperature	-20°C to +80°C
Component Materials	Polyamide & PVC Sheath


Regulations

Industrial
DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)
UL94 V-0 (Fire resistance)

Packaging
Tubepack®: 25 m, 100 m

Reliable performance is dependent upon the type of fluid conveyed and fittings being used.

Performance of Anti-Spark PA Tubing with PVC Sheath



O.D.	Tube O.D. Tolerance	PVC Sheath Thickness
PVC Sheath 8 to 14 mm	+0.10 / -0.10	1 mm
Inner Tubing 6 to 12 mm	+0.05 / -0.10	

Connected to Parker Legris push-in fittings, the calibration of PA tubing ensures perfect sealing based on NF E49-100 (semi-rigid PA inner tubing).






Tube O.D.	Sheath Removal Length for LF 3600 Push-In Fittings (mm)
4 mm	15± 1
6 mm	18± 1
8 mm	19± 1
10 mm	24± 1
12 mm	25± 1

For other fitting ranges, please consult us.

To calculate burst pressure, the values in this graph should be multiplied by 3.






1025P..V Anti-Spark Polyamide (PA) Tubing

Tubepack® 25 m



O.D. (mm)	I.D. (mm)						kg
6	4	25	1025P06V01	1025P06V02	1025P06V03	1025P06V04	1.238
8	6	30	1025P08V01	1025P08V02	1025P08V03	1025P08V04	1.693
10	8	55	1025P10V01	1025P10V02	1025P10V03	1025P10V04	2.029
12	10	70	1025P12V01	1025P12V02	1025P12V03	1025P12V04	2.970

1100P..V Anti-Spark Polyamide (PA) Tubing

Tubepack® 100 m


O.D. (mm)	I.D. (mm)						kg
6	4	25	1100P06V01	1100P06V02	1100P06V03	1100P06V04	2.338
8	6	30	1100P08V01	1100P08V02	1100P08V03	1100P08V04	3.767
10	8	55	1100P10V01	1100P10V02	1100P10V03	1100P10V04	4.767
12	10	70	1100P12V01	1100P12V02	1100P12V03	1100P12V04	6.567

6000 71 00 Stripping Tool for Anti-Spark Tubing

	Technical polymer, stainless steel		kg
		6000 71 00	0.098

Working Principle


Stripping Tool 6000 71 00




1. Place tube in stripping tool to adjust the blade height to the tube thickness.




2. Blade height is adjusted using the wheel at the bottom of the handle.



3. Once adjustments have been made, perform a 360° rotation around the tube with the tool.



4. Push down firmly on the metal part of the tool in order to hold tube properly.



5. Move the tool to the end of the tube to create an axial opening of the sheath.



6. The tube is correctly stripped.

PU Tubing

Polyurethane's **3 specific materials** - ether, ester and food-grade "crystal" - offer excellent flexibility and outstanding use in a wide range of applications, allowing for up to **50% space reduction** when compared to semi-rigid PA tubing.

Product Advantages

Excellent Mechanical Properties

- Consistent tensile strength for optimum longevity
- Optimal bend radius
- Good vibration absorption
- Unsurpassed abrasion resistance for a single layer tubing
- UV-resistant
- Superior vacuum capability due to surface hardness
- Remaining length marking
- Silicone-free

3 Material Grades

- PU ester: perfect for pneumatic applications
- PU ether: no water absorption ; superior chemical resistance to PU ester
- PU ether food-grade "crystal":
 - identification of fluids and circuits
 - chemical resistance superior to PU ether
 - improved longevity



Applications

- Food Process
- Robotics
- Cabling
- Pneumatics
- Automation
- In-Plant Automotive
- Rapid Cycles

Technical Characteristics

Compatible Fluids	Compressed air, industrial fluids (depending on the material type)
Working Pressure	Vacuum to 12 bar
Working Temperature	-20°C to +70°C
Component Materials	Polyurethane ester Polyurethane ether Polyurethane ether food-grade "crystal"

Regulations

Industrial


DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)

Food (PU ether food-grade "crystal")

FDA: 21 CFR 177.2600, 178.3297, 176.170, 178.2010
RG: 1935/2004 EC

Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Performance of PU Tubing



Tube O.D.	Tube O.D. Tolerance
3 to 8 mm	+0.10 / -0.10
10 to 16 mm	+0.15 / -0.15

Connected to Parker Legris push-in fittings, the calibration of PU tubing ensures perfect sealing based on NF E49-101.








Packaging

Tubepack®: 25 m, 100 m
Drum: 300 m, 500 m, 1 000 m

To calculate burst pressure, the values in this graph should be multiplied by 3.

1025U Polyurethane (PU) Ester Tubing








Tubepack® 25 m

O.D. (mm)	I.D. (mm)								kg
3	1.8	8	1025U03 01 18						0.020
4	2.5	10	1025U04 01	1025U04 02	1025U04 03	1025U04 04	1025U04 05	1025U04 06	0.310
5	3	13	1025U05 01			1025U05 04			0.522
6	4	15	1025U06 01	1025U06 02	1025U06 03	1025U06 04	1025U06 05	1025U06 06	0.591
8	5.5	20	1025U08 01	1025U08 02	1025U08 03	1025U08 04	1025U08 05	1025U08 06	0.971
10	7	25	1025U10 01	1025U10 02		1025U10 04	1025U10 05	1025U10 06	1.467
12	8	35	1025U12 01	1025U12 02		1025U12 04	1025U12 05	1025U12 06	2.406
14	9.5	45	1025U14 01 95			1025U14 04 95			2.815
16	11	45	1025U16 01 11	1025U16 02 11	1025U16 03 11	1025U16 04 11			2.815

Inch tubing available upon request

1100U Polyurethane (PU) Ester Tubing








Tubepack® 100 m

O.D. (mm)	I.D. (mm)								kg
4	2.5	10	1100U04 01	1100U04 02	1100U04 03	1100U04 04	1100U04 05	1100U04 06	1.092
5	3	13	1100U05 01			1100U05 04			1.092
6	4	15	1100U06 01	1100U06 02	1100U06 03	1100U06 04	1100U06 05	1100U06 06	2.064
8	5.5	20	1100U08 01	1100U08 02	1100U08 03	1100U08 04	1100U08 05	1100U08 06	3.610
10	7	25	1100U10 01			1100U10 04			6.105
12	8	35	1100U12 01			1100U12 04			8.610
14	9.5	45	1100U14 01 95			1100U14 04 95			11.215
16	11	45	1100U16 01 11	1100U16 02 11	1100U16 03 11	1100U16 04 11			12.176

Inch tubing available upon request








2003U Polyurethane (PU) Ester Tubing

Drum 300 m

O.D. (mm)	I.D. (mm)								kg
10	7	25	2003U10 01	2003U10 02	2003U10 03	2003U10 04	2003U10 05	2003U10 06	16.600








2005U Polyurethane (PU) Ester Tubing

Drum 500 m

O.D. (mm)	I.D. (mm)								kg
8	5.5	20	2005U08 01	2005U08 02	2005U08 03	2005U08 04	2005U08 05		17.100

2010U Polyurethane (PU) Ester Tubing









Drum 1000 m

O.D. (mm)	I.D. (mm)								kg
4	2.5	12	2010U04 01	2010U04 02	2010U04 03	2010U04 04	2010U04 05	2010U04 06	9.840
6	4	15	2010U06 01	2010U06 02	2010U06 03	2010U06 04	2010U06 05	2010U06 06	20.460

PU Tubing









1025U..R Polyurethane (PU) Ether Tubing

Tubepack® 25 m

O.D. (mm)	I.D. (mm)									kg
4	2.5	12	1025U04R01	1025U04R04	1025U04R08	1025U04R12	1025U04R13	1025U04R14	1025U04R17	0.310
5	3	13			1025U05R08					0.522
6	4	15	1025U06R01	1025U06R04	1025U06R08	1025U06R12	1025U06R13	1025U06R14	1025U06R17	0.591
8	5.5	20	1025U08R01	1025U08R04	1025U08R08	1025U08R12	1025U08R13	1025U08R14	1025U08R17	0.971
10	7	25	1025U10R01	1025U10R04	1025U10R08			1025U10R14		1.467
12	8	35	1025U12R01	1025U12R04	1025U12R08			1025U12R14		2.406
14	9.5	45		1025U14R01 95	1025U14R04 95					2.815
16	11	45			1025U16R08 11					2.815





1100U..R Polyurethane (PU) Ether Tubing

Tubepack® 100 m

O.D. (mm)	I.D. (mm)									kg
4	2.5	12	1100U04R01	1100U04R04	1100U04R08	1100U04R12	1100U04R13	1100U04R14	1100U04R17	1.092
6	4	15	1100U06R01	1100U06R04	1100U06R08	1100U06R12	1100U06R13	1100U06R14	1100U06R17	2.064
8	5.5	20	1100U08R01	1100U08R04	1100U08R08	1100U08R12	1100U08R13	1100U08R14	1100U08R17	3.610
10	7	25			1100U10R08			1100U10R14		6.109
12	8	35			1100U12R04			1100U12R08		8.610
14	9.5	45			1100U14R08 95					11.215
16	11	45			1100U16R08 11					12.176





2003U..R Polyurethane (PU) Ether Tubing

Drum 300 m

O.D. (mm)	I.D. (mm)					kg
10	7	25	2003U10R01	2003U10R04	2003U10R08	16.600





2005U..R Polyurethane (PU) Ether Tubing


Drum 500 m

O.D. (mm)	I.D. (mm)					kg
8	5.5	20	2005U08R01	2005U08R04	2005U08R08	15.600

2010U..R Polyurethane (PU) Ether Tubing

Drum 1000 m

O.D. (mm)	I.D. (mm)					kg
4	2.5	12	2010U04R01	2010U04R04	2010U04R08	8.670
6	4	15	2010U06R01	2010U06R04	2010U06R08	18.600



Flexible Calibrated Tubing

Technical Tubing & Hose

Antistatic PU Tubing

With a constant **10² Ω.m resistivity** across the entire thickness of the tubing wall, this tubing guarantees **perfect dissipation of accumulated static electricity**, thereby increasing safety.

Product Advantages

Security

- Low resistivity throughout the material
- Suitable for ATEX* areas
- Superior longevity
- Excellent vibration absorption
- UV-resistant
- Silicone-free

Machinery Optimisation

- Minimum bend radius allowing maximum space saving
- Good chemical resistance
- Wide temperature range
- Stable chemical characteristics throughout tubing



Antistatic Packaging
Pneumatics
Electronics
Spray Painting
Electrical Converters

Applications

Technical Characteristics


Compatible Fluids	Compressed air, industrial fluids
Working Pressure	Vacuum to 10 bar
Working Temperature	-20°C to +70°C
Component Materials	Polyurethane with conductive additive (50 shore D)

Regulations

DI: 94/9/EC (ATEX*)
 DI: 1907/2006 (REACH)
 DI: 2002/95/EC (RoHS), 2011/65/EC
 *For ATEX areas, please consult us

Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Performance of Antistatic PU Tubing



Tube O.D.	Tube O.D. Tolerance
3 to 8 mm	+0.10 / -0.10
10 to 12 mm	+0.15 / -0.15

Connected to Parker Legris push-in fittings, the calibration of Parker Legris tubing ensures perfect sealing based on NF E49-101.



Packaging

Tubepack®: 25 m, 100 m

To calculate burst pressure, the values in this graph should be multiplied by 3.



1025U..A Anti-Static Polyurethane (PU) Ester Tubing

Tubepack® 25 m

O.D. (mm)	I.D. (mm)			kg
4	2.5	12	1025U04A01	0.310
6	4	15	1025U06A01	0.591
8	5.5	25	1025U08A01	0.971

1100U..A Anti-Static Polyurethane (PU) Ester Tubing

Tubepack® 100 m

O.D. (mm)	I.D. (mm)			kg
3	1.8	10	1100U03A01	0.836
4	2.5	12	1100U04A01	1.092
6	4	15	1100U06A01	2.064
8	5.5	25	1100U08A01	3.610
10	7	35	1100U10A01	6.105
12	8	45	1100U12A01	8.610

Related Products

To maintain the antistatic properties throughout the circuit, it is recommended that this tubing be used with metallic fittings.

Push-In Fittings

[LF 3600](#) P. 1-65



[LF 3800](#) P. 1-77



[LF 3900](#) P. 1-77



Compression Fittings

[Brass](#) P. 5-5



[Stainless Steel](#) P. 5 -31



Anti-Spark PU Tubing

Combining **outstanding spark resistance** with superb **flexibility**, this range is perfectly suited for welding applications.

Two types of PU - ether with PVC sheath or single layer ether - are available and allow **rapid installation** with Parker Legris push-in fittings.

Product Advantages

PU with PVC Sheath

- High resistance to kinking and abrasion
- Non-adhesive jacket facilitating sheath removal
- Fluid direction marking
- Self-extinguishing sheath, protecting the inner tubing
- Silicone-free

Single Layer PU

- Minimum bend radius for maximum space saving
- Significant flexibility for rapid cycling
- Good chemical resistance
- Flow direction marking
- Fireproof material
- Silicone-free



Industrial Machinery
Compressed Air
Robotics
Mechanical Constraints
Cooling
Welding
Cabling

Applications

Technical Characteristics

Compatible Fluids	Industrial fluids, compressed air, coolants
Working Pressure	Vacuum to 14 bar
Working Temperature	-20°C to +70°C
Component Materials	PU ether with PVC sheath PU ether single layer

O.D. of Tube	Sheath Removal Length for LF 3600 (mm)
4 mm	15± 1
6 mm	18± 1
8 mm	19± 1
10 mm	24± 1
12 mm	25± 1

Regulations

UL94 V-0 (Fire resistance)
DI: 2002/95/EC (RoHS),
2011/65/EC
RG: 1907/2006 (REACH)

Packaging


Tubepack®: 25 m, 100 m

Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).


For other fitting ranges, please consult us.

Tubing Performance

Anti-Spark PU Tubing, with PVC Sheath



Anti-Spark PU Tubing, Single Layer








Tube O.D.	Tube O.D. Tolerance	Thickness and Tolerances of PVC Sheath
4 to 8 mm	+0.10 / -0.10	1mm +0.10 / -0.10
10 to 12 mm	+0.15 / -0.15	

Connected to Parker Legris push-in fittings, the calibration of Parker Legris tubing ensures perfect sealing based on NF E49-101 (inner tubing for sheathed or single layer tubing).

To calculate burst pressure, the values in these graphs should be multiplied by 3.






1025U..V Anti-Spark Sheath Polyurethane (PU) Ether Tubing

Tubepack® 25 m

O.D. (mm)	I.D. (mm)						kg
6	4	12	1025U06V01	1025U06V02	1025U06V03	1025U06V04	1.200
8	5.5	20	1025U08V01	1025U08V02	1025U08V03	1025U08V04	1.620
10	7	25	1025U10V01	1025U10V02	1025U10V03	1025U10V04	2.900
12	8	35	1025U12V01	1025U12V02	1025U12V03	1025U12V04	4.030






1100U..V Anti-Spark Sheath Polyurethane (PU) Ether Tubing

Tubepack® 100 m

O.D. (mm)	I.D. (mm)						kg
6	4	12	1100U06V01	1100U06V02	1100U06V03	1100U06V04	5.370
8	5.5	20	1100U08V01	1100U08V02	1100U08V03	1100U08V04	7.630
10	7	25	1100U10V01	1100U10V02	1100U10V03	1100U10V04	10.860
12	8	35	1100U12V01	1100U12V02	1100U12V03	1100U12V04	15.060






1025U..K Single Layer Anti-Spark Polyurethane (PU) Ether Tubing

Tubepack® 25 m



O.D. (mm)	I.D. (mm)						kg
4	2.5	12	1025U04K01	1025U04K02	1025U04K03	1025U04K04	0.230
6	4	15	1025U06K01	1025U06K02	1025U06K03	1025U06K04	0.580
8	5.5	20	1025U08K01	1025U08K02	1025U08K03	1025U08K04	0.860
10	7	25	1025U10K01	1025U10K02	1025U10K03	1025U10K04	1.230
12	8	35	1025U12K01	1025U12K02	1025U12K03	1025U12K04	2.080
14	9.5	45		1025U14K02 95	1025U14K03 95		2.620

1100U..K Single Layer Anti-Spark Polyurethane (PU) Ether Tubing

Tubepack® 100 m

O.D. (mm)	I.D. (mm)						kg
4	2.5	12	1100U04K01				0.900
6	4	15	1100U06K01	1100U06K02	1100U06K03	1100U06K04	2.320
8	5.5	20	1100U08K01	1100U08K02	1100U08K03	1100U08K04	3.030
10	7	25	1100U10K01	1100U10K02	1100U10K03	1100U10K04	5.100
12	8	35	1100U12K01	1100U12K02	1100U12K03	1100U12K04	8.600
14	9.5	45		1100U14K02 95	1100U14K03 95		10.676

6000 71 00 Stripping Tool for Anti-Spark Tubing

	Technical polymer, stainless steel		kg
		6000 71 00	0.098
	Working principle of the stripping tool page 3-17		

PE Tubing

Parker Legris offers two types of polyethylene tubing: **"Advanced PE" 50% reticulated** and **Low Density PE**. Our range of "Advanced PE" is designed for demanding environments, especially that of water treatment, without compromising operator **safety**.

Product Advantages

Advanced PE	50% reticulated material
	Best balance between flexibility and pressure/temperature resistance
	Resistant to a wide range of aggressive chemicals
	UV-stabilised: ideal for outdoor applications
	Approved for permanent contact with food and beverages
	Silicone-free

Low Density PE	Excellent resistance to aggressive and corrosive agents
	Good technical trade-off
	Food-grade material
	Silicone-free



Applications

- Beverage
- Chemical
- Petrochemical
- Food Process
- Water
- Water Treatment

Technical Characteristics

Tube	Advanced PE	Low Density PE
Compatible Fluids	Water, beverages and other fluids	Industrial fluids
Working Pressure	Vacuum to 16 bar	Vacuum to 20 bar
Working Temperature	-40°C to +95°C	-40°C to +60°C
Component Materials	High quality polyethylene: 50% reticulated PE 50% low density PE (44 shore D)	Low Density Polyethylene (44 shore D)

Regulations

Advanced PE Tubing

FDA: 21 CFR 177.1520
 RG: 1935/2004/EC
 DI: 97/23/EC (PED)
 DI: 2002/95/EC (RoHS), 2011/65/EC
 NSF 42/58 (1/4" and 3/8" approved for 10 bar and 1/2" approved for 8 bar at room temperature)
 NSF 51, 61 C-HOT
 ACS (except for purple colour)
 WRAS
 RG: 1907/2006 (REACH)


Low Density PE Tubing

FDA: 21 CFR 177.1520
 DI: 2002/95/EC (RoHS), 2011/65/EC
 DI: 97/23/EC (PED)


Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Tubing Performance

Advanced PE Tubing



Low Density PE Tubing



Tube O.D.	Tube O.D. Tolerance
1/4" to 1/2"	+0.10 / -0.10
4 to 14 mm	+0.10 / -0.10

Connected to Parker Legris push-in fittings, the calibration of Parker Legris tubing ensures perfect sealing.

Packaging









Advanced PE Tubing
 Tubepack®: 75 m, 150 m, 300 m
 250 feet, 500 feet, 1 000 feet

PE Tubing
 Tubepack®: 25 m, 100 m

To calculate burst pressure, the values in these graphs should be multiplied by 3.









1015Y..F Advanced Polyethylene (APE) Tubing

Drum 150 m

O.D. (mm)	I.D. (mm)		 Clear	 Black	 Green	 Red	 Blue	 Yellow	 White	kg
4	2.5	16	1015Y04F00	1015Y04F01	1015Y04F02	1015Y04F03	1015Y04F04	1015Y04F05	1015Y04F10	1.760
6	4	32	1015Y06F00	1015Y06F01	1015Y06F02	1015Y06F03	1015Y06F04	1015Y06F05	1015Y06F10	2.580
8	5.75	40	1015Y08F00	1015Y08F01	1015Y08F02	1015Y08F03	1015Y08F04	1015Y08F05	1015Y08F10	4.050
10	7		1015Y10F00	1015Y10F01	1015Y10F02	1015Y10F03	1015Y10F04	1015Y10F05	1015Y10F10	6.200









1030Y..F Advanced Polyethylene (APE) Tubing

Drum 300 m

O.D. (mm)	I.D. (mm)		 Clear	 Black	 Green	 Red	 Blue	 Yellow	 White	kg
4	2.5	16	1030Y04F00	1030Y04F01	1030Y04F02	1030Y04F03	1030Y04F04	1030Y04F05	1030Y04F10	2.860
6	4	32	1030Y06F00	1030Y06F01	1030Y06F02	1030Y06F03	1030Y06F04	1030Y06F05	1030Y06F10	4.800









1075Y..F Advanced Polyethylene (APE) Tubing

Drum 75 m

O.D. (mm)	I.D. (mm)		 Clear	 Black	 Green	 Red	 Blue	 Yellow	 White	kg
12	9	55	1075Y12F00	1075Y12F01	1075Y12F02	1075Y12F03	1075Y12F04	1075Y12F05	1075Y12F10	5.550









1096Y..F Advanced Polyethylene (APE) Tubing

Drum 250 ft

O.D. (inch)	I.D. (inch)		 Clear	 Black	 Green	 Red	 Blue	 Yellow	 White	kg
1/2	0.375	1.96	1096Y62F00	1096Y62F01	1096Y62F02	1096Y62F03	1096Y62F04	1096Y62F05	1096Y62F10	5.900









1098Y..F Advanced Polyethylene (APE) Tubing

Drum 500 ft

O.D. (inch)	I.D. (inch)		 Clear	 Black	 Green	 Red	 Blue	 Yellow	 White	kg
1/4	0.170	0.78	1098Y56F00	1098Y56F01	1098Y56F02	1098Y56F03	1098Y56F04	1098Y56F05	1098Y56F10	3.300
3/8	0.250	1.18	1098Y60F00	1098Y60F01	1098Y60F02	1098Y60F03	1098Y60F04	1098Y60F05	1098Y60F10	6.300

1099Y..F Advanced Polyethylene (APE) Tubing



Drum 1000 ft

O.D. (inch)	I.D. (inch)		 Clear	 Black	 Green	 Red	 Blue	 Yellow	 White	kg
1/4	0.170	0.78	1099Y56F00	1099Y56F01	1099Y56F02	1099Y56F03	1099Y56F04	1099Y56F05	1099Y56F10	5.500

Low Density Polyethylene (LDPE) Tubing



1025Y

Tubepack® 25 m

Ø ext. (inch)	Ø int. (inch)		 Clear	kg
1/8	1.57	13	1025Y53 00	0.270
1/4	4.3	32	1025Y56 00	0.400
3/8	6.35	50	1025Y60 00	0.760
1/2	9.65	64	1025Y62 00	1.330

1100Y

Tubepack® 100 m

O.D. (mm)	I.D. (mm)		 Clear	kg
4	2	25	1100Y04 00	0.910
6	4	35	1100Y06 00	1.500
8	6	55	1100Y08 00	2.140
10	8	80	1100Y10 00	2.710
12	9	65	1100Y12 00	4.750
14	11	80	1100Y14 00	5.650

Fluoropolymer Tubing – FEP

FEP (fluorinated ethylene propylene) tubing is a **robust engineering fluoropolymer** which provides excellent fluid visibility and is perfect for flow control monitoring.

Product Advantages

Flow Control	Transparent
	Flexible and non-flammable material
	Resistant to nearly all chemicals and solvents
Tried-&-Tested Properties	Excellent transmission of UV light
	Low friction coefficient
	Food-grade material
	Low permeability
	Easily weldable
	Silicone-free

Applications	Instrumentation
	Food Process
	UV
	Gas Sampling
	Chemical
	Temperature Cycling Laboratory


Technical Characteristics

Compatible Fluids	Industrial fluids
Working Pressure	0 to 28 bar
Working Temperature	-40°C to +150°C
Component Materials	Fluorinated ethylene propylene (pure)

Regulations
Food
FDA: 21 CFR 177.1550
RG: 1935/2004
Industrial
UL94 V-0 (Fire resistance)
DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)

Reliable performance is dependent upon the type of fluid conveyed and fittings being used.

Performance of FEP Tubing





Tube O.D.	Tube O.D. Tolerance
4 mm	+0.05 / -0.05
6 to 10 mm	+0.07 / -0.07
12 mm	+0.10 / -0.10

Packaging
Tubepack®: 5 m, 25 m, 100 m

Connected to Parker Legris push-in fittings, the calibration of Parker Legris tubing ensures perfect sealing.



1005T Fluoropolymer (FEP) Tubing

Tubepack® 5 m

O.D. (mm)	I.D. (mm)	 R	 Clear	kg
4	2.5	40	1005T04 00 25	0.155
6	4	50	1005T06 00	0.250
8	6	70	1005T08 00	0.385
10	8	120	1005T10 00	0.524
12	10	180	1005T12 00	0.547

1025T Fluoropolymer (FEP) Tubing

Tubepack® 25 m

O.D. (mm)	I.D. (mm)	 R	 Clear	kg
4	2.5	40	1025T04 00 25	0.506
6	4	50	1025T06 00	1.025
8	6	70	1025T08 00	1.431
10	8	120	1025T10 00	1.693
12	10	180	1025T12 00	1.913

Flexible Calibrated Tubing

Technical Tubing & Hose

Related Products

Parker Legris stainless steel fittings are perfectly suited for use with fluoropolymer tubing (PFA, FEP).

Push-In Fittings

[LF 3800](#) P. 1-77



[LF 3900](#) P. 1-77



Compression Fittings

[Stainless Steel](#) P. 5-31



Fluoropolymer Tubing - PFA

Parker Legris **PFA** (perfluoroalkoxy) tubing offers **10 times greater durability** than other fluoropolymer tubings (PTFE, FEP and PVDF) under severe chemical and mechanical conditions. This tubing range is available in **three material grades**, offering perfect compatibility with all applications, even in extreme environments.

Product Advantages

Great Versatility

- Exceptional chemical inertia
- A flexible alternative to stainless steel tubing
- Broad range of working temperatures, from cryogenic to extreme heat
- Non-stick properties allowing conveyance of many fluids & gases
- Outstanding resistance to ageing
- Fluoropolymer with the lowest permeability
- Non-flammable
- UV-transparent
- Tube marking on request
- Silicone-free

Three Material Grades

- Clear High Purity PFA: to cover all applications, including those requiring maximum mechanical resistance
- Coloured PFA: for circuit identification
- Black Antistatic PFA: eliminates all risk of electrostatic discharge



Food-Process
Fuel Cells
Electrical/Electronics
Aircraft
Oil/Gas Industry
Pharmaceutical
Medical
Chemical
Clean Rooms

Applications

Technical Characteristics

Compatible Fluids	Medical, bio-compatible, food process, gas, compressed air
Working Pressure	Vacuum to 36 bar
Working Temperature	-196°C to +260°C
Component Materials	Perfluoroalkoxy <ul style="list-style-type: none"> • High Purity PFA • Translucent coloured PFA • Antistatic PFA

Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Regulations

Medical

USP: Class VI (A)
External communication devices


Industrial

UL94 V-0 (Fire resistance)
DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)
DI: 94/09/EC (ATEX, black tubing)

Food Industry

FDA: 21 CFR 177.1550
(clear, translucent coloured)
RG: 1935/2004
NSF 51 (material)

Performance of PFA Tubing



Tube O.D.	Tube O.D. Tolerance
4 to 8 mm	+0.10 / -0.10
10 to 12 mm	+0.15 / -0.15

Connected to Parker Legris push-in fittings, the calibration of Parker Legris tubing ensures perfect sealing based on NF E49-100.






Packaging

Tubepack®: 10 m, 50 m, 100 m

To calculate burst pressure, the values in this graph should be multiplied by 3.






1010T..P Fluoropolymer (PFA) Tubing

Tubepack® 10 m

O.D. (mm)	I.D. (mm)		 Clear	 crystal	 crystal	 crystal	kg
4	2	12	1010T04P00	1010T04P12	1010T04P13	1010T04P14	0.087
6	4	34	1010T06P00	1010T06P12	1010T06P13	1010T06P14	0.237
8	6	60	1010T08P00	1010T08P12	1010T08P13	1010T08P14	0.410
10	8	95	1010T10P00	1010T10P12	1010T10P13	1010T10P14	0.723
12	9	120	1010T12P00	1010T12P12	1010T12P13	1010T12P14	1.148






1050T..P Fluoropolymer (PFA) Tubing

Tubepack® 50 m

O.D. (mm)	I.D. (mm)		 Clear	 crystal	 crystal	 crystal	kg
4	2	12	1050T04P00	1050T04P12	1050T04P13	1050T04P14	0.435
6	4	34	1050T06P00	1050T06P12	1050T06P13	1050T06P14	1.185
8	6	60	1050T08P00	1050T08P12	1050T08P13	1050T08P14	2.050
10	8	95	1050T10P00	1050T10P12	1050T10P13	1050T10P14	3.615
12	9	120	1050T12P00	1050T12P12	1050T12P13	1050T12P14	5.740



1100T..P Fluoropolymer (PFA) Tubing

Tubepack® 100 m

O.D. (mm)	I.D. (mm)		 Clear	 crystal	 crystal	 crystal	kg
4	2	12	1100T04P00	1100T04P12	1100T04P13	1100T04P14	0.870
6	4	34	1100T06P00	1100T06P12	1100T06P13	1100T06P14	2.370
8	6	60	1100T08P00	1100T08P12	1100T08P13	1100T08P14	4.100
10	8	95	1100T10P00	1100T10P12	1100T10P13	1100T10P14	7.230
12	9	120	1100T12P00	1100T12P12	1100T12P13	1100T12P14	11.480



1010T..A Fluoropolymer (PFA) Antistatic Tubing

Tubepack® 10 m

O.D. (mm)	I.D. (mm)			kg
4	2	12	1010T04A01	0.087
6	4	34	1010T06A01	0.237
8	6	60	1010T08A01	0.410
10	8	95	1010T10A01	0.723
12	9	120	1010T12A01	1.148

1050T..A Fluoropolymer (PFA) Antistatic Tubing

Tubepack® 50 m

O.D. (mm)	I.D. (mm)			kg
4	2	12	1050T04A01	0.435
6	4	34	1050T06A01	1.185
8	6	60	1050T08A01	2.050
10	8	95	1050T10A01	0.362
12	9	120	1050T12A01	5.740

Multi-Tubing

Our range of multi-tubing combines high quality performance and **space optimisation** in complex pneumatic circuits **covering a wide range of environments**. Many possible **configurations** are available, depending on the pressure, temperature, flexibility and compatibility requirements.

Product Advantages

Sheathed PA Tubing

- PVC sheath resistant to external damage:
 - abrasion
 - weld spatter
 - aggressive fluids
- Helically wound: minimum bend radius, compact installation
- Simplified routing
- Easy identification of circuits
- Same technical performance as PA
- Possible number of tubes: from 2 to 12, with numbering
- Silicone-free

Twin PU Ester Tubing

- Tubes fully joined for improved solidity
- External diameter maintained after separation
- Rapid identification of circuits
- Quick and easy installation
- Simplified routing
- 3 colour combinations available
- Silicone-free



Applications

- Pneumatics
- Automation
- Robotics
- Transportation
- In-Plant Automotive
- Process Industry

Technical Characteristics

Tube	PA	PU
Compatible Fluids	Compressed air, chemicals, industrial fluids	Compressed air, industrial fluids
Working Pressure	Vacuum to 24 bar	0 to 14 bar
Working Temperature	-40°C to +80°C	-20°C to +70°C
Component Materials	Polyamide	Polyurethane ester

Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Regulations

Industrial

DI: 2002/95/EC (RoHS), 2011/65/EC

DI: 97/23/EC (PED)

RG: 1907/2006 (REACH)

Performance and chemical resistance according to DIN 73378


Packaging

Sheathed PA Tubing:
Tubepack® 10 m, 50 m


Twin PU Ester Tubing:
Tubepack® 25 m

Tubing Performance

Sheathed PA Tubing



Twin PU Ester Tubing





Material	Tube O.D.	Tube O.D. Tolerance
PA	4 mm	+0.05 / -0.08
	6 to 8 mm	+0.05 / -0.10
PU	4 to 8 mm	+0.10 / -0.10

Connected to Parker Legris push-in fittings, the calibration of Parker Legris tubing ensures perfect sealing based on NF E49-100 (for semi-rigid PA) and NF E49-101 (for twin PU ester).

To calculate burst pressure, the values in these graphs should be multiplied by 3.



1010P.. M Semi-Rigid Polyamide (PA) Multi-Tubing

Reel 10 m

O.D. (mm)	I.D. (mm)		Number of tubes		kg
4	2.7	35	4	1010P04 00M04	1.440
4	2.7	45	7	1010P04 00M07	1.920
6	4	55	4	1010P06 00M04	2.300
6	4	60	7	1010P06 00M07	2.900
8	6	45	2	1010P08 00M02	2.600





1050P.. M Semi-Rigid Polyamide (PA) Multi-Tubing

Reel 50 m

O.D. (mm)	I.D. (mm)		Number of tubes		kg
4	2.7	20	2	1050P04 00M02	4.400
4	2.7	35	4	1050P04 00M04	6.600
4	2.7	45	7	1050P04 00M07	8.200
4	2.7	55	12	1050P04 00M12	12.444
6	4	45	2	1050P06 00M02	8.400
6	4	55	4	1050P06 00M04	14.500
6	4	60	7	1050P06 00M07	12.500
8	6	45	2	1050P08 00M02	13.000

1420U Twin Polyurethane (PU) Tubing


Tubepack® 25 m

O.D. tube (mm)	I.D. tube (mm)					kg
4	2.5	12	1420U04 11	1420U04 44	1420U04 41	0.620
6	4	15	1420U06 11	1420U06 44	1420U06 41	1.182
8	5.5	20	1420U08 11	1420U08 44	1420U08 41	1.942

Colour Selection



Multi-Tubing
Semi-Rigid PA/PVC Sheath



Related Products

To complement the Multi-Tubing range, Parker Legris proposes multi-connectors, shown in Chapter 1.

Push-In Fittings

Multi-Connector P. 1-31



PA Recoil Tubing

Parker Legris recoil tubing has a **lasting memory after multiple uses**, offering an **alternative to reels** for excellent ergonomics and space saving.

The pre-assembled tubes are equipped with a protection spring, preventing damage to the ends.

Product Advantages

Excellent Mechanical Properties

- Low pressure drop
- Good chemical compatibility
- Self-retracting
- Identical technical performance to PA tubing
- Silicone-free

Comprehensive Range

- Ready-to-use
- Various colours for circuit identification
- Available with pre-assembled connectors



Applications

- MRO
- Pneumatic Tools
- Transportation
- Lubrication
- Industrial Cleaning
- Robotics
- Car Washing

Technical Characteristics


Compatible Fluids	Compressed air, lubricants, Other fluids: please consult us
Working Pressure	Vacuum to 20 bar
Working Temperature	-20°C to +80°C
Component Materials	Polyamide (68 Shore D)

Regulations

DI: 97/23/EC (PED)
 RG: 1907/2006 (REACH)
 DI: 2002/95/EC (RoHS), 2011/65/EC

Reliable performance is dependent upon the type of fluid conveyed and fittings being used. Use is guaranteed with a vacuum of 755 mm Hg (99% vacuum).

Performance of PA Recoil Tubing





Tube O.D.	Passage	Tube O.D. Tolerance
6 mm	4 mm	+0.05 / -0.10
8 mm	6 mm	+0.05 / -0.10

Packaging

Plastic bags: 2m to 6 m
 Other lengths and colours on request

To calculate burst pressure, the values in these graphs should be multiplied by 3.

1470P Polyamide (PA) Recoil Tubing 2 m, Male BSPT Fitting

O.D. (mm)	I.D. (mm)	BSPT Thread			Total Closed Length (mm)	O.D. of Coil (mm)	kg
6	4	R1/4	1470P06 04 13	1470P06 07 13	520	60	0.143
8	6		1470P08 04 13	1470P08 07 13	560	70	0.174

Length of long straight section: 300 mm
Length of short straight section: 100 mm

1471P Polyamide (PA) Recoil Tubing 4 m, Male BSPT Fitting

O.D. (mm)	I.D. (mm)	BSPT Thread			Total Closed Length (mm)	O.D. of Coil (mm)	kg
6	4	R1/4	1471P06 04 13	1471P06 07 13	640	60	0.199
8	6		1471P08 04 13	1471P08 07 13	720	70	0.249

Length of long straight section: 300 mm
Length of short straight section: 100 mm




1472P Polyamide (PA) Recoil Tubing 6 m, Male BSPT Fitting

O.D. (mm)	I.D. (mm)	BSPT Thread			Total Closed Length (mm)	O.D. of Coil (mm)	kg
6	4	R1/4	1472P06 04 13	1472P06 07 13	760	60	0.260
8	6		1472P08 04 13	1472P08 07 13	880	70	0.329

Length of long straight section: 300 mm
Length of short straight section: 100 mm

Dimensions for Recoil Tubing

Service length: maximum recommended operating length in order to ensure that the coil will continue to contract after multiple uses.



PU Recoil Tubing

With its small coil diameter and good impact resistance, this polyurethane recoil tubing is perfect for installations requiring **flexibility** in confined spaces. Good resistance to shock and abrasion, together with a design integrating straight ends, allow for **easy and safe operation** of pneumatic equipment.


Product Advantages

Excellent Mechanical Properties

- Excellent coil memory
- Abrasion-resistant
- Perfect for rapid cycling applications
- Consistent tensile strength
- Optimum longevity
- Low pressure drop
- Lightweight with plastic protection spring
- Silicone-free

Comprehensive Range

- Available in 2 materials: PU ester and PU ether
- With or without pre-assembled fittings
- Pre-assembled plastic or metal protection springs to prevent damage to equipment and tubing



Applications

- Workshops
- Tooling
- Pneumatics
- Motion Technologies
- Robotics
- Industrial Machinery

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	0 to 10 bar
Working Temperature	-20°C to +70°C (assembled tubing)
Component Materials	Polyurethane (52 Shore D)

Regulations

Industrial
 NF E49-101
 DI: 2002/95/EC (RoHS), 2011/65/EC
 DI: 97/23/EC (PED)
 RG: 1907/2006 (REACH)


Packaging

Plastic bags: from 2 m to 7.5 m


Reliable performance is dependent upon the type of fluid conveyed and fittings being used.

Performance of PU Recoil Tubing

PU Ester Recoil Tubing






PU Ether Recoil Tubing



Tube O.D.	Tube I.D.	Tube O.D. Tolerance
4 to 8 mm	2.5 to 5.5 mm	+0.10 / -0.10
10 to 12 mm	7 to 8 mm	+0.15 / -0.15
3/8" and 19/32"	1/4" and 3/8"	+/- 0.005"




To calculate burst pressure, the values in these graphs should be multiplied by 3.

1470U Polyurethane (PU) Ester Recoil Tubing 2 m, Male BSPT Fitting

O.D. (mm)	I.D. (mm)	BSPT Thread				Total Closed Length (mm)	O.D. of Coil (mm)	kg
4	2.5	R1/8	1470U04 03 10	1470U04 04 10	1470U04 05 10	595	24	0.060
6	4	R1/4	1470U06 03 13	1470U06 04 13	1470U06 05 13	630	32	0.060
8	5	R1/4	1470U08 03 13	1470U08 04 13	1470U08 05 13	780	42	0.120
10	7	R1/4	1470U10 03 13	1470U10 04 13	1470U10 05 13	780	62	0.160
12	8	R3/8	1470U12 03 17	1470U12 04 17	1470U12 05 17	780	65	0.190




Length of long straight section, O.D. < 8 mm: 300 mm; Length of long straight section, O.D. ≥ 8 mm: 500 mm; Length of short straight section, for all O.D.: 100 mm

1471U Polyurethane (PU) Ester Recoil Tubing 4 m, Male BSPT Fitting

O.D. (mm)	I.D. (mm)	BSPT Thread				Total Closed Length (mm)	O.D. of Coil (mm)	kg
4	2.5	R1/8	1471U04 03 10	1471U04 04 10	1471U04 05 10	785	24	0.100
6	4	R1/4	1471U06 03 13	1471U06 04 13	1471U06 05 13	850	32	0.160
8	5	R1/4	1471U08 03 13	1471U08 04 13	1471U08 05 13	1000	42	0.200
10	7	R1/4	1471U10 03 13	1471U10 04 13	1471U10 05 13	1000	62	0.230
12	8	R3/8	1471U12 03 17	1471U12 04 17	1471U12 05 17	1140	65	0.260


Length of long straight section, O.D. < 8 mm: 300 mm; Length of long straight section, O.D. ≥ 8 mm: 500 mm; Length of short straight section, for all O.D.: 100 mm

1472U Polyurethane (PU) Ester Recoil Tubing 6 m, Male BSPT Fitting

O.D. (mm)	I.D. (mm)	BSPT Thread				Total Closed Length (mm)	O.D. of Coil (mm)	kg
8	5	R1/4	1472U08 03 13	1472U08 04 13	1472U08 05 13	1230	42	0.280
10	7	R1/4	1472U10 03 13	1472U10 04 13	1472U10 05 13	1140	62	0.295
12	8	R3/8	1472U12 03 17	1472U12 04 17	1472U12 05 17	1190	65	0.310


Length of long straight section, O.D. < 8 mm: 300 mm; Length of long straight section, O.D. ≥ 8 mm: 500 mm; Length of short straight section, for all O.D.: 100 mm

1460U Polyurethane (PU) Ester Recoil Tubing 2 m

O.D. (mm)	I.D. (mm)		Total Closed Length (mm)	O.D. of Coil (mm)	kg
8	5	1460U08 04	780	42	0.064
10	7	1460U10 04	780	62	0.122
12	8	1460U12 04	780	65	0.172


Length of long straight section, O.D. < 8 mm: 300 mm; Length of long straight section, O.D. ≥ 8 mm: 500 mm; Length of short straight section, for all O.D.: 100 mm

1461U Polyurethane (PU) Ester Recoil Tubing 4 m

O.D. (mm)	I.D. (mm)		Total Closed Length (mm)	O.D. of Coil (mm)	kg
8	5	1461U08 04	1000	42	0.128
10	7	1461U10 04	1000	62	0.244
12	8	1461U12 04	1000	65	0.344

Length of long straight section, O.D. < 8 mm: 300 mm; Length of long straight section, O.D. ≥ 8 mm: 500 mm; Length of short straight section, for all O.D.: 100 mm


1462U Polyurethane (PU) Ester Recoil Tubing 6 m

O.D. (mm)	I.D. (mm)		Total Closed Length (mm)	O.D. of Coil (mm)	kg
8	5	1462U08 04	1230	42	0.192
10	7	1462U10 04	1140	62	1.246
12	8	1462U12 04	1190	65	0.280


Length of long straight section, O.D. < 8 mm: 300 mm; Length of long straight section, O.D. ≥ 8 mm: 500 mm; Length of short straight section, for all O.D.: 100 mm

PU Recoil Tubing


1445U..R Recoil Polyurethane (PU) Ether Tubing 3 m, Male BSPP Fitting

O.D. (mm)	I.D. (mm)	BSPP Thread		Total Closed Length (mm)	O.D. of Coil (mm)	kg
8	5	G1/4	1445U08R04 13	819	40	0.170
3/8"	1/4"	G1/4	1445U60R04 13	769	60	0.230
12	8	G3/8	1445U12R04 17	789	80	0.310
14	9.5	G3/8	1445U14R04 17	759	110	0.460


1441U..R Recoil Polyurethane (PU) Ether Tubing 4 m, Male BSPP Fitting

O.D. (mm)	I.D. (mm)	BSPP Thread		Total Closed Length (mm)	O.D. of Coil (mm)	kg
8	5	G1/4	1441U08R04 13	889	40	0.220
3/8"	1/4"	G1/4	1441U60R04 13	819	60	0.260
12	8	G3/8	1441U12R04 17	849	80	0.400
14	9.5	G3/8	1441U14R04 17	809	110	0.554

1442U..R Recoil Polyurethane (PU) Ether Tubing 6 m, Male BSPP Fitting



O.D. (mm)	I.D. (mm)	BSPP Thread		Total Closed Length (mm)	O.D. of Coil (mm)	kg
8	5	G1/4	1442U08R04 13	1029	40	0.340
3/8"	1/4"	G1/4	1442U60R04 13	929	60	0.360
12	8	G3/8	1442U12R04 17	969	80	0.530
14	9.5	G3/8	1442U14R04 17	909	110	0.920

1447U..R Recoil Polyurethane (PU) Ether Tubing 7.5 m, Male BSPP Fitting



O.D. (mm)	I.D. (mm)	BSPP Thread		Total Closed Length (mm)	O.D. of Coil (mm)	kg
8	5	G1/4	1447U08R04 13	1134	40	0.420
3/8"	1/4"	G1/4	1447U60R04 13	1009	60	0.460
12	8	G3/8	1447U12R04 17	1059	80	0.600
14	9.5	G3/8	1447U14R04 17	984	110	1.150

Accessories

0694 Push-In Fitting with Protection Spring, Male BSPP Thread

	Nickel-plated brass, NBR 	ØD	C		E	F	G	L	kg
		8	G1/4	0694 08 13	6.5	16	24	104.5	0.067
		10	G1/4	0694 10 13	6.5	18	24	106.5	0.062
		12	G3/8	0694 12 17	7.5	20	29.5	126	0.080

0695 Push-In Fitting with Protection Spring, Male BSPT Thread

	Nickel-plated brass, NBR 	ØD	C		F	G	L	kg
		8	R1/4	0695 08 13	14	24	104.5	0.055
		10	R1/4	0695 10 13	18	24	106.5	0.064
		12	R3/8	0695 12 17	20	29.5	126	0.090

Braided PU Recoil Hose

This recoil hose offers all the advantages of polyurethane, combining the **durability** and **kink resistance** of bulkier braided hoses with great **elasticity** and maximum **flexibility**.

Product Advantages

- Excellent Mechanical Properties

Unsurpassed resistance to abrasion: 10 times better than rubber, polyamide and non-braided polyurethane
Excellent flexibility and coil memory: minimizes work fatigue
Highly kink and crush-resistant
Silicone-free
- Ready-to-Use

Pre-assembled threaded fittings
Tube ends protected with a plastic spring
Lightweight for easy handling
3 lengths available
Translucent blue: visibility of the fluid



Machine Tools
Industrial Assembly
Pneumatics
In-Plant Automotive
Workshops

Applications

Technical Characteristics


Compatible Fluids	Compressed air Other fluids: please consult us
Working Pressure	0 to 15 bar
Working Temperature	-40°C to +75°C
Component Materials	Polyurethane (85 shore A)

Regulations

DI: 97/23/EC(PED)
RG: 1907/2006 (REACH)
DI: 2002/95/EC (RoHS), 2011/65/EC

Reliable performance is dependent upon the type of fluid conveyed and fittings being used.

Performance of Braided PU Recoil Hose




Hose O.D.	Hose I.D.	Hose I.D. Tolerance
3/8" 15/32"	1/4" 5/16"	+/- 0.005"

Connected to Parker Legris push-in fittings, the calibration of PU tubing ensures perfect sealing.


Packaging
Plastic bags : 3 m to 7.5 m

To calculate burst pressure, the values in this graph should be multiplied by 4.


1445U..E Braided Polyurethane (PU) Recoil Hose 3 m, Male BSPP Fitting

Ø ext. (mm)	I.D. (mm)	BSPP Thread		Total Closed Length (mm)	O.D. of Coil (mm)	kg
3/8"	1/4"	G1/4	1445U60E04 13	870	42	0.210
12	8	G3/8	1445U12E04 17	880	55	0.300

1442U..E Braided Polyurethane (PU) Recoil Hose 6 m, Male BSPP Fitting

O.D. (mm)	I.D. (mm)	BSPP Thread		Total Closed Length (mm)	O.D. of Coil (mm)	kg
3/8"	1/4"	G1/4	1442U60E04 13	1140	42	0.420
12	8	G3/8	1442U12E04 17	1160	55	0.600

1447U..E Braided Polyurethane (PU) Recoil Hose 7.5 m, Male BSPP Fitting

O.D. (mm)	I.D. (mm)	BSPP Thread		Total Closed Length (mm)	O.D. of Coil (mm)	kg
3/8"	1/4"	G1/4	1447U60E04 13	1275	42	0.525
12	8	G3/8	1447U12E04 17	1300	55	0.750

Related Products

Parker Legris recoil tubing is designed for use with Parker Legris blowguns and couplers.

Industrial Blowguns

Polymer P. 7-3



Metal P. 7-12



Couplers

C 9000 P. 8-7



Metal P. 8-18



PVC Braided Hose

Parker Legris offers two **grades of PVC** which cover a wide range of industrial applications for the **transportation of various fluids**.

Product Advantages

Food-Grade PVC

Monograde tubing reinforced with a braided polyester ply
Flexible: space saving during installation
Translucent for visual identification:

- of the fluid
- of inner cleanliness
- of fluid flow

Food-grade, without phthalates
Silicone-free

Industrial PVC

Tubing with a braided polyester ply between 2 grades of PVC
Resistant to abrasion, impact and crushing
Increased durability
Lightweight and easy-to-use
Silicone-free



Applications

- Robotics
- In-Plant Automotive
- Pneumatics
- Semi-Conductors
- Textile
- Packaging
- Vacuum

Technical Characteristics

Hose	Food-Grade PVC	Industrial PVC
Compatible Fluids	Compressed air, other fluids	Compressed air
Working Pressure	0 to 15 bar	0 to 15 bar
Working Temperature	-20°C to +70°C	-25°C to +60°C
Component Materials	Translucent food-grade PVC, phthalate-free with polyester braid	Industrial blue PVC, multi-layer, with polyester braid

Regulations

Food-Grade PVC

FDA: 21 CFR 177.1550
RG: 1907/2006 (REACH)
RG: 1935/2004
DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 2007/10/EC (phthalates)


Industrial PVC

DI: 97/23/CE (PED)
RG: 1907/2006 (REACH)
DI: 2002/95/EC (RoHS), 2011/65/EC

Reliable performance is dependent upon the type of fluid conveyed and fittings being used.

Hose Performance

Food-Grade PVC



Hose Type	Hose I.D.	Hose I.D. Tolerance
Food-Grade PVC	4 to 6 mm	+0.5 / -0.5
	7 to 12 mm	+0.6 / -0.6
	15 to 19 mm	+0.8 / -0.8
Industrial PVC	6.3 mm	+0.3 / -0.3
	9 mm	+0.5 / -0.5
	12.7 mm	+0.6 / -0.6

Packaging



Reel: 25 m, 50 m
(with protective plastic bag)

To calculate burst pressure, the values in these graphs should be multiplied by 3.

1025V

Food-Grade Braided PVC Hose



Reel 25 m

O.D. (mm)	I.D. (mm)		 Clear	kg
8	4	10	1025V08 00 04	1.260
11	6	12	1025V11 00 06	2.253
13	7	14	1025V13 00 07	3.182
14	8	16	1025V14 00 08	3.434
16	10	25	1025V16 00 10	3.800
18	12	30	1025V18 00 12	4.423
23	15	40	1025V23 00 15	7.300
26	19	60	1025V26 00 19	7.300

1050V

Food-Grade Braided PVC Hose



Reel 50 m

O.D. (mm)	I.D. (mm)		 Clear	kg
8	4	10	1050V08 00 04	2.690
11	6	12	1050V11 00 06	4.200
13	7	14	1050V13 00 07	5.966
14	8	16	1050V14 00 08	6.058
16	10	25	1050V16 00 10	6.400
18	12	30	1050V18 00 12	8.250
23	15	40	1050V23 00 15	14.600
26	19	60	1050V26 00 19	14.600

1025V..C

Industrial-Grade Braided PVC Hose



Reel 25 m

O.D. (mm)	I.D. (mm)			kg
11	6	45	1025V11C04 06	2.175
14	9	63	1025V14C04 09	3.250
19	13	89	1025V19C04 13	4.975

1050V..C

Industrial-Grade Braided PVC Hose

Reel 50 m

O.D. (mm)	I.D. (mm)			kg
11	6	45	1050V11C04 06	4.350
14	9	63	1050V14C04 09	6.500
19	13	89	1050V19C04 13	9.950

Related Products

PVC tubing is designed for use with Parker Legris barb connectors and couplers.

Barb Connectors

0191 P. 9-16



0123 P. 9-10



Couplers

C 9000 P. 8-7



Metal P. 8-18



Self-Fastening NBR Hose

Parker Legris self-fastening hose is designed according to **CNOMO E07.21.115N***. This range of hose should be used with Legris barb connectors and provides both the **reliability** of self-fastening technology and **simplicity of installation**.

Product Advantages

Exceptional Endurance

Unsurpassed resistance to repetitive flexing
Protection against spark and flame
Abrasion and crush-resistant
UV-resistant

Ideal for In-Plant Automotive

Excellent ozone resistance
Perfect for cooling systems
Maximum flow with no pressure drop
4 colours for immediate circuit identification
Silicone-free

Ready-To-Use

No lubrication, additive (grease, oil, ...etc), or preparation time required
To connect: push the hose fully home against the fitting shoulder
To disassemble: cut the hose on the barbed side of the fitting



In-Plant Automotive
Cooling
Welding Robots
Pneumatics
Industrial Machinery

Applications

Technical Characteristics

Compatible Fluids	Coolants, compressed air
Working Pressure	0 to 16 bar
Working Temperature	-20°C to +100°C
Component Materials	Nitrile butadiene rubber & textile braid


Regulations

NFT 46-019-1
NFT 47 252
RG: 1907/2006 (REACH)
DI: 2002/95/EC (RoHS), 2011/65/EC
CNOMO: E07.21.115N

***CAUTION:** CNOMO certification is valid exclusively for red and green hose, only when connected to Legris' CNOMO-certified barb connectors 0132, 0133 and 0134.

Reliable performance is dependent upon the type of fluid conveyed and fittings being used.

Performance of Self-Fastening NBR Hose



DN mm CNOMO	DN (standard)	Hose I.D. (mm)	Hose I.D. Tolerance (mm)
6	1/4	6.3 mm	+0.4 / -0.4
8	3/8	9.5 mm	+0.5 / -0.5
12 16 20	1/2 5/8 3/4	12.7 mm 15.9 mm 19.1 mm	+0.6 / -0.6

Packaging






Drum: 20 m, 40 m, 80 m, 100 m

Use with water: maximum temperature 100°C
Use with air: maximum temperature 70°C

To calculate burst pressure, the values in this graph should be multiplied by 3.

1040H Braided Self-Fastening NBR Hose






Drum 40 m

DN	O.D. (mm)	I.D. (mm)						kg
1/4	13	6.3	60	1040H56 01	1040H56 02	1040H56 03	1040H56 04	7.000
3/8	16	9.5	70	1040H60 01	1040H60 02	1040H60 03	1040H60 04	8.600
1/2	19	12.7	120	1040H62 01	1040H62 02	1040H62 03	1040H62 04	9.450
5/8	23	15.9	140	1040H66 01	1040H66 02	1040H66 03	1040H66 04	13.000
3/4	27	19.1	170	1040H69 01	1040H69 02	1040H69 03	1040H69 04	16.500

Also available in 20 m length upon request

1080H Braided Self-Fastening NBR Hose






Drum 80 m

DN	O.D. (mm)	I.D. (mm)						kg
5/8	23	15.9	140	1080H66 01	1080H66 02	1080H66 03	1080H66 04	26.160
3/4	27	19.1	170	1080H69 01	1080H69 02	1080H69 03	1080H69 04	33.160

Also available in 20 m length upon request

1100H Braided Self-Fastening NBR Hose

Drum 100 m

DN	O.D. (mm)	I.D. (mm)						kg
1/4	13	6.3	60	1100H56 01	1100H56 02	1100H56 03	1100H56 04	14.660
3/8	16	9.5	70	1100H60 01	1100H60 02	1100H60 03	1100H60 04	20.600
1/2	19	12.7	120	1100H62 01	1100H62 02	1100H62 03	1100H62 04	23.000

Also available in 20 m length upon request

Related Products

Self-fastening hose is designed for use with Parker Legris brass barb connectors (CNOMO-certified).

Barb Connectors

0132 P. 5-25 **0133 .. 39** P. 5-25 **0134** P. 5-25



Installation Tool

Tool Part Number:
0650 00 00 05

This automatic installation tool reduces the effort required to connect self-fastening hose onto a barb connector.



Tube Cutting and Positioning

Cut the tube at a right angle and position the barb connector on the mounting tool.

Barb connector support



Press-Fitting the Tube




Activate the press-fit tool; connection is complete when the tube is fully home on the barb connector. This tool has been designed for use with 5 different diameters and is easy to operate.

Barb connector support






Accessories




0694 Push-In Fitting with Protection Spring, Male BSPP Thread

	Nickel-plated brass, NBR		ØD	C		E	F	G	L	kg
			8	G1/4	0694 08 13	6.5	16	24	104.5	0.067
			10	G1/4	0694 10 13	6.5	18	24	106.5	0.062
			12	G3/8	0694 12 17	7.5	20	29.5	126	0.080



0695 Push-In Fitting with Protection Spring, Male BSPT Thread

	Nickel-plated brass, NBR		ØD	C		F	G	L	kg
			8	R1/4	0695 08 13	14	24	104.5	0.055
			10	R1/4	0695 10 13	18	24	106.5	0.064
			12	R3/8	0695 12 17	20	29.5	126	0.090



3000 71 00 Tube Cutter

	Technical polymer			H	L	kg
			3000 71 00	25	79	0.029
			This tool is designed to give a clean cut at right angles to the tube axis for all resilient polymer tubing (polyamide, polyurethane, FEP, polyethylene, etc.) from 4 mm to 12 mm diameter inclusive. Replacement blades: part number 3000 71 00 05 A spring maintains the cutter in the closed position.			




3000 71 11 Tube Cutter

	Treated steel		kg
		3000 71 11	0.227

6000 71 00 Stripping Tool for Anti-Spark Tubing




	Technical polymer, stainless steel		kg
		6000 71 00	0.098
		Working principle of the stripping tool page 3-17	

1827 Stainless Steel Tube Support for Fluoropolymer Tubing

	Stainless steel 316L		ØD1	ØD2		L	kg
			6	4	1827 06 00	11.5	0.001
			8	6	1827 08 00	14	0.001
			10	8	1827 10 00	18	0.001
			12	9	1827 12 09	18	0.001
			12	10	1827 12 00	18	0.001
			16	14	1827 16 00	18	0.002




This tube support is necessary when using fluoropolymer FEP tubing at all temperatures compatible with the fitting/ tubing assembly.

0127 Brass Tube Support for Polymer Tubing

	Brass		ØD1	ØD2		L	kg
			4	2	0127 04 00	11	0.001
			4	2.7	0127 04 27	11	0.001
			5	3	0127 05 03	11	0.001
			5	3.3	0127 05 00	11.5	0.009
			6	4	0127 06 00	11.5	0.001
			8	5.5	0127 08 55	14	0.001
			8	6	0127 08 00	14	0.001
			10	7	0127 10 07	18	0.001
			10	7.5	0127 10 75	18	0.001
			10	8	0127 10 00	18	0.002
			12	8	0127 12 08	18	0.002
			12	9	0127 12 09	18	0.002
			12	10	0127 12 00	18	0.001
			14	11	0127 14 11	18	0.002
			14	12	0127 14 00	18	0.002
			15	12	0127 15 12	18	0.002
			16	13	0127 16 13	18	0.003
			18	14	0127 18 14	19.5	0.003
			20	15	0127 20 15	20.5	0.003
			22	16	0127 22 16	21	0.004
			25	19	0127 25 19	25	0.007




This tube support guarantees good gripping, at high temperatures and pressures, by preventing collapsing of the tube.

CLIP Clip Strip for Tubing and Fittings

	Technical polymer		ØD		H	K	N	kg
			4	CLIP 04 00	9	13.5	10.5	0.007
			6	CLIP 06 00	10.5	13	10.5	0.004
			8	CLIP 08 00	12.5	10.5	12	0.007
			10	CLIP 10 00	14	12	15	0.005
			12	CLIP 12 00	16.5	14	16.5	0.009
			14	CLIP 14 00	18	16	20.5	0.008

Delivered in boxes of 10 strips of the same diameter (complete with self-tapping screws of 95 mm length)
These clips can be used with metric or inch tubing.

0697 Clip for Braided Tubing

	Treated steel		ØD		H	K	L	L1	kg
			6-11	0697 00 01	7	5	12	7	0.004
			10-16	0697 00 02	12	9	21	13	0.011
			12-22	0697 00 03	12	9	21	13	0.015
			16-27	0697 00 04	12	9	24	13	0.015
			20-32	0697 00 05	12	9	24	13	0.016

Chemical Compatibility Chart

Recommended	1	Not Recommended	3
Satisfactory	2	Not Available	-

Substances	PA	PU ether	PU ester	Low Density PE	APE	FEP/PFA
Acetaldehyde	1	1	3	3	2	1
Acetone	1	3	1	2	1	1
Acetylene	-	-	-	3	-	1
Acid, chromic up to 10%	2	3	3	3	-	1
Acid, citric	1	1	1	1	1	1
Acid, formic up to 10%	-	-	-	3	-	1
Acid, hydrochloric up to 10%	3	1	3	1	1	1
Acid, phosphoric up to 50%		3	3	1	1	1
Acid, sulphuric up to 10%	3	1	1	1	1	1
Acid, acetic	3	1	3	1	1	1
Acid, nitric	2	1	3	2	-	1
Ammonia and gaseous	-	1	3	2	1	1
Ammonium chloride up to 10%	-	1	1	1	1	1
Benzene	1	3	3	3	2	1
Bromine	3	-	-	2	3	1
Butane	-	1	1		1	1
Butyl acetate	1	3	2	2		1
Butylic and butyl alcohol	1	3	2	1	1	1
Calcium choride	1	-	-	2	1	1
Carbon tetrachloride (sodium hypochlorite)	2	2	2		3	1
Chloroform	3	3	3	2	2	1
Compressed air	-	1	1	1	1	1
Copper sulphate	-	-	-	-	-	1
Cyclohexanone	1	3	3	3		1
Ethanol	1	2	2			1
Ethyl acetate	1	2	2	1	1	1
Ethyl alcohol	1	-	-	2	1	1
Ethylene oxide	-	-	-	3	2	1
Formalin (formaldehyde)	1	1	2	1	1	1
Freon 12-22	2	2	2	-	-	1
Glucose	-	1	2	1	1	1
Glycol (methyl)	-	3	3	-	-	1
Glycol (without H ₂ O)	-	1	1	1	1	1
Hexachloride	-	2	1	-	-	1
Hydrogen	1	1	2	-	1	1
Hydrogen peroxide (perydrol)	3	2	2	-	1	1
Kerosene	1	1	2	-	3	1
Magnesium chloride (up to 30%)	1	1	2	-	1	1
Methane	1	1	1	-	-	1
Methanol	2	1	1	-	-	1
Methyl acetate	-	2	2	-	-	1
Methyl alcohol (pure)	1	1	1	-	2	1

Chemical Compatibility Chart

Substances	PA	PU ether	PU ester	LDPE	APE	FEP/PFA
Methyl bromide	2	-	-	-	-	1
Methyl chloride	2	-	-	-	-	1
Methyl ethyl ketone	1	3	3	-	-	1
Methyl isobutyl ketone	1	3	3	-	-	1
Oils (ASTM class A)	1	1	1	-	-	1
Oils (ASTM class B)	1	2	1	-	-	1
Oils (ASTM class C)	1	2	1	-	-	1
Oils (ASTM class 1)	1	1	1	-	-	1
Oils (ASTM class 2)	1	1	1	-	-	1
Oils (ASTM class 3)	1	1	1	-	-	1
Oils (cutting)	1	1	1	-	3	1
Oils (paraffin)	1	1	2	-	-	1
Oils, engine (diesel)	1	2	2	2	2	1
Oxygen	1	1	1	1	1	1
Ozone	3	2	2	-	3	1
Perchlorate ethylene	1	3	3	-	-	1
Petrol, with up to 40% aromatics	3	3	2	-	3	1
Petrol, with more than 40% aromatics	1	3	3	-	3	1
Phenols	1	3	3	-	-	1
Potash	1	2	3	-	-	1
Potassium chloride up to 40%	-	1	2	-	-	1
Potassium hydroxide	1	-	-	-	1	1
Potassium manganate 5%	1	3	2	-	1	1
Potassium sulphate	1	-	-	-	-	1
Propane	1	1	1	-	-	1
Soda 50%	1	1	3	-	1	1
Sodium carbonate	1	-	-	-	1	1
Sodium chloride	-	1	2	-	-	1
Sodium hydroxide (caustic soda)	-	1	2	-	1	1
Sodium hypochlorite (bleach)	1	1	3	-	-	1
Sulphurous anhydride	1	-	-	-	-	1
Tetrachloroethylene	1	2	2	-	-	1
Toluene	1	2	2	3	3	1
Tributylphosphate	1	-	-	-	-	1
Trichlorethylene	1	3	3	-	-	1
Water (distilled, deionised)	-	1	3	2	1	1
Water (drinking, food)	1	1	3	1	1	1
Water (industrial)	1	1	3	1	1	1
Water (sea)	2	1	3	1	1	1
Xylem	1	2	2	-	-	1
Zinc chloride	1	1	1	-	-	1

For other fluids, concentrations or special implementation, please contact us.

Function Fittings

Flow Control Regulators

Piloted Function Fittings

Non-Return Valves

LIQUIfit®

Pressure Fittings

Other Function Fittings

Silencers



Function Fittings

Flow Control Regulators

(P. 4-6)



Function: controls the speed of the cylinder rod
Materials: polymer, metal, stainless steel
Pressure: 10 bar
Temperature: 0°C to +70°C
Ø metric: 3 mm to 18 mm
Threads: BSPP, BSPT, metric

Blocking Fittings

(P. 4-36)



Function: provides safety by locking the cylinder piston
Materials: nickel-plated brass, polymer
Pressure: 10 bar
Temperature: -20°C to +70°C
Ø metric: 6 mm to 12 mm
Threads: BSPP, BSPT

Piloted Non-Return Valves

(P. 4-38)



Function: provides safety by locking the cylinder piston
Materials: nickel-plated brass, polymer
Pressure: 10 bar
Temperature: -5°C to +60°C
Ø metric: 6 mm to 12 mm
Threads: BSPP

Non-Return Valves

(P. 4-40)



Function: allows air to pass in one direction only
Materials: polymer, nickel-plated brass
Pressure: 10 bar
Temperature: 0°C to +70°C
Ø metric: 4 mm to 12 mm
Threads: BSPP, BSPT, metric

Adjustable Non-Return Valves

(P. 4-42)



Function: allows air to pass in one direction with an adjustable opening pressure
Materials: FDA chemical nickel-plated brass
Pressure: 12 bar
Temperature: -20°C to +80°C
Threads: BSPP, metric

LIQUIfit® Non-Return Valves

(P. 4-44)



Function: allows fluid to pass in one direction only
Materials: polymer for food applications
Pressure: 10 bar
Temperature: 0°C to +65°C
Ø inch: 1/4" and 3/8"

Stainless Steel Non-Return Valves

(P. 4-46)



Function: allows fluid to pass in one direction only
Materials: stainless steel
Pressure: 0.5 to 40 bar
Temperature: -20°C to +180°C
DN : 10 mm to 25 mm
Threads: BSPP, NPT

Soft Start Fittings

(P. 4-48)



Function: protects the installation at start-up
Materials: polymer, nickel-plated brass
Pressure: 3 to 10 bar
Temperature: -15°C to +60°C
Ø metric : 8 mm to 12 mm
Threads: BSPP

Pneumatic Sensor Fittings

(P. 4-50)



Function: pneumatic or electric output signal, detects end of cylinder rod stroke
Materials: polymer, treated metal
Pressure: 3 to 8 bar
Temperature: -15°C to +60°C
Ø metric: 4 mm
Threads: BSPP, metric

Function Fittings

Pressure Regulators/Pressure Reducers (P. 4-52)



Function: limits the maximum pressure delivered to pneumatic equipment

Materials: polymer, treated metal

Pressure: 16 bar (upstream), 8 bar (downstream)

Temperature: -15°C to +70°C

Ø metric: 4 mm to 10 mm

Threads: BSPP

Snap Connectors (P. 4-56)



Function: isolates a circuit without venting the whole system

Materials: polymer, nickel-plated brass

Pressure: 10 bar

Temperature: -20°C to +80°C

DN : 5 mm to 7 mm

Threads: BSPP

Manually-Operated Valves (P. 4-58)



Function: opens/closes a circuit, with or without venting

Materials: polymer, nickel-plated brass, aluminium

Pressure: 16 bar, 10 bar

Temperature: -10°C to +80°C

Ø metric: 4 mm to 10 mm

Threads: BSPP, metric

Metal Quick Exhaust Valves (P. 4-60)



Function: increases the return speed of the cylinder

Materials: nickel-plated brass, aluminium, stainless steel

Pressure: 10 bar

Temperature: -20°C to +70°C

Threads: BSPP, BSPT, metric

Silencers (P. 4-62)



Function: reduces noise levels

Materials: sintered bronze, polyethylene, stainless steel, nickel-plated brass

Pressure: 12 bar

Temperature: -20°C to +180°C












Ø metric: 4 mm to 12 mm

Threads: BSPP, metric, NPT

Selecting Your Function Fitting

Protect Your System	Blocking Fittings	Maintain the load following an emergency stop of a pneumatic system.	Models 7880 - 7881 - 7883 - 7885 7886
	Soft Start Fittings	Increase the pressure gradually in order to protect it from potentially damaging shock when a pneumatic system is restarted.	Models 7860 - 7861 - 7870 - 7871
	Non-Return Valves	Allow compressed air to flow in one direction, and prevent it from flowing in the other. If the supply is accidentally shut off, the air can only escape in one direction.	Models 4890 - 4891 - 4892 - 4895 7930 - 7931 - 7932 - 7984 7985 - 7992 - 7994 - 7995 7996
	Piloted Non-Return Valves	Incorporate 3 functions into one product to protect your system: piloted non-return valve, flow control regulator and manual vent.	Models 7892 - 7894
Detect End of Cylinder Rod Stroke	Pneumatic Sensor Fittings	Detect the back pressure drop at the end of stroke to produce a signal (pneumatic or electronic) to allow reciprocation.	Models 7818 - 7828
Control and Improve the Performance of Your System	Pressure Regulators	Regulate and stabilise the pressure at a maximum determined value whatever the upstream pressure.	Models 7300
	Pressure Reducer Fittings	Reduce the pressure consumed in one section of the machine in order to save energy.	Models 7316 - 7318 - 7416 - 7471
	Quick Exhaust Valves	Increase the return speed of the cylinder by discharging the exhaust directly to atmosphere.	Models 7899 - 7970 - 7971
	Silencers	Reduce the noise levels whilst air is vented from a compressed air system.	Models 0670 - 0671 - 0672 - 0673 0674 - 0675 - 0676 - 0677
Working on Your System	Snap Fittings	Allow a circuit to be isolated without fully venting the system.	Models 7921 - 7926 - 7960 - 7961
	Manually-Operated Valves	Allow for repeated venting by simply moving the valve sleeve or the manually-operated valve lever.	Models 0669 - 7800 - 7801 - 7802

Symbols for Function Fittings

Regulating air flow 	Regulating pressure by stabilising at a required value 
Blocking air circulation 	Reducing pressure supply 
Blocking and regulating air flow 	Progressive pressurising of circuits 
Controlling allows the passage of fluid in one direction and prevents it in the other 	Isolating a circuit without venting the entire system 
Exhausting system and controlling pneumatic circuit supply 	Regulating, blocking and venting to protect the system and individuals 
Detecting pressure drop 	

Selecting Your Flow Control Regulator

The comprehensive range of Parker Legris flow control regulators provides a solution for all flow regulation functions in a pneumatic system.

Select the model suited to your application according to:

5 Key Requirements

1.	Condition of Use	Standard applications	Technical polymer models
		Severe applications	Metal models
2.	Connection Options	On cylinder or threaded control valve	Models with BSPP, BSPT and metric threads Models with NPT threads on request
		On cylinder or control valve with push-in connection	Plug-in models
3.	Dimensions	Standard applications require full flow rate performance and compact overall dimensions	Compact models
		Small diameter cylinders require precise and accurate adjustment and minimum size	Miniature models
4.	Type of Adjustment	Precise adjustment with locking nut ensuring the setting remains fixed	Models with external adjustment
		Precise adjustment with screwdriver and protection against unwanted adjustment	Models with recessed adjustment
5.	Installation Configuration	Standard applications	Banjo models
		Tube output that can be positioned through 180° and swivels with the tube movement	Models with swivel outlet
		Cylinder where access is difficult or where another function fitting is installed in the cylinder port	In-line models

Flow Control Regulator Range

Technical Polymer Version, BSPP and Metric

Recessed Adjustment

7010
7011
7012
Push-In
Page 4-10



External Adjustment

7060
7061
7062
Compact
Push-In
Page 4-11/12



7660
7662
7669
Miniature
Push-In
Page 4-13/14



Swivel Outlet

7040
7041
Compact
Push-In
Page 4-14



7640
7649
Miniature
Push-In
Page 4-15



In-Line

7770
7772
Push-In
Page 4-16



7776
Bulkhead
Push-In
Page 4-16



7771
Threaded
Page 4-16



7020
Straight
Push-In
Page 4-17



7000
Page 4-16



Plug-In

7030
7031
Compact
Push-In
Page 4-18



7630
7631
Miniature
Push-In
Page 4-18



Technical Polymer Version, BSPT

External Adjustment

7065
7066
7067
Compact
Push-In
Page 4-11/12



7665
7668
Miniature
Push-In
Page 4-13



Swivel Outlet and External Adjustment

7045
Compact
Push-In
Page 4-14



7645
Miniature
Push-In
Page 4-15



Brass, Nickel-Plated Brass and Aluminium Versions, BSPP and Metric

Recessed Adjustment

7130
Push-In
Page 4-19



7140
Threaded
Page 4-19



7160
Compression
Page 4-19



In-Line

7170
Bulkhead
Threaded
Page 4-21



External Adjustment

7762
Threaded
Page 4-21



7100
7101
Compact
Push-In
Page 4-20



7680
Compact
Push-In
Page 4-20



7180
Miniature
Push-In
Page 4-20



7110
7111
Compact
Threaded
Page 4-20/21



7190
Miniature
Threaded
Page 4-21



Stainless Steel Versions

7810
7812
Threaded
Page 4-23



7820
7822
Threaded
Page 4-23



Flow Control Regulators

Parker Legris flow control regulators with polymer, nickel-plated brass or aluminium bodies, external or recessed adjustment screws, offer **precise adjustment, accuracy** and **compactness** providing the solution for all applications.

Product Advantages

Improved Productivity

- Higher maximum flow than standard regulators
- Full flow with minimum pressure drop (model 7060)
- Optimal control of the cylinder rod speed
- 100% leak-tested in production
- Date coding to guarantee quality and traceability
- Reduce compressed air and energy consumption

Accuracy & Performance

- Precise adjustment for accurate flow regulation from initial to maximum opening
- Constant cylinder rod displacement speed
- Long-term stability of flow
- Reduced weight (polymer version)
- Mechanical strength and corrosion resistance with nickel-plated brass version

Ergonomics & Large Range

- External adjustment screw: easy to adjust without tooling and lockable
- Recessed adjustment screw: more compact and protects the adjustment mechanism
- Uni-directional: exhaust or inlet
- Bi-directional: adjustment of air flow in both directions
- 360° positioning
- NPT version on request



Applications

- Pneumatics
- Robotics
- Semi-Conductors
- Textile
- Automotive Process
- Packaging


Technical Characteristics

Compatible Fluids	Compressed air Other fluids: contact us	
Working Pressure	1 to 10 bar	
Working Temperature	0°C to +70°C	

Max. Tightening Torques (external adjustment screw)	Threads	M3 x0.5	M5 x0.8	G1/8	G1/4	G3/8	G1/2
	daN.m	0.06	0.16	0.8	1.2	3	3.5
Max. Tightening Torques (recessed adjustment screw)	Threads	—	M5 x0.8	G1/8	G1/4	G3/8	G1/2
	daN.m	—	0.1	0.4	0.5	0.6	0.7

You will find all the flow rate characteristic curves (to 6 bar) for flow control regulators at the end of the chapter.

Component Materials



Silicone-free

Flow Control Regulators

Operation

Parker Legris offers both uni-directional and bi-directional flow control regulators.


The uni-directional models control the flow of air in one direction through an adjustable restrictor, while allowing full flow in the opposite direction.

The bi-directional models control the flow of air in both directions.


A more precise and constant flow regulation is obtained when the regulator is fitted directly onto the cylinder.

Models with Recessed Adjustment


Uni-Directional (Exhaust Version)



Uni-Directional (Supply Version)




Bi-Directional Version




Models with External Adjustment


Uni-Directional (Exhaust Version)



Uni-Directional (Supply Version)




Bi-Directional Version




In-Line Models

Uni-Directional Version



Bi-Directional Version



For instant visual identification, each Parker Legris flow control regulator version is identified by the related pneumatic symbol and by a letter:

- uni-directional regulation on exhaust: letter A
- uni-directional regulation on supply: letter B
- bi-directional regulation: letter C


Regulators with Recessed Adjustment

7010

Flow Regulator with Recessed Adjustment Screw Exhaust, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		E	F	H	L	L1	kg
4	M5x0.8	7010 04 19	4	8	17.5	17	5	0.006
	G1/8	7010 04 10	5	13	25	19	7	0.018
6	M5x0.8	7010 06 19	4	8	17.5	19	5	0.006
	G1/8	7010 06 10	5	13	25	21	7	0.018
8	G1/4	7010 06 13	8	17	26.5	22	9.5	0.034
	G1/8	7010 08 10	5	13	25	26	7	0.019
10	G1/4	7010 08 13	8	17	26.5	27	9.5	0.035
	G3/8	7010 08 17	7.5	20	37.5	29	11	0.068
12	G1/4	7010 10 13	8	17	26.5	29	9.5	0.035
	G3/8	7010 10 17	7.5	20	37.5	31	11	0.067
12	G1/2	7010 10 21	8	23	43	37	13.5	0.118
	G3/8	7010 12 17	7.5	20	37.5	34.5	11	0.069
12	G1/2	7010 12 21	8	23	43	37	13.5	0.108

7011

Flow Regulator with Recessed Adjustment Screw Supply, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		E	F	H	L	L1	kg
4	M5x0.8	7011 04 19	4	8	17.5	17	5	0.006
	G1/8	7011 04 10	5	13	25	19	7	0.018
6	M5x0.8	7011 06 19	4	8	17.5	19	5	0.006
	G1/8	7011 06 10	5	13	25	21	7	0.018
8	G1/4	7011 06 13	8	17	26.5	22	9.5	0.034
	G1/8	7011 08 10	5	13	25	26	7	0.019
10	G1/4	7011 08 13	8	17	26.5	27	9.5	0.034
	G3/8	7011 08 17	7.5	20	37.5	29	11	0.067
10	G1/4	7011 10 13	8	17	26.5	29	9.5	0.036
	G3/8	7011 10 17	7.5	20	37.5	31	11	0.068

7012

Bi-Directional Flow Regulator with Recessed Adjustment Screw, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		E	F	H	L	L1	kg
4	M5x0.8	7012 04 19	4	8	17.5	17	5	0.006
	G1/8	7012 04 10	5	13	25	19	7	0.018
6	M5x0.8	7012 06 19	4	8	17.5	19	5	0.007
	G1/8	7012 06 10	5	13	25	21	7	0.019
8	G1/4	7012 06 13	8	17	26.5	22	9.5	0.036
	G1/8	7012 08 10	5	13	25	26	7	0.020
10	G1/4	7012 08 13	8	17	26.5	27	9.5	0.036
	G3/8	7012 08 17	7.5	20	37.5	29	11	0.070

Each pneumatic function fitting is identified by:

- the item type
- the tube outside diameter
- the thread or 2nd tube outside diameter

7010 06 10

Item type Tube O.D. Thread code


Compact Regulators with External Adjustment

7060

Compact Flow Regulator Exhaust, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		E	F	F1	H	H _{max}	H1	L	L1	ØT	kg
4	G1/8	7060 04 10	5	10	16	38	44	16	22	9	10	0.020
6	G1/8	7060 06 10	5	10	16	38	44	16	22	9	10	0.020
	G1/4	7060 06 13	5.5	10	16	36.5	42.5	15	22	9	10	0.020
	G1/8	7060 08 10	4.5	14	19	41.5	48	18	28	10.5	14	0.033
8	G1/4	7060 08 13	5.5	14	19	41.5	48	18.5	28	10.5	14	0.034
	G3/8	7060 08 17	5.5	14	19	41.5	48	17	28	11	14	0.034
10	G1/4	7060 10 13	5.5	17	23	45.5	53.5	20	31.5	12.5	17	0.053
	G3/8	7060 10 17	5.5	17	23	45.5	54	20	31.5	12.5	17	0.054
12	G3/8	7060 12 17	5.5	17	23	45.5	54	20	35	12.5	17	0.060
	G1/2	7060 12 21	7.5	17	24	45.5	54	20	35	13	17	0.058

7065

Compact Flow Regulator Exhaust, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	F1	H _{min}	H _{max}	H1	L	L1	ØT	kg
6	R1/8	7065 06 10	10	16	36.5	42.5	15	22	8	10	0.021
8	R1/8	7065 08 10	14	19	40	45	16.5	28	10.5	14	0.034
	R1/4	7065 08 13	14	19	40	45	16.5	28	10.5	14	0.036
	R1/4	7065 10 13	17	23	43.5	51.5	18	31.5	12.5	17	0.053
10	R3/8	7065 10 17	17	23	43.5	51.5	18	31.5	12.5	17	0.055
	R1/2	7065 10 21	17	23	43.5	51.5	18	31.5	12.5	17	0.059
	R1/4	7065 12 13	17	23	43.5	51.5	18	35	12.5	17	0.056
12	R3/8	7065 12 17	17	23	43.5	51.5	18	35	12.5	17	0.059
	R1/2	7065 12 21	17	23	43.5	51.5	18	35	12.5	17	0.064


Pre-coated thread

7061

Compact Flow Regulator Supply, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		E	F	F1	H	H _{max}	H1	L	L1	ØT	kg
4	G1/8	7061 04 10	5	10	16	38	44	16	22	9	10	0.020
6	G1/8	7061 06 10	5	10	16	38	44	16	22	9	10	0.020
	G1/4	7061 06 13	5.5	10	16	36.5	42.5	15	22	9	10	0.021
	G1/8	7061 08 10	4.5	14	19	41.5	48	18	28	10.5	14	0.033
8	G1/4	7061 08 13	5.5	14	19	41.5	48	18.5	28	10.5	14	0.034
	G3/8	7061 08 17	5.5	14	23	41.5	48	17	28	11	14	0.033
10	G1/4	7061 10 13	5.5	17	23	45.5	53.5	20	31.5	12.5	17	0.053
	G3/8	7061 10 17	5.5	17	23	45.5	54	20	31.5	12.5	17	0.054
12	G1/2	7061 12 21	7.5	17	24	45.5	54	20	35	13	17	0.060

7066

Compact Flow Regulator Supply, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	F1	H _{min}	H _{max}	H1	L	L1	ØT	kg
	R1/4	7066 10 13	17	23	43.5	51.5	18	31.5	12.5	17	0.020
10	R3/8	7066 10 17	17	23	43.5	51.5	18	31.5	12.5	17	0.020
	R1/2	7066 10 21	17	23	43.5	51.5	18	31.5	12.5	17	0.059
	R1/4	7066 12 13	17	23	43.5	51.5	18	35	12.5	17	0.056
12	R3/8	7066 12 17	17	23	43.5	51.5	18	35	12.5	17	0.059
	R1/2	7066 12 21	17	23	43.5	51.5	18	35	12.5	17	0.064

Pre-coated thread


Compact Regulators with External Adjustment

7062

Bi-Directional Compact Flow Regulator, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		E	F	F1	H	H _{max}	H1	L	L1	ØT	kg
4	G1/8	7062 04 10	5	10	16	38	44	16	22	9	10	0.025
6	G1/8	7062 06 10	5	10	16	38	44	16	22	9	10	0.025
	G1/4	7062 06 13	5.5	10	16	36.5	42.5	15	22	9	10	0.025
	G1/8	7062 08 10	4.5	14	19	41.5	48	18	28	10.5	14	0.043
8	G1/4	7062 08 13	5.5	14	19	41.5	48	18.5	28	10.5	14	0.046
	G3/8	7062 08 17	5.5	14	19	41.5	48	17	28	11	14	0.042

7067

Bi-Directional Compact Flow Regulator, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	F1	H _{min}	H _{max}	H1	L	L1	ØT	kg
4	R1/8	7067 04 10	10	16	36.5	42.5	14.7	22	9	10	0.025
6	R1/8	7067 06 10	10	16	36.5	42.5	14.7	22	9	10	0.010
	R1/4	7067 06 13	10	16	36.5	42.5	14.7	22	9	10	0.014
	R1/8	7067 08 10	14	19	40	45	16.5	28	10.5	14	0.034
8	R1/4	7067 08 13	14	19	40	45	16.5	28	10.5	14	0.036
	R3/8	7067 08 17	14	19	40	45	16.5	28	11	14	0.042

Pre-coated thread


Miniature Regulators with External Adjustment

7660

Miniature Flow Regulator Exhaust, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	G	H min	H max	L	L1	kg
3	M3x0.5	7660 03 09	6	9	23.5	26	17	4.5	0.007
	M5x0.8	7660 03 19	6	9	23.5	26	17	4.5	0.006
4	M3x0.5	7660 04 09	6	9	23.5	26	16.5	4.5	0.007
	M5x0.8	7660 04 19	6	9	23.5	26	17	4.5	0.006
6	G1/8	7660 06 10	7	11.5	27	29.5	18	6	0.012
	M5x0.8	7660 06 19	6	9	23.5	26	18	4.5	0.007
8	G1/8	7660 08 10	13	14	26.5	31	26	7	0.021
	G1/4	7660 08 13	16	19	29	34	27.5	9.5	0.033
	G3/8	7660 08 17	20	23	36	42	29	11.5	0.062

7665

Miniature Flow Regulator Exhaust, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	G	H min	H max	L	L1	kg
4	R1/8	7665 04 10	7	11.5	25	27.5	18	6	0.012
	R1/8	7665 06 10	7	11.5	25	27.5	18.5	6	0.012
6	R1/4	7665 06 13	8	13.5	27.5	30	19	7	0.019
	R3/8	7665 06 17	17	13.5	31.5	34	19	7	0.025
8	R1/8	7665 08 10	13	14	24	28.5	26	7	0.021
	R1/4	7665 08 13	16	19	25	29	27.5	9.5	0.033
	R3/8	7665 08 17	20	23	30	36	29	11.5	0.061


Pre-coated thread

7669

Miniature Flow Regulator Supply, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	G	H min	H max	L	L1	kg
3	M3x0.5	7669 03 09	6	9	23.5	26	17	4.5	0.008
	M5x0.8	7669 03 19	6	9	23.5	26	17	4.5	0.007
4	M3x0.5	7669 04 19	6	9	23.5	26	17	4.5	0.006
	G1/8	7669 04 10	7	11.5	27	29.5	18	6	0.012
6	M5x0.8	7669 06 19	6	9	23.5	26	18	4.5	0.007
	G1/8	7669 06 10	7	11.5	27	29.5	18.5	6	0.013
8	G1/4	7669 06 13	8	12	30	32.5	19	6	0.019
	G1/8	7669 08 10	13	14	26.5	31	26	7	0.021
	G1/4	7669 08 13	16	19	29	34	27.5	9.5	0.033
	G3/8	7669 08 17	20	23	36	42	29	11.5	0.063

7668

Miniature Flow Regulator Supply, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	G	H min	H max	L	L1	kg
4	R1/8	7668 04 10	7	11.5	25	27.5	18	6	0.011
	R1/8	7668 06 10	7	11.5	25	27.5	18.5	6	0.012
6	R1/4	7668 06 13	8	13.5	27.5	30	19	7	0.019
	R1/8	7668 08 10	13	14	24	28.5	26	7	0.020
8	R1/4	7668 08 13	16	19	25	29	27.5	9.5	0.032
	R3/8	7668 08 17	20	23	30	36	29	11.5	0.061

Pre-coated thread


Regulators with External Adjustment

7662

Bi-Directional Miniature Flow Regulator, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	G	H _{min}	H _{max}	L	L1	kg
4	M5x0.8	7662 04 19	6	9	23.5	26	17	4.5	0.007
	G1/8	7662 04 10	7	11.5	27	29.5	18	6	0.013
6	M5x0.8	7662 06 19	6	9	23.5	26	18	4.5	0.010
	G1/8	7662 06 10	7	11.5	27	29.5	18.5	6	0.013
	G1/4	7662 06 13	8	12	30	32.5	19	6	0.019

7040

Compact Flow Regulator Swivel Outlet Exhaust, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	F1	G	H _{min}	H _{max}	H1	H2	L	kg
6	G1/8	7040 06 10	16	10	10.5	38	44	16	18	23.5	0.024
	G1/4	7040 06 13	16	10	10.5	36.5	42.5	16	16.5	23.5	0.025
8	G1/8	7040 08 10	19	14	13.5	41.5	48	23	19	28	0.037
	G1/4	7040 08 13	19	14	13.5	41.5	48	23	19.5	28	0.039
10	G3/8	7040 08 17	19	14	13.5	41.5	48	23	17.5	28	0.020
	G1/4	7040 10 13	23	17	16	45.5	53.5	26.5	21	35	0.051
12	G3/8	7040 10 17	23	17	16	45.5	54	26.5	21.5	35	0.063
	G3/8	7040 12 17	23	17	19	45.5	54	30.5	21.5	38	0.066
	G1/2	7040 12 21	24	17	19	45.5	54	30.5	21	38	0.071

7045

Compact Flow Regulator Swivel Outlet Exhaust, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	F1	G	H _{min}	H _{max}	H1	H2	L	kg
6	R1/4	7045 06 13	16	10	10.5	36.5	42.5	16	16.5	23.5	0.030
	R1/8	7045 08 10	19	14	13.5	40	46	23	17	28	0.014
8	R1/4	7045 08 13	19	14	13.5	40	46	23	17	28	0.043
	R3/8	7045 08 17	19	14	13.5	40	46	23	17	28	0.044
10	R1/4	7045 10 13	23	17	16	43.5	51.5	26.5	19	35	0.062
	R3/8	7045 10 17	23	17	16	43.5	51.5	26.5	19	35	0.065
12	R3/8	7045 12 17	23	17	19	43.5	51.5	31	19	38	0.065
	R1/2	7045 12 21	23	17	19	43.5	51.5	31	19	38	0.070


Pre-coated thread

7041

Compact Flow Regulator Swivel Outlet Supply, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	F1	G	H _{min}	H _{max}	H1	H2	L	kg
6	G1/4	7041 06 13	16	10	10.5	36.5	42.5	16	16.5	23.5	0.024
8	G1/8	7041 08 10	19	14	13.5	41.5	48	23	19	28	0.037
	G1/4	7041 08 13	19	14	13.5	41.5	48	23	19.5	28	0.039


Miniature Regulators with Swivel Outlet and External Adjustment

7640

Miniature Swivel Outlet Flow Regulator Exhaust, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	G	H _{min}	H _{max}	H1	H2	L	kg
4	M5x0.8	7640 04 19	6	8.5	23.5	26	14	6.5	19.5	0.011
	G1/8	7640 04 10	7	8.5	27	29.5	14	8	19.5	0.015
6	M5x0.8	7640 06 19	6	10.5	23.5	26	16	6.5	21	0.001
	G1/8	7640 06 10	7	10.5	27	29.5	16	8	20.5	0.015

7645

Miniature Swivel Outlet Flow Regulator Exhaust, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	G	H _{min}	H _{max}	H1	H2	J	L	kg
4	R1/8	7645 04 10	7	8.5	25	27.5	14	6	11.5	19.5	0.014
6	R1/8	7645 06 10	7	10.5	25	27.5	16	6	11.5	21.5	0.012


Pre-coated thread

7649

Miniature Swivel Outlet Flow Regulator Supply, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	G	H _{min}	H _{max}	H1	H2	L	kg
4	M5x0.8	7649 04 19	6	8.5	23.5	26	14	6.5	19	0.015
	G1/8	7649 04 10	7	8.5	27	29.5	14	8.5	19.5	0.014
6	M5x0.8	7649 06 19	6	10.5	23.5	26	16	6.5	21	0.008
	G1/8	7649 06 10	7	10.5	27	29.5	16	8.5	21.5	0.015

Associated Products

All our flow control regulators are compatible with the range of polyamide and polyurethane tubing shown in Chapter 3.


In-Line Regulators with External Adjustment

7770

In-Line One-Way Flow Regulator



Technical polymer, NBR




ØD		F	H _{min}	H _{max}	K	L	L1	N	N1	ØT	kg
4	7770 04 00	5	29.5	33.5	12	36	15	11	8	2.2	0.010
6	7770 06 00	8	40.5	44.5	17	51	23	17	11	3.2	0.028
8	7770 08 00	11	46.5	52.5	18.5	58	26	20	12.5	3.2	0.048
10	7770 10 00	14	53	61	24	73	33	26	16	4.2	0.097
12	7770 12 00	14	59	67.5	28	85	35	27.5	20	4.2	0.132

7772

Bi-Directional In-Line Flow Regulator



Technical polymer, NBR




ØD		F	H _{min}	H _{max}	K	L	L1	N	N1	ØT	kg
4	7772 04 00	5	29.5	33.5	12	36	15	11	8	2.2	0.011
6	7772 06 00	8	40	44.5	17	51	23	17	11	3.2	0.032
8	7772 08 00	11	46.5	52.5	18.5	58	26	20	12.5	3.2	0.054

7776

Panel-Mountable In-Line One-Way Flow Regulator



Technical polymer, NBR



ØD		F	F1	H	H _{max}	H1	H2	K	L	ØT	kg
4	7776 04 00*	14	-	21.5	25.5	6.5	11	6	36	10.5	0.017
6	7776 06 00*	19	-	27.5	32.5	7.5	13.5	7	51	16.5	0.042
8	7776 08 00	24	11	28.5	34.5	9	13.5	7	58	18.5	0.069
10	7776 10 00	30	14	29.5	38.5	11.5	13.5	7	73	24.5	0.136
12	7776 12 00	32	14	32	42	12.5	15.5	8	85	27.5	0.185


*Ultrafine adjustment

7771

In-Line One-Way Flow Regulator, Female BSPP Thread



Technical polymer, nickel-plated brass, NBR



C		F	F1	H _{min}	H _{max}	L	L1	N	N1	ØT	kg
G1/8	7771 10 10	13	8	39.5	44.5	68.5	23	17	11	3.2	0.043
G1/4	7771 13 13	16	11	44	50	83	26	20	12.5	3.2	0.103
G3/8	7771 17 17	19	14	52	61	97	33	26	16	4.2	0.160
G1/2	7771 21 21	24	14	57.5	67.5	121	35	27.5	20	4.2	0.260

7000

Joining Clips



Technical polymer










ØD		kg
4	7000 00 05	0,004
6	7000 00 05	0,004
8	7000 00 05	0,004
10	7000 00 06	0,009
12	7000 00 06	0,009

In-Line Regulators with External Adjustment

7020

Straight Flow Regulator Exhaust, Male BSPP Thread

<div>  <div>A</div> </div>	<div>  </div>	<div>  </div>	<div> <div>Technical polymer, nickel-plated brass, NBR</div> </div>					
			<div> <div>ØD</div> <div>C</div> <div>  </div> </div>	F	G	H min	H max	kg
4	G1/8	7020 04 10	<div>  </div>	18	21.5	38.5	44	0.062
				18	21.5	38.5	44	0.058
6	G1/4	7020 06 13	<div>  </div>	18	21.5	38.5	44	0.059
				24	27	46.5	52.5	0.110
8	G1/4	7020 08 13	<div>  </div>	24	27	46.5	52.5	0.112


Plug-In Regulators with External Adjustment

7030

Compact Plug-In Flow Regulator, Exhaust



Technical polymer, nickel-plated brass, NBR




ØD		F	G	H min	H max	H1	H2	L	kg
6	7030 06 00	10	16	35	41	14	17	22	0.013
8	7030 08 00	14	19	39.5	46.5	16	21.5	28	0.022
10	7030 10 00	17	23	43.5	51.5	17.5	24.5	31.5	0.030
12	7030 12 00	17	23	43	51	17	27	35	0.044

7031

Compact Plug-In Flow Regulator, Supply



Technical polymer, nickel-plated brass, NBR




ØD		F	G	H min	H max	H1	H2	L	kg
6	7031 06 00	10	16	35	41	14	17	22	0.013
8	7031 08 00	14	19	39.5	46.5	16	21.5	28	0.035
10	7031 10 00	17	23	43.5	51.5	17.5	24.5	31.5	0.010
12	7031 12 00	17	23	43	51	17	27	35	0.044

7630

Miniature Plug-In Flow Regulator, Exhaust



Technical polymer, nickel-plated brass, NBR




ØD		F	G	H min	H max	H1	H2	L	kg
4	7630 04 00	6	9	25.5	28	9.5	15.5	17	0.007
6	7630 06 00	7	11.5	27.5	29	10.5	17	18.5	0.012

7631

Miniature Plug-In Flow Regulator, Supply





Technical polymer, nickel-plated brass, NBR





ØD		F	G	H min	H max	H1	H2	L	kg
4	7631 04 00	6	9	25.5	28	9.5	15.5	17	0.007
6	7631 06 00	7	11.5	27.5	29	10.5	17	18.5	0.011

Metal Regulators with Recessed Adjustment



7130 Flow Regulator, Exhaust, Male BSPP and Metric Thread

A	Nickel-plated brass, NBR	ØD	C		E	F	H	J	L	kg
		4	M5x0.8	7130 04 19	4	8	17	9	19	0.015
			G1/8	7130 04 10	5	13	34	15	20	0.037
		6	M5x0.8	7130 06 19	4	8	17	9	24	0.013
			G1/8	7130 06 10	5	13	34	15	22	0.038
			G1/4	7130 06 13	8	17	39	18	24	0.062
		8	G1/8	7130 08 10	5	13	34	15	25	0.042
			G1/4	7130 08 13	8	17	39	18	28	0.066
			G3/8	7130 08 17	7	20	47	21.5	29	0.109
		10	G1/4	7130 10 13	8	17	39	18	30	0.075
			G3/8	7130 10 17	7	20	47	21.5	32	0.120
			G1/2	7130 10 21	8	23	61	28	34	0.222
		12	G3/8	7130 12 17	7	20	47	22	36	0.064
			G1/2	7130 12 21	8	23	61	28	38	0.306

7140 Flow Regulator, Exhaust, Male/Female BSPP and Metric Thread

A	Nickel-plated brass, NBR	C		E	E1	F	H	J	L	kg
		M5x0.8	7140 19 19	4	4	8	21	9	11	0.009
		G1/8	7140 10 10	5	8	13	32	15	17	0.040
		G1/4	7140 13 13	8	12	17	39	18	24	0.073
		G3/8	7140 17 17	7	12	20	47	21.5	27	0.125
		G1/2	7140 21 21	8	15	23	61	28	31	0.238

7160 Flow Regulator with Brass Compression Fitting, Exhaust, Male BSPP Thread

A	Nickel-plated brass, NBR	ØD	C		F	F1	H	J	L	L1	kg
		4	G1/8	7160 04 10	13	10	26	17	25.5	14.5	0.049
			G1/8	7160 06 10	13	13	26	17	25.5	14.5	0.054
		6	G1/4	7160 06 13	17	13	31.5	22	28.5	17.5	0.103
			G1/8	7160 08 10	13	14	26	17	29.5	15.5	0.055
		8	G1/4	7160 08 13	17	14	31.5	22	31	17	0.103
			G1/4	7160 10 13	17	19	31.5	22	35	19	0.118
		10	G3/8	7160 10 17	20	19	44.5	22	37.5	19	0.188
			G1/2	7160 10 21	23	19	50	27	37.5	19	0.202
		12	G3/8	7160 12 17	20	22	44.5	22	38	21.5	0.200
			G1/2	7160 12 21	23	22	50	27	38	21.5	0.213


Metal Regulators with External Adjustment

7100

Compact Flow Regulator, Exhaust, Male BSPP Thread



Nickel-plated brass, NBR




ØD	C		F	F1	H _{min}	H _{max}	H1	L	kg
4	G1/8	7100 04 10	10	19	47	53	23	21	0.078
6	G1/8	7100 06 10	10	19	47	53	23	24.5	0.080
	G1/4	7100 06 13	10	19	47.5	53	23.5	24.5	0.083
8	G1/8	7100 08 10	14	19	50	55	24.5	29	0.097
	G1/4	7100 08 13	14	19	50	56	25	29	0.100
10	G3/8	7100 08 17	17	25	56	62	27	30.5	0.154
	G1/4	7100 10 13	14	19	50	56	25	35	0.103
12	G3/8	7100 10 17	17	25	56	62	27	35	0.157
	G3/8	7100 12 17	17	25	56	62	27	38	0.198
14	G1/2	7100 12 21	17	25	55	62	27	38	0.207
	G1/2	7100 14 21	17	25	55	62	27	41	0.205

7101

Compact Flow Regulator, Supply, Male BSPP Thread



Nickel-plated brass, NBR




ØD	C		F	F1	H _{min}	H _{max}	H1	L	kg
4	G1/8	7101 04 10	10	19	47	53	23	21	0.096
6	G1/8	7101 06 10	10	19	47	53	23	24.5	0.080
	G1/4	7101 06 13	10	19	47.5	53	23.5	24.5	0.080
8	G1/8	7101 08 10	14	19	50	55	24.5	29	0.097
	G1/4	7101 08 13	14	19	50	56	25	29	0.100
10	G3/8	7101 08 17	17	25	56	62	27	30.5	0.155

7680

Compact Flow Regulator, Male BSPP Thread



Nickel-plated brass, NBR




ØD	C		E	F	H _{min}	H _{max}	J	L	kg
6	G1/8	7680 06 10	5	13	39	44	7.5	24.5	0.045
	G1/8	7680 08 10	5	13	39	44	7.5	24.5	0.047
8	G1/4	7680 08 13	8	17	41	47	9	27	0.076
	G3/8	7680 10 17	7	20	50	60	11	34	0.133
12	G1/2	7680 12 21	8	23	65	77	14	36.5	0.165

7180

Miniature Flow Regulator Exhaust, Male BSPP and Metric Thread



Nickel-plated brass, NBR




ØD	C		E	F	H _{min}	H _{max}	J	L	kg
4	M5x0.8	7180 04 19	4	8	24	29	10	19	0.012
	G1/8	7180 04 10	5	13	39	44	15	20	0.042
6	M5x0.8	7180 06 19	4	8	24	29	10	24	0.015
	G1/8	7180 06 10	5	13	39	44	15	22	0.043
8	G1/8	7180 08 10	5	13	39	44	15	26	0.049

7110

Compact Flow Regulator Exhaust, Male/Female BSPP Thread



Nickel-plated brass, NBR







C		F	F1	H _{min}	H _{max}	H1	L	kg
G1/8	7110 10 10	10	19	47	52.5	23	22.5	0.079
G1/4	7110 13 13	14	19	50.5	55.5	25	32	0.108
G3/8	7110 17 17	17	25	56	62	27	34.5	0.212
G1/2	7110 21 21	17	25	55	62	27	37.5	0.192

Metal Regulators with External Adjustment





7111

Compact Flow Regulator Supply, Male/Female BSPP Thread

	Nickel-plated brass, NBR		C	F	F1	H _{min}	H _{max}	H1	L	kg
			G1/8	10	19	47	52.5	23	22.5	0.079
			G1/4	14	19	50.5	55.5	25	32	0.107





7190

Miniature Flow Regulator Exhaust, Male/Female BSPP and Metric Thread

	Nickel-plated brass, NBR		C	E	E1	F	H _{min}	H _{max}	J	L	kg
			M5x0.8	4	4	8	24	29	10	11	0.012
			G1/8	5	8	13	39	44	15	17	0.044

7762





Flow Regulator Exhaust, with Brass Compression Fitting, Male BSPP Thread

	Brass, NBR		ØD	C	F	F1	F2	H _{min}	H _{max}	J	L	kg
			8	G1/8	14	14	7	35.5	38.5	17	28.5	0.056
			10	G1/4	19	17	10	44	49	22	36.5	0.129
			14	G3/8	24	22	13	58	65	27	37.5	0.219
			18	G1/2	30	27	19	62.5	68.5	34	44	0.403

*with adjustment knurl

7170

Panel-Mountable In-Line Flow Regulator, Female BSPP and Metric Thread

	Treated aluminium, NBR		C	F	H _{min}	H _{max}	H1	K	L	L1	ØT	kg
			M5x0.8	12	38	42	15	12	25	18	4.5	0.022
			G1/8	15	49	56	22	18	35	24.7	4.5	0.056
			G1/4	15	57	64	30	20	46	35	6.5	0.086
			G3/8	22	62	73	30	25	50	35	6.5	0.155
			G1/2	22	72	83	40	25	60	44	6.5	0.196

Stainless Steel Flow Control Regulators

Stainless steel flow control regulators are used to **regulate the speed of a cylinder rod** as well as gas flow in environments with high mechanical or chemical constraints.

Product Advantages

Robust | Suitable for corrosive environments
Excellent mechanical and chemical resistance
100% leak-tested in production
No contamination of conveyed fluids

Optimised Design | Smooth external surfaces to facilitate cleaning
Fully compatible with food environments
Accurate and easy adjustment

Applications
Food Process
Robotics
Textile
Semi-Conductors
Packaging
Pneumatics
Automotive Process


Technical Characteristics

Compatible Fluids	Compressed air 7822: all compatible fluids depending on whether FKM or PTFE seals are used
Working Pressure	7810-7812: 1 to 10 bar 7820: 1 to 16 bar 7822: 1 to 40 bar
Working Temperature	7810 – 7812: 0°C to +70°C 7820 – 7822: -15° to +120°C

Component Materials



External Components




Regulations


DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)
RG: External Components: 21CFR (FDA)
RG: External Components: 1935/2004/EC

Operation

Exhaust Model with External Adjustment



Bi-Directional Model with External Adjustment




Stainless Steel Flow Control Regulators

7810 Flow Regulator Exhaust, Male/Female BSPP and Metric Thread



Stainless steel 316L, FKM




C		E	E1	F	H min	H max	J	L	kg
M5x0.8	7810 19 19	4	4	8	22	26	9	11	0.011
G1/8	7810 10 10	6	8	13	32	38	15	17	0.039
G1/4	7810 13 13	9	12	17	35	40	18	24	0.072
G3/8	7810 17 17	8	12	20	43	53	22	27	0.125
G1/2	7810 21 21	9	15	23	60	71	28	31	0.261

7812 Bi-Directional Flow Regulator, Male/Female BSPP and Metric Thread



Stainless steel 316L, FKM




C		E	E1	F	H min	H max	J	L	kg
M5x0.8	7812 19 19	4	4	8	22	26	9	11	0.290
G1/8	7812 10 10	6	8	13	32	38	15	17	0.040
G1/4	7812 13 13	9	12	17	35	40	18	24	0.074
G3/8	7812 17 17	8	12	20	43	53	22	24	0.125
G1/2	7812 21 21	9	15	23	60	71	28	31	0.261

7820 In-Line One-Way Flow Regulator, Female BSPP Thread



Stainless steel 316L, FKM




C	DN		H min	H max	H1	K	L	L1	N	ØT	kg
G1/8	7	7820 00 10	47	52.5	30	20	40	20	30	20	0.175
G1/4	7	7820 00 13	47	52.5	30	20	40	20	30	20	0.164
G3/8	9	7820 00 17	56	65	35	25	50	25	36	25	0.298
G1/2	12	7820 00 21	76	87	40	30	60	30	42	30	0.261

7822 Bi-Directional In-Line Flow Regulator, Female BSPP Thread



Stainless steel 316L, FKM



C	DN		H min	H max	H1	K	L	L1	N	ØT	kg
G1/8	7	7822 00 10	48	52.5	30	20	40	20	30	20	0.176
G1/4	7	7822 00 13	48	52.5	30	20	40	20	30	20	0.165
G3/8	9	7822 00 17	58	65	35	25	50	25	36	20	0.296
G1/2	12	7822 00 21	76	87	40	30	60	30	42	30	0.270

You will also find our range of stainless steel push-in fittings, compression fittings, valves and accessories in this catalogue.


Flow Characteristics (at 6 bar)

for Flow Control Regulators




7010
7011
7012

7010



7011



7012

Flow characteristics for model 7012:

- exhaust version (see model 7010, direction of adjustment)
- supply version (see model 7011, direction of adjustment)

6 bar

█ Direction of adjustment

█ Return

F: Flow in Nl/min

N: Number of turns


Flow Characteristics (at 6 bar)

for Flow Control Regulators




7060
7061
7062

7060



7061



7062

Flow characteristics for model 7062:

- exhaust version (see model 7060, direction of adjustment)
- supply version (see model 7061, direction of adjustment)


Flow Characteristics (at 6 bar)

for Flow Control Regulators




7660
7669
7662

7660



7669



7662

Flow characteristics for model 7662:

- exhaust version: see model 7660, direction of adjustment
- supply version: see model 7669, direction of adjustment

6 bar

 Direction of adjustment
 Return

F: Flow in Nl/min

N: Number of turns


Flow Characteristics (at 6 bar)

for Flow Control Regulators




7640
7649


7640




7649



7771



7020




Flow Characteristics (at 6 bar)


for Flow Control Regulators




7770




7776



7030
7031



7630
7631



6 bar

— Direction of adjustment
— Return

F: Flow in l/min

N: Number of turns


Flow Characteristics (at 6 bar)

for Flow Control Regulators




7065
7066
7067

7065



7066



7067


Flow characteristics for model 7067:

- exhaust version: see model 7065, direction of adjustment
- supply version: see model 7066, direction of adjustment




7665
7668

7665



7668




Flow Characteristics (at 6 bar)


for Flow Control Regulators



7045



7130



6 bar

 Direction of adjustment
 Return

F: Flow in Nl/min


N: Number of turns

Flow Characteristics (at 6 bar)


for Flow Control Regulators




7140



7160



7762




Flow Characteristics (at 6 bar)

for Flow Control Regulators




7100
7101


7100



7101



7680



6 bar

Direction of adjustment
 Return

F: Flow in Nl/min


N: Number of turns

Flow Characteristics (at 6 bar)


for Flow Control Regulators




7180




**7110
7111**



7111



7170



Function Fittings Range

Blocking Fittings

7880
BSPP
Page 4-37

7881
BSPP
Page 4-37

7885
BSPT
Page 4-37

7886
BSPT
Page 4-37

7883
BSPP
Page 4-37



Piloted Non-Return Valves

7892
BSPP
Page 4-39

7894
BSPP
Page 4-39



Non-Return Valves

7996
Page 4-41

7984
7994
BSPP/Metric
Page 4-41

7985
7995
BSPT
Page 4-41



Adjustable Non-Return Valves

7930
BSPP/Metric
Page 4-43

7931
BSPP
Page 4-43

7932
BSPP
Page 4-43



LIQUIfit® Non-Return Valves

7992
Page 4-45



Stainless Steel Non-Return Valves

4890
BSPP
Page 4-47

4891
BSPP
Page 4-47

4892
BSPP
Page 4-47

4895
NPT
Page 4-47



Soft Start Fittings

7860
BSPP
Page 4-49

7870
BSPP
Page 4-49

7861
BSPP
Page 4-49

7871
BSPP
Page 4-49



Pneumatic Sensor Fittings

7818
BSPP/Metric
Page 4-51

7828
BSPP/Metric
Page 4-51



Pressure Regulator Fittings

7300
BSPP
Page 4-53



Pressure Reducer Fittings

7318
BSPP
Page 4-55

7471
BSPP
Page 4-55

7316
Page 4-55

7416
BSPP
Page 4-55

7000
Page 4-55

7000
Page 4-55



Snap Fittings

7926
Page 4-57

7921
BSPP
Page 4-57

7960
Page 4-57

7961
BSPP
Page 4-57



Manually-Operated Valves

7800
7801
BSPP/Metric
Page 4-59

7802
BSPP
Page 4-59

0669
BSPP/Metric
Page 4-59



Function Fittings Range

Metal Quick Exhaust Valves

- 7970**
BSPP/Metric
Page 4-61
- 7971**
BSPP/BSPT
Page 4-61
- 7899**
BSPP
Page 4-61



Silencers

- 0674**
BSPP/Metric
Page 4-63
- 0676**
BSPP/Metric
Page 4-63
- 0670**
BSPP
Page 4-63
- 0673**
BSPP/Metric
Page 4-63
- 0675**
BSPP/Metric
Page 4-63
- 0671**
Page 4-64
- 0677**
BSPP
Page 4-64
- 0672**
BSPP
Page 4-64
- 0682**
BSPP
Page 4-64
- 0683**
NPT
Page 4-64



Blocking Fittings

Blocking fittings, mounted in pairs on a cylinder, lock the piston by simultaneously **cutting off the supply and exhaust** when the pilot signal is removed.

Product Advantages

Optimum Performance

Optimum flow: no effect on the performance of the cylinder
Compact size
Fully orientable for excellent flexibility in circuit installation
100% leak-tested in production
Date coding to guarantee quality and traceability

Robust

Suitable for the most demanding environments
Excellent corrosion and spark resistance to salt spray and sparks (threaded models)
Proven push-in technology




Applications
Robotics
Machine Tools
Textile
Packaging
Pneumatics
Automotive Process

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	1 to 10 bar
Working Temperature	-20°C to +70°C

Connection	Supply Flow 6 bar	Pilot and depilot threshold depending on supply pressure					
			2 bar	4 bar	6 bar	8 bar	10 bar
ØD 6 and 8 mm, threads G1/8, G1/4, R1/8, R1/4	650NI/min	Pilot Pressure	2.40	2.90	3.30	3.60	4.00
	650NI/min	Depilot Pressure	1.50	1.80	2.15	2.40	2.80
ØD 10 and 12 mm, threads G3/8, G1/2, R3/8, R1/2	1600NI/min	Pilot Pressure	2.70	3.20	3.50	3.80	4.10
	1600NI/min	Depilot Pressure	1.40	1.80	2.10	2.40	2.70

Component Materials




Silicone-free

Regulations


DI: 2002/95/EC (RoHS)
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)

Operation


Cylinder in Operation (pilot signal active)




Pilot signal authorises movement



Cylinder Blocked (pilot signal removed)




No signal blocks movement



Installation

Mounted in pairs, blocking fittings are installed directly on the cylinder. Being fully orientable, they offer excellent flexibility in the design and installation of pneumatic circuits.




Blocking Fittings

7880

Blocking Fitting, Male BSPP Thread



Nickel-plated brass, NBR




ØD	C		E	F	G	H	H1	H2	J	L	kg
6	G1/8	7880 06 10	5.5	21	24	53	24.5	21	17	28	0.126
	G1/4	7880 06 13	6.5	21	24	53	24.5	21	17	28	0.128
8	G1/4	7880 08 13	6.5	21	24	53	24.5	21	17	28	0.122
	G3/8	7880 08 17	7.5	21	24	53	24.5	21	17	28	0.127
10	G3/8	7880 10 17	7.5	24	28	58	25	25	27	35	0.209
12	G1/2	7880 12 21	9	24	28	58	25	25	27	37.5	0.222

7885

Blocking Fitting, Male BSPT Thread



Nickel-plated brass, NBR




ØD	C		F	G	H	H1	H2	J	L	kg
6	R1/8	7885 06 10	21	24	51.5	25	20	17	28	0.127
	R1/4	7885 06 13	21	24	51.5	25	20	17	28	0.131
8	R1/4	7885 08 13	21	24	51.5	25	20	17	28	0.126
	R3/8	7885 08 17	21	24	51.5	25	20	17	28	0.130
10	R3/8	7885 10 17	24	28	57	25	24	27	35	0.222
	R1/2	7885 12 21	24	28	57	25	24	27	37.5	0.229

7881

Blocking Fitting, Male/Female BSPP Thread



Nickel-plated brass, NBR




C1	C2		E	F	G	H	H1	H2	J	L	kg
G1/8	G1/4	7881 13 10	5.5	21	24	53	24.5	21	17	25.5	0.118
G1/4	G1/4	7881 13 13	6.5	21	24	53	24.5	21	17	25.5	0.119
G3/8	G3/8	7881 17 17	7.5	24	28	58	25	25	27	34	0.211
G1/2	G1/2	7881 21 21	9	24	28	58	25	25	27	40	0.226

7886

Blocking Fitting, Male/Female BSPT Thread



Nickel-plated brass, NBR




C1	C2		F	G	H	H1	H2	J	L	kg
R1/8	R1/4	7886 13 10	21	24	51.5	25	20	17	26.5	0.121
R1/4	R1/4	7886 13 13	21	24	51.5	25	20	17	26.5	0.126
R3/8	R3/8	7886 17 17	24	28	57	25	24	27	34	0.225
R1/2	R1/2	7886 21 21	24	28	57	25	24	27	40	0.240

7883

Blocker/Flow Regulator, Male BSPP Thread



Nickel-plated brass, technical polymer, NBR



ØD	C		G	H	H1	L	L _{max}	L1	kg
4	G1/8	7883 04 10	21.5	53	21	46.5	52	12	0.166
	G1/4	7883 06 10	21.5	53	21	46.5	52	12	0.163
6	G1/4	7883 06 13	21.5	53	21	46.5	52	12	0.166
	G3/8	7883 08 13	27	57.5	24.5	54	60	14	0.251
8	G3/8	7883 08 17	27	57.5	24.5	54	60	14	0.254

Combination of blocking and flow regulation functions
Working temperature: 0 to +70°C

Piloted Non-Return Valves

Piloted non-return valves are designed to **protect installations**: if the compressed air supply is removed, they lock the air supply to the cylinder, thus maintaining it in position.

Product Advantages

System Protection

Protection of your system
Control of inlet and outlet flow: cylinder operation optimised
Vent saves time on restart after maintenance operations (model 7894)

3 Functions in 1 Product

A multi-purpose fitting:

- piloted non-return valve
- flow control regulator
- manual exhaust

 All-in-one product: integrated fittings for the control and supply

Flexible Operation

Orientable and adjustable through 3 axes
Can be integrated into any installation configuration
Push-in connection for quicker and more reliable installation
Mounted in pairs directly on the cylinder



Applications

- Pneumatics
- Assembly
- Robotics
- Machine Tools
- Packaging
- Handling
- Automotive Process


Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	1 to 10 bar
Working Temperature	-5°C to +60°C
Cracking Pressure	0.3 bar

Regulations

DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)


Component Materials



Silicone-free


Operation

Normal Operation




Pilot signal (P)
Regulation of cylinder rod speed (R)

Emergency Stop or Pressure Drop



Drop/removal of pilot pressure (P) = cylinder rod locked

Venting Operation









Venting (V) returns the cylinder rod to the start position, emptying the pressure chamber through the flow regulator (R) and pilot line (P)

Piloted Non-Return Valves







7892

Piloted Non-Return Valve, Male BSPP Thread

<div data-bbox="97 232 137 306">  </div> <div data-bbox="137 232 344 539">  </div>	<div data-bbox="351 232 592 275"> <p>Technical polymer, nickel-plated brass, NBR</p> </div> <div data-bbox="351 275 592 539">  </div>	<table> <tr> <th>ØD</th><th>C</th><th></th><th>E</th><th>F</th><th>G</th><th>H</th><th>H1</th><th>H2</th><th>L</th><th>kg</th></tr> <tr> <td rowspan="2">6</td><td>G1/8</td><td>7892 06 10</td><td>6</td><td>13</td><td>14</td><td>42</td><td>30</td><td>7</td><td>21</td><td>0.020</td></tr> <tr> <td>G1/4</td><td>7892 06 13</td><td>9</td><td>17</td><td>18.5</td><td>45</td><td>32</td><td>9</td><td>23</td><td>0.042</td></tr> <tr> <td rowspan="2">8</td><td>G1/8</td><td>7892 08 10</td><td>6</td><td>13</td><td>14</td><td>42</td><td>29</td><td>9</td><td>25</td><td>0.020</td></tr> <tr> <td>G1/4</td><td>7892 08 13</td><td>9</td><td>17</td><td>18.5</td><td>45</td><td>32</td><td>9</td><td>27</td><td>0.042</td></tr> <tr> <td rowspan="2">10</td><td>G3/8</td><td>7892 08 17</td><td>6</td><td>20</td><td>22.5</td><td>57</td><td>41</td><td>11</td><td>28</td><td>0.093</td></tr> <tr> <td>G3/8</td><td>7892 10 17</td><td>6</td><td>20</td><td>22.5</td><td>57</td><td>41</td><td>11</td><td>31</td><td>0.144</td></tr> <tr> <td rowspan="2">12</td><td>G1/2</td><td>7892 10 21</td><td>10</td><td>24</td><td>28</td><td>63</td><td>47</td><td>16</td><td>36</td><td>0.109</td></tr> <tr> <td>G1/2</td><td>7892 12 21</td><td>10</td><td>24</td><td>28</td><td>63</td><td>47</td><td>16</td><td>36</td><td>0.150</td></tr> </table>	ØD	C		E	F	G	H	H1	H2	L	kg	6	G1/8	7892 06 10	6	13	14	42	30	7	21	0.020	G1/4	7892 06 13	9	17	18.5	45	32	9	23	0.042	8	G1/8	7892 08 10	6	13	14	42	29	9	25	0.020	G1/4	7892 08 13	9	17	18.5	45	32	9	27	0.042	10	G3/8	7892 08 17	6	20	22.5	57	41	11	28	0.093	G3/8	7892 10 17	6	20	22.5	57	41	11	31	0.144	12	G1/2	7892 10 21	10	24	28	63	47	16	36	0.109	G1/2	7892 12 21	10	24	28	63	47	16	36	0.150
ØD	C		E	F	G	H	H1	H2	L	kg																																																																																							
6	G1/8	7892 06 10	6	13	14	42	30	7	21	0.020																																																																																							
	G1/4	7892 06 13	9	17	18.5	45	32	9	23	0.042																																																																																							
8	G1/8	7892 08 10	6	13	14	42	29	9	25	0.020																																																																																							
	G1/4	7892 08 13	9	17	18.5	45	32	9	27	0.042																																																																																							
10	G3/8	7892 08 17	6	20	22.5	57	41	11	28	0.093																																																																																							
	G3/8	7892 10 17	6	20	22.5	57	41	11	31	0.144																																																																																							
12	G1/2	7892 10 21	10	24	28	63	47	16	36	0.109																																																																																							
	G1/2	7892 12 21	10	24	28	63	47	16	36	0.150																																																																																							


7894

Piloted Non-Return Valve with Flow Regulator and Exhaust, Male BSPP Thread


<div>   </div>	<div> <div> Technical polymer, nickel-plated brass, NBR </div> <div>  </div> </div>	<table> <tr> <th>ØD</th><th>C</th><th></th><th>E</th><th>F1</th><th>F2</th><th>G</th><th>H</th><th>H1</th><th>H2</th><th>H3</th><th>L</th><th>L_{max}</th><th>L1</th><th>kg</th></tr> <tr> <td rowspan="2">6</td><td>G1/8</td><td>7894 06 10</td><td>6</td><td>13</td><td>8</td><td>14</td><td>46</td><td>7</td><td>24</td><td>31</td><td>48.5</td><td>51</td><td>16</td><td>0.041</td></tr> <tr> <td>G1/4</td><td>7894 06 13</td><td>9</td><td>17</td><td>10</td><td>18.5</td><td>49</td><td>11</td><td>18</td><td>31</td><td>59.5</td><td>65</td><td>17</td><td>0.067</td></tr> <tr> <td rowspan="3">8</td><td>G1/8</td><td>7894 08 10</td><td>6</td><td>13</td><td>8</td><td>14</td><td>46</td><td>7</td><td>27</td><td>31</td><td>48.5</td><td>51</td><td>22</td><td>0.051</td></tr> <tr> <td>G1/4</td><td>7894 08 13</td><td>9</td><td>17</td><td>10</td><td>18.5</td><td>49</td><td>11</td><td>23</td><td>31</td><td>59.5</td><td>65</td><td>23</td><td>0.068</td></tr> <tr> <td>G3/8</td><td>7894 08 17</td><td>7</td><td>20</td><td>14</td><td>22.5</td><td>69</td><td>13</td><td>21</td><td>40</td><td>67.5</td><td>73</td><td>23</td><td>0.060</td></tr> <tr> <td rowspan="2">10</td><td>G3/8</td><td>7894 10 17</td><td>7</td><td>20</td><td>14</td><td>22.5</td><td>69</td><td>13</td><td>29</td><td>40</td><td>67.5</td><td>73</td><td>26</td><td>0.061</td></tr> <tr> <td>G1/2</td><td>7894 10 21</td><td>9</td><td>24</td><td>17</td><td>28</td><td>76</td><td>12.5</td><td>26</td><td>47</td><td>74</td><td>81</td><td>26</td><td>0.234</td></tr> <tr> <td>12</td><td>G1/2</td><td>7894 12 21</td><td>9</td><td>24</td><td>17</td><td>28</td><td>76</td><td>12.5</td><td>27</td><td>47</td><td>74</td><td>81</td><td>30</td><td>0.237</td></tr> </table>	ØD	C		E	F1	F2	G	H	H1	H2	H3	L	L _{max}	L1	kg	6	G1/8	7894 06 10	6	13	8	14	46	7	24	31	48.5	51	16	0.041	G1/4	7894 06 13	9	17	10	18.5	49	11	18	31	59.5	65	17	0.067	8	G1/8	7894 08 10	6	13	8	14	46	7	27	31	48.5	51	22	0.051	G1/4	7894 08 13	9	17	10	18.5	49	11	23	31	59.5	65	23	0.068	G3/8	7894 08 17	7	20	14	22.5	69	13	21	40	67.5	73	23	0.060	10	G3/8	7894 10 17	7	20	14	22.5	69	13	29	40	67.5	73	26	0.061	G1/2	7894 10 21	9	24	17	28	76	12.5	26	47	74	81	26	0.234	12	G1/2	7894 12 21	9	24	17	28	76	12.5	27	47	74	81	30	0.237
ØD	C		E	F1	F2	G	H	H1	H2	H3	L	L _{max}	L1	kg																																																																																																																							
6	G1/8	7894 06 10	6	13	8	14	46	7	24	31	48.5	51	16	0.041																																																																																																																							
	G1/4	7894 06 13	9	17	10	18.5	49	11	18	31	59.5	65	17	0.067																																																																																																																							
8	G1/8	7894 08 10	6	13	8	14	46	7	27	31	48.5	51	22	0.051																																																																																																																							
	G1/4	7894 08 13	9	17	10	18.5	49	11	23	31	59.5	65	23	0.068																																																																																																																							
	G3/8	7894 08 17	7	20	14	22.5	69	13	21	40	67.5	73	23	0.060																																																																																																																							
10	G3/8	7894 10 17	7	20	14	22.5	69	13	29	40	67.5	73	26	0.061																																																																																																																							
	G1/2	7894 10 21	9	24	17	28	76	12.5	26	47	74	81	26	0.234																																																																																																																							
12	G1/2	7894 12 21	9	24	17	28	76	12.5	27	47	74	81	30	0.237																																																																																																																							


3104

Unequal Tee



Technical polymer, NBR



ØD	ØD1		G	H	L/2	kg
6	4	3104 06 04	10.5	22.5	17.5	0.005
8	4	3104 08 04	13.5	29	22.5	0.014
10	4	3104 10 04	16	33	26	0.027
12	4	3104 12 04	19	39	31	0.034

Model	Pilot and depilot threshold					
		2 bar	4 bar	6 bar	8 bar	10 bar
G1/8	Pilot Pressure	1.2	1.72	2.44	2.96	3.56
	Depilot Pressure	0.56	0.96	1.12	1.76	2.12
G1/4	Pilot Pressure	0.92	1.52	2.12	2.68	3.28
	Depilot Pressure	0.64	1.16	1.68	2.16	2.64
G3/8	Pilot Pressure	1.12	1.84	2.56	3.32	4.08
	Depilot Pressure	0.64	1.04	1.44	1.84	2.36
G1/2	Pilot Pressure	1.04	1.60	2.12	2.76	3.88
	Depilot Pressure	0.76	1.28	1.76	2.20	2.72

Maximum Flow at 6 bar (NI/min)	7894 06 10	7894 06 13	7894 08 10	7894 08 13	7894 08 17	7894 10 17	7894 10 21	7894 12 21
Direction of Adjustment	250	475	240	585	875	940	1535	1560
Return	365	620	355	815	1085	1205	1860	1940

Non-Return Valves

Non-return valves allow compressed air to flow in one direction and prevent it from flowing in the other. Fitted upstream of the circuit to be protected, they provide **total protection**.

Product Advantages

Variety of Applications

Wide range
Push-in connection: ease of use
Available in threaded or push-in version

Powerful Design

Lip seals for improved sealing performance
Excellent vibration resistance
Compact
Lightweight
Symbol showing the operating direction of flow
Safe installation with colour codes:
• green push-button: supply version
• red push-button: exhaust version




Automotive Process
Robotics
Vacuum
Textile
Semi-Conductors
Packaging
Pneumatics

Applications

Technical Characteristics

Compatible Fluids	Compressed air	
Working Pressure	1 to 10 bar	
Working Temperature	0°C to +70°C	
Cracking Pressure	0.3 bar	
Flow Characteristics (NI/min)	Model	Flow at 6 bar
	4 mm	350
	6 mm	670
	8 mm	1080
	10 mm	2230
	12 mm	2300

Component Materials




Silicone-free

Regulations


DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)

Operation


In-Line Version




Supply Version



Exhaust Version



Installation Diagram




Non-Return Valves

7996

In-Line Equal Non-Return Valve



Technical polymer, nickel-plated brass, NBR




ØD		G	L	kg
4	7996 04 00	16	38.5	0.008
6	7996 06 00	16	41	0.013
8	7996 08 00	19	51.5	0.017
10	7996 10 00	23	63.5	0.070
12	7996 12 00	23	66.5	0.050

7984

In-Line Non-Return Valve, Supply, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		E	F	H	kg
4	M5x0.8	7984 04 19	3	9	32	0.008
	G1/8	7984 04 10	5	16	28.5	0.015
6	G1/8	7984 06 10	5	16	30.5	0.015
	G1/4	7984 06 13	5.5	16	30.5	0.015
8	G1/8	7984 08 10	5	19	36	0.021
	G1/4	7984 08 13	5.5	19	36	0.023
10	G3/8	7984 10 17	5.5	23	42	0.047
12	G3/8	7984 12 17	5.5	23	42	0.010
	G1/2	7984 12 21	7.5	23	44	0.041

7994

In-Line Non-Return Valve, Exhaust, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		E	F	H	kg
4	M5x0.8	7994 04 19	3	9	32	0.790
	G1/8	7994 04 10	5	16	28.5	0.018
6	G1/8	7994 06 10	5	16	30.5	0.015
	G1/4	7994 06 13	5.5	16	30.5	0.015
8	G1/8	7994 08 10	5	19	36	0.023
	G1/4	7994 08 13	5.5	19	36	0.023
10	G3/8	7994 10 17	5.5	23	42	0.050
12	G3/8	7994 12 17	5.5	23	42	0.043
	G1/2	7994 12 21	7.5	23	44	0.045

7985

In-Line Non-Return Valve, Supply, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	H	kg
4	R1/8	7985 04 10	16	28.5	0.016
	R1/8	7985 06 10	16	30.5	0.016
6	R1/4	7985 06 13	16	30.5	0.021
	R1/8	7985 08 10	19	36	0.022
8	R1/4	7985 08 13	19	36	0.020
	R3/8	7985 10 17	23	42	0.049
10	R3/8	7985 12 17	23	42	0.042
	R1/2	7985 12 21	23	44	0.048


Pre-coated thread

7995

In-Line Non-Return Valve, Exhaust, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	H	kg
4	R1/8	7995 04 10	16	28.5	0.015
	R1/8	7995 06 10	16	30.5	0.016
6	R1/4	7995 06 13	16	30.5	0.022
	R1/8	7995 08 10	19	36	0.022
8	R1/4	7995 08 13	19	36	0.026
	R3/8	7995 10 17	23	42	0.048
10	R3/8	7995 12 17	23	42	0.042
	R1/2	7995 12 21	23	44	0.048

Pre-coated thread

Nickel-Plated Brass Adjustable Non-Return Valves

These nickel-plated brass adjustable non-return valves, suitable for **harsh environments**, allow compressed air to flow in one direction and prevent flow in the other. This product incorporates **precise adjustment** of opening pressure for greater flexibility.

Product Advantages

Robust	Excellent resistance to abrasion and corrosion Developed for the food process industry
Optimised Inventory Management	A single valve for multiple opening pressure settings Limits the number of versions Flexibility of use
Protection & Safety	Maintains downstream pressure if upstream pressure drops Designed with locking nut to protect initial setting in the event of: <ul style="list-style-type: none"> • vibration • intensive use • accidental handling Adjustment and locking of the non-return valve cracking pressure with two different Allen keys prevents the settings from being accidentally changed Smooth external profile to facilitate cleaning in situ Maximum constant flow guaranteed whatever the setting of the cracking pressure




Applications

- Printing
- Machine Tools
- Food Process
- Petrochemical
- Textile
- Automotive Process
- Chemical

Technical Characteristics

Compatible Fluids	Compressed air					
Working Pressure	0 to 12 bar					
Working Temperature	-20°C to +80°C					
Cracking Pressure	Threads	0 to 4 turns (values given as an example only)				
	M5x0.8 - G1/8 - G1/4	1 to 0.10 bar				
	G3/8	1 to 0.15 bar				
	G1/2	1 to 0.20 bar				
Max. Tightening Torques	Threads	M5x0.8	G1/8	G1/4	G3/8	G1/2
	daN.m	0.16	0.8	1.2	3	3.5

Component Materials




Silicone-free

Regulations

DI: 2002/95/EC (RoHS)
RG: External Components: 21CFR (FDA)
(seal: § 177.2600, nickel: §184.1537, grease: NSF H1)
RG: 1935/2004 (external surface flow ≥ 0.02 litre per hour)
DI: 2006/42/EC (external surface $R_a < 0.8 \mu\text{m}$)
RG: 1907/2006 (REACH)


Operation

Step 1




Unscrew the locking nut with an Allen key.

Step 2



Unscrew the adjustment nut with a smaller Allen key to adjust the cracking pressure. The number of turns adjusts the cracking pressure from 1 bar to 0.10 bar.

Step 3



Tighten the locking nut with the Allen key to lock the cracking pressure setting. Then, control the pressure with a pressure gauge downstream.


Nickel-Plated Brass Adjustable Non-Return Valves

7930

Adjustable Check Valve, Double Female BSPP and Metric Thread



FDA chemical nickel-plated brass,
FKM




C		E	E1	F	F1	F2	L	kg
M5x0.8	7930 19 19	8	4	13	4	6	49	0.055
G1/8	7930 10 10	8	6	13	4	6	45	0.033
G1/4	7930 13 13	10	7.5	16	6	8	54	0.073
G3/8	7930 17 17	11	8.5	20	8	10	61.5	0.163
G1/2	7930 21 21	13	10	24	10	12	73	0.171

7931

Adjustable Check Valve Supply, Male/Female BSPP Thread



FDA chemical nickel-plated brass,
FKM




C		E	E1	F	F1	F2	L	kg
G1/8	7931 10 10	5.5	6	13	4	6	51.5	0.043
G1/4	7931 13 13	6.5	7.5	16	6	8	61.5	0.208
G3/8	7931 17 17	7.5	8.5	20	8	10	70	0.125
G1/2	7931 21 21	9	10	24	10	12	82.5	0.212

7932

Adjustable Check Valve Exhaust, Male/Female BSPP Thread



FDA chemical nickel-plated brass,
FKM



C		E	E1	F	F1	F2	L	kg
G1/8	7932 10 10	5.5	8	13	4	6	51.5	0.009
G1/4	7932 13 13	6.5	10	16	6	8	61.5	0.058
G3/8	7932 17 17	7.5	11	20	8	10	70	0.123
G1/2	7932 21 21	9	13	24	10	12	82.5	0.212

LIQUIfit® Non-Return Valves

LIQUIfit® non-return valves meet the requirements for conveying **beverages**. They allow flow in one direction and prevent any return flow. Fitted in the circuit, they provide **total protection**.

Product Advantages

Suitable for Beverage Applications

- Fully compatible for use with water, beverages and liquid food-stuffs (liquids and gas)
- Very low cracking threshold
- Excellent chemical compatibility
- Resistant to cleaning products
- Hygienic design with smooth surfaces
- Fluid direction indicated
- EPDM sealing technology




Water Softeners
Water Treatment
Water Purification
Drinks Dispensers
Hot & Cold Water Systems

Applications

Technical Characteristics

Compatible Fluids	Water, beverages, liquid foodstuffs
Working Pressure	1 to 10 bar
Working Temperature	0°C to +65°C
Cracking Pressure	< 0.05 bar

Component Materials








Silicone-free

Regulations

DI: 2002/95/EC (RoHS), 2011/65/EC
FDA: 21 CFR 177.1550
NSF 51 (referenced material)
NSF 61
RG: 1907/2006 (REACH)

7992 Single Non-Return Valve

  	Acetal, EPDM 	ØD		G	L	kg
		1/4	7992 56 00WP2	17	51	0.008
		3/8	7992 60 00WP2	20	55	0.011

Associated Products

- The full range of LIQUIfit® products can be found in this catalogue:
- Push-in fittings for metric and inch tubing (Chapter 1)
 - Valves (Chapter 6)

To complement the LIQUIfit® range, Parker Legris Advanced PE tubing (Chapter 3) is suited to the most demanding environments, approved for permanent contact with beverage and food products, as well as for water treatment.

Stainless Steel Non-Return Valves

Stainless steel non-return valves are ideally suited to **harsh environments** and for conveying **many industrial fluids**. These products allow fluids to flow in one direction and prevent them from flowing in the other.

Product Advantages

Demanding Environments	Robust design
	Suitable for use with many chemicals or in corrosive environments
	Compatible with many fluids
Compact & Versatile	Reduced dimensions
	Smooth external surfaces contribute to equipment cleanliness
	Flow direction symbol protects against incorrect installation
	Hexagonal body to facilitate installation




- Applications
- Pneumatics
 - Machine Tools
 - Food Process
 - Printing
 - Chemical
 - Textile
 - Automotive Process

Technical Characteristics

Compatible Fluids	Many fluids		
Working Pressure	0.5 to 40 bar		
Working Temperature	-20°C to +180°C		
Flow Characteristics	Threads	NI/min	Kv
	G1/8	18.88	1.60
	G1/4	19.91	1.69
	G3/8	35.54	3.01
	G1/2	36.50	3.10
	G3/4	65.86	5.59
	G1	92.60	7.86
Cracking Pressure	0.25 bar		

Component Materials



Silicone-free

Regulations

- DI: 2002/95/EC (RoHS)
- RG: 1907/2006 (REACH)
- DI: 97/23/EC (PED)


Stainless Steel Non-Return Valves

4890

Non-Return Valve, Female BSPP Thread



Stainless steel 316L, FKM




C	DN		F	G	L	kg
G1/8	10	4890 10 10	17	22	50	0.083
G1/4	10	4890 13 13	17	22	50	0.074
G3/8	15	4890 17 17	22	30	67	0.183
G1/2	15	4890 21 21	24	30	71	0.209
G3/4	20	4890 27 27	32	42	84	0.289
G1	25	4890 34 34	38	42	90	0.519

4891

Non-Return Valve, Supply, Male BSPP Thread/Exhaust, Female BSPP Thread



Stainless steel 316L, FKM




C	DN		F	G	L	kg
G1/8	10	4891 10 10	17	22	56	0.100
G1/4	10	4891 13 13	17	22	58	0.082
G3/8	15	4891 17 17	22	30	75	0.189
G1/2	15	4891 21 21	24	30	79	0.209
G3/4	20	4891 27 27	32	42	84	0.300
G1	25	4891 34 34	38	42	102	0.519

4892

Non-Return Valve, Supply, Female BSPP Thread/Exhaust, Male BSPP Thread



Stainless steel 316L, FKM




C	DN		F	G	L	kg
G1/8	10	4892 10 10	17	22	56	0.100
G1/4	10	4892 13 13	17	22	58	0.082
G3/8	15	4892 17 17	22	30	75	0.191
G1/2	15	4892 21 21	24	30	79	0.209
G3/4	20	4892 27 27	32	42	84	0.300
G1	25	4892 34 34	38	42	102	0.519

4895

Non-Return Valve, Female NPT Thread



Stainless steel 316L, FKM



C	DN		F	G	L	kg
NPT1/8	10	4895 11 11	17	22	50	0.083
NPT1/4	10	4895 14 14	17	22	54	0.079
NPT3/8	15	4895 18 18	22	30	67	0.197
NPT1/2	15	4895 22 22	24	30	77	0.194

Soft Start Fittings

These fittings protect your system by preventing sudden shocks. On start-up, they control the **pressure increase** in the downstream circuit; this helps **prevent the risk** of industrial accidents.

Product Advantages

Protection of Equipment & Personnel

- Prevents the risk of damage after any stoppage which requires the system to be vented
- Returns the control valve to its initial position in total safety
- Adjustment of the pressurisation speed
- Protects the adjustment mechanism using a recessed adjustment screw

Mounted on FRL

- Models 7860 and 7861: yellow identification washer
- Protection for the whole system
- Simultaneous pressurisation speed of the whole system

Mounted on Control Valve

- Models 7870 and 7871: black identification washer
- Protection of individual circuits
- Mounted on the control valve, it optimises the pressurisation speed of a specific cylinder



Applications

- Pneumatic Systems
- Robotics
- Textile
- Semi-Conductors
- Packaging
- Pneumatics

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	3 to 10 bar
Working Temperature	-15°C to +60°C

Max. Tightening Torques	Threads		daN.m
	G1/4		1.3
	G3/8		1.5
	G1/2		1.8
Flow Characteristics	Model	Flow at 6 bar	Kv
	7860 08 13	1500 NI/min	0.80
	7860 10 13	2100 NI/min	1.20
	7860 10 17	2200 NI/min	1.30
	7860 12 17	3100 NI/min	1.00
	7860 12 21	3100 NI/min	1.00
	7861 13 13	2100 NI/min	1.20
	7861 17 17	3100 NI/min	1.00
	7861 21 21	3100 NI/min	1.00
	7870 08 13	1500 NI/min	0.80
	7870 10 13	2000 NI/min	1.15
	7870 10 17	2000 NI/min	1.15
	7871 13 13	2000 NI/min	1.15
	7871 17 17	2000 NI/min	1.15


Component Materials

Internal seal: NBR

Adjustment screw:
nickel-plated brass

Washer:
technical polymer

Body:
technical polymer
or nickel-plated brass




Silicone-free

Regulations


DI: 2002/95/CE (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/CE (PED)

Operation

Filter, Regulator, Lubricator




Control Valve




Soft Start Fittings

7860

Soft Start Fitting for Isolating Valve, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	H _{min}	H _{max}	J	L	L1	kg
8	G1/4	7860 08 13	17	54	61	20	35	10	0.064
10	G1/4	7860 10 13	22	55	62	25	41	12.5	0.112
	G3/8	7860 10 17	22	55	62	25	41	12.5	0.115
12	G3/8	7860 12 17	22	55	62	25	45	12.5	0.125
	G1/2	7860 12 21	22	63.5	70.5	25	45	12.5	0.152

7861

Soft Start Fitting for Isolating Valve, Male/Female BSPP Thread



Nickel-plated brass, NBR




C		F	H _{min}	H _{max}	J	L	L1	kg
G1/4	7861 13 13	22	54	62	24	31	12	0.147
G3/8	7861 17 17	22	55	62	24	31	12	0.139

7870

Soft Start Fitting for Control Valve, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	H _{min}	H _{max}	J	L	L1	kg
8	G1/4	7870 08 13	17	54	61	20	35	10	0.066
10	G1/4	7870 10 13	22	55	62	25	41	12.5	0.114
	G3/8	7870 10 17	22	55	62	25	41	12.5	0.117

7871

Soft Start Fitting for Control Valve, Male/Female BSPP Thread



Nickel-plated brass, NBR



C		F	H _{min}	H _{max}	J	L	L1	kg
G1/4	7871 13 13	22	55	62	24	31	12	0.148
G3/8	7871 17 17	22	55	62	24	31	12	0.141


Adjustment of the Filling Screw

Adjusting the screw to regulate the flow of air optimises the time taken to pressurise depending on the air volume to be refilled and the system requirements.

To adjust:


- immobilise the piston using a spanner
- adjust the screw with an Allen key
 - 1.5 mm key for 8 mm diameter
 - 2.5 mm key for 10 and 12 mm diameter

Max. tightening torque: 0.1 daN.m



Cylinder Pressure Cycle

When the downstream pressure reaches 2/3 of the supply pressure, full flow is automatically established



Pneumatic Sensor Fittings

The sensor detects the pressure drop when a cylinder reaches the end of its stroke. They produce a **pneumatic or electric output signal** when the pressure drop in the exhaust chamber of the cylinder goes below their back pressure threshold.

Product Advantages

Easy-to-Use

Suited to changes of series: no adjustment to position detectors is necessary

With Pneumatic Output

Totally pneumatic installation

2 possible installations:

- Supplied with permanent pressure (P1): produces a pneumatic signal when the back pressure threshold is reached
- Supplied from the control valve-cylinder circuit on the opposite side: no unexpected pneumatic signal (S) can appear during pressurisation due to the actuating pressure which supplies the sensor fitting (P1)

With Electrical Output

Combined electrical and pneumatic installation

Installation with continuous electrical supply only (BU)

Guarantees an electrical signal when the back pressure threshold is reached




Applications
Robotics
Textile
Semi-Conductors
Packaging
Pneumatics

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	3 to 8 bar
Working Temperature	-15°C to +60°C
Back Pressure	0.85 to 1 bar
Switching Time	Model 7818: 3 ms
Open/Closed Contact	Model 7828: 2A / 0-48 V 2A / 250 V 50 Hz

Component Materials



Silicone-free

Regulations

DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)


Operation

Pneumatic Installation Diagram




P': Exhaust back pressure
P: Dynamic pressure
P1: Sensor supply pressure
S: Output signal

Electrical Installation Diagram




Connection via 3 core 0.5 mm² cable, 2 meters long.
Contactor: 5A / 250 V ~ or 5W / 48 V ==

Cylinder in Operation







Cylinder in Final Position





Pneumatic Sensor Fittings

7818 Pneumatic Sensor Fitting, Male BSPP and Metric Thread

	Technical polymer, zamak, brass, NBR										
		ØD	C		F	H	J	L	L1	kg	
			M5x0.8	7818 04 19*		8	16	11	43.5	5.5	0.025
			G1/8	7818 04 10		14	23	16	44.5	8	0.043
		4	G1/4	7818 04 13		17	28	19.5	46.5	10	0.061
			G3/8	7818 04 17		22	29	23.5	49	12	0.083
			G1/2	7818 04 21		27	30	31.5	52.5	16	0.125
		* Bolt zinc passivated steel									

* Bolt zinc passivated steel

7818 Pneumatic Sensor, Male/Female BSPP Thread


	Technical polymer, zamak, brass, NBR				F	H	J	L	L1	kg
	C		G1/8	7818 19 10	14	23	16	40.5	8	0.047
			G1/4	7818 19 13	17	28	19.5	42.5	10	0.065

7828 Pneumatic/Electric Sensor, Male/Female BSPP and Metric Thread

Technical polymer, brass, NBR


C		F	H	H1	J	L	L1	kg
M5x0.8	7828 00 19	8	20	10	11	49	5.5	0.120
G1/8	7828 00 10	6	20	10	16	52	8	0.131
G1/4	7828 00 13	8	20	10	21	54	10.5	0.145
G3/8	7828 00 17	10	22	12	28	57	14	0.182
G1/2	7828 00 21	12	26	14	33	58	16.5	0.206

Cylinder Pressure Cycle



Installation Diagram

Depending on model, S1, S2 and P1 may be pneumatic or electric. See the installation diagrams opposite.



Pressure Regulators

Parker Legris pressure regulators **stabilise at the maximum determined value** the pressure delivered to the pneumatic equipment, whatever the fluctuations of the pressure upstream.

Product Advantages

Ergonomics

- Easy adjustment of the output pressure through the knurled screw
- Lockable adjustment possible
- Output pressure adjustment options marked on the screw

Energy Savings

- Setting of the optimum pressure enables the equipment to function correctly
- Installation in a manifold allows optimum output pressures to be delivered to specific parts of the circuit
- Designed for applications where cylinder force needs to be controlled: marking, sleeving, crimping cylinders etc.



Applications

- Robotics
- Textile
- Semi-Conductors
- Packaging
- Pneumatics

Technical Characteristics

Compatible Fluids	Compressed air		
Working Pressure	Upstream pressure: 1 to 16 bar Downstream pressure: 1 to 8 bar		
Working Temperature	-10°C to +70°C		

Max. Tightening Torques	Threads	G1/8	G1/4	G3/8
	daN.m	0.4	0.5	0.6

Component Materials



Silicone-free


Regulations

DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)

Operation


Mounting Upstream of the Control Valve

Adjustment of the piston feed pressure in both directions




Mounting Downstream of the Control Valve

Phase 1: adjustment of the piston speed in a single direction




Phase 2: in return direction, pressure is supplied through the control valve




Pressure Regulators

7300

Pressure Regulator, Male BSPP Thread




Technical polymer, nickel-plated brass, NBR



ØD	C		E	F1	F2	G1	G2	H max	L1	L2	kg
4	G1/8	7300 04 10	4.5	17	13	14	17	65	7	18.5	0.047
	G1/8	7300 06 10	4.5	17	13	14	17	65	7	20	0.047
6	G1/4	7300 06 13	7.5	17	13	14	17	74.5	9.5	22	0.065
	G1/8	7300 08 10	4.5	17	13	14	17	65	7	25	0.048
8	G1/4	7300 08 13	7.5	17	13	14	17	74.5	9.5	27	0.066
	G3/8	7300 08 17	8.5	22	17	18.5	22	84	11.5	28.5	0.121
10	G1/4	7300 10 13	7.5	17	13	14	17	74.5	9.5	29	0.067
	G3/8	7300 10 17	8.5	22	17	18.5	22	84	11.5	30.5	0.122

Flow Characteristics at 7 bar (Nl/min)



Pressure Reducers

Parker Legris pressure reducers are designed to **set the pressure** of a compressed air circuit to a determined value. They therefore enable **energy saving** by limiting the cylinder pressure.

Product Advantages

Design & Performance

- Optimisation of the pressure at the minimum values required to provide final force and energy consumption
- Manual adjustment protected by a plug
- Visual indication of the differential pressure by colour code

Two Models Available

- Banjo: fitted directly on the control valve or terminal block
- In-line: fitted in the pipework, between the control valve and cylinder



Applications

- Robotics
- Textile
- Semi-Conductors
- Packaging
- Pneumatics

Technical Characteristics

Compatible Fluids	Compressed air				
Working Pressure	1 to 8 bar				
Working Temperature	-15°C to +60°C				
Max. Tightening Torques for Models 7318 and 7471	Threads	G1/8	G1/4	G3/8	G1/2
	daN.m	0.8	1.2	3	3.5

Regulations

DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)

Component Materials


Internal seals: NBR




Silicone-free

Operation

Installation Diagram




Cylinder Pressure Cycle




Manual Adjustment

To ease access to the adjustment, Parker Legris has designed a plug-in manual control system.



To prevent access to the setting mechanism, a sealing plug may be used.



This may be removed if necessary as follows:

1. Pierce the centre
2. Remove the plug




Pressure Reducers

7318

Banjo Pressure Reducer, Male BSPP Thread



Zamak, nickel-plated brass, NBR




ØD	C		F	G	H _{min}	H _{max}	L	L1	kg
6	G1/8	7318 06 10	19	20	49	57	43	10.5	0.137
	G1/4	7318 06 13	19	20	49	57	43	10.5	0.137
8	G1/4	7318 08 13	19	20	49	57	40	10.5	0.134
	G1/4	7318 10 13	27	20	55	64	50	14	0.251
10	G3/8	7318 10 17	27	26	55	94	50	14	0.253

7471

Banjo Pressure Reducer, Male/Female BSPP Thread



Zamak, nickel-plated brass, NBR




C		F	F1	G	H _{min}	H _{max}	L	L1	kg
G1/8	7471 10 10	19	19	20	49	57	45	10.5	0.158
G1/4	7471 13 13	19	19	20	49	57	45	10.5	0.149
G3/8	7471 17 17	24	27	26	55	64	56	14	0.290
G1/2	7471 21 21	30	30	31	75	86	63	16.5	0.502

7316

In-Line Tube-to-Tube Pressure Reducer



Nickel-plated brass, NBR




ØD		F	H _{min}	H _{max}	L	L1	ØT	kg
6	7316 06 00	22	49	57	74	32	18.5	0.212
8	7316 08 00	22	49	57	71	32	18.5	0.200
10	7316 10 00	27	61	70	89	41	22.5	0.412

7416

In-Line Pressure Reducer, Female BSPP Thread



Nickel-plated brass, NBR



C		F	F1	H _{min}	H _{max}	K	L	L1	ØT	kg
G1/8	7416 10 10	17	19	49	57	4	74	35	18.5	0.212
G1/4	7416 13 13	17	19	49	57	4	83	44	18.5	0.214
G3/8	7416 17 17	22	27	61	70	5	90	44	22.5	0.401
G1/2	7416 21 21	27	30	75	86	7	119	61	22.5	0.651

7000

Sealing Plug for Pressure Reducer



Technical polymer




	G	kg
7000 00 01	8	0.001

7000

Manual Ratchet Control for Pressure Reducer



Nickel-plated brass, NBR



	F	G	H	kg
7000 00 00	6	22	15	0.040

Snap Fittings

The snap fittings enable a **circuit to be isolated** without the need to vent the complete system. They are designed to facilitate repeated connections and disconnections in total safety.



Product Advantages

Performance & Safety

- Partial venting of systems while work is carried out
- Energy and time saving during maintenance operations
- Protection of individuals by maintaining pressure if necessary
- Audible click indicates connection
- Circuit identification by coloured rings (on request)

Applications

- Control Panels
- Robotics
- Semi-Conductors
- Packaging
- Pneumatics
- Automotive Process


Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	0 to 10 bar
Working Temperature	-20°C to +80°C
Flow Characteristics at 6 bar	DN 5 mm: 1000 NI/min DN 7 mm: 1900 NI/min

Regulations

DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)


Component Materials




Silicone-free

Operation



Circuit Closed



Circuit Open



Flow Characteristics - Pressure Drop




Snap Fittings

7926

Body with Push-In Connection



Technical polymer, nickel-plated brass, NBR




ØD	DN		G	L	kg
6	5	7926 05 06	18.5	44	0.020
8	5	7926 05 08	18.5	49	0.024
10	7.3	7926 07 10	22	58.5	0.044

7921

Body with Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




C	DN		E	F	G	H	kg
G1/8	5	7921 05 10	5.5	16	18.5	31.5	0.022
G1/4	5	7921 05 13	5.5	16	18.5	31.5	0.023
	7.3	7921 07 13	5.5	20	22	37.5	0.039
G3/8	7.3	7921 07 17	5.5	20	22	37.5	0.041

7960

Straight Probe, Push-In Connection



Technical polymer, NBR




ØD	DN		G	H	H1	kg
6	5	7960 05 06	13.5	36.5	17.5	0.007
8	5	7960 05 08	13.5	37	18	0.003
10	7.3	7960 07 10	16	41	20.5	0.004

7961

Straight Probe, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR



C	DN		E	F	G	H	H1	kg
G1/8	5	7961 05 10	5.5	13	13.5	46	27	0.017
G1/4	5	7961 05 13	5.5	16	13.5	46	27	0.019
	7.3	7961 07 13	5.5	16	16	51.5	31	0.025
G3/8	7.3	7961 07 17	5.5	20	16	51.5	31	0.034

Manually-Operated Valves

Manually-operated valves offer a **reliable** and **durable** system for opening and closing the circuit when the system has to be **switched frequently**. They provide a significant reduction in the time needed to work on pneumatic circuits.

Product Advantages

Manual Switch-Operated Valves

Downstream control supply provided by simply moving the lever
2 models available to provide the best solution for the system:

- 3/2: opening, closing, venting
- 2/2: opening, closing

Compact and ergonomic (can be positioned through 360°)
Push-in connections

Valves with Sliding Sleeve

Uni-directional use ensures the downstream circuit is vented
Operated in the plane of the tube
Lightweight due to the use of aluminium
Ideal for complex installations in a restricted space
Immediate identification of the venting system by the colour (red)



Applications

- Robotics
- Conveyors
- Textile
- Plastics Engineering
- Printing
- Pneumatics
- Packaging

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	0 to 10 bar Model 0669: 0 to 16 bar
Working Temperature	-10°C to +80°C Model 0669: -5°C to +70°C

Component Materials


Seals: NBR

Bolt:

Manual switch-operated valve: nickel-plated brass with seal
Sleeve valve: nickel-plated brass

Body:

Manual switch-operated valve: technical polymer
Sleeve valve: nickel-plated brass



Silicone-free

Regulations

DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)


Operation

Switch-Operated Valves




Open

Closed




Sleeve Valves



Open: downstream supply

Closed: downstream exhaust




Manually-Operated Valves

7800

3/2 Manual Switch-Operated Valve, Supply, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	F1	H	L1	L2	kg
4	M5x0.8	7800 04 19	14	14	42	7	18.5	0.008
	G1/8	7800 04 10	14	14	43	7	18.5	0.022
6	M5x0.8	7800 06 19	14	14	42	7	18.5	0.009
	G1/8	7800 06 10	14	14	43	7	20	0.023
8	G1/4	7800 06 13	17	14	50.5	9	22	0.048
	G1/8	7800 08 10	14	14	43	7	25	0.023
10	G1/4	7800 08 13	17	14	50.5	9	27	0.048
	G1/4	7800 10 13	17	14	50.5	9	29	0.048


For part numbers 7800 04 19 and 7800 06 19, adaptor sealing is effected by a flat PTFE seal and tightening torque is maximum 0.16 daN.m.

7801

3/2 Manual Switch-Operated Valve, Control, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	F1	H	L1	L2	kg
4	G1/8	7801 04 10	14	14	43	7	18.5	0.023
6	G1/8	7801 06 10	14	14	43	7	20	0.023
	G1/4	7801 06 13	17	14	50.5	9	22	0.048
8	G1/8	7801 08 10	14	14	43	7	25	0.026
	G1/4	7801 08 13	17	14	50.5	9	27	0.049
10	G1/4	7801 10 13	17	14	50.5	9	29	0.051

7802

2/2 Manual Switch-Operated Valve, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	F1	H	L1	L2	kg
4	G1/8	7802 04 10	14	14	43	7	18.5	0.023
6	G1/8	7802 06 10	14	14	43	7	20	0.024
	G1/4	7802 06 13	17	14	50.5	9	22	0.050
8	G1/8	7802 08 10	14	14	43	7	25	0.024
	G1/4	7802 08 13	17	14	50.5	9	27	0.052
10	G1/4	7802 10 13	17	14	50.5	9	29	0.052

0669

3/2 Sleeve Valve, Female BSPP and Metric Thread



Nickel-plated brass, aluminium, NBR



C	DN		F	G	L	kg
M5x0.8	2.5	0669 02 19	10	14	30.5	0.012
G1/8	4	0669 04 10	14	25	48	0.050
G1/4	7	0669 07 13	19	30	58	0.096
G3/8	10	0669 10 17	22	35	68	0.154
G1/2	14	0669 14 21	27	40	75	0.210
G3/4	19	0669 19 27	32	50	83	0.324

Metal Quick Exhaust Valves

This range of metal quick exhaust valves is offered in nickel-plated brass, aluminium and stainless steel. These valves, which are suitable for **any environment**, increase the **return speed** of the cylinder rod by allowing the exhaust to pass directly to atmosphere.

Product Advantages

Time Saving & Compact

Reduction in cycle times: return speed improved
Dimensions optimised for space reduction
Exhaust silencer incorporated on some models
Excellent exhaust capacity
Robust

Nickel-Plated Brass or Stainless Steel

Ideal for applications in restrictive environments
Orientation as required
Many installation options and choice of silencer
Designed without retention areas to optimise frequent cleaning operations (stainless steel)

Aluminium

Protection of individuals through low noise emissions
Lightweight and robust
Silencer integrated for greater compactness




Applications

- Robotics
- Conveyors
- Textile
- Plastics Engineering
- Printing
- Pneumatics
- Packaging

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	7970: 0.7 to 10 bar 7971 and 7899: 2 to 10 bar
Working Temperature	7970: -20°C to +70°C 7971: -10°C to +70°C 7899: Threads G1/8 and G1/4: -10°C to +120°C Threads G3/8 to G1: -20°C to +180°C

Component Materials




Silicone-free

Regulations


DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 97/23/EC (PED)

Operation

Mounted on Cylinder



Installation Diagram




Metal Quick Exhaust Valves

7970

Elbow Quick Exhaust Valve, Female BSPP and Metric Thread



Nickel-plated brass



C		E	F	H	H1	L	kg
M5x0.8	7970 19 19	5	10	24.8	15.6	4	0.028
G1/8	7970 10 10	7.5	14	42	28	8	0.084
G1/4	7970 13 13	11	19	53	34.5	11	0.146
G3/8	7970 17 17	12	21	58	36	12	0.149
G1/2	7970 21 21	14	26	71	44	14	0.314
G3/4	7970 27 27	16	32	86	52	18	0.449
G1	7970 34 34	19	38	94	56	19	0.530


Noise level:
7971 10 10 : 70 dBa
7971 13 13 : 70 dBa
7971 17 17 : 72 dBa
7971 21 21 : 88 dBa

7971

Elbow Quick Exhaust Valve, Male BSPT/Female BSPP Thread



Treated aluminium




C	C1		F	H	kg
G1/8	R1/8	7971 10 10	18	51	0.013
G1/4	R1/4	7971 13 13	18	49	0.018
G3/8	R3/8	7971 17 17	27	56	0.048
G1/2	R1/2	7971 21 21	34	70	0.086

7899

Quick Exhaust Valve, Female BSPP Thread



Stainless steel 316L



C	DN		F	F1	H	L	L1	L2	kg
G1/8	7	7899 00 10	17	22	31.5	37.5	21	16.5	0.097
G1/4	7	7899 00 13	17	22	31.5	37.5	21	16.5	0.083
G3/8	9	7899 00 17	22	26	37	44.5	25.5	19	0.139
G1/2	12	7899 00 21	27	32	45	54	31	23	0.240
G3/4	18	7899 00 27	38	46	65	79	44	35	0.795
G1	18	7899 00 34	38	46	65	79	44	35	0.674

To complement our exhaust valves 7970 and 7899, you will find a full range of silencers on the following pages.

Silencers

Silencers are designed for installation on exhaust circuits **to reduce the noise levels** of equipment while operating, thus improving user comfort.

Product Advantages

- Variety of Applications**
- 2 versions incorporating flow control regulation
 - Extremely compact models available
 - Polyethylene: excellent balance between exhaust flow rate and noise reduction
 - Sintered bronze: robust and economic
 - 316L stainless steel: increased chemical resistance and mechanical strength




Applications

- Robotics
- Textile
- Semi-Conductors
- Packaging
- Pneumatics

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	Polyethylene: 0 to 10 bar Sintered bronze: 0 to 12 bar 316L stainless steel: 0 to 12 bar
Working Temperature	Polyethylene: -10°C to +80°C Sintered bronze: -20°C to +150°C 316L stainless steel: -20°C to +180°C

Component Materials



Silicone-free

Regulations

- DI: 2002/95/EC (RoHS)
- RG: 1907/2006 (REACH)
- DI: 97/23/EC (PED)
- DI: 2003/10/EC (Noise Directive)
Requirement to use ear protection if exposure > 8 hours (85 dBA)
- RG: 1910.95(b) (OSHA)
Requirement to use ear protection if exposure > 8 hours (90 dBA)




Flow and Noise Levels for Silencers 0672 and 0676

0672	Number of Turns						Noise Level in dBA at 6 bar and 350 NI/min
	0	1	2	3	4	5	
0672 00 10	0	200	600	740	-	-	81
0672 00 13	0	300	650	1280	-	-	82
0672 00 17	0	450	950	1300	1500	-	83
0672 00 21	0	830	1430	1800	2100	2220	83




0676	Number of Turns										Noise Level in dBA at 6 bar and 350 NI/min
	0	1	2	3	4	5	6	7	8	9	
0676 00 10	0	30	90	210	335	370	390	390	395	395	82
0676 00 13	0	22	25	50	340	750	940	980	1000	1025	84
0676 00 19	0	22	69	97	125	143	-	-	-	-	81
0676 00 17	0	518	1147	1716	2153	2571	2823	2930	-	-	85
0676 00 21		814	1849	2880	4087	5044	5236	-	-	-	86

Silencers



0674 Polymer Silencer, Male BSPP and Metric Thread

	<p>Technical polymer</p> 	C		E	G	H	kg
		M5x0.8	0674 00 19	4	6.5	23	0.003
		G1/8	0674 00 10	6	12.5	34	0.002
		G1/4	0674 00 13	7	15.5	42.5	0.003
		G3/8	0674 00 17	11.5	18.5	67.5	0.007
		G1/2	0674 00 21	11	23.5	78	0.010
		G3/4	0674 00 27	15.5	38.5	131	0.035
		G1	0674 00 34	19.5	49	160	0.056



0676 Flow Control Polymer Silencer, Male BSPP and Metric Thread

	<p>Technical polymer</p> 	C		F	F1	G	H	H1	kg
		M5x0.8	0676 00 19	8	1.5	9.2	16	11	0.008
		G1/8	0676 00 10	13	2.5	15	20.5	14.5	0.003
		G1/4	0676 00 13	15	4	18	29	22	0.007
		G3/8	0676 00 17	20	6	24	38	30	0.018
G1/2	0676 00 21	25	8	30	50	40	0.045		



0670 Threaded Silencer, Male BSPP Thread

	Sintered bronze, brass	C		G	J	L	L1	kg
		G1/8	0670 00 10	12	7	22	17	0.007
		G1/4	0670 00 13	15	9	27	21	0.015
		G3/8	0670 00 17	19	11	35	28	0.028
		G1/2	0670 00 21	23	13	43	34	0.049
		G3/4	0670 00 27	30	17	55	45	0.091
		G1	0670 00 34	37	21	65	53	0.152

0673 Compact Silencer, Male BSPP and Metric Thread




	Sintered bronze, brass	C		E	F	H	kg
		M5x0.8	0673 00 19	4	7	8	0.001
		G1/8	0673 00 10	8	14	14	0.008
		G1/4	0673 00 13	8	17	14	0.012
		G3/8	0673 00 17	10	22	18	0.020
		G1/2	0673 00 21	12	27	21	0.042

0675 Threaded Silencer, Male BSPP and Metric Thread




	Sintered bronze, brass	C		F	L	L1	kg
		M5x0.8	0675 00 19	7	16	12	0.002
		M7x1	0675 00 55	11	25	19	0.005
		G1/8	0675 00 10	14	42	34	0.014
		G1/4	0675 00 13	17	52	44	0.022
		G3/8	0675 00 17	22	54	44	0.037
		G1/2	0675 00 21	27	65	53	0.072

Silencers




0671 Push-In Silencer

	Sintered bronze, nickel-plated brass		ØD		G	L	L1	kg
			4	0671 04 00	13	41.5	24.5	0.015
			6	0671 06 00	15	48	29	0.024
			8	0671 08 00	15	49.5	29.5	0.025
			10	0671 10 00	19.5	68	43.5	0.052
			12	0671 12 00	20	68.5	43	0.052




0677 Miniature Silencer, Male BSPP Thread

	Brass		C		G	H	kg
			G1/8	0677 00 10	6	6	0.002
			G1/4	0677 00 13	8	6	0.003
			G3/8	0677 00 17	11	7	0.006
			G1/2	0677 00 21	14	8	0.010
			G3/4	0677 00 27	19	11	0.019
			G1	0677 00 34	25	10	0.025




0672 Flow Control Silencer, Male BSPP Thread

	Sintered bronze, nickel-plated brass		C		E	F	G	H min	H max	kg
			G1/8	0672 00 10	8	14	14	17	21	0.017
			G1/4	0672 00 13	8	17	17	20	24	0.029
			G3/8	0672 00 17	10	22	22	20	28	0.058
			G1/2	0672 00 21	12	27	27	28	37	0.094

0682 Compact Silencer, Male BSPP Thread

	Stainless steel 316L		C		E	F	G	H	kg
			G1/8	0682 00 10	8	7	14	15	0.007
			G1/4	0682 00 13	8	7	17	15	0.011
			G3/8	0682 00 17	10	8	22	18	0.019
			G1/2	0682 00 21	12	10	27	22	0.038
			G3/4	0682 00 27	15	12	32	27	0.063
			G1	0682 00 34	18	14	38	32	0.117

0683 Compact Silencer, Male NPT Thread

	Stainless steel 316L		C		E	F	G	H	kg
			NPT1/8	0683 00 11	7	7	14	14	0.007
			NPT1/4	0683 00 14	11	7	17	18	0.014
			NPT3/8	0683 00 18	11	8	22	19	0.021
			NPT1/2	0683 00 22	15	10	27	25	0.043

Compression Fittings

Brass Compression Fittings

Stainless Steel Compression Fittings

PL Nickel-Plated Brass Spigot Fittings






Compression Fittings

Brass Compression Fittings


(P. 5-5)



Fluids: compressed air, non-corrosive industrial fluids
Materials: forged or machined brass
Pressure: 550 bar
Temperature: -40°C to +250°C
Ø metric: 4 mm to 28 mm

Stainless Steel Compression Fittings

(P. 5-31)



Fluids: compressed air, coolants, industrial and corrosive fluids
Materials: 316L stainless steel
Pressure: 400 bar
Temperature: -40°C to +250°C
Ø metric: 6 mm to 16 mm

PL Nickel-Plated Brass Spigot Fittings

(P. 5-41)



Fluids: compressed air, compatible industrial fluids
Materials: forged or machined nickel-plated brass
Pressure: 40 bar
Temperature: -40°C to +100°C
Ø metric: 4 mm to 14 mm

Compression Fitting Part Numbers

Item Type	0105142799	Suffix
01XX: brass 18XX: stainless steel	<div>Ø</div> <div>04 = 4 mm 06 = 6 mm ... 20 = 20 mm 28 = 28 mm</div>	<div>Thread</div> <div>10 = 1/8 13 = 1/4 ... 21 = 1/2 27 = 3/4</div>
		39: bonded seal 40: treated steel 60: nut 70: polymer nut 99: chemical nickel

PL Fitting Part Numbers

Item Type	F3BPL8/10-1/4	Thread
FBPL F3BPL HBPL WBPL ...	<div>Ø</div> <div>2.7/4 4/6 6/8 7.5/10 8/10 10/12 11/14</div>	<div>BSPT & NPT:</div> <div>1/8 1/4 3/8 ... Metric: M10 M12</div>

Brass Compression Fitting Range

Brass Fittings

Stud Fittings

0105
BSPT
Page 5-9



0105
NPT
Page 5-9



0101
BSPP/Metric
Page 5-10



0101..39
BSPP
Page 5-10



0101
Metric
Page 5-11



0114
BSPP
Page 5-11



0109
BSPT
Page 5-12



0109
NPT
Page 5-12



0199
BSPP
Page 5-12



0108
BSPT
Page 5-13



0103
BSPT
Page 5-13



0118
BSPP
Page 5-14



0118..39
BSPP
Page 5-14



0119
BSPP
Page 5-15



0119..39
BSPP
Page 5-15



Tube-to-Tube Fittings

0106
Page 5-15



0113
Page 5-16



0116
Page 5-16



0102
Page 5-16



0104
Page 5-17



0142
Page 5-17



0107
Page 5-17



Complementary Fittings

0166
Page 5-20



0124
Page 5-21



0124..40
Page 5-21



0111
Page 5-21



0110
Page 5-22



0110..40
Page 5-22



0110..60
Page 5-22



0110..70
Page 5-22



Self-Fastening Hose Barb Connectors

0132
Page 5-25



0133..39
Page 5-25



0134
Page 5-25



Accessories

0122
Page 5-26



0165
Page 5-26



0126
Page 5-27



0125
Page 5-27



0220
Page 5-27



0220..39
Page 5-27



0120
Page 5-28



0112
Page 5-28



0128..39
Page 5-29



0151..39
Page 5-29



0168..39
Page 5-29



0127
Page 5-30



Brass Compression Fittings

These **"universal"** fittings provide users with **numerous connection** options for a wide variety of tube materials without the need for tube threading or soldering. This range **guarantees** excellent long-term sealing and performance.

Product Advantages

Simple to Install and Use

Suitable for pneumatic and medium pressure hydraulic applications
Compatible with many industrial fluids
Large product range: 22 configurations
Excellent sealing due to the tightening of the olive onto the tube
Metallic sealing guarantees maximum service life
High strength brass for increased mechanical reliability

Wide Variety of Tubing

Connection of different types of tubing and hose: metal, polymer, steel, rubber, etc.
Multiple tube diameters can be connected using the Parker Legris reducer assembly system
No insert required for rigid and semi-rigid polyamide tubing below 14 mm



Applications


- Pneumatics
- Cooling
- Automotive Process
- Lubrication
- Fluid Transmission
- Packaging
- Industrial Machinery

Technical Characteristics

Compatible Fluids	Water, machining oil, fuel, hydraulic oil, compressed air, chemical fluids, disinfectants
Working Pressure	Vacuum to 550 bar
Working Temperature	-40°C to +250°C
Tightening Torque	See "Technical Characteristics" on opposite page

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Maximum Bore Diameters

The table below shows the recommended compatibility of tube size, BSPP male thread and maximum bore.

Tube O.D.	BSPP Thread	Max. Bore
4-5-6	G1/8	4
6-8-10	G1/4	7
10-12-14	G3/8	11
14-15-16-18	G1/2	14
18-20-22	G3/4	18
22-25-28	G1	24

Tube Length for Assembly

Minimum length of tube (L) between 2 fittings.



ØD	L (mm)	ØD	L (mm)	ØD	L (mm)
4	26.5	12	39	20	51
5	26	14	41	22	54
6	26	15	41	25	62
8	32	16	46.5	28	62
10	39	18	49.5		

Regulations

CNOMO: E07.21.115N
(for robotic equipment in the automotive industry)
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)
DI: 2002/95/EC (RoHS)
DI: 94/9/EC (ATEX)

Technical Characteristics

Installing Compression Fittings

Cutting the Tube



Cut the polymer or metal tube square.

Preparing the Connection




For metal tubing, de-burr the tube prior to connection. Tube bending should be done before connection.



Slide the nut onto the tube; lubricate the threads on the body and nut along with the olive to facilitate tightening (for metal tubing as well). Fit the olive onto the end of the tube.

Connecting the Tube



Push the tube up against the shoulder of the body of the fitting and hand tighten.

Final Assembly



Tighten the nut using a spanner or torque wrench to enable the olive to bite on the tube, the connection being completed when the recommended tightening torque is reached (see tables below).




It is recommended to use an insert in order to prevent tube creeping (diameter > 14mm)


Recommended Nut Tightening Torque

Tightening torque in daN.m =

maximum tightening torque of a 0110 nut and 0124 olive with copper, brass or steel tube.



Nut 0110 and 0110..40



Nut 0110..60

Ø D (mm)	Ø F 0110	Ø F 0110..60	Max. daN.m Copper or Brass	Ø F 0110..40	Max. daN.m Steel
4	10	11	0.7	10	1.5
5	12	13	0.7	12	1.5
6	13	13	1.5	13	2.5
8	14	16	1.5	14	2.5
10	19	20	1.8	19	3
12	22	22	3	22	4.5
14	24	24	3.5	24	5.5
15	24	24	4	24	6
16	27	27	5	27	7
18	30	30	6	30	9
20	32	32	6	32	10
22	36	36	7	36	12
25	41	41	8	41	13
28	42		9		

Customised Fittings

Working directly with its customers and based on its knowledge and experience, Parker Legris can design customised brass compression fittings for specific requirements using the customer's specifications.

The range of compression fittings also offers nickel chemical surface treatment in order to improve the corrosion resistance and chemical compatibility of the fittings (the model number of the fitting is then given the suffix 99).

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.



Technical Characteristics

The use of Parker Legris brass compression fittings is dependant on the tube material. Tables of recommended working pressure for the different tubes are shown below.

Recommended Tube Type

Copper tube: copper which has been "cold rolled", cold drawn and in straight lengths.

Brass tube: in cold-rolled straight lengths (same working pressure as for copper tube).

"Coiled annealed" copper tube: reduces working pressure by 35%; must be avoided completely if vibration is present.

Steel tube: "thin wall" cold drawn, seamless, bright annealed and in straight lengths.
6 mm to 16 mm O.D.: max. wall thickness 1 mm
Above 16 mm O.D.: max. wall thickness 1.5 mm




Polyamide tube: semi-rigid
For rigid polyamide tube, multiply the figures in this table by 1.8.

Recommended Tube-Fitting Assembly Configurations

Assembled using Parker Legris brass olive and nut.

Assembled using Parker Legris steel olive and nut (nut type 0110..40).

Assembled using Parker Legris brass olive and nut.



When using a plastic nut type 0110..70, the maximum working pressure is 10 bar, for all diameters.

Working Pressure Coefficients for Semi-Rigid Polyamide Tubing

Temperature °C	-40°C / -15°C	-15°C / +30°C	+30°C / +50°C	+50°C / +70°C	+70°C / +100°C
Factor	1.8	1	0.68	0.55	0.31

Parker Legris brass compression fittings are not compatible with ammonia and its derivatives.

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.


Brass Compression Fittings

0105

Stud Fitting, Male BSPT Thread



Brass



ØD	C		F	F1	H _{max}	H1	kg
4	R1/8	0105 04 10	10	10	17	7	0.012
	R1/8	0105 05 10	11	12	17.5	7.5	0.016
5	R1/4	0105 05 13	14	12	17.5	7.5	0.022
	R1/8	0105 06 10	11	13	18	7.5	0.017
6	R1/4	0105 06 13	14	13	18	7.5	0.024
	R3/8	0105 06 17	17	13	18	8.5	0.031
	R1/8	0105 08 10	13	14	19.5	7	0.020
8	R1/4	0105 08 13	14	14	19.5	7	0.025
	R3/8	0105 08 17	17	14	20.5	8	0.032
	R1/8	0105 10 10	17	19	24	9	0.043
10	R1/4	0105 10 13	17	19	24	9	0.047
	R3/8	0105 10 17	17	19	24	9	0.048
	R1/2	0105 10 21	22	19	25	10	0.067
12	R1/4	0105 12 13	19	22	24	9	0.059
	R3/8	0105 12 17	19	22	24	9	0.060
	R1/2	0105 12 21	22	22	25	10	0.076
14	R1/4	0105 14 13	22	24	25	8	0.068
	R3/8	0105 14 17	22	24	25	8	0.068
	R1/2	0105 14 21	22	24	26	9	0.080
	R3/4	0105 14 27	27	24	27	10	0.107
15	R3/8	0105 15 17	22	24	25	8	0.065
	R1/2	0105 15 21	22	24	26	9	0.076
	R1/4	0105 16 13	24	27	27	9.5	0.092
16	R3/8	0105 16 17	24	27	27	9.5	0.092
	R1/2	0105 16 21	24	27	27	9.5	0.099
	R3/4	0105 16 27	27	27	28	10.5	0.123
18	R1/2	0105 18 21	27	30	30	10.5	0.127
	R3/4	0105 18 27	27	30	30	10.5	0.138
20	R1/2	0105 20 21	30	32	32	11	0.148
	R3/4	0105 20 27	30	32	32	11	0.157
	R1/2	0105 22 21	32	36	33	11	0.187
22	R3/4	0105 22 27	32	36	33	11	0.196
	R1	0105 22 34	36	36	33	11	0.227
25	R3/4	0105 25 27	36	41	36	11	0.261
	R1	0105 25 34	36	41	36	11	0.278
28	R3/4	0105 28 27	41	42	36	11	0.274
	R1	0105 28 34	41	42	36	11	0.283

Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.

Brass Compression Fittings


Compression Fittings

0105

Stud Fitting, Male NPT Thread



Brass



ØD	C		F	F1	H _{max}	H1	kg
6	NPT1/8	0105 06 11	11	13	18	7.5	0.018
	NPT1/4	0105 06 14	14	13	18	7.5	0.027
8	NPT1/8	0105 08 11	13	14	21	7	0.021
	NPT1/4	0105 08 14	14	14	18.5	7	0.026
	NPT1/4	0105 10 14	17	19	24	9	0.048
10	NPT3/8	0105 10 18	17	19	24	9	0.048
	NPT1/2	0105 10 22	22	19	25	10	0.066


Brass Compression Fittings

0101

Stud Fitting with Captive Sealing Washer, Male BSPP and Metric Thread



Brass, technical polymer



ØD	C		E	F	F1	H _{max}	H1	kg
4	M5x0.8	0101 04 19	5	10	10	16.5	8	0.011
	G1/8	0101 04 10	6.5	13	10	16.5	8	0.016
5	G1/8	0101 05 10	6.5	13	12	17.5	8.5	0.018
6	G1/8	0101 06 10	6.5	13	13	18	8.5	0.020
	G1/4	0101 06 13	8	17	13	18	9.5	0.030
	G1/8	0101 08 10	6.5	13	14	19	8.5	0.021
8	G1/4	0101 08 13	8	17	14	19.5	9	0.032
	G3/8	0101 08 17	11	22	14	20	10.5	0.044
10	G1/4	0101 10 13	8	17	19	24	11	0.049
	G3/8	0101 10 17	11	22	19	24	11.5	0.061
	G1/4	0101 12 13	8	19	22	24	11	0.062
12	G3/8	0101 12 17	11	22	22	24	11.5	0.069
	G1/2	0101 12 21	12	27	22	24	12	0.089
14	G3/8	0101 14 17	11	22	24	25	10.5	0.074
	G1/2	0101 14 21	12	27	24	25	11	0.094
	G3/8	0101 15 17	11	22	24	25	10.5	0.071
15	G1/2	0101 15 21	12	27	24	25	11	0.093
	G3/8	0101 16 17	11	22	27	27	12	0.092
	G1/2	0101 16 21	12	27	27	27	12.5	0.109
18	G1/2	0101 18 21	12	27	30	29.5	12.5	0.128
	G3/4	0101 18 27	13	32	30	29.5	13	0.152
20	G3/4	0101 20 27	13	32	32	31	13	0.164
	G3/4	0101 22 27	13	32	36	32	13	0.195
22	G1	0101 22 34	15	41	36	31	13.5	0.259
	G3/4	0101 25 27	13	36	41	35.5	13	0.261
25	G1	0101 25 34	15	41	41	35.5	13	0.169
28	G1	0101 28 34	15	41	42	35.5	13.5	0.300


With pre-assembled captive sealing washer
Sealing washers 0602 are shown in Chapter 9.

0101..39

Stud Fitting, with Bi-Material Seal, Male BSPP



Brass, zinc-plated steel with NBR seal



ØD	C		E	F	F1	H _{max}	H1	kg
4	G1/8	0101 04 10 39	5.5	13	10	17.5	9	0.016
5	G1/8	0101 05 10 39	5.5	13	12	18.5	9.5	0.019
6	G1/8	0101 06 10 39	5.5	13	13	19	9.5	0.020
	G1/4	0101 06 13 39	7	17	13	19	10.5	0.030
	G1/8	0101 08 10 39	5.5	13	14	20	9.5	0.022
8	G1/4	0101 08 13 39	7	17	14	20.5	10	0.032
	G3/8	0101 08 17 39	9.5	22	14	21.5	12	0.045
10	G1/4	0101 10 13 39	7	17	19	25	12	0.048
	G3/8	0101 10 17 39	9.5	22	19	25.5	13	0.062
	G1/4	0101 12 13 39	7	19	22	25	12	0.063
12	G3/8	0101 12 17 39	9.5	22	22	25	13	0.071
	G1/2	0101 12 21 39	10.5	27	22	25	13.5	0.091
	G3/8	0101 14 17 39	9.5	22	24	26.5	12	0.075
14	G1/2	0101 14 21 39	10.5	27	24	26.5	12.5	0.095
	G3/8	0101 15 17 39	9.5	22	24	26.5	12	0.073
	G1/2	0101 15 21 39	10.5	27	24	26.5	12.5	0.095
16	G3/8	0101 16 17 39	9.5	22	27	28.5	13.5	0.092
	G1/2	0101 16 21 39	10.5	27	27	28.5	14	0.111
18	G1/2	0101 18 21 39	10.5	27	30	31	14	0.129
	G3/4	0101 18 27 39	11.5	32	30	31	14.5	0.155
20	G3/4	0101 20 27 39	11.5	32	32	32.5	14.5	0.164
	G3/4	0101 22 27 39	11.5	32	36	32.5	14.5	0.197
22	G1	0101 22 34 39	13	41	36	33	15.5	0.259
	G1	0101 25 34 39	13	41	41	37.5	15.5	0.309
25	G1	0101 25 34 39	13	41	41	37.5	15.5	0.309
28	G1	0101 28 34 39	13	41	42	37.5	15.5	0.301

Thread with bi-material seal
Bi-material sealing washers, part number 0139, can be found in Chapter 9


Brass Compression Fittings

0101

Stud Fitting, Male Metric Thread



Brass



ØD	C		E	F	F1	H _{max}	H1	kg
4	M7x1	0101 04 55	6.5	10	10	16.5	7.5	0.012
	M8x1	0101 04 56	6.5	11	10	16.5	7.5	0.013
5	M8x1	0101 05 56	6.5	11	12	17.5	8	0.016
	M10x1	0101 05 60	6.5	14	12	17.5	8.5	0.020
6	M10x1	0101 06 60	6.5	14	13	18	8.5	0.021
	M10x1.5	0101 06 62	6.5	14	13	18	8.5	0.021
8	M12x1	0101 08 65	8	17	14	19.5	9	0.029
	M12x1.25	0101 08 66	8	17	14	19.5	9	0.029
	M13x1.25	0101 08 68	8	17	14	19.5	9	0.030
10	M14x1.25	0101 10 70	8	17	19	24	11	0.047
	M14x1.5	0101 10 71	8	17	19	24	11	0.047
	M16x1.25	0101 10 74	9	19	19	24	11	0.051
	M16x1.5	0101 10 75	9	19	19	24	11	0.051
	M18x1.5	0101 10 78	9	22	19	24	11.5	0.060
12	M16x1.25	0101 12 74	9	19	22	24	11	0.061
	M16x1.5	0101 12 75	9	19	22	24	11	0.061
	M18x1.5	0101 12 78	9	22	22	24	11.5	0.070
14	M18x1.5	0101 14 78	9	22	24	25	10.5	0.077
	M20x1.5	0101 14 80	10	24	24	25	11	0.084
15	M18x1.5	0101 15 78	9	22	24	25	10.5	0.071
	M20x1.5	0101 16 80	10	24	27	27	12.5	0.102
16	M22x1.5	0101 16 82	10	27	27	27	12.5	0.111
	M22x1.5	0101 18 82	10	27	30	29.5	12.5	0.129
18	M24x1.5	0101 18 83	11	30	30	29.5	13	0.142


Brass Compression Fittings

0114

Stud Fitting, Female BSPP Thread



Brass



ØD	C		E	F	F1	H _{max}	H1	kg
4	G1/8	0114 04 10	9.5	14	10	26	16.5	0.020
	G1/4	0114 04 13	13.5	17	10	30	20.5	0.030
5	G1/8	0114 05 10	9.5	14	12	28	17	0.023
	G1/4	0114 05 13	13.5	17	12	31	21	0.033
6	G1/8	0114 06 10	9.5	14	13	28	17	0.025
	G1/4	0114 06 13	13.5	17	13	32	21	0.034
8	G3/8	0114 06 17	14	22	13	32	21.5	0.051
	G1/8	0114 08 10	9.5	14	14	29	16.5	0.026
	G1/4	0114 08 13	13.5	17	14	33	20.5	0.036
10	G3/8	0114 08 17	14	22	14	34	21	0.052
	G1/4	0114 10 13	13.5	17	19	37	21.5	0.052
	G3/8	0114 10 17	14	22	19	37	22	0.068
12	G1/2	0114 10 21	18.5	27	19	42	26.5	0.099
	G1/4	0114 12 13	13.5	19	22	36	20.5	0.069
	G3/8	0114 12 17	14	22	22	37	22	0.078
14	G1/2	0114 12 21	18.5	27	22	42	26.5	0.109
	G1/4	0114 14 13	13.5	22	24	36	18.5	0.085
	G3/8	0114 14 17	14	22	24	38	21	0.048
15	G1/2	0114 14 21	18.5	27	24	43	25.5	0.113
	G3/8	0114 15 17	14	22	24	38	21	0.078
	G1/2	0114 15 21	18.5	27	24	43	25.5	0.109
16	G1/4	0114 16 13	13.5	24	27	36	18	0.107
	G3/8	0114 16 17	14	24	27	38	20.5	0.106
	G1/2	0114 16 21	18.5	27	27	44	26	0.127
18	G3/8	0114 18 17	14	27	30	39	19.5	0.140
	G1/2	0114 18 21	18.5	27	30	45	26	0.144
	G3/4	0114 18 27	19.5	32	30	46	27	0.165
20	G3/8	0114 20 17	14	30	32	38	18	0.161
	G1/2	0114 20 21	18.5	30	32	44.5	24	0.173
	G3/4	0114 20 27	19.5	32	32	47	26.5	0.170
22	G3/4	0114 22 27	19.5	32	36	48	26.5	0.204
	G3/4	0114 25 27	19.5	36	41	50.5	26	0.297

Compression Fittings


Brass Compression Fittings

0109

Stud Elbow, Male BSPT Thread



Brass



ØD	C		F	H	J	L max	L1	kg
4	R1/8	0109 04 10	10	17	8	19	9.5	0.016
	R1/4	0109 04 13	10	20	10	19	11	0.026
5	R1/8	0109 05 10	12	17.5	8	21	11	0.019
	R1/4	0109 05 13	12	21.5	10	22	12	0.028
6	R1/8	0109 06 10	13	18	8	22	11	0.021
	R1/4	0109 06 13	13	21.5	10	22	12	0.031
8	R1/8	0109 08 10	14	18.5	10	28	15	0.028
	R1/4	0109 08 13	14	22	10	28	15	0.033
	R3/8	0109 08 17	14	24	12	28	15	0.044
	R1/4	0109 10 13	19	25	12	30	14.5	0.052
10	R3/8	0109 10 17	19	25.5	12	30	14.5	0.060
	R1/2	0109 10 21	19	32	19	36	21	0.109
12	R1/4	0109 12 13	22	26	15	30	15	0.074
	R3/8	0109 12 17	22	27	15	30	15	0.077
	R1/2	0109 12 21	22	32	19	36	21	0.116
	R3/8	0109 14 17	24	30	19	35	18	0.105
14	R1/2	0109 14 21	24	32	19	35	18	0.112
	R3/8	0109 15 17	24	30	19	35	18	0.099
15	R1/2	0109 15 21	24	32	19	35	18	0.106
	R3/8	0109 16 17	27	30	19	39	21	0.120
16	R1/2	0109 16 21	27	33.5	19	39	21	0.130
	R3/4	0109 16 27	27	36.5	23	41	23	0.189
18	R1/2	0109 18 21	30	35.5	23	41	21.5	0.182
	R3/4	0109 18 27	30	36.5	23	41	21.5	0.199
20	R1/2	0109 20 21	32	36.5	23	42	21.5	0.181
	R3/4	0109 20 27	32	38	23	42	21.5	0.200
22	R3/4	0109 22 27	36	40	27	50	30	0.288
	R1	0109 22 34	36	44	27	50	30	0.342
25	R3/4	0109 25 27	41	43	27	54	30	0.325
	R1	0109 25 34	41	44	27	54	30	0.367
28	R3/4	0109 28 27	42	46	32	54	30	0.402
	R1	0109 28 34	42	48	32	54	30	0.384


Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.

0109

Stud Elbow, Male NPT Thread



Brass




ØD	C		F	H	J	L max	L1	kg
6	NPT1/8	0109 06 11	13	18	8	22	11	0.021
	NPT1/4	0109 06 14	13	21.5	10	22	12	0.030
8	NPT1/8	0109 08 11	14	18.5	10	28	15	0.028
	NPT1/4	0109 08 14	14	22	10	28	15	0.033
10	NPT1/4	0109 10 14	19	25	12	30	14.5	0.053

0199

Stud Orientable Elbow, Male BSPP Thread



Brass, NBR



ØD	C		F	F1	H	H1	H1 max	J	L max	L1	kg
4	G1/8	0199 04 10	14	10	23	16	17	8	19	9.5	0.023
	G1/4	0199 04 13	19	10	30.5	22	23.5	10	19	11	0.043
6	G1/8	0199 06 10	14	13	23	16	17	8	22	11	0.027
	G1/4	0199 06 13	19	13	30.5	22	23.5	10	22	12	0.047
8	G1/8	0199 08 10	14	14	24	17	18	10	28	15	0.033
	G1/4	0199 08 13	19	14	30.5	22	23.5	10	28	15	0.051
	G3/8	0199 08 17	22	14	33.5	24	25.5	12	28	15	0.065
	G1/4	0199 10 13	19	19	31	22.5	24	12	30	14.5	0.068
10	G3/8	0199 10 17	22	19	33.5	24	25.5	12	30	14.5	0.079
	G1/2	0199 10 21	27	19	40	29.5	31	19	37	22	0.138
14	G3/8	0199 14 17	22	24	35.5	26	27.5	19	35	18	0.119
	G1/2	0199 14 21	27	24	40	29.5	31	19	35	18	0.141
18	G1/2	0199 18 21	27	30	40	29	30.5	23	41	21.5	0.187
	G3/4	0199 18 27	32	30	43.5	32	33.5	23	41	21.5	0.222
22	G3/4	0199 22 27	32	36	45.5	34	36	32	51	31	0.382
	G1	0199 22 34	41	36	54	40.5	43	32	51	31	0.408
28	G1	0199 28 34	41	42	54	40.5	43	32	54	30	0.420

The body will orientate for positioning purposes


Brass Compression Fittings

0108

Stud Branch Tee, Male BSPT Thread



Brass



ØD	C		F	H	J	L1	L/2	kg
4	R1/8	0108 04 10	10	17	8	9.5	19	0.025
5	R1/8	0108 05 10	12	17.5	8	11	21	0.017
6	R1/8	0108 06 10	13	18	8	11	22	0.032
	R1/4	0108 06 13	13	21.5	10	16	27	0.047
8	R1/8	0108 08 10	14	18.5	10	15	28	0.045
	R1/4	0108 08 13	14	22	10	15	28	0.050
	R3/8	0108 08 17	14	24	12	15	28	0.061
10	R1/4	0108 10 13	19	25	12	14.5	30	0.084
	R3/8	0108 10 17	19	25.5	12	14.5	30	0.090
12	R1/4	0108 12 13	22	26	15	15	30	0.116
	R3/8	0108 12 17	22	27	15	15	30	0.117
14	R3/8	0108 14 17	24	30	19	18	35	0.153
	R1/2	0108 14 21	24	32	19	18	35	0.168
15	R3/8	0108 15 17	24	30	19	18	35	0.145
	R1/2	0108 15 21	24	32	19	18	35	0.155
16	R3/8	0108 16 17	27	30	19	21	39	0.190
	R1/2	0108 16 21	27	33.5	19	21	39	0.203
18	R1/2	0108 18 21	30	35.5	23	21.5	41	0.265
	R3/4	0108 18 27	30	36.5	23	21.5	41	0.292
20	R3/4	0108 20 27	32	38	23	21.5	42	0.298
22	R3/4	0108 22 27	36	40	27	29	50	0.435
	R1	0108 22 34	36	44	27	29	50	0.466


Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.

0103

Stud Run Tee, Male BSPT Thread



Brass



ØD	C		F	H max	H1	H2	J	kg
4	R1/8	0103 04 10	10	19	17	9.5	8	0.025
5	R1/8	0103 05 10	12	21	17.5	11	8	0.030
6	R1/8	0103 06 10	13	22	18	11	8	0.033
	R1/4	0103 06 13	13	27	21.5	16	10	0.048
8	R1/8	0103 08 10	14	28	18.5	15	10	0.045
	R1/4	0103 08 13	14	28	22	15	10	0.050
	R3/8	0103 08 17	14	28	24	15	12	0.061
10	R1/4	0103 10 13	19	30	25	14.5	12	0.084
	R3/8	0103 10 17	19	30	25.5	14.5	12	0.092
12	R1/4	0103 12 13	22	30	26	15	15	0.114
	R3/8	0103 12 17	22	30	27	15	15	0.120
14	R3/8	0103 14 17	24	35	30	18	19	0.161
	R1/2	0103 14 21	24	35	32	18	19	0.169
15	R3/8	0103 15 17	24	35	30	18	19	0.148
	R1/2	0103 15 21	24	35	32	18	19	0.158
16	R3/8	0103 16 17	27	39	30	21	19	0.192
	R1/2	0103 16 21	27	39	33.5	21	19	0.199
18	R1/2	0103 18 21	30	41	35.5	21.5	23	0.269
	R3/4	0103 18 27	30	41	36.5	21.5	23	0.282
20	R3/4	0103 20 27	32	42	38	21.5	23	0.298
22	R3/4	0103 22 27	36	50	40	29	27	0.435

Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.


Brass Compression Fittings

0118

Single Banjo, with Captive Sealing Washer, Male BSPP Thread



Brass, technical polymer



ØD	C		F	F1	H	H1	L _{max}	L1	N	kg
4	G1/8	0118 04 10	14	10	24	9.5	24	14.5	17.5	0.038
5	G1/8	0118 05 10	14	12	24	9.5	25	14.5	17.5	0.041
	G1/4	0118 05 13	17	12	25	10	26	16	21	0.058
6	G1/8	0118 06 10	14	13	24	9.5	25	14.5	17.5	0.041
	G1/4	0118 06 13	17	13	25	10	26	16	21	0.056
8	G1/8	0118 08 10	14	14	24	9.5	28	15.5	17.5	0.054
	G1/4	0118 08 13	17	14	25	10	28	15.5	21	0.057
10	G3/8	0118 08 17	22	14	32	13	30	18	26.5	0.111
	G1/4	0118 10 13	17	19	31	13	34	19	23	0.120
12	G3/8	0118 10 17	22	19	32	13	34	19	26.5	0.129
	G1/4	0118 12 13	17	22	34	14.5	34	19	23	0.126
14	G3/8	0118 12 17	22	22	35	14.5	34	19	26.5	0.133
	G1/4	0118 14 13	17	24	37	16	37	20.5	28	0.154
15	G3/8	0118 14 17	22	24	38	16	37	20.5	28	0.195
	G1/2	0118 14 21	27	24	40	16	38	20.5	32.5	0.208
16	G3/8	0118 15 17	22	24	38	16	37	20.5	28	0.190
	G1/2	0118 15 21	27	24	40	16	38	20.5	32.5	0.198
18	G1/2	0118 16 21	27	27	42	16	38	21	32.5	0.221
20	G1/2	0118 18 21	27	30	46	19.5	43	24.5	36	0.366
22	G3/4	0118 20 27	32	32	49	20	44	24.5	39	0.403
	G3/4	0118 22 27	32	36	53	22	45	24.5	39	0.459


With pre-assembled captive sealing washer
Sealing washers 0602 can be found in Chapter 9.

0118..39

Single Banjo with Bi-Material Seal, Male BSPP Thread



Brass, zinc-plated steel with NBR seal



ØD	C		F	F1	H	H1	L _{max}	L1	N	kg
4	G1/8	0118 04 10 39	14	10	23	9.5	24	14.5	17.5	0.038
5	G1/8	0118 05 10 39	14	12	23	9.5	25	14.5	17.5	0.041
	G1/4	0118 05 13 39	17	12	24	10	26	16	21	0.064
6	G1/8	0118 06 10 39	14	13	23	9.5	25	14.5	17.5	0.042
	G1/4	0118 06 13 39	17	13	24	10	26	16	21	0.057
8	G1/8	0118 08 10 39	14	14	23	9.5	28	15.5	17.5	0.055
	G1/4	0118 08 13 39	17	14	24	10	28	15.5	21	0.058
10	G3/8	0118 08 17 39	22	14	31.5	13.5	30	18	26.5	0.113
	G1/4	0118 10 13 39	17	19	30	13	34	19	23	0.118
12	G3/8	0118 10 17 39	22	19	31.5	13.5	34	19	26.5	0.128
	G1/4	0118 12 13 39	17	22	33	14.5	34	19	23	0.128
14	G3/8	0118 12 17 39	22	22	34.5	15	34	19	26.5	0.140
	G1/4	0118 14 13 39	17	24	36	16	37	20.5	28	0.189
15	G3/8	0118 14 17 39	22	24	37.5	16.5	37	20.5	28	0.198
	G1/2	0118 14 21 39	27	24	39	16.5	38	20.5	32.5	0.205
16	G3/8	0118 15 17 39	22	24	37.5	16.5	37	20.5	28	0.389
	G1/2	0118 15 21 39	27	24	40	16.5	38	20.5	32.5	0.202
18	G1/2	0118 16 21 39	27	27	40	16.5	38	21	32.5	0.225
20	G1/2	0118 18 21 39	27	30	47	20	43	24.5	36	0.369
22	G3/4	0118 20 27 39	32	32	50	20.5	44	24.5	39	0.394
	G3/4	0118 22 27 39	32	36	54	22.5	45	24.5	39	0.462

With bi-material sealing washer
Bi-material sealing washers, part number 0139, can be found in Chapter 9.


Brass Compression Fittings

0119

Double Banjo with Captive Sealing Washer, Male BSPP Thread



Brass, technical polymer



ØD	C		F	F1	H	H1	L1	L/2	N	kg
4	G1/8	0119 04 10	14	10	24	9.5	14.5	24	17.5	0.049
6	G1/8	0119 06 10	14	13	24	9.5	14.5	25	17.5	0.056
	G1/4	0119 06 13	17	13	25	10	16	26.5	21	0.038
8	G1/8	0119 08 10	14	14	24	9.5	15.5	28	17.5	0.069
	G1/4	0119 08 13	17	14	25	10	15.5	28	21	0.074
	G3/8	0119 08 17	22	14	32	13	18	30.5	26.5	0.140
10	G1/4	0119 10 13	17	19	31	13	19	34	23	0.156
	G3/8	0119 10 17	22	19	32	13	19	34	26.5	0.165
12	G1/4	0119 12 13	17	22	34	14.5	19	34	23	0.180
	G3/8	0119 12 17	22	22	35	14.5	19	34	26.5	0.182
14	G1/4	0119 14 13	17	24	37	16	20.5	37.5	28	0.246
	G3/8	0119 14 17	22	24	38	16	20.5	37.5	28	0.247
	G1/2	0119 14 21	27	24	40	16	20.5	38	32.5	0.219

Thread with pre-assembled washer


Sealing washers 0602 can be found in Chapter 9.

0119..39

Double Banjo with Bi-Material Seal, Male BSPP Thread



Brass, zinc-plated steel with NBR seal



ØD	C		F	F1	H	H1	L1	L/2	N	kg
4	G1/8	0119 04 10 39	14	10	23	9.5	14.5	24	17.5	0.050
5	G1/8	0119 05 10 39	14	12	23	9.5	14.5	25	17.5	0.049
	G1/4	0119 05 13 39	17	12	24	10	126	26	21	0.072
6	G1/8	0119 06 10 39	14	13	23	9.5	14.5	25	17.5	0.056
	G1/4	0119 06 13 39	17	13	24	10	16	26	21	0.071
	G1/8	0119 08 10 39	14	14	23	9.5	15.5	28	17.5	0.072
8	G1/4	0119 08 13 39	17	14	24	10	15.5	28	21	0.080
	G3/8	0119 08 17 39	22	14	31.5	13.5	18	30	26.5	0.118
10	G1/4	0119 10 13 39	17	19	30	13	19	34	23	0.156
	G3/8	0119 10 17 39	22	19	31.5	13.5	19	34	26.5	0.167
12	G1/4	0119 12 13 39	17	22	33	14.5	19	34	23	0.180
	G3/8	0119 12 17 39	22	22	34.5	15	19	34	26.5	0.183
	G1/4	0119 14 13 39	17	24	36	16	20.5	37	28	0.248
14	G3/8	0119 14 17 39	22	24	37.5	16.5	20.5	37	28	0.247
	G1/2	0119 14 21 39	27	24	39	16.5	20.5	38	32.5	0.262
15	G3/8	0119 15 17 39	22	24	37.5	16.5	20.5	37	28	0.246
	G1/2	0119 15 21 39	27	24	40	16.5	20.5	38	32.5	0.251
18	G1/2	0119 18 21 39	27	30	47	20	24.5	43	36	0.469
20	G3/4	0119 20 27 39	32	32	50	20.5	24.5	44	39	0.638
22	G3/4	0119 22 27 39	32	36	54	22.5	24.5	45	39	0.610

Thread with pre-assembled washer


Bi-material sealing washers, part number 0139, can be found in Chapter 9.

0106

Equal Tube-to-Tube Connector



Brass




ØD		F	F1	L _{max}	L1	kg
4	0106 04 00	10	10	28	10	0.016
5	0106 05 00	11	12	31	11	0.023
6	0106 06 00	11	13	32	11	0.026
8	0106 08 00	13	14	36	10	0.031
10	0106 10 00	17	19	42	13	0.070
12	0106 12 00	19	22	42	13	0.092
14	0106 14 00	22	24	45	11	0.104
15	0106 15 00	22	24	45	11	0.097
16	0106 16 00	24	27	48	13	0.141
18	0106 18 00	27	30	53	14	0.186
20	0106 20 00	30	32	56	14	0.211
22	0106 22 00	32	36	60	14	0.283
25	0106 25 00	36	41	64	14	0.396
28	0106 28 00	41	42	64	14	0.399

Brass Compression Fittings


0113 Equal Tube-to-Tube Connector with Mounting Boss

Brass

ØD		F	H	H1	L1	L/2	N	kg
4	0113 04 00	10	10.5	7	9.5	19	6	0.022
6	0113 06 00	13	13	9	10	20.5	7	0.033
8	0113 08 00	14	14.5	9.5	11	23.5	8	0.041
10	0113 10 00	19	19.5	12.5	11	26	9	0.082
12	0113 12 00	22	22	14	12	26.5	11	0.107
14	0113 14 00	24	25	16	11	28	12	0.122


0116 Equal Bulkhead Connector

Brass

ØD		F	F1	F2	L _{max}	L1 _{max}	L2	L3	ØT _{min}	kg
4	0116 04 00	10	10	13	27	17	7	17	8.3	0.024
5	0116 05 00	13	12	14	28	18	7.5	17.5	10.3	0.035
6	0116 06 00	13	13	14	28	19	7.5	17.5	10.3	0.037
8	0116 08 00	14	14	17	29	20	7	17	12.3	0.045
10	0116 10 00	19	19	22	33	25	9	19	16.5	0.101
12	0116 12 00	22	22	22	33	25	9	19	18.5	0.121
14	0116 14 00	24	24	24	35	25	8	18	20.5	0.145
15	0116 15 00	24	24	24	35	25	8	18	20.5	0.134
16	0116 16 00	27	27	27	36	28	9.5	19.5	22.5	0.189
18	0116 18 00	27	30	30	40	30	10.5	20.5	24.5	0.237
20	0116 20 00	32	30	32	41	31	11	21	27.5	0.274
22	0116 22 00	36	36	36	42	32	11	21	30.5	0.372
25	0116 25 00	36	41	38	46	36	11	21	33.5	0.469

0102 Equal Elbow


Brass

ØD		F	J	L _{max}	kg
4	0102 04 00	10	5	19	0.016
5	0102 05 00	12	8	21	0.024
6	0102 06 00	13	8	22	0.027
8	0102 08 00	14	10	28	0.038
10	0102 10 00	19	12	30	0.073
12	0102 12 00	22	15	30	0.098
14	0102 14 00	24	19	35	0.133
15	0102 15 00	24	19	35	0.122
16	0102 16 00	27	19	39	0.164
18	0102 18 00	30	23	41	0.231
20	0102 20 00	32	23	42	0.233
22	0102 22 00	36	27	50	0.371
25	0102 25 00	41	27	54	0.446
28	0102 28 00	42	32	54.5	0.478

Brass Compression Fittings

0104


Equal Tee



ØD		F	H	J	L/2	kg
4	0104 04 00	10	9.5	8	19	0.028
5	0104 05 00	12	11	8	21	0.036
6	0104 06 00	13	11	8	22	0.040
8	0104 08 00	14	15	10	28	0.055
10	0104 10 00	19	14.5	12	30	0.105
12	0104 12 00	22	15	15	30	0.142
14	0104 14 00	24	18	19	35	0.190
15	0104 15 00	24	18	19	35	0.175
16	0104 16 00	27	21	19	39	0.239
18	0104 18 00	30	21.5	23	41	0.330
20	0104 20 00	32	21.5	23	42	0.330
22	0104 22 00	36	29	27	50	0.518
25	0104 25 00	41	29	27	54	0.630
28	0104 28 00	42	30	32	55	0.660

0142


Equal Y Piece with Mounting Boss



ØD		F	H _{max}	H1	L _{max}	L1	ØT	Kg
4	0142 04 00	10	16.5	7	26.5	17	4.2	0.032
6	0142 06 00	13	19.5	8.5	28	17	4.2	0.049
8	0142 08 00	14	21	8	30	17	6.2	0.061
10	0142 10 00	19	24.5	9	37.5	22	6.2	0.128
12	0142 12 00	22	26	11	38	23	6.2	0.110
14	0142 14 00	24	28	11	41.5	24.5	6.2	0.201
15	0142 15 00	24	28	11	41.5	24.5	6.2	0.204
16	0142 16 00	27	30	12	43	25	6.2	0.252
18	0142 18 00	30	31.5	12	50.5	31	10.2	0.220
25	0142 25 00	41	39	14	59	34	10.2	0.728

0107

Equal Cross



ØD		F	H	J	L/2	Kg
4	0107 04 00	10	9.5	8	19	0.035
5	0107 05 00	12	11	8	21	0.047
6	0107 06 00	13	11	8	22	0.052
8	0107 08 00	14	15	11	28	0.073
10	0107 10 00	19	14.5	14	30	0.142
12	0107 12 00	22	15	15	35	0.096
14	0107 14 00	24	18	20	35	0.246
15	0107 15 00	24	18	20	35	0.227
16	0107 16 00	27	21	20	39	0.312
18	0107 18 00	30	21.5	25	41	0.426
20	0107 20 00	32	21.5	25	42	0.429
22	0107 22 00	36	29	27	50	0.676
25	0107 25 00	41	29	27	50	0.819


Complementary Brass Fittings

Reducers, Olives and Nuts

This innovative reducer system, using a full range of nuts and olives, enables **different diameters** of steel, copper, brass or polymer tubes to be fitted onto **a single Parker Legris compression fitting**.

Product Advantages

Efficient Solution	Reduces envelope dimensions
	Quick and easy to assemble, whatever the diameters and tube material
Multiple Combinations	Improved stock management
	Silicone-free
Multiple Combinations	A single connector for up to 4 different tube materials and sizes
	Example: <ul style="list-style-type: none"> • polymer tube 4 mm O.D. • copper tube 8 mm O.D. • brass tube 12 mm O.D. • braided PVC hose 12 mm I.D.
A full range of olives and nuts to optimise all assembly operations	



- Applications
- Pneumatics
 - Cooling
 - Automotive Process
 - Lubrication
 - Fluid Transmission
 - Packaging
 - Industrial Machinery

- Regulations
- DI: 97/23/EC (PED)
 - RG: 1907/2006 (REACH)
 - DI: 2002/95/EC (RoHS)
 - DI: 94/9/EC (ATEX)

Reducer Assembly Procedure

Operation	Assembly Sequence	Assembled Fitting
1 Assemble the reducer Place the reducer in the fitting body.	1 	
2 Assemble the nut and olive Place the nut and then the olive onto the tube.	2 	
3 Assemble the nut Push the tubing into the fitting until it butts against the tube reducer. Tighten the nut to the recommended torque (see opposite page).	3 	

















Complementary Brass Fittings

Assembly Configuration

The table and information given below illustrate the large number of options available with Parker Legris brass compression fittings. To these must be added the advantages specific to the original Parker Legris reducer shown on the previous page.



Brass Body

0110 Brass 			0110..60 Brass 		0110..40 Steel 	0110..70* Polymer 
	0124 Brass	0111 BNA** Brass	0124 Brass	0111 BNA** Brass	0124...40 Steel	
No olive required to assemble the plug						No olive required to assemble the tube
Brass plug: 0126	Copper, cold-rolled brass, polymer tube and barb connectors 0122 and 0165	Coiled annealed copper tube	Cold-rolled copper tube for vibration and side loading, etc.	Coiled annealed copper tube for vibration and side loading, etc.	Steel or copper tube: low/medium hydraulic pressure, lubricate before assembly	Polymer tube
						

*Assembly specifications for nut-olive 0110 ..70

This part functions as both olive and nut for flexible polymer tube assemblies:

1. Hand tighten the polymer nut-olive a few turns onto the body of the fitting; the knurling makes this easier.
2. Then introduce the polymer tube and push home into the body of the fitting.
3. Continue manually tightening the polymer nut-olive.
4. Finish tightening using a spanner until the nut body disengages and turns freely, which acts as a torque limiter.

N.B.: To avoid damaging the threads, do not insert the tube before hand tightening the nut-olive into the body of the fitting.


**Bureau de Normalisation de l'Automobile (French Automotive Bureau of Standards)

Recommended Tightening Torque


Tightening torque in daN.m =

maximum tightening torque of a **0110** nut and **0124** olive with copper, brass or steel tube.

Nut **0110** and **0110..40**



Nut **0110..60**



Ø D (mm)	ØF 0110	ØF 0110..60	max. daN.m copper or brass	ØF 0110..40	max. daN.m steel
4	10	11	0.7	10	1.5
5	12	13	0.7	12	1.5
6	13	13	1.5	13	2.5
8	14	16	1.5	14	2.5
10	19	20	1.8	19	3
12	22	22	3	22	4.5
14	24	24	3.5	24	5.5
15	24	24	4	24	6
16	27	27	5	27	7
18	30	30	6	30	9
20	32	32	6	32	10
22	36	36	7	36	12
25	41	41	8	41	13
28	42		9		


Complementary Brass Compression Fittings

0166

3-Piece Reducer



Brass



ØD1	ØD2		F	kg
4	5	0166 04 05	13	0.011
	6	0166 04 06	13	0.011
	8	0166 04 08	14	0.012
	10	0166 04 10	19	0.031
	12	0166 04 12	22	0.044
	14	0166 04 14	24	0.054
5	15	0166 04 15	24	0.056
	6	0166 05 06	13	0.010
	8	0166 05 08	14	0.012
	10	0166 05 10	19	0.030
	12	0166 05 12	22	0.044
	14	0166 05 14	24	0.053
6	16	0166 05 16	27	0.078
	8	0166 06 08	14	0.012
	10	0166 06 10	19	0.030
	12	0166 06 12	22	0.043
	14	0166 06 14	24	0.052
	15	0166 06 15	24	0.054
8	16	0166 06 16	27	0.077
	10	0166 08 10	19	0.027
	12	0166 08 12	22	0.040
	14	0166 08 14	24	0.051
	15	0166 08 15	24	0.053
	16	0166 08 16	27	0.076
10	18	0166 08 18	30	0.100
	12	0166 10 12	22	0.037
	14	0166 10 14	24	0.045
	15	0166 10 15	24	0.047
	16	0166 10 16	27	0.068
	18	0166 10 18	30	0.095
12	20	0166 10 20	32	0.107
	22	0166 10 22	36	0.144
	25	0166 10 25	41	0.209
	14	0166 12 14	24	0.043
	15	0166 12 15	24	0.043
	16	0166 12 16	27	0.066
14	18	0166 12 18	30	0.092
	20	0166 12 20	32	0.102
	22	0166 12 22	36	0.140
	25	0166 12 25	41	0.200
	16	0166 14 16	27	0.060
	18	0166 14 18	30	0.084
15	20	0166 14 20	32	0.095
	22	0166 14 22	36	0.133
	25	0166 14 25	41	0.189
	18	0166 15 18	30	0.081
	22	0166 15 22	36	0.130
	18	0166 16 18	30	0.078
16	20	0166 16 20	32	0.088
	22	0166 16 22	36	0.126
	25	0166 16 25	41	0.185
	20	0166 18 20	32	0.082
	22	0166 18 22	36	0.118
	25	0166 18 25	41	0.180
18	28	0166 18 28	42	0.176
	20	0166 20 25	41	0.168
	22	0166 22 28	42	0.168

ØD1: tube to be fitted



ØD2: for an x mm Ø fitting

Each of the above part numbers comprises:



- a reduction piece
- an olive, PN 0124
- a sleeve nut

Complementary Brass Compression Fittings



0124 Brass Olive

	Brass 	ØD		kg
		4	0124 04 00	0.001
		5	0124 05 00	0.001
		6	0124 06 00	0.001
		8	0124 08 00	0.001
		10	0124 10 00	0.003
		12	0124 12 00	0.004
		14	0124 14 00	0.005
		15	0124 15 00	0.004
		16	0124 16 00	0.006
		18	0124 18 00	0.007
		20	0124 20 00	0.009
		22	0124 22 00	0.012
		25	0124 25 00	0.017
		28	0124 28 00	0.017

0124..40 Steel Olive



	Zinc-plated steel 	ØD		kg
		4	0124 04 00 40	0.001
		6	0124 06 00 40	0.001
		8	0124 08 00 40	0.001
		10	0124 10 00 40	0.003
		12	0124 12 00 40	0.003
		14	0124 14 00 40	0.005
		15	0124 15 00 40	0.004
		16	0124 16 00 40	0.006
		18	0124 18 00 40	0.007
		20	0124 20 00 40	0.007
		22	0124 22 00 40	0.010
		25	0124 25 00 40	0.014

0111 BNA* Brass Olive



	Brass 	ØD		kg
		4	0111 04 00	0.001
		5	0111 05 00	0.001
		6	0111 06 00	0.001
		8	0111 08 00	0.001
		10	0111 10 00	0.002
		12	0111 12 00	0.002
		14	0111 14 00	0.003
		15	0111 15 00	0.003
		16	0111 16 00	0.003
*BNA: Bureau de Normalisation de l'Automobile (standards organization in the field of Automotive Process)				

Complementary Brass Compression Fittings



0110 Brass Nut

	Brass		ØD	C		F	L	kg
			4	M8x1	0110 04 00	10	11	0.005
			5	M10x1	0110 05 00	12	11	0.006
			6	M10x1	0110 06 00	13	11	0.008
			8	M12x1	0110 08 00	14	13	0.008
			10	M16x1.5	0110 10 00	19	15	0.019
			12	M18x1.5	0110 12 00	22	15	0.026
			14	M20x1.5	0110 14 00	24	15	0.029
			15	M20x1.5	0110 15 00	24	15	0.028
			16	M22x1.5	0110 16 00	27	17	0.042
			18	M24x1.5	0110 18 00	30	18	0.057
			20	M27x1.5	0110 20 00	32	18	0.057
			22	M30x1.5	0110 22 00	36	19	0.078
			25	M33x1.5	0110 25 00	41	21	0.121
			28	M36x1.5	0110 28 00	42	21	0.110



0110..40 Steel Nut

	Zinc-plated steel		ØD	C		F	L	kg
			4	M8x1	0110 04 00 40	10	11	0.004
			5	M10x1	0110 05 00 40	12	11.5	0.005
			6	M10x1	0110 06 00 40	13	12	0.008
			8	M12x1	0110 08 00 40	14	13.5	0.008
			10	M16x1.5	0110 10 00 40	19	16	0.018
			12	M18x1.5	0110 12 00 40	22	16.5	0.027
			14	M20x1.5	0110 14 00 40	24	17	0.030
			15	M20x1.5	0110 15 00 40	24	17	0.029
			16	M22x1.5	0110 16 00 40	27	18	0.042
			18	M24x1.5	0110 18 00 40	30	19	0.056
			20	M27x1.5	0110 20 00 40	32	20.5	0.061
			22	M30x1.5	0110 22 00 40	36	21.5	0.085

0110..60 Brass Long Nut

	Brass		ØD	C		F	L	kg
			4	M8x1	0110 04 00 60	11	14.5	0.007
			5	M10x1	0110 05 00 60	13	17	0.008
			6	M10x1	0110 06 00 60	13	17.5	0.011
			8	M12x1	0110 08 00 60	16	20	0.019
			10	M16x1.5	0110 10 00 60	20	23	0.032
			12	M18x1.5	0110 12 00 60	22	25	0.039
			14	M20x1.5	0110 14 00 60	24	30	0.051
			15	M20x1.5	0110 15 00 60	24	30	0.049
			16	M22x1.5	0110 16 00 60	27	32	0.070
			18	M24x1.5	0110 18 00 60	30	35	0.098
			20	M27x1.5	0110 20 00 60	32	35	0.102
			22	M30x1.5	0110 22 00 60	36	36	0.129

0110..70 Technical Polymer Nut-Olive

	Technical polymer		ØD	C		F	L	kg
			4	M8x1	0110 04 00 70	8	13	0.008
			6	M10x1	0110 06 00 70	11	15	0.002
			8	M12x1	0110 08 00 70	13	16	0.002
			10	M16x1.5	0110 10 00 70	17	19	0.004
			12	M18x1.5	0110 12 00 70	19	19	0.005
			14	M20x1.5	0110 14 00 70	22	20	0.005
			16	M22x1.5	0110 16 00 70	24	21	0.008

NB: polymer nut-olives should not be used on metal tubing.



Self-Fastening Barb Connectors for NBR Hose

This range of fittings is designed to meet the requirements of the automotive and robotics industries, combining as it does **optimum CNOMO manufacturing quality**, simple installation, reliable operation and a **long service life**.

Product Advantages

Perfect for Self-Fastening NBR Hose

- Quick and simple to install
- Compatible with the Parker Legris range of brass compression fittings
- Mechanical properties proven for use in industrial robotic installations
- Spark-resistant

Ergonomic and Time-Saving

- Fitting does not require lubrication or clamping, reducing assembly time
- Visual stop confirms installation is correct and improves operating safety
- Removal by cutting the tube
- The fitting can be re-used if necessary



Applications


- Welding Robots
- Pneumatics
- Compressed Air Systems
- Automotive Process
- Cooling

Technical Characteristics

Compatible Fluids	Coolants, compressed air						
Working Pressure	0 to 16 bar						
Working Temperature	0°C to +100°C (water) -20°C to +70°C (air)						
Tightening Torque, Type 0132	DN	6	8	10	14	18	22
	daN.m	0.7	1.5	1.8	3.5	6	7

Reliable performance is dependent upon the type of fluid conveyed and hose being used.

Component Materials



Silicone-free

Self-Fastening Hose Assembly Machine

Machine designed to assemble a barb connector and a self-fastening NBR hose.
Machine part number:
0650 00 00 05



Tube Cutting and Positioning

Cut the hose square and position the barb connector on the mounting tool.

Barb Connector Support



Press-Fitting the Tube

Activate the press-fit tool; connection is complete when the tube is fully home on the barb connector. This tool has been designed for use with 5 different diameters and is easy to operate.

Barb Connector Support






Regulations

Industrial
 DI: 2002/95/EC (RoHS), 2011/65/EC
 DI: 97/23/EC (PED)
 RG: 1907/2006 (REACH)
 CNOMO: E07.21.115N




Self-Fastening Barb Connectors for NBR Hose

0132 Self-Fastening Barb Connector for Brass Compression Fitting

	Brass		ØD	ØD1	ØD2		F	G	L	L1	ØT	kg
			6	6.3	13	0132 06 56	12	16.5	32.5	12.5	4.8	0.010
			8	6.3	13	0132 08 56	14	16.5	29.5	11.5	4.8	0.015
			10	6.3	13	0132 10 56	19	16.5	30	14	4.8	0.028
				9.5	16	0132 10 60	19	19.5	34	14	7.5	0.030
			14	9.5	16	0132 14 60	24	19.5	35.5	15	7.5	0.050
				12.7	19	0132 14 62	24	23.5	39.5	15	10	0.054
			18	12.7	19	0132 18 62	30	23.5	41.5	17	10	0.090
				15.9	23	0132 18 66	30	27	50	17	13.5	0.090
			22	19.1	27	0132 22 69	36	30.5	56.5	17	16	0.128

Polymer collar




0133..39 Self-Fastening Barb Connector with Bi-Material Seal, Male BSPP Thread

	Brass, zinc-plated steel with NBR seal		ØD1	ØD2	C		E	F	G	H	L	ØT	kg
			6.3	13	G1/8	0133 56 10 39	5.5	13	14	20	31.5	4.8	0.012
				13	G1/4	0133 56 13 39	7	17	17	20	33.5	4.8	0.018
			9.5	16	G1/4	0133 60 13 39	7	17	17	24	37.5	7.5	0.022
				16	G3/8	0133 60 17 39	9.5	22	22	24	42.5	7.5	0.038
			12.7	19	G3/8	0133 62 17 39	9.5	22	22	28	46.5	10	0.045
				19	G1/2	0133 62 21 39	10.5	27	26	28	48.5	10	0.060
			15.9	23	G1/2	0133 66 21 39	10.5	27	26	36.5	57	13.5	0.064
				23	G3/4	0133 66 27 39	11.5	32	32	36.5	59	13.5	0.095
			19.1	27	G3/4	0133 69 27 39	11.5	32	32	43	65.5	16	0.111

Thread with bi-material seal and polymer collar.

Bi-material sealing washer part number 0139 can be found in Chapter 9.

0134 Self-Fastening Barb Connector, Male BSPT Thread

	Brass		ØD1	ØD2	C		F	G	L	L1	ØT	kg
			6.3	13	R1/8	0134 56 10	14	16.5	32.5	20	4.8	0.015
				13	R1/4	0134 56 13	14	16.5	37	20	4.8	0.020
			9.5	16	R1/4	0134 60 13	14	19.5	41	24	7.5	0.022
				16	R3/8	0134 60 17	19	19.5	41.5	24	7.5	0.036
			12.7	19	R3/8	0134 62 17	19	23.5	45.5	28	10	0.038
				19	R1/2	0134 62 21	22	23.5	50	28	10	0.062
			15.9	23	R1/2	0134 66 21	22	27	58.5	36.5	13.5	0.056
				23	R3/4	0134 66 27	27	27	60.5	36.5	13.5	0.101
			19.1	27	R3/4	0134 69 27	27	30.5	67	43	16	0.108

Polymer collar

Self-fastening NBR hose is selected by nominal diameter; for example:

Barb Connector	O.D. (Tube)	Ø DN (Tube)	Self-Fastening NBR hose
0132 10 56	10	1/4	10..H 56...




Brass Adaptors

0122

Barb Connector for Hose



Brass




ØD1	ØD2		ØD3	L	L1	ØT min	kg
4	4	0122 04 04	6	37.5	22.5	3	0.004
5	4	0122 05 04	6	37.5	22.5	3	0.003
6	4	0122 06 04	6	37.5	22.5	3	0.005
	7	0122 06 07	9	37.5	22.5	6	0.007
8	6	0122 08 06	8	40	22.5	5	0.007
	7	0122 08 07	9	40	22.5	6	0.008
	10	0122 08 10	12.5	40	22.5	9	0.013
10	7	0122 10 07	9	43	22.5	6	0.010
	10	0122 10 10	12.5	43	22.5	9	0.014
12	10	0122 12 10	12.5	43	22.5	9	0.014
	13	0122 12 13	15	50	29.5	12	0.018
14	13	0122 14 13	15	52	29.5	12	0.019
	16	0122 14 16	18.5	60.5	38	15	0.308
15	13	0122 15 13	15	52	29.5	12	0.019
	16	0122 15 16	18.5	60.5	38	15	0.032
16	13	0122 16 13	15	53.5	29.5	12	0.021
	16	0122 16 16	18.5	62	38	15	0.032
18	16	0122 18 16	18.5	62	38	15	0.032
	19	0122 18 19	21.5	62	38	18	0.041
20	16	0122 20 16	18.5	64	38	15	0.034
	19	0122 20 19	21.5	64	38	18	0.038
22	19	0122 22 19	21.5	64	38	18	0.039
	19	0122 25 19	21.5	70	38	18	0.049
25	25	0122 25 25	27.5	70	38	24	0.054
28	25	0122 28 25	27.5	70	38	24	0.087

0165

Barb Connector for Flexible Tubing




Brass



ØD1	ØD2		ØD3	L	L1	ØT min	kg
4	4	0165 04 06	4.3	30	15	2	0.002
5	4	0165 05 06	4.3	30	15	2	0.010
6	4	0165 06 06	4.3	30	15	2	0.003
	6	0165 06 08	6.4	30	15	4	0.004
	8	0165 06 10	8.4	30	15	4	0.004
8	6	0165 08 08	6.4	32.5	15	4	0.006
	8	0165 08 10	8.4	32.5	15	6	0.006
	10	0165 08 12	10.7	37.5	20	8	0.009
10	8	0165 10 10	8.4	35.5	15	6	0.008
	10	0165 10 12	10.7	40.5	20	8	0.010
12	12	0165 10 14	12.7	40.5	20	8	0.012
	10	0165 12 12	10.7	40.5	20	8	0.011
12	12	0165 12 14	12.7	40.5	20	10	0.013
	14	0165 14 14	12.7	42.5	20	10	0.014
15	13	0165 15 16	13.7	42.5	20	11	0.016
16	13	0165 16 16	13.7	44	20	11	0.018




Assembly: Barb Connectors

Our barb connectors 0122 and 0165 are designed to be used with different types of hose. They are secured using the nut and olive provided with the fitting.



Brass Adaptors

0126 Plug for Compression Fitting

	Brass		ØD 		L kg	
			4	0126 04 00	10	0.001
			5	0126 05 00	10	0.003
			6	0126 06 00	10	0.003
			8	0126 08 00	11.5	0.006
			10	0126 10 00	13	0.010
			12	0126 12 00	13	0.014
			14	0126 14 00	13.5	0.020
			15	0126 15 00	13.5	0.022
			16	0126 16 00	16	0.029
			18	0126 18 00	16	0.039
			20	0126 20 00	16	0.045
			22	0126 22 00	18	0.003
			28	0126 28 00	19.5	0.108

The plug is used to blank off an outlet in a compression fitting, replacing the olive.
When an open outlet is required, simply dismantle and replace the plug with the tube olive, reusing the nut.
The plug is also reusable.

0125 Tube End Plug for Compression Fitting

Brass

ØD

C

F

L

L1

kg

4

M8x1

0125 04 00

10

12

8

0.006

6

M10x1

0125 06 00

11

13.5

9.5

0.008

8

M12x1

0125 08 00

14

14

9

0.013

10

M16x1.5

0125 10 00

17

18

11

0.025

12

M18x1.5

0125 12 00

19

18

11

0.030

14

M20x1.5

0125 14 00

22

19

11

0.041

This plug enables unused tubes to be blanked off.

The male thread on the plug has the same pitch as the female thread on the sleeve nut of a standard Parker Legris fitting. Therefore the plug screwed into the sleeve nut blanks off the tube.

To reopen the passage, simply unscrew the plug and fit the required coupler.

No further treatment of the tube is required.

0220 Hex Head Plug with Captive Sealing Washer, Male BSPP and Metric Thread

Brass, technical polymer

C

F

G

H

kg

M5x0.8

0220 19 00

8

8

5

0.002

G1/8

0220 10 00

14

14

7.5

0.011

G1/4

0220 13 00

17

17

7.5

0.019

G3/8

0220 17 00

17

22

8.5

0.024

G1/2

0220 21 00

22

27

10

0.040

Thread with pre-assembled washer.

M5: with screwdriver slot for tightening.


Maximum allowable working pressure = 20 bar.

Part number with suffix 99, maximum allowable working pressure = 250 bar, example: 0220 19 00 99.


Conforms to BNA 229 (with the exception of M5 model): BSPP thread, ISO ISO 228-1;

metric thread, ISO NFE 03-054.

0220..39 Hex Head Plug with Bi-Material Seal, Male BSPP Thread



Brass, zinc-plated steel with NBR seal



C		F	G	H1	kg
G1/8	0220 10 00 39	14	14	6.5	0.012
G1/4	0220 13 00 39	17	17	6.5	0.020
G3/8	0220 17 00 39	17	22	8	0.025
G1/2	0220 21 00 39	22	26	9	0.043
G3/4	0220 27 00 39	22	32	10	0.060
G1	0220 34 00 39	27	39.5	10.5	0.089

Plug with bi-material seal.

Bi-material washers part number 0139 can be found in Chapter 9.


Brass Adaptors

0120

Stud Standpipe, Male BSPT Thread



Brass




ØD	C		F	L	L1	kg
4	R1/8	0120 04 10	11	25.5	14	0.007
5	R1/8	0120 05 10	11	26	14.5	0.007
6	R1/8	0120 06 10	11	26.5	15	0.008
	R1/4	0120 06 13	14	31	15	0.015
8	R1/8	0120 08 10	11	28.5	17	0.009
	R1/4	0120 08 13	14	33	17	0.016
10	R3/8	0120 08 17	17	33.5	17	0.020
	R1/4	0120 10 13	14	36	20	0.018
12	R3/8	0120 10 17	17	36.5	20	0.022
	R1/2	0120 10 21	22	41	20	0.038
14	R1/4	0120 12 13	14	36	20	0.018
	R3/8	0120 12 17	17	36.5	20	0.022
16	R1/2	0120 12 21	22	41	20	0.041
	R3/8	0120 14 17	17	38	21.5	0.024
18	R1/2	0120 14 21	22	42.5	21.5	0.041
	R3/8	0120 15 17	17	38	21.5	0.023
20	R1/2	0120 15 21	22	42.5	21.5	0.041
	R3/8	0120 16 17	17	39.5	23	0.024
22	R1/2	0120 16 21	22	44	23	0.042
	R1/2	0120 18 21	22	44.5	23.5	0.042
24	R3/4	0120 18 27	27	47.5	23.5	0.071
	R3/4	0120 20 27	27	49	25	0.071
26	R3/4	0120 22 27	27	48.5	25.5	0.067
	R1	0120 22 34	36	52.5	25.5	0.116
28	R1	0120 25 34	36	57	30	0.119
30	R1	0120 28 34	36	57	30	0.138

0112

Sleeve Nut for Compression Fitting, Male Metric Thread



Brass






ØD	C		E	F	L	kg
4	M8x1	0112 04 00	7	10	13	0.005
5	M10x1	0112 05 00	7.5	11	13.5	0.007
6	M10x1	0112 06 00	7.5	11	13.5	0.006
8	M12x1	0112 08 00	8	13	15	0.008
10	M16x1.5	0112 10 00	11	17	18	0.018
12	M18x1.5	0112 12 00	11	19	18	0.021
14	M20x1.5	0112 14 00	11	22	18	0.026

This product was designed to allow the tube to be fitted directly into the tapped port in a body using a standard Parker Legris olive.
For the corresponding drawings (cavity for Parker Legris olive), please consult us.




Brass Adaptors

0128..39 Stud Standpipe with Bi-Material Seal, Male BSPP Thread

	Brass, zinc-plated steel with NBR seal 	ØD C 						E F H Kg
		4	G1/8	0128 04 10 39				7.5 13 20 0.009
			G1/4	0128 04 13 39				9 17 22 0.015
		6	G1/8	0128 06 10 39				7.5 13 21 0.010
			G1/4	0128 06 13 39				9 17 23 0.016
			G1/8	0128 08 10 39				7.5 13 23 0.011
		8	G1/4	0128 08 13 39				9 17 25 0.017
			G3/8	0128 08 17 39				12 22 26 0.033
			G1/4	0128 10 13 39				9 17 28 0.018
		10	G3/8	0128 10 17 39				12 22 29 0.034
			G1/2	0128 10 21 39				27 27 30 0.048
		14	G3/8	0128 14 17 39				12 22 30.5 0.035
			G1/2	0128 14 21 39				27 27 31.5 0.049
		18	G1/2	0128 18 21 39				27 27 33.5 0.052
			G3/4	0128 18 27 39				14 32 34.5 0.084
		22	G3/4	0128 22 27 39				14 32 36.5 0.082
			G1	0128 22 34 39				16.5 41 38 0.123
		28	G1	0128 28 34 39				16.5 41 42.5 0.149




With bi-material seal.
Bi-material washers part number 0139 can be found in Chapter 9.

0151..39 Straight Male Orientable Adaptor, with Bi-Material Seal, Male BSPP Thread

	Brass, NBR, zinc-plated steel with NBR seal 	C 						E E1 F F1 H H1 kg
		G1/8	0151 10 10 39					5.5 7 13 14 6 6.5 0.017
		G1/4	0151 13 13 39					7 8.5 17 19 6.5 9 0.036
		G3/8	0151 17 17 39					9.5 9.5 22 22 9 9 0.057
		G1/2	0151 21 21 39					10.5 10.5 27 27 10 10 0.083
		G3/4	0151 27 27 39					11.5 11.5 32 32 11 10 0.121
		G1	0151 34 34 39					13 13.5 41 41 12.5 10.5 0.230

With bi-material seal.
Bi-material washers part number 0139 can be found in Chapter 9.

0168..39 Reducer, with Bi-Material Seal, Male BSPP Thread/Female BSPP and Metric Thread




	Brass, zinc-plated steel with NBR seal 	C1 C2 						E F H kg
		G1/8	M5x0.8	0168 10 19 39				8 14 4.5 0.009
		G1/4	M5x0.8	0168 13 19 39				8 17 5 0.018
			G1/8	0168 13 10 39				8 17 5 0.012
		G3/8	G1/8	0168 17 10 39				10 19 5 0.020
			G1/4	0168 17 13 39				10 19 5 0.013
			G1/8	0168 21 10 39				12 24 7.5 0.052
		G1/2	G1/4	0168 21 13 39				12 24 7.5 0.043
			G3/8	0168 21 17 39				12 24 7.5 0.030
			G1/4	0168 27 13 39				12 32 9.5 0.099
		G3/4	G3/8	0168 27 17 39				12 32 9.5 0.086
			G1/2	0168 27 21 39				12 32 9.5 0.065

With bi-material seal.
Bi-material washers part number 0139 can be found in Chapter 9.

Brass Adaptors

0127

Tube Support for Polymer Tubing

	Brass		ØD1	ØD2		L	kg
			4	2	0127 04 00	11	0.001
				2.7	0127 04 27	11	0.001
			5	3	0127 05 03	11	0.001
				3.3	0127 05 00	11.5	0.009
			6	4	0127 06 00	11.5	0.001
				5.5	0127 08 55	14	0.001
			8	6	0127 08 00	14	0.001
				7	0127 10 07	18	0.001
			10	7.5	0127 10 75	18	0.001
				8	0127 10 00	18	0.002
				8	0127 12 08	18	0.002
			12	9	0127 12 09	18	0.002
				10	0127 12 00	18	0.001
				11	0127 14 11	18	0.002
			14	12	0127 14 00	18	0.002
				12	0127 15 12	18	0.002
			15	12	0127 15 12	18	0.002
				13	0127 16 13	18	0.003
			16	13	0127 16 13	18	0.003
				14	0127 18 14	19.5	0.003
			18	14	0127 18 14	19.5	0.003
				15	0127 20 15	20.5	0.003
			20	15	0127 20 15	20.5	0.003
				16	0127 22 16	21	0.004
			22	16	0127 22 16	21	0.004
				19	0127 25 19	25	0.007
			25	19	0127 25 19	25	0.007

This tube support guarantees good gripping, at high temperatures and pressures, by preventing collapsing of the tube.





Stainless Steel Compression Fitting Range

Stainless Steel Fittings

Stud Fittings

1805 BSPT Page 5-34	1805 NPT Page 5-34	1814 BSPP Page 5-34	1809 BSPT Page 5-35	1809 NPT Page 5-35	1820 BSPT Page 5-35	1820 NPT Page 5-35
						

Tube-to-Tube Fittings

1806 Page 5-36	1816 Page 5-36	1802 Page 5-36	1804 Page 5-36
			

Complementary Fittings

1866 Page 5-39	1824 Page 5-39	1810 Page 5-39
		

Accessories

1822 Page 5-39	1827 Page 5-39
	

Stainless Steel Compression Fittings

Manufactured in 316L stainless steel, these fittings combine all the advantages of the "universal" compression fitting with **excellent resistance** to environmental conditions and **corrosive fluids**. They are pressure and temperature-resistant and are able to withstand strong vibration and water hammer.

Product Advantages

For Use in Many Environments

Manufactured in 316L stainless steel
Suitable for all environments and fluids
Resistant to water hammer and vibration
Excellent sealing and retention of the tube
Suitable for pneumatic and medium pressure hydraulic applications
Metallic sealing guarantees maximum service life

Many Tube Options

Possibility of easily connecting different tube materials and diameters to the same fitting body
No tube support required for rigid and semi-rigid polyamide tubing below 12 mm



Applications
Food Process
Fluid Transmission
Pneumatics
Automotive Process
Petrochemical
Chemical
Offshore Oil & Gas


Technical Characteristics

Compatible Fluids	Many fluids				
Working Pressure	Vacuum to 400 bar (80 bar in corrosive environments)				
Working Temperature	-40°C to +250°C				

Tightening Torques	DN	6	8	10	12	16
	daN.m	2	3	4	6.5	9.5

Reliable performance is dependent upon the type of fluid conveyed and tubing being used. Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Maximum Bore Diameters

The table below shows the recommended compatibility of tube size, BSPP male thread and maximum bore.

Tube O.D	BSPP Thread	Max. Bore
6	G1/8	4
6-8-10	G1/4	7
10-12	G3/8	11
16	G1/2	14

Tube Length for Assembly

Minimum length of tube (L) between 2 fittings.



ØD	L mm	ØD	L mm
4	26.5	10	39
6	26	12	39
8	32	16	46.5

Regulations

DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1935/2004
RG: 1907/2006 (REACH)
DI: 94/09/EC (ATEX)
FDA: 21 CFR 177.1550
NACE MR0175: compatible materials
ISO 15156-1/-2/-3: compatible materials


Stainless Steel Compression Fittings

Installation

Fitting

The fitting comprises three parts (body/olive/nut). For assembly procedure, please see Brass Compression Fitting page.

Diagram: Assembled Fitting




A very slight distortion of the tube appears; this shows the fitting has been correctly tightened.

Orientable Elbow Assembly


Elbow
1802

Adaptor
1820



Customised Fittings

If our standard range does not meet your needs, Parker Legris can develop customised solutions for your applications.



Technical Characteristics

The use of Parker Legris stainless steel compression fittings is dependant on the tube material. Tables of recommended working pressure for the different tubes are shown below.

Recommended Tube Type

Semi-rigid polyamide or fluoropolymer tube

Stainless steel tube

"Thin Wall" cold-drawn seamless, annealed and passivated:
wall thickness tolerance ± 0.1 mm.

For use with "thin wall" stainless steel tube from 6 mm to 16 mm O.D.,
maximum wall thickness 1 mm.

Recommended Tube/Fitting Assembly Configurations

Assembled using Parker Legris olive and nut in stainless steel, with a tube support.


Stainless steel tube

Stainless steel tube: in cold-rolled straight lengths

Coiled annealed stainless tube: reduces working pressure by 35%; do not use if there is vibration.


Semi-Rigid Polyamide Tube

Maximum Working Pressure (bar)



Stainless Steel Tube

Maximum Working Pressure (bar)



Working Pressure Coefficients for Semi-Rigid Tubing



Temperature °C	-40°C / -15°C	-15°C / +30°C	+30°C / +50°C	+50°C / +70°C	+70°C / +100°C
Factor	1.8	1	0.68	0.55	0.31

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.

Stainless Steel Compression Fittings



1805

Stud Fitting, Male BSPT Thread

	ØD	C				F	F1	H max	H1	kg
	6	R1/8	1805 06 10			12	13	19.5	7.5	0.017
		R1/4	1805 06 13			14	13	19.5	7.5	0.025
	8	R1/8	1805 08 10			13	14	21	7	0.019
		R1/4	1805 08 13			14	14	21	7	0.024
	10	R1/4	1805 10 13			17	19	25.5	9	0.044
		R3/8	1805 10 17			17	19	25.5	9	0.049
		R1/2	1805 10 21			22	19	26.5	10	0.076
		R1/4	1805 12 13			19	22	26	9	0.054
	12	R3/8	1805 12 17			19	22	26	9	0.058
		R1/2	1805 12 21			22	22	27	10	0.081
	16	R3/8	1805 16 17			24	27	28.5	9.5	0.086
		R1/2	1805 16 21			24	27	28.5	9.5	0.094



1805

Stud Fitting, Male NPT Thread

	ØD	C				F	F1	H max	H1	kg
	6	NPT1/8	1805 06 11			12	13	19.5	7.5	0.018
		NPT1/4	1805 06 14			14	13	19.5	7.5	0.027
		NPT3/8	1805 06 18			19	13	20.5	8.5	0.033
		NPT1/2	1805 06 22			22	13	21.5	9.5	0.049
	8	NPT1/8	1805 08 11			13	14	21	7	0.020
		NPT1/4	1805 08 14			14	14	21	7	0.027
	10	NPT1/4	1805 10 14			17	19	25.5	9	0.045
		NPT3/8	1805 10 18			19	19	25.5	9	0.055
		NPT1/2	1805 10 22			22	19	26.5	10	0.083
	12	NPT1/4	1805 12 14			19	22	26	9	0.056
		NPT3/8	1805 12 18			19	22	26	9	0.061
		NPT1/2	1805 12 22			22	22	27	10	0.087
	16	NPT3/8	1805 16 18			24	27	28.5	9.5	0.087
		NPT1/2	1805 16 22			24	27	28.5	9.5	0.097

1814

Stud Fitting, Female BSPP Thread

	ØD	C				E	F	F1	H max	H1	kg
	6	G1/8	1814 06 10			7.5	14	13	29	17	0.023
		G1/4	1814 06 13			11	17	13	29	21	0.032
	8	G1/4	1814 08 13			11	17	14	34.5	20.5	0.033
		G3/8	1814 10 17			11.5	22	19	38.5	22	0.064
	10	G1/2	1814 10 21			15	27	19	43	26.5	0.093
		G3/8	1814 12 17			11.5	22	22	39	22	0.072
	12	G1/2	1814 12 21			15	27	22	43.5	26.5	0.100
		G1/2	1814 16 21			15	27	27	45	26	0.120

Stainless Steel Compression Fittings

1809

Stud Elbow, Male BSPT Thread

ØD	C		F	H	J	L _{max}	L1	kg
6	R1/8	1809 06 10	13	18	8	25.5	13.5	0.021
	R1/4	1809 06 13	13	23	10	25.5	13.5	0.030
8	R1/8	1809 08 10	14	20.5	10	28.5	14.5	0.027
	R1/4	1809 08 13	14	23	10	28.5	14.5	0.031
10	R1/4	1809 10 13	19	25	12	32.5	16	0.050
	R3/8	1809 10 17	19	25.5	12	32.5	16	0.058
12	R1/2	1809 12 21	19	32	18	36.5	20	0.091
	R1/4	1809 12 13	22	26	14	34	17	0.067
16	R3/8	1809 12 17	22	27	14	34	17	0.070
	R1/2	1809 12 21	22	32	18	37	20	0.098
	R3/8	1809 16 17	27	28.5	18	39.5	21	0.107
	R1/2	1809 16 21	27	31.5	18	39.5	21	0.114

1809

Stud Elbow, Male NPT Thread

ØD	C		F	H	J	L _{max}	L1	kg
6	NPT1/8	1809 06 11	13	19.5	8	25.5	13.5	0.022
	NPT1/4	1809 06 14	13	25.5	10	25.5	13.5	0.031
	NPT3/8	1809 06 18	13	28	12	27	15	0.046
	NPT1/2	1809 06 22	13	34	12	29	17	0.072
8	NPT1/8	1809 08 11	14	22	10	28.5	14.5	0.028
	NPT1/4	1809 08 14	14	25.5	10	28.5	14.5	0.033
10	NPT1/4	1809 10 14	19	27.5	12	32.5	16	0.052
	NPT3/8	1809 10 18	19	28	12	32.5	16	0.061
12	NPT1/2	1809 10 22	19	35	18	36.5	20	0.096
	NPT1/4	1809 12 14	22	28.5	14	34	17	0.069
16	NPT3/8	1809 12 18	22	29.5	14	34	17	0.074
	NPT1/2	1809 12 22	22	35	18	37	20	0.102
	NPT3/8	1809 16 18	27	31	18	39.5	21	0.110
	NPT1/2	1809 16 22	27	34.5	18	39.5	21	0.116

1820

Stud Standpipe, Male BSPT Thread

ØD	C		F	L	L1	kg
6	R1/8	1820 06 10	12	26.5	15	0.009
	R1/4	1820 06 13	14	31	15	0.017
8	R1/8	1820 08 10	12	28.5	17	0.008
	R1/4	1820 08 13	14	33	17	0.016
10	R1/4	1820 10 13	14	36	20	0.016
	R3/8	1820 10 17	17	36.5	20	0.025
12	R1/2	1820 10 21	22	41	20	0.052
	R1/4	1820 12 13	14	36	20	0.016
16	R3/8	1820 12 17	17	36.5	20	0.022
	R1/2	1820 12 21	22	41	20	0.048
	R3/8	1820 16 17	17	39.5	23	0.022
	R1/2	1820 16 21	22	44	23	0.038




1820

Stud Standpipe, Male NPT Thread

ØD	C		F	L	L1	kg
6	NPT1/8	1820 06 11	12	26.5	15	0.009
	NPT1/4	1820 06 14	14	31	15	0.019
8	NPT1/8	1820 08 11	12	28.5	17	0.009
	NPT1/4	1820 08 14	14	33	17	0.019
10	NPT1/4	1820 10 14	14	36	20	0.018
	NPT3/8	1820 10 18	19	36.5	20	0.032
12	NPT1/2	1820 10 22	22	41	20	0.060
	NPT1/4	1820 12 14	14	36	20	0.019
16	NPT3/8	1820 12 18	19	36.5	20	0.028
	NPT1/2	1820 12 22	22	41	20	0.053
	NPT3/8	1820 16 18	19	39.5	23	0.027
	NPT1/2	1820 16 22	22	44	23	0.042


Stainless Steel Compression Fittings

1806 Equal Tube-to-Tube Connector


	Stainless steel 316L		ØD			F		F1	L _{max}	L1	kg
			6	1806 06 00		12	13	34.5	11	0.025	
			8	1806 08 00		13	14	38.5	10	0.029	
			10	1806 10 00		17	19	46	13	0.066	
			12	1806 12 00		19	22	47	13	0.085	
			16	1806 16 00		24	27	51	13	0.135	

1816 Equal Bulkhead Connector


Stainless steel 316L


ØD		F	F1	L _{max}	L1 _{max}	L2	L3	ØT _{min}	kg
6	1816 06 00	13	13	28	19	7.5	17	10.5	0.034
8	1816 08 00	14	14	29	20	7	17	12.5	0.042
10	1816 10 00	19	19	33	25	9	19	16.5	0.094
12	1816 12 00	22	22	33	25	9	19	18.5	0.113
16	1816 16 00	27	27	36	28	9.5	19.5	22.5	0.179

1802 Equal Elbow




Stainless steel 316L





ØD		F	J	L _{max}	L1	kg
6	1802 06 00	13	8	25.5	13.5	0.028
8	1802 08 00	14	10	28.5	14.5	0.035
10	1802 10 00	19	12	32.5	16	0.071
12	1802 12 00	22	14	34	17	0.093
16	1802 16 00	27	18	39.5	21	0.151

1804 Equal Tee



Stainless steel 316L



ØD		F	J	L1	L/2	kg
6	1804 06 00	13	8	13.5	25.5	0.040
8	1804 08 00	14	10	14.5	28.5	0.050
10	1804 10 00	19	12	16	32.5	0.103
12	1804 12 00	22	14	17	34	0.133
16	1804 16 00	27	18	21	39.5	0.214

Complementary Stainless Steel Fittings

Reducers, Olives and Nuts

This innovative reducer system, using a full range of nuts and olives, enables **different diameters** of stainless steel, fluoropolymer or polymer tubes to be fitted onto **a single Parker Legris compression fitting**.

Product Advantages

Efficient Solution

- Reduces envelope dimensions
- Quick and easy to assemble, whatever the diameters and tube material
- Improved stock management
- Silicone-free

Multiple Combinations

- A single connector for up to 3 different tube materials and sizes.
- Example:
 - Advanced PE tubing 6 mm O.D.
 - stainless steel tubing 8 mm O.D.
 - fluoropolymer tubing 12 mm O.D. or braided PVC hose 10 mm I.D.
- A full range of olives and nuts to optimise all assembly operations




Food Process
Fluid Transmission
Pneumatics
Automotive Process
Petrochemical
Cooling & Heating
Chemical
Offshore Oil & Gas

Applications

Reducer Assembly Procedure

Operation	Assembly Sequence	Assembled Fitting
1 Assemble the reducer Place the reducer in the fitting body.	1 	
2 Assemble the nut and olive Place the nut and then the olive onto the tube.	2 	
3 Assemble the nut Push the tube into the fitting until it bottoms on the reducer. Tighten the nut to the recommended torque (see opposite page).	3 	

Assembly: Barb Connectors



Regulations

DI: 2002/95/EC (RoHS), 2011/65/EC
 DI: 97/23/EC (PED)
 RG: 1935/2004
 RG: 1907/2006 (REACH)
 DI: 94/09/EC (ATEX)
 FDA: 21 CFR 177.1550
 NACE MR0175: compatible materials
 ISO 15156-1/-2/-3: compatible materials

Our barb connector 1822 is designed to be also used with different types of hose. It is secured using the nut and olive provided with the fitting.

Stainless Steel Compression Fittings

1866 3-Piece Reducer

Stainless steel 316L		ØD1	ØD2		F	kg
		6	8	1866 06 08	14	0.011
			10	1866 06 10	19	0.028
			12	1866 06 12	22	0.040
		8	10	1866 08 10	19	0.026
			12	1866 08 12	22	0.037
			16	1866 08 16	27	0.071
		10	12	1866 10 12	22	0.034
			16	1866 10 16	27	0.065
			16	1866 12 16	27	0.061

1824 Stainless Steel Olive

Stainless steel 316L	ØD		kg
	6	1824 06 00	0.001
	8	1824 08 00	0.001
	10	1824 10 00	0.003
	12	1824 12 00	0.004
	16	1824 16 00	0.005

1810 Stainless Steel Nut

Stainless steel 316L	ØD	C		F	L	kg
	6	M10x1	1810 06 00	13	11	0.007
	8	M12x1	1810 08 00	14	13	0.008
	10	M16x1.5	1810 10 00	19	15	0.017
	12	M18x1.5	1810 12 00	22	15	0.024
	16	M22x1.5	1810 16 00	27	17	0.041


1822 Barb Adaptor for Hose

Stainless steel 316L	ØD1	ØD2		ØD3	L	L1	ØT min	kg
	6	7	1822 06 07	9	37.5	22.5	6	0.006
		6	1822 08 06	8	40	22.5	5	0.007
		7	1822 08 07	9	40	22.5	6	0.007
	8	10	1822 08 10	12.5	40	22.5	9	0.011
		7	1822 10 07	9	43	22.5	6	0.009
		10	1822 10 10	12.5	43	22.5	9	0.013
	10	10	1822 12 10	12.2	43	22.5	9	0.012
		13	1822 12 13	15	50	29.5	13	0.016

1827 Stainless Steel Tube Support

Stainless steel 316L	ØD1	ØD2		L	kg
	6	4	1827 06 00	11.5	0.001
	8	6	1827 08 00	14	0.001
	10	8	1827 10 00	18	0.001
	12	9	1827 12 09	18	0.001
	12	10	1827 12 00	18	0.001
	16	14	1827 16 00	18	0.002

This tube support is necessary when using fluoropolymer tubing at all temperatures compatible with the fitting/tubing assembly.



PL Nickel-Plated Brass Spigot Fitting Range

PL Nickel-Plated Brass Spigot Fittings

Stud Fittings

FBPL NPT Page 5-43	F3BPL BSPT Page 5-43	F4BPL BSPP Page 5-43	F8BPL Metric Page 5-43	CBPL NPT Page 5-44	C3BPL BSPT Page 5-44
					
C4BPL BSPP Page 5-44	C8BPL Metric Page 5-44	RBPL NPT Page 5-45	R3BPL BSPT Page 5-45	SBPL NPT Page 5-45	S3BPL BSPT Page 5-45
					

Banjo Fitting

COR4BPL
BSPP
Page 5-45



Tube-to-Tube Fittings

HBPL
Connector
Page 5-46



JBPL
Connector
Page 5-46



WBPL
Bulkhead
Connector
Page 5-46



Complementary Fitting

BPLM
Nut
Page 5-46



PL Nickel-Plated Brass Spigot Fittings

This range of Parker Legris has a sealing system which guarantees **excellent sealing and full flow**. PL fittings for flexible tubing are **fully re-usable**. They provide excellent compatibility with a wide variety of fluids.

Product Advantages

Rapid Assembly

Nut design allows hand tightening with soft tubing (PU, PE etc.)
Quick to assemble and disassemble
Compatible with all flexible tubes of hardness up to 90 shore A (polyurethane, polyamide, polyethylene, fluoropolymers, etc.)
Mechanical stop on the body to prevent overtightening

Performance

Special spigot design ensures full flow and excellent tensile performance
Reliable direct sealing system without the use of a seal or olive
Low and medium pressure
Nickel-plated for increased corrosion resistance



Applications

- Food Process
- Painting
- Pneumatic Systems
- Chemical
- Welding
- Laboratories
- Railway


Technical Characteristics

Compatible Fluids	Compressed air Other fluids: contact us
Working Pressure	Vacuum to 40 bar
Working Temperature	-40°C to +100°C

Tensile Performance (polyamide tubing)	Ø	2.7/4	4/6	6/8	7.5/10	8/10	10/12	11/14
	daN	11	41	52	88	67	79	149

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free


Installation

Cutting the Tube




Cut the polymer tube square.

Preparing the Connection



Slide the nut onto the tube.

Connecting the Tube



Push the tube home into the body of the fitting.

Final Assembly





Tighten the nut by hand (in the case of soft tubing) or using a spanner (for semi-rigid tubing) until it comes into contact with the end stop.

Stud Fittings



FBPL

Stud Fitting, Male NPT Thread

	Nickel-plated brass			ØD	C		F	F1	H	kg
				2.7x4	NPT1/8	FBPL2.7/4-1/8	11	8	22	0.011
				4x6	NPT1/8	FBPL4/6-1/8	11	11	25	0.016
				4x6	NPT1/4	FBPL4/6-1/4aV	11	11	29	0.026
				6x8	NPT1/8	FBPL6/8-1/8	14	13	25	0.016
				6x8	NPT1/4	FBPL6/8-1/4	12	13	29	0.023
				8x10	NPT1/4	FBPL8/10-1/4	14	16	30	0.031
				8x10	NPT3/8	FBPL8/10-3/8	14	16	31	0.040
				10x12	NPT3/8	FBPL10/12-3/8	14	17	33	0.040



F3BPL

Stud Fitting, Male BSPT Thread

	Nickel-plated brass			ØD			F	F1	H	kg
				2.7x4	R1/8	F3BPL2.7/4-1/8	10	8	20.5	0.009
				4x6	R1/8	F3BPL4/6-1/8	10	11	23.5	0.016
				4x6	R1/4	F3BPL4/6-1/4	14	11	26.5	0.025
				6x8	R1/8	F3BPL6/8-1/8	12	13	23.5	0.015
				6x8	R1/4	F3BPL6/8-1/4	14	13	26.5	0.023
				6x8	R3/8	F3BPL6/8-3/8	17	13	27.6	0.026
				7.5x10	R1/4	F3BPL7.5/10-1/4	14	16	27.5	0.031
				7.5x10	R3/8	F3BPL7.5/10-3/8	17	16	28.6	0.037
				8x10	R1/4	F3BPL8/10-1/4	14	16	27.5	0.031
				8x10	R3/8	F3BPL8/10-3/8	17	16	28.6	0.043
				10x12	R3/8	F3BPL10/12-3/8	17	17	30.1	0.036
				11x14	R3/8	F3BPL11/14-3/8	19	22	32.5	0.058

F4BPL



Stud Fitting, Male BSPP Thread

	Nickel-plated brass			ØD	C		E	F	F1	H	kg
				4x6	G1/8	F4BPL4/6-1/8	8	14	11	26	0.021
				6x8	G1/4	F4BPL6/8-1/4	9	17	13	28	0.030

These fittings are supplied with a copper seal.

F8BPL


Stud Fitting, Male Metric Straight Thread

	Nickel-plated brass			ØD	C		E	F	F1	H	kg
				6x8	M10x1	F8BPL6/8M10	7	14	13	28	0.021
				6x8	M12x1.25	F8BPL6/8M12	7	17	13	28	0.024

These fittings are supplied with a copper seal.



Fitting Dimensions

D: Tube O.D. (mm)	C: Metric Thread	D1: Bore Diameter (mm)	F: Hex (mm)	H: Tube Insertion Length (mm)
4x2.7	M6x0.75	1.5	8	4.5
6x4	M9x0.75	3	11	6.5
8x6	M11x0.75	5	13	6.5
10x7.5	M13x1	6.5	17	7
10x8	M13x1	6.5	17	7
12x10	M15x1.25	9	17	7.5
14x11	M18x1.50	9.5	22	8.5





Stud Fittings



CBPL Stud Elbow, Male NPT Thread

	Nickel-plated brass					F	H	J	L	kg
	ØD	C								
	2.7x4	NPT1/8				8	18	8	22	0.019
	4x6	NPT1/8				11	18	8	24	0.023
	4x6	NPT1/4				11	23	10	25	0.036
	6x8	NPT1/8				13	19	10	25	0.027
	6x8	NPT1/4				13	23	10	25	0.034
	8x10	NPT1/4				16	24	12	28	0.058
	8x10	NPT3/8				16	25	12	28	0.059
	10x12	NPT3/8				17	27	14	32	0.051

C3BPL Stud Elbow, Male BSPT Thread



	Nickel-plated brass					F	H	J	L	kg
	ØD	C								
	2.7x4	R1/8				8	17	8	22	0.018
	4x6	R1/8				11	17	8	24	0.022
	4x6	R1/4				11	21.5	10	25	0.031
	6x8	R1/8				13	18	10	25	0.025
	6x8	R1/4				13	21.5	10	25	0.031
	6x8	R3/8				13	23.1	12	27	0.050
	7.5x10	R1/4				16	22.5	12	28	0.057
	7.5x10	R3/8				16	23.1	12	28	0.058
	8x10	R1/4				16	21.5	12	28	0.057
	8x10	R3/8				16	23.1	12	28	0.058
	10x12	R3/8				17	25.1	14	32	0.052
	11x14	R3/8				22	25.1	16	34	0.094

C4BPL Stud Elbow, Male BSPP Thread

	Nickel-plated brass, NBR					E	F	F1	H	J	L	kg
	ØD	C										
	6x8	G1/4				7	13	13	27	12	27	0.063

These fittings are supplied with nitrile seals.

C8BPL Stud Elbow, Male Metric Straight Thread



	Nickel-plated brass, NBR					E	F	F1	H	J	L	kg
	ØD	C										
	6x8	M10x1				7	14	13	27.25	10	21.5	0.031
	6x8	M12x1				7	13	13	26	12	25	0.063

These fittings are supplied with nitrile seals.

Stud Fittings



RBPL

Stud Run Tee, Male NPT Thread

	Nickel-plated brass		ØD	C		F	H	H1	H2	J	kg
			4x6	NPT1/8	RBPL4/6-1/8	11	42	24	18	8	0.037
			4x6	NPT1/4	RBPL4/6-1/4	11	48	25	23	10	0.050
			6x8	NPT1/4	RBLP6/8-1/4	13	48	25	23	10	0.046



R3BPL

Stud Run Tee, Male BSPT Thread

	Nickel-plated brass		ØD	C		F	H	H1	H2	J	kg
			4x6	R1/8	R3BPL4/6-1/8	11	42	24	17	8	0.035
			4x6	R1/4	R3BPL4/6-1/4	11	48	25	21.5	10	0.048
			6x8	R1/8	R3BPL6/8-1/8	13	44	25	18	10	0.037
			6x8	R1/4	R3BLP6/8-1/4	13	48	25	21.5	10	0.045



SBPL

Stud Branch Tee, Male NPT Thread

	Nickel-plated brass		ØD	C		F	H	J	L	L1	kg
			4x6	NPT1/8	SBPL4/6-1/8	11	18	8	48	24	0.035
			4x6	NPT1/4	SBPL4/6-1/4	11	23	10	50	25	0.050
			6x8	NPT1/4	SBPL6/8-1/4	13	23	10	50	25	0.049



S3BPL

Branch Tee, Male BSPT Thread

	Nickel-plated brass		ØD	C		F	H	J	L	L1	kg
			4x6	R1/8	S3BPL4/6-1/8	11	17	8	48	24	0.035
			4x6	R1/4	S3BPL4/6-1/4	11	21.5	10	50	25	0.048
			6x8	R1/8	S3BPL6/8-1/8	13	18	10	50	25	0.037
			6x8	R1/4	S3BLP6/8-1/4	13	21.5	10	50	25	0.045

COR4BPL

Single Banjo, Male BSPP Thread




	Nickel-plated brass		ØD	C		E	F	F1	H	H1	L	kg
			4x6	G1/8	COR4BPL4/6-1/8	7	14	11	27	16	24	0.068
			4x6	G1/4	COR4BPL4/6-1/4	8	19	11	29	17	26	0.096
			6x8	G1/8	COR4BPL6/8-1/8	7	14	13	27	16	25	0.068
			6x8	G1/4	COR4BLP6/8-1/4	8	19	13	30	17	27	0.096

These parts are supplied with peripheral seals.
The banjo bolt is made of steel.

PL Tube-to-Tube and Complementary Fittings




HBPL

Equal Tube-to-Tube Connector

	Nickel-plated brass 	ØD		F	F1	L	kg
		2.7x4	HBPL2.7/4	7	8	24	0.010
		4x6	HBPL4/6	10	11	30	0.021
		6x8	HBPL6/8	12	13	30	0.022
		8x10	HBPL8/10	14	16	32	0.043
		10x12	HBPL10/12	16	17	36	0.056
		11x14	HBPL11/14	19	22	40	0.087




JBPL

Equal Tee

	Nickel-plated brass 	ØD		F	J	L	L1	kg
		2.7x4	JBPL2.7/4	8	8	44	22	0.024
		4x6	JBPL4/6	11	8	48	24	0.042
		6x8	JBPL6/8	13	10	50	25	0.045
		7.5x10	JBPL7.5/10	16	12	56	28	0.086
		8x10	JBPL8/10	16	12	56	28	0.085
		10x12	JBPL10/12	17	14	64	32	0.100
		11x14	JBPL11/14	22	16	68	34	0.168




WBPL

Equal Bulkhead Connector

	Nickel-plated brass 	ØD		F	F1	F2	K_{max}	L	L1	T_{min}	kg
		4x6	WBPL4/6	13	11	13	5	39	22	M9x0.75	0.030
		6x8	WBPL6/8	14	13	16	5	39	22	M11x0.75	0.032
		8x10	WBPL8/10	16	16	17	5	43	24	M13x1	0.057
		10x12	WBPL10/12	19	17	19	5	46	26	M15x1.25	0.064
		11x14	WBPL11/14	22	22	22	5	50	28	M18x1.5	0.112

BPLM

Nut

	Nickel-plated brass 	ØD	C		F	L	kg
		2.7x4	M6x0.75	BPL4M	8	10	0.003
		4x6	M9x0.75	BPL6M	11	13	0.006
		6x8	M11x0.75	BPL8M	13	13	0.008
		7.5x10	M13x1	BPL10M	16	14	0.014
		8x10	M13x1	BPL10M	16	14	0.014
		10x12	M15x1.25	BPL12M	17	16	0.012
		11x14	M18x1.5	BPL14M	22	18	0.025

Industrial Valves

Ball Valves

LIQUIfit®

Needle and Butterfly Valves

Axial Valves



Industrial Valves

Ball Valves, Universal Series

(P. 6-8)



Fluids: compressed air, slightly corrosive fluids

Materials: nickel-plated forged brass

Pressure: 40 bar

Temperature: -20°C to +80°C

DN: 4 mm to 40 mm

Ball Valves, Universal Series, Vented

(P. 6-13)



Fluids: compressed air, slightly corrosive fluids

Materials: nickel-plated forged brass

Pressure: 40 bar

Temperature: -20°C to +80°C

DN: 4 mm to 23 mm

Ball Valves, Universal Series, Lockable

(P. 6-15)



Fluids: compressed air, slightly corrosive fluids

Materials: nickel-plated forged brass, galvanised steel and epoxy locking system

Pressure: 40 bar

Temperature: -20°C to +80°C

DN: 4 mm to 23 mm

Ball Valves, Universal Customised Series

(P. 6-9)



Fluids: compressed air, many fluids

Materials: nickel-plated forged brass, choice of seal material (NBR, EPDM, FKM, PTFE...)

Pressure: 40 bar

Temperature: -20°C to +100°C

DN: 4 mm to 40 mm

Ball Valves, Universal Light Series

(P. 6-16)



Fluids: compressed air, slightly corrosive fluids

Materials: forged brass or nickel-plated forged brass

Pressure: 12 bar

Temperature: -20°C to +80°C

DN: 4 mm to 13 mm

Ball Valves, DVGW Series

(P. 6-20)



Fluids: compressed air, water, gas

Materials: nickel-plated forged brass

Pressure: 40 bar

Temperature: -40°C to +170°C

DN: 8 mm to 50 mm

Ball Valves, Standard Series

(P. 6-22)



Fluids: compatible fluids

Materials: nickel or chromium-plated brass with PTFE seal

Pressure: 35 bar

Temperature: -20°C to +130°C

DN: 8 mm to 100 mm

Ball Valves, Stainless Steel Series

(P. 6-28)



Fluids: all fluids

Materials: 316L stainless steel

Pressure: 65 bar

Temperature: -20°C to +150°C

DN: 8 mm to 50 mm

Ball Valves, Stainless Steel Light Series

(P. 6-28)



Fluids: all fluids

Materials: 316L stainless steel

Pressure: 65 bar

Temperature: -20°C to +120°C

DN: 4 mm to 10 mm

Industrial Valves

Ball Valves, High Pressure Series

[P. 6-30]



Fluids: lubricants, gases
Materials: zinc-plated brass
Pressure: 300 bar
Temperature: -15°C to +80°C
DN : 7 mm to 13 mm

Ball Valves, Mini Series

[P. 6-32]



Fluids: compressed air
Materials: technical polymer
Pressure: 10 bar
Temperature: -20°C to +80°C
DN : 4 mm to 12 mm

Ball Valves, LIQUIfit®

[P. 6-34]



Fluids: water, beverages, CO₂, inert gases
Materials: polypropylene, EPDM seal
Pressure: 10 bar
Temperature: -15°C to +100°C
Tube Ø: 1/4" and 3/8"

Needle Valves, Brass

[P. 6-37]



Fluids: compressed air, industrial fluids
Materials: shot-blasted forged brass, nickel-plated
Pressure: 120 bar
Temperature: -20°C to +100°C
DN : 4 mm to 10 mm

Needle Valves, Stainless Steel

[P. 6-41]



Fluids: all fluids
Materials: 316L stainless steel
Pressure: 400 bar
Temperature: -20°C to +180°C
DN : 3 mm to 6 mm

Butterfly Valves

[P. 6-42]



Fluids: compressed air, abrasive fluids
Materials: shot-blasted forged brass, nickel-plated
Pressure: 16 bar
Temperature: -20°C to +80°C
DN : 6 mm to 18 mm

Axial Valves

[P. 6-45]



Fluids: compressed air, industrial fluids
Materials: nickel-plated brass
Pressure: 10 bar
Temperature: -20°C to +135°C
Threads : 3/8" to 2"

Ball Valve Range

Universal and Universal Customised Series

In-Line

0402 2/2 Page 6-10
0401 2/2 Page 6-10
0400 2/2 Page 6-10
0411 2/2 Page 6-10
0414 2/2 Page 6-10



In-Line with Fixing Holes and Panel Mounting

0446 2/2 Page 6-11
6402 2/2 Page 6-11
6401 2/2 Page 6-11



Right-Angled

0472 2/2 Page 6-11
0471 2/2 Page 6-11



In-Line, 3-Way

0482 3/3 Page 6-12
0483 3/3 Page 6-12



In-Line, 3-Way with Fixing Holes and Panel Mounting

0448 3/3 Page 6-12
0452 3/2 Page 6-12



Universal Series, Vented

In-Line

0489 3/2 Page 6-13
0449 3/2 Page 6-13
0469 3/2 Page 6-13



Right-Angled

0462 3/2 Page 6-14
0461 3/2 Page 6-14



Universal Lockable Series

In-Line

0432 2/2 Page 6-15



In-Line, Vented

0439 3/2 Page 6-15
0436 3/2 Page 6-15
0437 3/2 Page 6-15



In-Line, 3-Way

0438 3/2 Page 6-15



Universal Light Series

In-Line

0492 2/2 Page 6-17
0491 2/2 Page 6-17
0490 2/2 Page 6-17



In-Line, Vented

0494 2/2 Page 6-18



In-Line with Square Stem

0497 2/2 Page 6-18
0496 2/2 Page 6-18



Ball Valve Range

DVGW Series

In-Line

BVG4-L

2/2
Page 6-21



BVGT4-L

2/2
Page 6-21



Standard Series

In-Line

4902

2/2
Page 6-23



BVGT4-C

2/2
Page 6-23



Compact

4991

2/2
Page 6-23



4992

2/2
Page 6-23



In-Line, Lockable

BVG4-LOCK

2/2
Page 6-24



In-Line, Lockable, Vented

BVG4P-LOCK

3/2
Page 6-24



Stainless Steel Series

In-Line

4832

Mountable and dismountable
2/2
Page 6-29



4812

Mountable
2/2
Page 6-29



4810

One-Piece Construction
2/2
Page 6-29



0465

Light Series
2/2
Page 6-29



High Pressure Series

In-Line

4402

2/2
Page 6-31



Mini Series

In-Line

7910

2/2
Page 6-33



7911

2/2
Page 6-33



In-Line, Vented and Accessories

7913

3/2
Page 6-33



7914

3/2
Page 6-33



7000

Page 6-33



LIQUIFIT®

In-Line

4020

2/2
Page 6-35



4021

2/2
Page 6-35



4023

2/2
Page 6-35



Right-Angled

4022

2/2
Page 6-35



Accessories

3130

Page 6-35



Ball Valves, Universal Series

This range of valves has patented **seal wear compensating** technology for **reliable** and **durable** sealing, **protecting** any system whether under pressure or **vacuum**.

Product Advantages

Durability & Reliability

Automatic seal wear compensation for long-term reliability
Robust, corrosion-resistant materials
100% leak-tested in production
Date coding to guarantee quality and traceability

Versatility & Performance

Ideal for ensuring the performance of pneumatic circuits
Customised valves for all special applications
Unequalled performance under vacuum
Smooth operation thanks to self-lubricating seals
Large range of working pressures and temperatures
Lever can be repositioned and replaced
Many configurations to satisfy all system requirements



Applications

- Pneumatics
- Vacuum
- Transportation
- Packaging
- Textile
- Sawmill
- Rubber & Plastics


Technical Characteristics

Compatible Fluids	Industrial fluids					
Working Pressure	Vacuum to 40 bar					
Working Temperature	-20°C to + 80°C					

Tightening Torques	Threads	G1/8	G1/4	G3/8	G1/2	G3/4	G1
	daN.m	0.10 to 0.20	0.10 to 0.20	0.15 to 0.25	0.20 to 0.35	0.50 to 0.70	0.50 to 0.70
	Threads	G1¼	G1½	G2			
	daN.m	0.40 to 0.60	0.80 to 1.20	0.80 to 1.20			

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99 % vacuum).

Component Materials



Silicone-free

Regulations

DI: 97/23/EC (module PED A - diameters greater than 25 mm)
DI: 2006/42/EC (Machinery Directive)
DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)

Universal Series

Installation Options

Lockable Valves

Our lockable ball valves have been developed in order to prevent potentially dangerous consequences caused by unintended operation. Lockable in different positions, this range meets international safety requirements, such as ISO 4414.

The valves are lockable:

- at one point: models 0432 and 0439
- at three points: models 0437 and 0438

Vented Valves

To stop fluid circulation and vent the circuit, 2 venting systems are provided:

- with threaded exhaust, to allow discharge of downstream media
- with pin-hole vent, for applications with no special discharge requirement

Fluid flow direction is indicated by an arrow on the valve body.

Mountable Valves

On steel plate:


- bulkhead fixing
- complete valve below bulkhead

On frame:

- assemble with bolts


On wooden panel:







- assemble with woodscrews









Universal Customised Valve Series

Based on the standard components of the universal series, this range allows the valve to be adapted to specific needs. There are 6 product versions available on request.

Product Codes			
Valve type	0402	04	10 22
0400		Thread	Suffix
0401			
0402			
...			
04 = 4 mm		10 = 1/8"	20 = blue/red
05 = 5 mm		13 = 1/4"	22 = green/blue
...		...	26 = yellow/yellow
40 = 40 mm		48 = 2"	27 = blue/green
			30 = white/red
			32 = white/green

Identification					
Each series may be easily identified by a colour marking on the lever.					
					
20	22	26	27	30	32

Suffix Specification															
Identification		Body		Lever			Ball		Stem and Wear-Compensation Seals			Seat Seals			Application Examples
Suffix on the body	Colour bands on the lever	Nickel-plated brass	Chemical nickel-plated brass	Standard	Nickel-plated brass	Chemical nickel-plated brass	Nickel-plated polished brass	Chemical nickel-plated brass	EPDM	FKM	PTFE white	Rilsan: graphite-impregnated	Filled PTFE	PTFE white	
20		•		•			•			•		•			Hydrocarbons
22		•		•				•		•			•		Industrial fluids and high temperature
26*		•			•			•			• olive			•	Corrosive liquids or high temperature
27			•			•		•		•			•		Industrial fluids and/or harsh environments
30**		•		•			•		•			•			Gaseous oxygen circuits
32		•		•				•	•				•		Water and steam circuits

*degreased **oxygen-compatible grease

A usage chart in this chapter shows which type of valve to use according to the fluid being conveyed.

Universal and Universal Customised Series

0402

2/2 In-Line Ball Valve, Female BSPP Thread



		Nickel-plated brass, NBR		C	DN		E	F	F1	H	H1	L	L1	M	kg
				G1/8	4	0402 04 10	8	-	14	35	29	44	25	48	0.094
					7	0402 07 10	8	19	19	38	31	51	27	48	0.166
				G1/4	7	0402 07 13	12	19	19	38	31	53	28	48	0.156
				G3/8	10	0402 10 17	12	24	24	45	43	59	31	69	0.244
				G1/2	13	0402 13 21	15	27	27	47	44	67	34	69	0.292
				G3/4	20	0402 20 27	16.5	32	38	63	54	80	39	108	0.655
				G1	23	0402 23 34	19	41	46	67	57	94	47	108	1.036
				G1 1/4	32	0402 32 42*	21.5	55	60	97	115	112	59	180	2.467
				G1 1/2	32	0402 32 49*	22	55	60	97	115	120	62	180	2.340
					40	0402 40 49*	22	55	55	104	-	111	55	190	2.445
				G2	40	0402 40 48*	26	70	70	104	-	122	61	190	2.614

*Models with CE marking
Maximum working pressure: 40 bar

0401

2/2 In-Line Ball Valve, Male/Female BSPP Thread







		Nickel-plated brass, NBR		C	DN		E	E1	F	H	H1	J	L	L1	M	kg
				G1/8	4	0401 04 10	8	7	14	35	29	14	45	25	48	0.094
					5	0401 05 10	8	7	19	38	31	19	51	27	48	0.160
				G1/4	7	0401 07 13	12	9	19	38	31	19	52	28	48	0.150
				G3/8	10	0401 10 17	12	11	24	45	43	24	58	31	69	0.234
				G1/2	13	0401 13 21	15	12	27	47	44	27	66	34	69	0.286
				G3/4	18	0401 18 27	16.5	12	38	63	54	39	79	39	108	0.652
				G1	23	0401 23 34	19	15	46	67	57	48	91	47	108	0.952
				G1 1/4	32	0401 32 42*	21.5	18	60	97	115	55	113	59	108	2.385

*Models with CE marking
Maximum working pressure: 40 bar

0400


2/2 In-Line Ball Valve, Male BSPP Thread



	Nickel-plated brass, NBR														
		C			E	F	H	H1	J	L	L1	M	kg		
		G1/8	4	0400 04 10	7	14	35	29	14	45	25	48	0.094		
		G1/4	7	0400 07 13	9	19	38	31	19	60	36	48	0.166		
		G3/8	10	0400 10 17	11	24	45	43	24	70	43	69	0.252		
		G1/2	13	0400 13 21	12	27	47	44	27	78	45	69	0.324		
G3/4	18	0400 18 27	12	38	63	54	39	90	50	108	0.714				
Maximum working pressure: 40 bar															

0411

2/2 In-Line Ball Valve with Connections for Use with Steel Tube




		Nickel-plated brass, NBR		ØD	DN		F	F1	H	H1	J	L	L1	M	kg
				6	4	0411 04 06	14	19	38	31	19	76	30	48	0.073
				8	6	0411 06 08	17	19	38	31	19	77	30	48	0.095
				10	7	0411 07 10	19	19	38	31	19	78	31	48	0.100
				12	10	0411 10 12	22	24	45	43	24	85	36	69	0.110

Maximum working pressure: 40 bar

0414

2/2 In-Line Ball Valve with Compression Connections



		Nickel-plated brass, NBR		ØD	DN		F	F1	H	H1	J	L	L1	M	kg
				6	4	0414 04 06	13	19	38	31	19	72	31	48	0.177
				8	6	0414 06 08	14	19	38	31	19	74	30	48	0.180
				10	7	0414 07 10	19	19	38	31	19	78	31	48	0.210
				12	10	0414 10 12	22	24	45	43	24	86	36	69	0.308

Maximum working pressure: 40 bar


Universal and Universal Customised Series

0446

2/2 In-Line Panel-Mountable Ball Valve, Female BSPP Thread



Nickel-plated brass, NBR



C	DN		E	F	F1	H	H1	H2	L	L1	M	ØT	kg
G1/8	4	0446 04 10	8	14	22	37	14	12	44	25	48	16.5	0.112
G1/4	7	0446 07 13	12	19	24	45	19	14	53	28	48	20.5	0.188
G3/8	10	0446 10 17	12	24	27	50	21	21	59	31	69	20.5	0.294
G1/2	13	0446 13 21	15	27	27	51	23	21	67	34	69	20.5	0.338

Maximum working pressure: 20 bar


*For G1/8 version, maximum panel thickness = 3 mm

6402

2/2 In-Line Ball Valve for Screw Fixing, Female BSPP Thread



Nickel-plated brass, NBR



C	DN		E	F	F1	G	H1	H2	L	L1	M	N	ØT	kg
G1/8	4	6402 04 10	8	14	14	18	18	30	44	25	48	25	4x70	0.132
G1/4	7	6402 07 13	12	19	19	19	24	31	53	28	48	31	5x80	0.216
G3/8	10	6402 10 17	12	24	24	20	30	45	59	31	69	31	5x80	0.324
G1/2	13	6402 13 21	15	27	27	20	34	47	67	34	69	34	6x100	0.404
G3/4	20	6402 20 27	16.5	32	38	27	44	52	80	39	108	43	8x125	0.830
G1	23	6402 23 34	19	41	46	27	53	56	94	47	108	51	8x125	1.290


Maximum working pressure: 40 bar

6401

2/2 In-Line Ball Valve for Screw Fixing, Male/Female BSPP Thread



Nickel-plated brass, NBR



C	DN		E	E1	F	G	H1	H2	L	L1	M	N	ØT	kg
G1/8	4	6401 04 10	8	7	14	18	18	30	45	25	48	25	4x70	0.127
G1/4	7	6401 07 13	12	9	19	19	24	31	52	28	48	31	5x80	0.212
G3/8	10	6401 10 17	12	11	24	20	30	45	58	31	69	31	5x80	0.306
G1/2	13	6401 13 21	15	12	27	20	34	47	67	34	69	34	6x100	0.394


Maximum working pressure: 40 bar

0472

2/2 Right-Angled Ball Valve, Female BSPP Thread



Nickel-plated brass, NBR



C	DN		E	F	H	H1	H2	J	L	L1	M	kg
G1/8	4	0472 04 10	8	14	35	29	18	14	34	25	48	0.096
	6	0472 06 10	8	19	38	31	20	22	37	27	48	0.183
G1/4	6	0472 06 13	12	19	38	31	24	22	38	28	48	0.191
G3/8	9	0472 09 17	12	24	45	43	27	25	46	31	69	0.260
G1/2	12	0472 12 21	15	27	47	44	33	29	49	34	69	0.312
G3/4	18	0472 18 27	16.5	38	59	51	40	39	60	39	108	0.704
G1	23	0472 23 34	19	46	63	55	47	48	72	47	108	1.062


Maximum working pressure: 20 bar

0471

2/2 Right-Angled Ball Valve, Male/Female BSPP Thread



Nickel-plated brass, NBR




C	DN		E	E1	F	H	H1	H2	J	L	L1	M	kg
G1/8	4	0471 04 10	8	7	14	35	29	19	14	34	25	48	0.096
	6	0471 06 10	8	7	19	38	31	22	22	37	27	48	0.182
G1/4	6	0471 06 13	12	9	19	38	31	25	22	38	28	48	0.187
G3/8	9	0471 09 17	12	11	24	45	43	28	25	46	31	69	0.256
G1/2	12	0471 12 21	15	12	27	47	44	32	29	49	34	69	0.300
G3/4	18	0471 18 27	16.5	12	38	59	51	37	39	60	39	108	0.682
G1	23	0471 23 34	19	15	46	63	55	44	48	72	47	108	1.020

Maximum working pressure: 20 bar

Universal and Universal Customised Series

0482

3/3 Right-Angle Ported Ball Valve, Female BSPP Thread




Nickel-plated brass, NBR		C	DN		E	F	H	H1	H2	J	L	L1	M	kg
		G1/8	4	0482 04 10	8	14	35	29	18	14	44	25	48	0.103
		G1/4	6	0482 06 13	12	19	38	31	24	22	53	28	48	0.200
		G3/8	9	0482 09 17	12	24	45	43	27	25	59	31	69	0.284
		G1/2	12	0482 12 21	15	27	47	44	33	29	67	34	69	0.346
		G3/4	18	0482 18 27	16.5	38	59	51	40	39	80	39	108	0.742
		G1	23	0482 23 34	19	46	63	55	47	48	94	47	108	1.160

Maximum working pressure: 20 bar

Closed

0483

3/3 Right-Angle Ported Ball Valve without Closed Position, Female BSPP Thread




Nickel-plated brass, NBR		C	DN		E	F	H	H1	H2	J	L	L1	M	kg
		G1/8	4	0483 04 10	8	14	35	29	18	14	44	25	48	0.102
		G1/4	6	0483 06 13	12	19	38	31	24	22	53	28	48	0.196
		G3/8	9	0483 09 17	12	24	45	43	27	25	59	31	69	0.278
		G1/2	12	0483 12 21	15	27	47	44	33	29	67	34	69	0.340
		G3/4	18	0483 18 27	16.5	38	59	51	40	39	80	39	108	0.716
		G1	23	0483 23 34	19	46	63	55	47	48	94	47	108	1.066

Maximum working pressure: 20 bar

Closed

0448

3/2 Panel-Mountable Right-Angled Ball Valve, Female BSPP Thread



Nickel-plated brass, NBR		C	DN		E	F	F1	H	H1	H2	H3	J	L	L1	M	ØT	kg
		G1/8	4	0448 04 10	8	14	22	37	14	18	12	14	44	25	48	16.5	0.126
		G1/4	6	0448 06 13	12	19	24	45	19	24	14	22	53	28	48	20.5	0.230
		G3/8	9	0448 09 17	12	24	27	50	21	27	21	25	59	31	69	20.5	0.328
		G1/2	12	0448 12 21	15	27	27	51	23	33	21	29	67	34	69	20.5	0.392
		Maximum working pressure: 20 bar															
		*For G1/8 version: maximum panel thickness = 3 mm															

Closed

0452

3/2 Panel-Mountable Equal Plane Ball Valve, Female BSPP Thread



Nickel-plated brass, NBR		C	DN		E	F	F1	H	H1	H2	J	K	L	ØT	kg
		G1/8	4	0452 04 10	8	14	22	39	10	8	16	18	25	19	0.130
		G1/4	6	0452 06 13	12	19	24	40	11	11	23	24	28	20	0.206
		Maximum working pressure: 20 bar													
		Closed													


Universal Series, Vented

0489

3/2 In-Line Vented Ball Valve, Female BSPP and Metric Thread



Nickel-plated brass, NBR



C	C1	DN		E	F	F1	H	H1	H2	L	L1	M	ØT	kg
G1/4	M5x0.8	7	0489 07 13	12	24	24	46	43	17	59	31	69	2	0.270
G3/8	M5x0.8	10	0489 10 17	12	24	24	46	43	17	59	31	69	2	0.243
G1/2	G1/8	13	0489 13 21	15	27	27	47	44	24	67	34	69	2	0.310
G3/4	G1/4	18	0489 18 27	16.5	32	38	63	54	33	80	39	108	2.5	0.670
G1	G1/4	23	0489 23 34	19	41	46	67	57	37	94	47	108	3	1.050


Maximum working pressure: 40 bar

0449

3/2 Panel-Mountable In-Line Ball Valve, Female BSPP and Metric Thread



Nickel-plated brass, NBR



C	C1	DN		E	F	F1	H	H1	H2	H3	L	L1	M	ØT	kg
G1/4	M5x0.8	7	0449 07 13	12	24	27	50	20	17	21	59	31	69	2.5	0.313
G3/8	M5x0.8	10	0449 10 17	12	24	27	50	20	17	21	59	31	69	2.5	0.291
G1/2	G1/8	13	0449 13 21	15	27	27	52	23	24	21	67	34	69	4	0.352


Maximum working pressure: 20 bar

0469

3/2 In-Line Vented Ball Valve, Female BSPP Thread



Nickel-plated brass, NBR




C	DN		E	F	F1	H	H1	L	L1	M	ØT	kg
G1/8	4	0469 04 10	8	14	14	35	29	44	25	48	1.5	0.092
G1/4	7	0469 07 13	12	24	24	46	43	59	31	70	2	0.268
G3/8	10	0469 10 17	12	24	24	46	43	59	31	70	2	0.246
G1/2	13	0469 13 21	15	27	27	47	44	67	34	70	2	0.294
G3/4	18	0469 18 27	16.5	32	38	63	54	80	39	108	2.5	0.668
G1	23	0469 23 34	19	41	46	67	57	94	47	108	3	1.026


Maximum working pressure: 40 bar

Operation of Vented Ball Valves

With vent connected to a tube = collection of purged media



With vent connected to a silencer = noiseless discharge to atmosphere



You will find our ranges of fittings, tubing and silencers in Chapters 1, 3 and 9.


Universal Series, Vented

0462

3/2 Right-Angled Ball Valve with Vent, Female BSPP Thread



Nickel-plated brass, NBR



C	DN		E	F	H	H1	H2	J	L	L1	M	kg
G1/8	6	0462 06 10	8	19	38	31	20	22	37	27	48	0.192
G1/4	6	0462 06 13	12	19	38	31	24	22	38	28	48	0.185
G3/8	9	0462 09 17	12	24	45	43	27	25	46	31	69	0.261
G1/2	12	0462 12 21	15	27	47	44	33	29	49	34	69	0.312
G3/4	18	0462 18 27	16.5	38	59	51	40	39	60	39	108	0.698
G1	23	0462 23 34	19	46	63	55	47	48	72	47	108	1.066


Maximum working pressure: 20 bar

0461

3/2 Right-Angled Ball Valve with Vent, Male/Female BSPP Thread



Nickel-plated brass, NBR




C	DN		E	E1	F	H	H1	H2	J	L	L1	M	kg
G1/8	6	0461 06 10	8	7	19	38	31	20	22	37	27	48	0.182
G1/4	6	0461 06 13	12	9	19	38	31	24	22	38	28	48	0.186
G3/8	9	0461 09 17	12	11	24	45	43	27	25	46	31	69	0.257
G1/2	12	0461 12 21	15	12	27	47	44	33	29	49	34	69	0.304
G3/4	18	0461 18 27	16.5	12	38	59	51	40	39	60	39	108	0.648


Maximum working pressure: 20 bar

Operation of Right-Angled Vented Ball Valves

With pin-hole vent = purge to atmosphere without silencer




Operation of Lockable Vented Ball Valves



Removable lever: where the lever is obstructed in its movement, it can be refitted the opposite way.

Operation of 3/2 Lockable Valves

Drilled below and square in the horizontal plane, these valves provide a connection between: either port 1 and port 2, or port 2 and port 3.



Removable lever: where the lever is obstructed in its movement, it can be refitted the opposite way.

Universal Series, Lockable

0432

2/2 In-Line Lockable Ball Valve, Female BSPP Thread



Nickel-plated brass, NBR

C	DN		E	F	F1	H	H1	L	L1	M	kg
G1/8	4	0432 04 10	8	19	19	59	54	51	27	69	0.415
G1/4	7	0432 07 13	12	19	19	59	54	59	28	69	0.396
G3/8	10	0432 10 17	12	24	24	60	55	59	31	69	0.460
G1/2	13	0432 13 21	15	27	27	62	57	67	34	69	0.522
G3/4	20	0432 20 27	16.5	32	38	66	56	80	39	108	0.800
G1	23	0432 23 34	19	41	46	70	59	94	47	108	1.186



Maximum working pressure: 40 bar
Handle is not removable.
Fixed and mobile plates: zinc-plated steel.

0439

3/2 In-line Vented Lockable Ball Valve, Female BSPP Thread



Nickel-plated brass, NBR





C			E	F	F1	H	H1	L	L1	M	ØT	kg
G1/8	4	0439 04 10	8	19	19	59	54	51	27	69	2	0.410
G1/4	7	0439 07 13	12	19	24	60	55	59	31	69	2	0.480
G3/8	10	0439 10 17	12	24	24	60	55	59	31	69	2	0.460
G1/2	13	0439 13 21	15	27	27	62	57	67	34	69	2	0.514
G3/4	18	0439 18 27	16.5	32	38	66	56	80	39	108	2.5	0.810
G1	23	0439 23 34	19	41	46	70	59	94	47	108	3	1.185

Maximum working pressure: 40 bar
Handle is not removable.
Fixed and mobile plates: zinc-plated steel.

0436

3/2 In-Line Lockable Ball Valve with Threaded Exhaust Port, Female BSPP and Metric Thread






	Nickel-plated brass, NBR												
													
													
	C	C1	DN		E	F	F1	H	H1	L	L1	M	kg
	G3/8	M5x0.8	10	0436 10 17	12	24	24	60	17	60	32	69	0.475
	G1/2	G1/8	13	0436 13 21	15	27	27	60	24.5	67.5	34.5	69	0.500
G3/4	G1/4	18	0436 18 27	16.5	32	38	69.5	33	80	39.5	108	0.850	
G1	G1/4	23	0436 23 34	19	32	38	69.5	33	80	39.5	108	1.215	
Maximum working pressure: 40 bar Handle is not removable. Fixed and mobile plates: zinc-plated steel.													

0437

3/2 In-line Vented 3-Point Lockable Ball Valve, Female BSPP Thread







	Nickel-plated brass, NBR												
	C			E	F	F1	H	L	L1	M	ØT	kg	
	G1/4	7	0437 07 13	12	24	24	60	59	32	69.5	2	0.476	
	G3/8	10	0437 10 17	12	24	24	60	60	32	69.5	2	0.456	
	G1/2	13	0437 13 21	15	27	27	60	67.5	34.5	69.5	2	0.510	
	G3/4	18	0437 18 27	16.5	32	38	69.5	80	39.5	108.5	2.5	0.820	
	G1	23	0437 23 34	19	41	46	73	94.5	47.5	108.5	3	1.192	
Maximum working pressure: 40 bar Handle is not removable. Fixed and mobile plates: zinc-plated steel.													

0438

3/2 Right-Angled 3-Point Lockable Ball Valve, Female BSPP Thread



	Nickel-plated brass, NBR												
		C			E	F	H	H1	J	L	L1	kg	
		G3/8	9	0438 09 17	12	38	76	34	39	73	35	0.970	
		G1/2	12	0438 12 21	15	38	76	37	39	78	38	0.947	
		G3/4	18	0438 18 27	16.5	38	76	40	39	80	40	0.905	
		G1	23	0438 23 34	19	46	80	47	48	94	47	1.295	
Maximum working pressure: 20 bar Fixed plate: zinc-plated steel, mobile plate: steel, grey epoxy-coated. Removable handle: where the handle is obstructed in its movement, it can be refitted opposite the original position.													

Ball Valves, Universal Light Series

Using the Universal Series technology, the Parker Legris light series valves offer the advantages of **compactness**, **ease of operation** and **long-term reliability**.

Product Advantages

Easy-to-Use	<p>Ease of operation due to the low friction design</p> <p>The short levers may be repositioned and exchanged</p> <p>Extremely compact</p> <p>Wide range of configurations</p>
Maximum Efficiency	<p>Excellent performance under vacuum</p> <p>Full flow</p> <p>Chemical nickel-plated brass with high phosphorous content for outstanding corrosion resistance</p> <p>Automatic seal wear compensation system</p>
Reliability	<p>Tried-and-tested technology</p> <p>Forged brass provides mechanical strength and long service life</p> <p>100% leak-tested in production</p> <p>Date coding to guarantee quality and traceability</p>



Applications

- Vacuum
- Transportation
- Packaging
- Textile
- Pneumatics
- Sawmills
- Rubber & Plastics


Technical Characteristics

Compatible Fluids	Compressed air Other fluids: see compatibility chart at the end of this chapter
Working Pressure	Vacuum to 12 bar
Working Temperature	-20°C to +80°C

Tightening Torques	Threads	G1/8	G1/4	G3/8	G1/2	G3/4
	daN.m	0.10 to 0.20	0.10 to 0.20	0.15 to 0.25	0.20 to 0.35	0.50 to 0.70

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).


Component Materials




Silicone-free

Regulations


DI: 97/23/EC (module PED A - diameters greater than 25 mm)
 DI: 2006/42/EC (Machinery Directive)
 DI: 2002/95/EC (RoHS)
 RG: 1907/2006 (REACH)



C	(DN)		E	F	H	L	L1	M	kg
G1/4	4	0492 04 13	9	17	34	39.5	17	35	0.073
G3/8	7	0492 07 17	11	22	38	45	20	43	0.128
G1/2	10	0492 10 21	12	24	44	54	25	50	0.162
G3/4	13	0492 13 27	14	30	46	62	28	50	0.240


Technical polymer handle


Technical polymer handle




C	DN		E	F	H	L	L1	M	kg
G1/4	4	0492 04 13 64	9	17	36	39.5	17	25	0.090

Short handle in zamak




C	DN		E	E1	F	H	L	L1	M	kg
G1/4	4	0491 04 13	9	7	17	34	39.5	17	35	0.070
G3/8	7	0491 07 17	11	8	22	38	45	20	43	0.124
G1/2	10	0491 10 21	12	10	24	44	53	24	50	0.160
G3/4	13	0491 13 27	14	12	30	46	59	25	50	0.238


Technical polymer handle



C	DN		E	E1	F	H	L	L1	M	kg
G1/4	4	0491 04 13 64	9	7	17	36	39.5	17	25	0.092

Short handle in zamak




C	DN		E	F	H	L	L1	M	kg
G1/4	4	0490 04 13	7	17	34	39	17	35	0.070
G3/8	7	0490 07 17	8	22	38	44	20	43	0.109
G1/2	10	0490 10 21	10	24	44	53	24	50	0.160
G3/4	13	0490 13 27	12	30	46	59	25	50	0.233


Technical polymer handle

Universal Light Series


0494

2/2 In-Line Ball Valve, 2 Vent Plugs, Female BSPP Thread



	C	DN		E	F	F1	H	L	L1	L2	M	kg
	G3/8	7	0494 07 17	11	22	16	38	60	20	15	43	0.178
Technical polymer handle												


Nickel-plated brass, NBR




0497

2/2 Ball Valve, Square Stem, Female BSPP Thread



	C	DN		E	F	H	J	L	L1	kg
	G1/4	4	0497 04 13	9	17	25	7	39	17	0.066
	G3/8	7	0497 07 17	11	22	26	7	45	20	0.122
	G1/2	10	0497 10 21	12	24	29	10	54	25	0.148
	G3/4	13	0497 13 27	14	30	30	10	62	28	0.230


Brass, NBR




0496

2/2 Ball Valve, Square Stem, Male/Female BSPP Thread



	C	DN		E	E1	F	H	J	L	L1	kg
	G1/4	4	0496 04 13	7	9	17	25	7	39	17	0.065
	G3/8	7	0496 07 17	8	11	22	26	7	45	20	0.118
	G1/2	10	0496 10 21	10	12	24	29	10	53	24	0.150
	G3/4	13	0496 13 27	12	14	30	30	10	59	28	0.222

Brass, NBR





Ball Valves, DVGW Series

The combination of long threads, a reinforced sealing system and **DVGW** certification makes this valve perfect for the **transmission of gas and water**.

Product Advantages

Reliability & Sealing

Stem prevented from being ejected in the event of overpressure
Two stem seals to prevent leakage
Date coding to guarantee quality and traceability

Optimum Performance

Full flow minimises pressure drop
Nickel-plated brass provides improved corrosion resistance and increased chemical compatibility
Can be operated at very low temperatures

Long Threads

Excellent fitting compatibility:

- dimensions compliant with DIN 3357
- BSPP threads compliant with DIN 2999/ISO 228



Applications


- Robotics
- Pneumatics
- Water & Gas Handling
- Machine Tools
- Textile
- Wood Industry

Technical Characteristics

Compatible Fluids	Compressed air, water, gas
Working Pressure	1/4" to 2": 0 to 40 bar
Working Temperature	-40°C to +170°C

Reliable performance is dependent upon the type of fluid conveyed.


Component Materials




Silicone-free

Working Pressure and Temperature

Pressure - Temperature



Pressure Drop



Regulations

Industrial
DI: 97/23/EC
(PED B+D module EC 1115)

Water
DVGW: W 570-1
DIN EN 13228
BGA KTW
DVGW: W270


Gas
DIN EN 33

DVGW Series

BVG4-L 2/2 In-Line Ball Valve, Female BSPP Thread



Nickel-plated brass, PTFE




C	DN		E	F	ØG	H	L	M	kg
G1/4	8	BVG4-1/4L	12	20	25	38	50	82	0.150
G3/8	10	BVG4-3/8L	12	20	25	38	60	82	0.150
G1/2	15	BVG4-1/2L	15.5	25	32.5	43	75	100	0.255
G3/4	20	BVG4-3/4L	17	32	39	50	80	120	0.390
G1	25	BVG4-1L	21	41	47.5	54	90	120	0.590
G1¼	32	BVG4-1,1/4L	23	50	59	73	110	158	0.980
G1½	40	BVG4-1,1/2/4L	23	55	71.5	79	120	158	1.205
G2	50	BVG4-2L	26.5	70	86	86	140	158	1.960

BVGT4-L 2/2 In-Line Ball Valve, Female BSPP Thread



Nickel-plated brass, PTFE



C	DN		E	F	ØG	H	L	M	kg
G1/4	8	BVGT4-1/4L	12	20	25	39	50	50	0.150
G3/8	10	BVGT4-3/8L	12	20	25	39	60	50	0.150
G1/2	15	BVGT4-1/2L	15.5	25	32.5	43	75	50	0.230
G3/4	20	BVGT4-3/4L	17	32	39	47	80	60	0.350
G1	25	BVGT4-1L	21	41	47.5	51	90	60	0.550

Compact lever

Ball Valves, Standard Series

This range of valves with **fluoropolymer seals**, available in compact, standard and lockable series, covers many **industrial applications** for which the fluids conveyed and working temperatures require this seal material.

Product Advantages

Optimised Installation

- Full fluid flow
- Long or butterfly lever
- Corrosion resistance
- A lockable version for operational safety
- Good value/performance ratio

Wide Compatibility

- Numerous compatible fluids
- Can be used for low and medium pressure applications
- Surface treatment for corrosion protection



Applications


- Machine Tool
- Agricultural Machinery
- Textile
- Pneumatics
- Plumbing
- Air Conditioning
- Heating

Technical Characteristics

Model	Standard and Lockable Series	Compact Series
Compatible Fluids	Compressed air, gas, water, water vapour, oil and all fluids compatible with the component materials	
Working Pressure	0 to 30 bar	0 to 35 bar
Working Temperature	-20°C to +130°C	-10°C to +90°C

Reliable performance is dependent upon the type of fluid conveyed.

Component Materials



Silicone-free

Regulations

Industrial

DI: 97/23/EC (module PED A - EC diameters greater than 25 mm)

DI: Machinery Directive 2006/42/EC

DI: 2002/95/EC (RoHS)


RG: 1907/2006 (REACH-I)


DI: 89/392/EC

Standard Series


4902


2/2 Standard In-Line Ball Valve, Female BSPP Thread





Nickel-plated brass, PTFE



C	DN		PN	E	F	H	L	M	kg
G1/4	10	4902 10 13	30	11	20	43	51.5	98	0.154
G3/8	10	4902 10 17	30	11.4	20	43	51.5	98	0.138
G1/2	15	4902 15 21	30	13.5	25	47	55	98	0.202
G3/4	20	4902 20 27	30	12.5	31	58	57.5	122	0.322
G1	25	4902 25 34	30	15	38	60	69.5	122	0.468
G1¼	32	4902 32 42*	25	17	48	77	81.5	153	0.794
G1½	40	4902 40 49*	25	18	54	83	95	153	1.082
G2	50	4902 50 48*	25	22	66	95	113	162	1.787
G2½	65	4902 65 47*	30	22	85	132	136	255	4.500
G3	80	4902 80 46*	30	25	99	140	157	255	5.840
G4	100	4902 01 45*	30	29	125	154	191	255	9.040

*Models with CE marking





Model from 2½": double stem seal in FPM

Working temperature: -40°C to +170°C

BVGT4-C

2/2 Standard In-Line Ball Valve, Female BSPP Thread






	<p>Sand-blasted nickel-plated brass, PTFE</p> 	C			E	F	G	H	L	M	kg
		G1/4	8	BVGT4-1/4C	9	20	25	40	39	50	0.130
		G3/8	10	BVGT4-3/8C	9	20	25	40	39	50	0.120
		G1/2	15	BVGT4-1/2C	11	25	32.5	44	50	50	0.180
		G3/4	20	BVGT4-3/4C	12	31	39	49	54	50	0.265
		G1	25	BVGT4-1C	14	38	47.5	53	67	50	0.390
Compact lever											

4991

2/2 Standard Compact In-Line Ball Valve, Male/Female BSPP Thread






	Chromium-plated brass, PTFE 	C	DN		E	E1	F	H	L	L1	M	kg
		G1/8	6	4991 00 10	10	10	21	30	41.5	10	24	0.091
		G1/4	8	4991 00 13	11	11	21	30	41.5	11	24	0.087
		G3/8	8	4991 00 17	11	11	21	30	41.5	10.5	24	0.087
		G1/2	10	4991 00 21	13	13	25	32	49	12.5	24	0.134

4992

2/2 Standard Compact In-Line Ball Valve, Female BSPP Thread




	Chromium-plated brass, PTFE 	C	DN		E	F	H	L	L1	M	kg
		G1/8	6	4992 00 10	10	21	30	41.5	10	24	0.110
		G1/4	8	4992 00 13	11	21	30	41.5	11	24	0.106
		G3/8	8	4992 00 17	11	21	30	41.5	10.5	24	0.094
		G1/2	10	4992 00 21	13	25	32	49	12.5	24	0.142


Standard Series

BVG4-LOCK

2/2 In-Line Lockable Ball Valve, Female BSPP Thread



Sand-blasted nickel-plated brass,
PTFE




C	DN		E	F	H	L	L1	M	kg
G1/4	8	BVG4-1/4LOCK	12	20	47.5	45	22.5	96	0.154
G3/8	10	BVG4-3/8LOCK	12	20	47.5	45	22.5	96	0.171
G1/2	15	BVG4-1/2LOCK	15.5	25	52	59	29.5	96	0.238
G3/4	20	BVG4-3/4LOCK	17	31	59.5	64	32	117	0.370
G1	25	BVG4-1LOCK	21	40	63.5	81	40.5	117	0.580

BVG4P-LOCK

2/2 In-Line Lockable Vented Ball Valve, Female BSPP Thread



Sand-blasted nickel-plated brass,
PTFE



C	DN		E	F	H	L	L1	M	kg
G1/4	8	BVG4P-1/4LOCK	12	20	47.5	45	22.5	96	0.155
G3/8	10	BVG4P-3/8LOCK	12	20	47.5	45	22.5	96	0.172
G1/2	15	BVG4P-1/2LOCK	15.5	25	52	59	29.5	96	0.239
G3/4	20	BVG4P-3/4LOCK	17	31	59.5	64	32	117	0.371
G1	25	BVG4P-1LOCK	21	40	63.5	81	40.5	117	0.581

Ball Valves:

Usage Chart

The chart below shows the compatibility between valves and fluids along with their pressure and temperature characteristics.

Certain models have a maximum working pressure which differs from that given in this table. In this case, the pressure is shown in the heading for the model number in question.

N.B.: Above 32 mm or 1¼" diameters, divide the maximum pressure by 2.

If the fluid you are using is not shown in this chart, please contact us.

Chemical Description	Maximum Pressure (bar)	Temperature °C		Universal and Light Series	Standard Series	DVGW series	Customised Series					
		Min.	Max.				20	22	26	27	30	32
"Aromatic" hydrocarbons	20	-20	+60					●				
Acetone and other ketones	20	-20	+60									●
Acetophenone	20	-20	+60									●
Acetylene - Acetone	20	-20	+60									●
Acetylene (gas)	20	-20	+60	●	●	●						
Alcohol (100%)	20	-20	Boiling									●
Aluminium (liquid suspension, thick)	40	-20	+90	●	●	●						
Amyl alcohol	20	-20	Boiling									●
Animal fats, greases	20	+5	+200		●	●			●			
Antifreeze or glycol (diluted)	40	-20	+40	●	●	●						
Argon (gas) Ar	20	-20	+60	●	●	●						
Barium - Hydroxide	20	-20	+40									●
Benzaldehyde	20	-20	+60									●
Benzene	20	-20	+60					●				
Benzyl alcohol	20	-20	Boiling					●				
Borax (pastes or solutions)	20	-20	+60									●
Brake fluids (automobile)	20	-20	+90									●
Bromochlorotrifluorethane	20	-20	+60		●	●			●			
Butadiene (hydrocarbon)	20	-20	+60							●		
Butane	20	-20	+60	●	●	●						
Butanol	20	-20	Boiling					●				
Butyl alcohol	20	-20	Boiling					●				
Butylene (hydrocarbon)	20	-20	+60					●				
Carbon dioxide gas CO ₂	40	-20	+60	●	●							
Castor oil	40	-20	+90	●	●							
Compressed air	20	-25	+180					●				
Creosotes	20	-20	+60							●		
Cresols	20	-20	+60							●		
Crude oil	20	-20	+40				●					
Cutting oil	40	-20	+90	●	●							
Decalin (hydrocarbon, solvent)	20	-20	+60							●		
Detergents (solutions)	20	-20	+100									●
Diacetone alcohol	20	-20	Boiling									●
Diesel oils	40	-20	+90	●	●							
Di-Esters	20	-20	+90					●				
Di-Isobutylene	20	-20	+60							●		
Di-Pentane	20	-20	+60					●				

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.

Ball Valves: Usage Chart

Chemical Description	Max. Pressure (bar)	Temperature °C		Universal and Light Series	Standard Series	DVGW Series	Customised Series					
		Min.	Max.				20	22	26	27	30	32
Di-Pentene (solvents, varnish)	20	-20	+60					●				
Di-Phenyl-Oxide (thin detergents)	20	-20	+60							●		
Distilled water	40		+90	●	●	●						
Edible fats	20	+5	+200		●				●			
Edible oils	20	+5	+200		●				●			
Erytrene (see Butadiene)	20	-20	+60							●		
Ethane (gas) CH ₂ CH ₃	20	-20	+60	●	●							
Ethane (hydrocarbon gas)	20	-20	+60							●		
Ethyl alcohol	20	-20	+60									●
Ethylene glycol (antifreeze) - see Glycols	20	-20	+120									●
Fatty alcohols	20	-20	Boiling					●				
Fuel oils	40	-20	+40	●	●	●						
Fuels-Diesels	40	-20	+40	●	●							
Gaseous oxygen (ambient air)	20	-20	+40								●	
Glycerine	20	-20	+40	●	●							
Glycol (for antifreeze, lubricants)	40	-20	+40	●	●							
Graphite in suspension in water, oils and greases	40	-20	+90	●	●							
Greases (from petroleum)	40	-20	+90	●	●							
Helium (gas)	20	-20	+60								●	
Heptanal	20	-20	+50	●	●							
Hexane (solvent)	20	-20	+60								●	
Hydraulic oils (petroleum-based)	40	-20	+90	●	●							
Hydrogen (gas)	20	-20	+60								●	
Inks	20	-20	+60							●		
Insecticides	20	0	+40	●	●	●						
Iso-Butane (aliphatic hydrocarbon)	20	-20	+60							●		
Iso-Octane	20	-20	+60							●		
Isopropyl alcohol	20	-20	Boiling									●
Krypton (gas) Kr	20	-20	+60	●	●	●						
Light water	40		+80	●	●	●						
Lighting gas	20	-20	+40			●						
Methane (gas) CH ₄	20	-20	+60	●	●	●						
Methanol	20	-20	Boiling									●
Methyl alcohol	20	-20	Boiling									●
Methylated spirit	40	-20	+40	●	●	●						
Mineral oils	40	-20	+90	●	●							
Natural gas	20	-20	+40			●						
Natural waxes (vegetable, beeswax, carnauba, Chinese, lignite)	40	-20	+90							●		
Neatsfoot oil	40	-20	+90	●	●	●						
Neon (Gas) Ne	20	-20	+60	●	●	●						
Nitrogen (gas) N ²	40	-20	+90	●	●	●						
Oil (petroleum-based) and water emulsions	40	-20	+90	●	●	●						

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.

Ball Valves: Usage Chart

Chemical Description	Max. Pressure (bar)	Temperature °C		Universal and Light Series	Standard Series	DVGW Series	Customised Series					
		Min.	Max.				20	22	26	27	30	32
Oils "synthetic"	20	-20	+100									●
Ordinary petrol	20	-20	+40	●	●							
Oxygenated water	40	-20	+30				●					
Paints and relevant solvents	20	-20	+60		●	●			●			
Paraffin oil	40	-20	+90	●	●	●						
Paraffins	20	-20	+60	●	●	●						
Pentane (liquid hydrocarbon)	20	-20	+60	●	●	●						
Pentanol 1 and 2	20	-20	Boiling									●
Petrol "super"	20	-20	+40				●					
Petroleum mineral oils	20	-20	+160					●				
Phenol (aqueous or alcoholic)	20	-20	+60		●	●			●			
Propane	20	-20	+60	●	●	●						
Propanol 1 and 2	20	-20	Boiling									●
Propanone 2	20	-20	+60									●
Propene or Propylene	20	-20	+60					●				
Propyl alcohol	20	-20	Boiling									●
Propylene or Propene	20	-20	+60					●				
Rapeseed oil	40	-20	+90	●	●							
Saponifying liquids	20	-20	+30	●	●	●						
Seawater	40		+80	●	●	●						
Seawater (high temperature)	20		+150			●				●		
Soaps	20	-20	+100									●
Soaps (liquid or paste)	40	-20	+40	●	●	●						
Sodium carbonate (with water)	20	0	+40	●	●	●						
Starch (gels or pastes)	40	+10	+40	●	●	●						
Steam	20	-20	+150									●
Toluene (terpenic hydrocarbon)	20	-20	+60		●	●			●			
Trichlorethylene	20	-20	+65					●				
Turpentine	20	-20	+50	●	●	●						
Varnish and paints	20	-20	+60		●	●			●			
Vaseline	40	-20	+60	●	●	●						
Vaseline oil	40	-20	+90	●	●	●						
Water (carbonated)	40		+90	●	●	●						
Water (high temperature)	20		+150			●						●
Xenon (gas) Xe	20	-20	+60	●	●	●						
Xylene	20	-20	+60					●				

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.

Ball Valves, Stainless Steel Series

Stainless steel series ball valves can withstand **corrosive fluids** and **environments**.

With full flow, high pressure and temperature capabilities, these valves are suitable for many applications.

Product Advantages

Reliability

- Full flow
- Excellent chemical compatibility
- High resistance to pressure/temperature
- Light series version: 100% leak-tested in production, date coding to guarantee quality and traceability

Versatility

- Three in-line versions:
 - One-piece: cannot be disassembled
 - 3-piece: easily disassembled for maintenance and cleaning
 - Light Series: for maximum compactness
- Fixing plate: 4812 and 4832
 - Through-bulkhead fitting
 - Pneumatic or electronic actuation (ISO 5211 standard)



Applications


- Food Process
- Aviation
- Chemical
- Semi-Conductors
- Medical
- Petrochemical
- Laboratories
- Pharmaceutical

Technical Characteristics

Compatible Fluids	Type 4810, 4812 and 4832	Type 0465
	All fluids	All fluids
Working Pressure	0 to 65 bar	Vacuum to 20 bar
Working Temperature	-20°C to +150°C	-20°C to +120°C


Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

Component Materials




Pressure and Temperature Resistance

Version 4810, 4812 and 4832



Version 0465



Regulations

Industrial



DI: 97/23/EC (module PED A - EC diameters greater than 25 mm)
DI: Machinery Directive 2006/42/EC
DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 89/392/EC

Stainless Steel Series

4832

2/2 In-Line 3-Piece Ball Valve with Fixing Plate, Female BSPP Thread





	Stainless steel 316L, PTFE		C	DN		E	F	G	H	K	L	M	ØT	kg
			G1/4	10	4832 10 13	18	22	36	50	36	57	110.5	5.5	0.272
			G3/8	10	4832 10 17	18	22	36	50	36	57	110.5	5.5	0.400
			G1/2	15	4832 15 21	20.5	27	36	64	36	65	131.5	6	0.442
			G3/4	20	4832 20 27	22.5	32	42	68	42	76	131.5	5.5	0.568
			G1	25	4832 25 34	27	41	42	78.5	42	92	174.5	6	1.035
			G1¼	32	4832 32 42*	30	50	42	83.5	42	106.5	174.5	5.5	1.530
			G1½	40	4832 40 49*	31	55	50	100	50	116	250.5	6.5	2.146
			G2	50	4832 50 48*	36	70	50	107	50	136	250.5	6.5	3.140

*Models with CE marking

4812

2/2 In-Line Ball Valve with Fixing Plate, Female BSPP Thread





	Stainless steel 316L, PTFE		C	DN		E	G	H	L	M	ØT	kg
			G1/4	10	4812 10 13	10	36	50	55	110	5.5	0.263
			G3/8	10	4812 10 17	11	36	50	55	110	5.5	0.254
			G1/2	15	4812 15 21	15	36	53	66	110	5.5	0.336
			G3/4	20	4812 20 27	16	42	67	79	130	5.5	0.574
			G1	25	4812 25 34	19	42	79	93	175	5.5	1.000
			G1¼	32	4812 32 42*	21	42	83	100	175	5.5	1.337
			G1½	40	4812 40 49*	21	50	100	110	250	5.5	2.214
			G2	50	4812 50 48*	26	70	107	131	250	8.5	3.262

*Models with CE marking

4810

2/2 In-Line Ball Valve, Female BSPP Thread





	Stainless steel 316L, PTFE		C	DN		E	G	H	L	M	kg
			G1/4	8	4810 08 13	10	30	44.5	53.5	110.5	0.205
			G3/8	10	4810 10 17	10	30	44.5	53.5	110.5	0.194
			G1/2	15	4810 15 21	13	32.5	47	60	110.5	0.245
			G3/4	20	4810 20 27	14	40	54.5	70	131.5	0.420
			G1	25	4810 25 34	17	49	58.5	79	131.5	0.648

Threads conform to ISO 228-1

0465

2/2 In-Line Light Series Ball Valve, Female BSPP Thread



	Stainless steel 303, PTFE		C	DN		E	F	F1	H	L	kg
			G1/4	4	0465 04 13	13	19	24	36	50	0.226
			G3/8	7	0465 07 17	13	24	27	39	55	0.278
			G1/2	10	0465 10 21	16	27	30	40	62	0.322

Silicone-free

Ball Valves, High Pressure Series

These valves are suitable for **applications** with pressures **up to 300 bar**.

High performance materials and quality manufacturing allow for a wide range of operating pressures and temperatures.

Product Advantages

High Pressure & Safety

Good sealing at low and high pressure
Robust design with secure, non-removable inlet and outlet ports
Forged brass providing excellent long-term strength under severe conditions of use
100% leak-tested in production
Date coding to guarantee quality and traceability

Easy-to-Use

Fixing screws for through-bulkhead mounting
The lever may be repositioned or replaced with a handwheel
Low operating torque



Automotive Process
Foundry
Forming
Machine Tools
Textile
Spectacle-Making Industry
Turbines
Deep-Sea Diving


Applications

Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	Vacuum to 300 bar
Working Temperature	-15°C to +80°C

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free


Regulations

DI: 97/23/EC (module PED A - diameters greater than 25 mm)
DI: 2006/42/EC (Machinery Directive)
DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)

Installation Options


Bulkhead Mounting

Through bulkhead with screws



Surface Mounting

With brackets and screws






High Pressure Series

4402

2/2 In-Line High Pressure Ball Valve, Female BSPP Thread



	Treated brass, NBR 		C	DN		E	H1	H2	H3	J	K	L	L1	N	N1	kg
			G1/4	7	4402 07 13	12	50	13	15	30	30	58	25	15	20	0.402
			G3/8	10	4402 10 17	12	54	23	19	36	39	72	36	20	30	0.722
			G1/2	13	4402 13 21	15	56	23	21	40	42	79	36	20	30	0.870

Ball Valves, Mini Series

With their **push-in connections**, these polymer lightweight ball valves allow for a significant reduction in installation time while offering **full flow capability** and **compact dimensions**.

Product Advantages

Optimum Solution

- Full flow
- Marked with the pneumatic symbol for identification of its function
- Lightweight and compact
- Extremely compact, easy-to-operate lever
- Lever with screwdriver slot to facilitate operation
- Designed for polymer tubing with no tube preparation
- Can be mounted on a wall or adjacent using staples

Proven Technology

- LF 3000® push-in connection, excellent static and dynamic sealing
- High-strength polyamide
- Excellent long-term performance
- Automatic seal wear compensation for long-term reliability
- 100% leak-tested in production
- Date coding to guarantee quality and traceability



Robotics
Vacuum
Semi-Conductors
Packaging
Textile
Pneumatics

Applications


Technical Characteristics

Compatible Fluids	Compressed air			
Working Pressure	Vacuum to 10 bar			
Working Temperature	-20°C to +80°C			

Tightening Torques	Threads	G1/8	G1/4	G3/8	G1/2
	daN.m	0.8	1.2	3	3.5

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99 % vacuum).

Component Materials




Silicone-free


Operation

Vented Valve, Open Position

3/2 model with vent




Vented Valve, Closed Position




Mini Series

7910 2/2 In-Line Mini-Ball Valve



Technical polymer, NBR




ØD		G	H	H1	K	L	N	kg
4	7910 04 00	15	37	7.5	22	51	16	0.039
6	7910 06 00	15	37	7.5	22	52	16	0.034
8	7910 08 00	15	37	7.5	22	52	16	0.025
10	7910 10 00	20	43	11	30	66	22	0.060
12	7910 12 00	20	43	11	30	66	22	0.040

7911 2/2 In-Line Mini-Ball Valve, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	G	H	K	L	L1	N	kg
6	G1/8	7911 06 10	13	14	37	22	62	37	16	0.045
8	G1/4	7911 08 13	16	17.5	37	22	61	35	16	0.040
10	G3/8	7911 10 17	20	22	43	30	74	41	22	0.075
12	G1/2	7911 12 21	24	26	43	30	75	42	22	0.075

7913 3/2 In-Line Mini-Ball Valve with Vent




Technical polymer, NBR




ØD		G	H	H1	K	L	N	kg
4	7913 04 00	15	37	7.5	22	51	16	0.040
6	7913 06 00	15	37	7.5	22	52	16	0.035
8	7913 08 00	15	37	7.5	22	52	16	0.025
10	7913 10 00	20	43	11	30	66	22	0.060
12	7913 12 00	20	43	11	30	66	22	0.045

7914 3/2 In-Line Mini-Ball Valve with Vent, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	G	H	K	L	L1	N	kg
6	G1/8	7914 06 10	13	14	37	22	62	37	16	0.045
8	G1/4	7914 08 13	16	17.5	37	22	61	35	16	0.040
10	G3/8	7914 10 17	20	22	43	30	74	41	22	0.058
12	G1/2	7914 12 21	24	26	43	30	75	42	22	0.075

7000 Joining Clips

Technical polymer



ØD		kg
4	7000 00 05	0.004
6	7000 00 05	0.004
8	7000 00 05	0.004
10	7000 00 06	0.009
12	7000 00 06	0.009

LIQUIfit® Ball Valves

This range of valves offers an innovative solution in the treatment of **water and the handling of beverages** while protecting **health**. These **compact and reliable** valves offer perfect **sealing** and excellent **cleanliness**.

Product Advantages

Innovative Technology & Increased Reliability

Full flow to limit turbulence
Full-flow self-cleaning ball maintains the cleanliness of the circuit
Tube retention with gripping ring prevents pumping effect
Push-in connection and disconnection
Sealing technology using patented EPDM seal

High Performance

Inert technical polymer providing the best mechanical strength, thermal and chemical resistance
Carstick® connection providing resistance to water hammer
Other configurations available on request




Beverage Dispensers
Inert Gases
Cooling
Food Process
Water Purification
Water Coolers

Applications

Technical Characteristics

Compatible Fluids	Water, drinks, beverages			
Working Pressure	0 to 10 bar at 20°C			
Working Temperature	-15°C to +100°C			
Tightening Torques	Threads	1/4" NPTF	3/8" NPTF	1/2" NPTF
	daN.m	1.5	3	3

Component Materials




Silicone-free

Regulations

FDA: 21 CFR
NSF: 51 and lead < 0.25%
WQA: Water Quality Association

4020

2/2 In-Line Ball Valve



	Polypropylene, glass fibre-reinforced, EPDM 	ØD		H	H1	L	L1	kg
		1/4	4020 56 00WP2	25	13	65	31	0.015
		3/8	4020 60 00WP2	36	13	68	30.5	0.028

4021

2/2 In-Line Ball Valve, Male NPTF Thread



	Polypropylene, glass fibre-reinforced, EPDM 	ØD	C		H	H1	L	L1	kg
		1/4	NPT1/4	4021 56 14WP2	36	13	61	31	0.029
		3/8	NPT3/8	4021 60 18WP2	36	13	64	33.5	0.028

4023

2/2 In-Line Ball Valve, Female NPTF Thread



	Polypropylene, glass fibre-reinforced, EPDM 	ØD	C		H	H1	L	L1	kg
		1/4	NPT1/4	4023 56 14WP2	36	13	58	31	0.000
		3/8	NPT3/8	4023 60 18WP2	36	13	64	33.5	0.000

4022

2/2 Right-Angled Ball Valve, Female NPTF Thread




	Polypropylene, glass fibre-reinforced, EPDM 	ØD	C		H	H1	L	L1	kg
		1/4	NPT1/4	4022 56 14WP2	52	29	44	31	0.016
		3/8	NPT3/8	4022 60 18WP2	52	29	47	33.5	0.027

3130

Tamper-Proof Safety Clip





Technical polymer 	ØD							H	K	kg
	1/4	3130 56 01	3130 56 02	3130 56 03	3130 56 04	3130 56 05	3130 56 10	8	3.2	0.001
	3/8	3130 60 01	3130 60 02	3130 60 03	3130 60 04	3130 60 05	3130 60 10	10.8	4.2	0.001



Needle and Butterfly Valves

Brass Needle Valve

In-Line			Right-Angled	
0502 Page 6-39	0501 Page 6-39	0510 Page 6-39	0532 Page 6-39	0531 Page 6-39
				

Drain Valve		Venting Pressure Gauge Valve	Pressure Relief Valve
0562 BSPP/Metric Page 6-40	0563 NPT Page 6-40	0627 BSPP Page 6-40	0630 BSPP Page 6-40
			

Stainless Steel Needle Valve

In-Line
0591 Page 6-41


Butterfly Valve

In-Line
4602 Page 6-43


Needle Valves

Parker Legris compact needle valves can be installed in any system and are designed for applications requiring accurate **leak-free fluid control** and **excellent service life**.

Product Advantages

Robust and Easy-to-Use

Accurate flow control
Forged brass for improved long-term mechanical strength
Robust stem for good operational reliability
Corrosion resistance

Wide Range

Two materials (nickel-plated brass and stainless steel) suitable for many applications
Numerous valve and safety accessory configurations



Pneumatics
Water Circuits
Machine Tools
Rubber Industry
Packaging
Textile


Applications

Technical Characteristics

	Brass	Stainless Steel
Compatible Fluids	Compressed air, water, industrial fluids, etc. Other fluids: contact us	Many fluids
Working Pressure	0 to 120 bar	0 to 400 bar
Working Temperature	-20°C to +100°C (except model 0510)	-20°C to +180°C
Tightening Torques	Threads	G1/8 G1/4 G3/8 G1/2
	daN.m	0.10 to 0.20 0.10 to 0.20 0.15 to 0.25 0.20 to 0.35

Reliable performance is dependent upon the type of fluid conveyed.

Component Materials



Silicone-free


Regulations





DI: 97/23/EC (module PED A - diameters greater than 25 mm)
DI: 2006/42/EC (Machinery Directive)
DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)

Brass Needle Valves

0502

In-Line Needle Valve, Female BSPP Thread



	<p>Nickel-plated brass</p> 	C			E	H	H _{max}	J	L/2	kg
		G1/8	4	0502 04 10	9	56	50	17	23	0.133
		G1/4	4	0502 04 13	11	56	50	17	23	0.118
		G3/8	6	0502 06 17	12	67	60	-	26	0.171
			9	0502 09 17	12	82	70	-	33	0.426

0501

In-Line Needle Valve, Male/Female BSPP Thread



	Nickel-plated brass											
	C	DN			E	E1	H	H _{max}	J	L	kg	
	G1/8	4		0501 04 10	9	7	56	50	17	44	0.118	
	G1/4	4		0501 04 13	11	9.5	56	50	17	46	0.115	
	G3/8	6		0501 06 17	12	9.5	67	60	-	48	0.158	

0510

In-Line Needle Valve with Compression Connections



	Nickel-plated brass											
	ØD	C	DN		F	H _{min}	H _{max}	L/2	kg			
	6	M10x1	4	0510 04 06	13	42	46	29	0.083			
	8	M12x1	8	0510 05 08	14	42	46	30	0.083			
	10	M16x1.5	5	0510 05 10	19	42	46	31	0.111			

The needle is sealed by an O-ring.
Maximum operating pressure: Ø4: 100 bar, Ø5: 60 bar
Working temperature: -15°C to +70°C
Tightening torques: please refer to the Compression Fittings chapter of this catalogue.

0532

Right-Angle Needle Valve, Female BSPP Thread



	Nickel-plated brass											
	C	DN			E	H _{min}	H _{max}	H1	J	L	kg	
	G1/8	4		0532 04 10	9	46	52	19	17	19	0.093	
	G1/4	4		0532 04 13	11	46	52	21	17	21	0.087	
		6		0532 06 13	11	55	63	26	22	26	0.169	

0531




Right-Angle Needle Valve, Male/Female BSPP Thread






	Nickel-plated brass											
	C	DN			E	E1	H _{min}	H _{max}	H1	J	L	kg
	G1/8	4		0531 04 10	7	9	46	52	19	17	19	0.082
	G1/4	4		0531 04 13	9.5	11	46	52	21	17	21	0.090
		6		0531 06 13	9.5	11	55	63	25	22	26	0.155
	G3/8	6		0531 06 17	9.5	12	55	63	25	22	27	0.153
	G1/2	10		0531 10 21	13	16	62	72	34	26	33	0.330

Brass Needle Valves




0562 Needle Drain Valve, Male BSPP and Metric Thread

	Brass		C			E		F		H		kg
			M10x1	5		0562 05 60	8	16	37.5	40	0.031	
			G1/8	5		0562 05 10	8	16	36	40	0.032	
			G1/4	5		0562 05 13	10	19	38.5	42.5	0.040	




0563 Needle Drain Valve, Male NPT Thread

	Brass		C			F		H		kg
			NPT1/4	5		0563 05 14	14	28.5	32.5	0.021

0627 Automatic Vent Pressure Gauge Valve, Female BSPP Thread

	Nickel-plated brass, NBR		C			F		H		K		L		kg
			G1/4			0627 00 13	19	43.5	20	40	0.097			
Pressure: 10 bar This isolating valve is used to connect a pressure gauge to a circuit. Resetting the lever isolates and vents the gauge. A locking pin can be used to enable the gauge to be fitted permanently.														

0630 Pressure Relief Valve, Male BSPP Thread




	Brass		C			E		F		H		kg
			G1/4			0630 06 13	9	17	42.5	0.050		
This valve is delivered without calibration, but can be adjusted by inserting metal washers into the hexagon (F).												

Stainless Steel Needle Valves

0591

Needle Valve, Female BSPP Thread



	Stainless steel 316L, PTFE											
			C	DN		F	H min	H max	H1	L	L1	kg
			G1/8	3	0591 03 10	22	90	99	25	45	48	0.345
			G1/4	4	0591 04 13	22	90	99	25	50	48	0.356
			G3/8	5	0591 05 17	22	90	104	30	56	48	0.430
			G1/2	6	0591 06 21	22	90	104	30	62	48	0.483

Butterfly Valves

In these robust valves, the internal component used to shut off the flow is a segment of a sphere. This allows **frequent operation with very low torque**, **no fluid retention areas** and therefore excellent mechanical performance.

Product Advantages

Compact & Abrasion-Resistant

- Excellent with abrasive fluids (including solid particles)
- Fluid flow direction marked for greater safety (uni-directional)
- Smooth operation
- Can be easily adapted for use with auxiliary actuators
- More compact than a ball valve with equivalent nominal diameter
- Simple and efficient design for a long service life

Applications


- Painting & Printing
- Machine Tools
- Pneumatics
- Powder Conveyance
- Plumbing
- Rubber Industry
- Petrochemical

Technical Characteristics

Compatible Fluids	Compressed air, industrial gases, water, cutting oils, hydraulic oils, fuel oil, fuel, etc.
Working Pressure	0 to 16 bar
Working Temperature	-20°C to +80°C

Reliable performance is dependent upon the type of fluid conveyed.

Component Materials



Silicone-free

Regulations





DI: 97/23/EC (module PED A - diameters greater than 25 mm)
DI: 2006/42/EC (Machinery Directive)
DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)

Butterfly Valves

4602

2/2 Butterfly Shut-Off Valve, Female BSPP Thread



	<p>Nickel-plated brass, NBR</p> 	C									
				E	F	H	L	M	kg		
		G1/4	6	4602 06 13	9	17	35	34	54	0.098	
		G3/8	7	4602 07 17	11	22	35	39	54	0.136	
		G1/2	10	4602 10 21	12	24	37	42	54	0.140	
		G3/4	13	4602 13 27	14	30	40	49	54	0.208	
		G1		18	4602 18 34	15	41	46	55	54	0.412
Black epoxy-coated zamak handle											



Axial Valve Range

In-Line Normally Closed

4202..20
FKM Seal
2/2
Page 6-48



4202..30
EPDM Seal
2/2
Page 6-48



In-Line Normally Open

4212..20
FKM Seal
2/2
Page 6-48



4212..30
EPDM Seal
2/2
Page 6-48



In-Line Double-Acting

4222..20
FKM Seal
2/2
Page 6-48



4222..30
EPDM Seal
2/2
Page 6-49



Accessories

4298
Sub-Base
Page 6-49



4298
Solenoid Valve
Page 6-49



4299
Pneumatic Button
Page 6-49



Axial Valves

The Parker Legris axial valve is the only valve to incorporate both the **valve and actuation function**. With pneumatic or electro-pneumatic control, it avoids many of the restrictions associated with traditional actuators.

Product Advantages

Optimisation & Safety

Very compact: up to 50% smaller than valves with separate actuators
Simple to install: ready-to-use
Common sub-base for solenoid control
Automation of the open/close function
Operation independent of the upstream and downstream pressure in the circuit

Comprehensive Offer

Two seal materials for a wider chemical and temperature range
Pneumatic, electro-pneumatic or dual actuation control
Three versions: normally closed, normally open and double-acting

Performance

Full flow: low pressure drop
Excellent pressure/temperature performance
Compatible with many industrial fluids



Flow Control
Plastic Injection Moulding
Rubber Industry
Pneumatics
Textile
Printing
Packaging
Robotics

Applications

Technical Characteristics


Compatible Fluids	Depending on type of seal – FKM: water, air, oils, greases, etc. – EPDM: hot water, air, steam, etc.
Working Pressure	10 bar max.
Pilot Pressure	NC and NO: 4.2 to 8 bar Double-acting: 3 to 8 bar
Working Temperature	-20°C to +135°C (suffix 20 FKM) -20°C to +120°C (suffix 30 EPDM)

Tightening Torques	Threads	G3/8	G1/2	G3/4	G1	G1¼	G1½	G2
	daN.m	0.15 to 0.25	0.20 to 0.35	0.50 to 0.70	0.50 to 0.70	0.40 to 0.60	0.80 to 1.20	0.80 to 1.20


Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 740 mm Hg (97% vacuum).

Flow Curve and Pressure Drop (Kv)

Kv in m³/h (ambient water temperature, under a differential pressure of 1 bar)



Component Materials



Silicone-free


Regulations

DI: 97/23/EC (module PED A - diameters greater than 25 mm)
DI: 2006/42/EC (Machinery Directive)
DI: 2002/95/EC (RoHS)
RG: 1907/2006 (REACH)
DI: 94/9/EC (ATEX) - for pneumatic operation versions

Axial Valves

Operation

Depending on operational requirement, air is passed into the actuation chamber to open or close the valve.




Installation Options

The **Parker Legris** axial valve offers 3 different control methods dependant on the requirements of the installation:

Pneumatic Control

Example: Double-acting axial valve 4222


- local compressed air control
- for repetitive on/off cycles
- remote control where access to the machine is difficult
- for explosive or explosion prevention areas



Electro-Pneumatic Control

Example: Normally closed axial valve 4202
+ sub-base and Mini-solenoid valve 4298


- for automated industrial systems requiring remote control
- Namur seating plane solenoid valve



Dual Pneumatic and Electro-Pneumatic Control




Example: Normally open axial valve 4212
+ sub-base and Mini-solenoid valve 4298
+ Pneumatic push-button 4299

- dual control structure
- for increased safety: prevents localised operating errors
- Namur seating plane solenoid valve






Axial Valves




4202..20 Normally Closed Axial Valve with FKM Seal, Female BSPP Thread

		C		F	G	H	H1	L	kg
		G3/8	4202 10 17 20	22	46	54	31	98	0.815
		G1/2	4202 15 21 20	27	52	60	35	112	1.092
		G3/4	4202 20 27 20	33	64	70	38	135	1.624
		G1	4202 25 34 20	41	69	76	41.5	143	2.033
		G1¼	4202 32 42 20*	50	86	91	48	165	3.266
		G1½	4202 40 49 20*	60	96	102	54	180	4.195
G2	4202 50 48 20*	75	109	115	60.5	207	6.465		
Pilot port: G1/8 - Delivered with a silencer *Models with CE marking									




4202..30 Normally Closed Axial Valve with EPDM Seal, Female BSPP Thread

	<p>Nickel-plated brass, EPDM</p> 	C		F	G	H	H1	L	kg
		G3/8	4202 10 17 30	22	46	54	31	98	0.828
		G1/2	4202 15 21 30	27	52	60	35	112	1.098
		G3/4	4202 20 27 30	33	64	70	38	135	1.624
		G1	4202 25 34 30	41	69	76	41.5	143	1.998
		G1¼	4202 32 42 30*	50	86	91	48	165	3.315
		G1½	4202 40 49 30*	60	96	102	54	180	4.195
		G2	4202 50 48 30*	75	109	115	60.5	207	6.360
<p>Pilot port: G1/8 - Delivered with a silencer</p> <p>*Models with CE marking</p>									

4212..20 Normally Open Axial Valve with FKM Seal, Female BSPP Thread

	<p>Nickel-plated brass, FKM</p> 	C		F	G	H	H1	L	kg
		G3/8	4212 10 17 20	22	46	54	31	98	0.829
		G1/2	4212 15 21 20	27	52	60	35	112	1.100
		G3/4	4212 20 27 20	33	64	70	38	135	1.637
		G1	4212 25 34 20	41	69	76	41.5	143	2.037
		G1¼	4212 32 42 20*	50	86	91	48	165	0.030
		G1½	4212 40 49 20*	60	96	102	54	180	4.188
		G2	4212 50 48 20*	75	109	115	60.5	207	6.555
<p>Pilot port: G1/8 - Delivered with a silencer</p> <p>*Models with CE marking</p>									

4212..30 Normally Open Axial Valve with EPDM seal, Female BSPP Thread

	<p>Nickel-plated brass, EPDM</p> 	C		F	G	H	H1	L	kg
		G3/8	4212 10 17 30	22	46	54	31	98	0.827
		G1/2	4212 15 21 30	27	52	60	35	112	1.152
		G3/4	4212 20 27 30	33	64	70	38	135	1.575
		G1	4212 25 34 30	41	69	76	41.5	143	2.055
		G1¼	4212 32 42 30*	50	86	91	48	165	3.301
		G1½	4212 40 49 30*	60	96	102	54	180	4.775
		G2	4212 50 48 30*	75	109	115	60.5	207	6.360
<p>Pilot port: G1/8 - Delivered with a silencer</p> <p>*Models with CE marking</p>									

4222..20 Double-Acting Axial Valve with FKM Seal, Female BSPP Thread

Nickel-plated brass, FKM

C

F

G

H

H1

L

kg

G3/8

4222 10 17 20

22

46

54

31

98

0.802

G1/2

4222 15 21 20

27

52

60

35

112

1.063

G3/4

4222 20 27 20

33

64

70

38

135

1.572

G1

4222 25 34 20

41

69

76

41.5

143

1.942

G1¼

4222 32 42 20*

50

86

91

48

165

3.058

G1½

4222 40 49 20*

60

96

102

54

180

3.995

G2

4222 50 48 20*

75

109

115

60.5

207

6.275

Pilot port: G1/8

*Models with CE marking

Axial Valves

4222..30 Double Acting Axial Valve with EPDM seal, Female BSPP Thread

Nickel-plated brass, EPDM

C

F

G

H

H1

L

kg

G3/8

4222 10 17 30

22

46

54

31

98

0.832

G1/2

4222 15 21 30

27

52

60

35

112

1.046

G3/4

4222 20 27 30

33

64

70

38

135

1.662

G1

4222 25 34 30

41

69

76

41.5

143

1.938

G1¼

4222 32 42 30*

50

86

91

48

165

3.301

G1½

4222 40 49 30*

60

96

102

54

180

4.260

G2

4222 50 48 30*

75

109

115

60.5

207




6.520

Pilot port: G1/8




Delivered with a silencer

*Models with CE marking




4298 Sub-Base for Solenoid Pilot Valve

	<p>Treated aluminium, NBR</p> 	C		kg
		M5x0.8	4298 00 01	0.095
		<p>The sub-base is fitted directly to the axial valve and allows the mounting of a 15x15 solenoid valve. Supplied with 2 fixing bolts, silencer and seals.</p>		

4298 Mini-Solenoid Valve 1W/12VA

	Anodised aluminium 	Voltage		kg
		24V = CC*	4298 01 01	0.052
		24V ~ CA**	4298 01 02	0.058
		110V ~ CA**	4298 02 01	0.051
		220V ~ CA**	4298 02 02	0.054
		*Direct current **Alternating current		

4299 Pneumatic Button/Electro-Pneumatic


	Nickel-plated brass 	Contact		kg
		Standard*	4299 01 01	0.085
		With key*	4299 01 02	0.110
		Standard**	4299 02 01	0.102
		With key**	4299 02 02	0.124
		Bulkhead fixing hole diameter: Ø22 mm *1 pneumatic contact **1 electro-pneumatic contact Available upon request only		

Industrial Blowguns

Polymer

Metal

Kits





Blowguns

Standard Blowgun (P. 7-7)



Fluids: compressed air
Materials: technical polymer, NBR
Pressure: 10 bar
Temperature: -15°C to +50°C
 (DN) : 3.5 mm

Safety Blowgun (P. 7-7)



Fluids: compressed air
Materials: technical polymer, NBR
Pressure: 10 bar
Temperature: -15°C to +50°C
 (DN) : 3 mm

Energy-Saving Blowgun (P. 7-7)



Fluids: compressed air
Materials: technical polymer, NBR
Pressure: 10 bar
Temperature: -15°C to +50°C
 (DN) : according to nozzle

Versatile Blowguns (P. 7-6)



Fluids: compressed air
Materials: technical polymer, NBR
Pressure: 10 bar
Temperature: -15°C to +50°C
 (DN) : according to nozzle

Metal Blowguns (P. 7-14)



Fluids: compressed air
Materials: forged nickel-plated brass, NBR
Pressure: 10 bar
Temperature: -15°C to +50°C
 (DN) : 2 mm

Water Pistol (P. 7-14)



Fluids: industrial fluids and water
Materials: zamak, NBR
Pressure: 20 bar
Temperature: -20°C to +100°C
 (DN) : 12 mm

Blowgun Kits (P. 7-16)



Fluids: compressed air
Materials: technical polymer
Pressure: 10 bar
Temperature: -15°C to +50°C
 (DN) : according to model

Nozzles (P. 7-10)



Fluids: compressed air
Materials: nickel-plated brass
Pressure: 10 bar
Temperature: -15°C to +50°C
 (DN) : according to model

Blowgun Range

Polymer Blowguns

Standard	Safety	Energy-Saving	With Interchangeable Nozzle	
0659 Page 7-7	0654 Page 7-7	0653 Lower Connection Page 7-7	0652 Lower Connection Page 7-8	0655 Upper Connection Page 7-8
				

Pre-Assembled with Nozzle			
0651 Lower Connection Page 7-8	0658 Upper Connection Page 7-9	0656 Lower Connection Page 7-9	0657 Upper Connection Page 7-9
			








Nozzles for Polymer Blowguns

0690 01 Standard Page 7-10	0690 02 Safety Page 7-10	0690 03 Straight Tube (long) Page 7-10	0690 04 Straight Tube (short), Safety Page 7-10	0690 05 Angled Tube (long) Page 7-10	0690 06 Angled Tube (short) Safety Page 7-11
					
0690 06 01 Angled Tube (short) Page 7-11	0690 07 LF 3000® Nozzle Page 7-11	0690 08 Coanda Page 7-11	0690 09 Air Screen Page 7-11	0690 10 Booster Page 7-12	0690 11 Booster with Air Screen Page 7-12
					

Metal Blowguns

Button-Operated	Lever-Operated	Water Pistol	
0623 Page 7-15	0622 Page 7-15	2299 Page 7-15	2299 Page 7-15
			

Blowgun Kits

0631..09 Standard Page 7-17	0631..01 Safety Page 7-17	0631..23 Energy-Saving Page 7-17	0631..03 0631..02 Standard Nozzle Page 7-17/18	0631..05 0631..04 Angled Nozzle, Safety Page 7-18	0631..07 0631..06 Interchangeable Nozzle Page 7-18/19
					
0631..08 Energy-Saving Interchangeable Nozzle Page 7-19					
					

Polymer Blowguns

The Parker Legris polymer blowgun offers **ease of use**, **energy saving**, adaptability and efficiency. These blowguns comply with **international regulations** for health, **safety** and **noise** levels.

Product Advantages

Quality & Performance

Comply with international standards for noise and pressure regulation
Powerful flow with progressive control
Rotating nozzle for directional jet
Durable, shock-resistant materials
100% leak and flow-tested in production
Date coding to guarantee quality and traceability

Safety & Sustainable Development

40% energy consumption reduction with Energy-Saving model
Complete user safety with the Safety model
Wide selection of nozzles which comply with noise and pressure level regulations

Ergonomics & Versatility

Comfortable to use
Lightweight and easy to use
Wide range of models and nozzles for optimum blowing power and flow rate
Lower or upper connection



Manufacturing Workshops
Cleaning
Blowing
Mixing
Ejection
Cooling
Packaging

Applications

Technical Characteristics

Compatible Fluids	Compressed air Other fluids: contact us
Working Pressure	0 to 10 bar
Working Temperature	Air: -15°C to +50°C Dry air: -20°C to +80°C
Tubes	Recoil tubes and hose

Regulations

Compliance for all blowguns:

DI: 97/23/EC (PED)
DI: 2002/95/EC (RoHS),
2011/65/EC
DI: 1907/2006 (REACH)

Protection of design

All designs and models of Parker Legris blowguns have been registered with the following numbers:
13224 / 13225 / 13226.

Compliance for specific blowguns:

DI: 1910.242 (b) [OSHA]
The static pressure must be less than 30 psi in case the nozzle becomes blocked.
DI: 1910.95 (b) [OSHA]
The noise level must be less than 90 dBA over 8 hours' exposure.
DI: 2003/10/EC
Regulation relating to exposure to noise, particularly with regard to risks to hearing. The noise level must be less than 87 dBA.






Component Materials








Silicone-free

Polymer Blowguns






0659 Standard Blowgun, Lower Connection with Short Angled Nozzle, Female BSPP Thread

	Technical polymer, nickel-plated brass, treated aluminium, NBR		C			F	H	L	kg
			G1/4	3.5	0659 00 13	20	120	223	0.072
			Nozzle: aluminium, NPT version available.						
<p>Progressive flow depending on the trigger position</p>  <p>Pressure: 6 bar</p> <p>475 Nl/min</p> <p>82 dBA</p> <p>OSHA 1910.242 (b) OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>									

0654 Safety Blowgun, Lower Connection, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR		C			F	H	H1	L	L1	kg
			G1/4	3	0654 00 13	20	117	35	148	73	0.189
			Nozzle: nickel-plated brass, NPT version available.								
<p>Progressive flow depending on the trigger position</p>  <p>Pressure: 6 bar</p> <p>250 Nl/min</p> <p>80 dBA</p> <p>OSHA 1910.242 (b) OSHA 1910.95 (b) 2003/10/EC directive: No ear defenders necessary</p>											

0653 Energy-Saving Blowgun, Lower Connection with Interchangeable Nozzle, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR		C	C1		F	H	H1	L	kg		
			G1/4 M12x1.25 0653 66 13					20	117	34	147	0.144
			Flow characteristics depend on the type of nozzle used. Delivered without nozzle. A value calculator for energy savings is available.									
			Progressive flow depending on the trigger position									
												
			Pressure: 6 bar									
			Trigger position (mm)									
			120 Nl/min									
			80 dBA			Noise level measured without nozzle						
												
			OSHA 1910.242 (b): Depends on type of nozzle OSHA 1910.95 (b) 2003/10/EC directive: No ear defenders necessary									



Maximum Flow Rate
(tolerance +/-10%)



Noise Level
ISO 15744



Diffusion
Cone



Compliance
with Standards

Operation: Safety Blowgun



Flow stopped completely and pressure reduced to 0.5 bar







Operation: Blowgun with Safety Nozzle









Flow diverted and pressure reduced to 0.5 bar

Polymer Blowguns









0652 Progressive Control Blowgun, Lower Connection with Interchangeable Nozzle, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR		C	C1		F	H	H1	L	kg
			G1/4	M12x1.25	0652 66 13	20	117	34	147	0.163
			Flow characteristics depend on the type of nozzle used. Delivered without nozzle.					<div> Depending on the type of nozzle</div> <div> 86 dBA Noise level measured without nozzle</div> <div> OSHA 1910.242 (b): Depends on type of nozzle OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</div>		

0655 Progressive Control Blowgun, Upper Connection with Interchangeable Nozzle, Female BSPP Thread



	Technical polymer, nickel-plated brass, NBR		C	C1		F	H	H1	L	kg
			G1/4	M12x1.25	0655 66 13	20	117	37	145	0.014
			Flow characteristics depend on the type of nozzle used. Delivered without nozzle.					<div> Depending on the type of nozzle</div> <div> 86 dBA Noise level measured without nozzle</div> <div> OSHA 1910.242 (b): Depends on type of nozzle OSHA 1910.95 (b) 2003/10/EC directive: Requires ear defenders to be used when exposure is > 8 hours</div>		

0651 Progressive Control Blowgun, Lower Connection with Standard Nozzle, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR		C			F	H	H1	L	L1	kg
			G1/4	2.5	0651 66 13	20	117	34	147	10	0.168
			Nozzle: nickel-plated brass			 327 Nl/min Flow produced with nozzle 0690 01 00  86 dBA  OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours					
			<p>Progressive flow depending on the trigger position</p>  <p>Pressure: 6 bar</p> <p>Trigger position (mm)</p>								

Polymer Blowguns


0658 Progressive Control Blowgun, Upper Connection with Standard Nozzle, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR	C	DN		F	H	H1	L	L1	kg
		G1/4	2.5	0658 66 13	20	117	37	145	10	0.195

Nozzle: nickel-plated brass

Progressive flow depending on the trigger position

Flow (Nl/min)



Pressure: 6 bar



Trigger position (mm)

327 Nl/min Flow produced with nozzle 0690 01 00

86 dBA

OSHA 1910.95 (b)
2003/10/EC directive:
Requirement to use ear protection if exposure > 8 hours


0656 Safety Progressive Control Blowgun, Lower Connection with Short Angled Nozzle, Female BSPP

	Technical polymer, nickel-plated brass, NBR	C	DN		F	H	H1	L	L1	kg
		G1/4	2.5	0656 66 13	20	117	34	147	81	0.173

Nozzle: nickel-plated brass

Progressive flow depending on the trigger position

Flow (Nl/min)



Pressure: 6 bar



Trigger position (mm)

524 Nl/min Flow produced with nozzle 0690 06 01

86 dBA

OSHA 1910.242 (b)
OSHA 1910.95 (b)
2003/10/EC directive:
Requirement to use ear protection if exposure > 8 hours


0657 Safety Progressive Control Blowgun, Upper Connection with Short Angled Nozzle, Female BSPP

	Technical polymer, nickel-plated brass, NBR	C	DN		F	H	H1	L	L1	kg
		G1/4	2.5	0657 66 13	20	117	37	145	82	0.168

Nozzle: nickel-plated brass

Progressive flow depending on the trigger position

Flow (Nl/min)



Pressure: 6 bar

Trigger position (mm)




524 Nl/min Flow produced with nozzle 0690 06 01

86 dBA




OSHA 1910.242 (b)
OSHA 1910.95 (b)
2003/10/EC directive:
Requirement to use ear protection if exposure > 8 hours

Nozzles for Polymer Blowguns




0690 01 Standard Nozzle

	Nickel-plated brass	C	DN		G	L	L1	kg
		M12x1.25	2.5	0690 01 00	15	31	9	0.024
 <ul style="list-style-type: none"> Versatile use Progressive and powerful air jet <p>327 Nl/min 86 dBA 23°</p> <p>OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>								




0690 02 Safety Nozzle

	Nickel-plated brass	C	DN		G	L	L1	kg
		M12x1.25	2.5	0690 02 00	15	31	9	0.024
 <ul style="list-style-type: none"> Fluidised Powders Air screen effect Safety: avoids the nozzle becoming completely blocked <p>315 Nl/min 83 dBA 26°</p> <p>OSHA 1910.95 (b)/1910.242 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>								




0690 03 Straight Nozzle (Long)

	Nickel-plated brass	C	DN		G	L	L1	kg
		M12x1.25	2.5	0690 03 00	15	332	307	0.068
 <ul style="list-style-type: none"> Restricted Access Progressive and powerful air jet <p>386 Nl/min 82 dBA 21°</p> <p>OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>								

0690 04 Safety Straight Nozzle (Short)










	Nickel-plated brass	C	DN		G	L	L1	kg
		M12x1.25	2.5	0690 04 00	15	102	77	0.033
 <ul style="list-style-type: none"> Restricted Access Air screen effect and directional jet Safety: avoids the nozzle becoming completely blocked <p>410 Nl/min 82 dBA 21°</p> <p>OSHA 1910.242 (b)/ OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>								

0690 05 Angled Nozzle (Long)










	Nickel-plated brass	C	DN		G	L	L1	kg
		M12x1.25	2.5	0690 05 00	15	316	292	0.065
 <ul style="list-style-type: none"> Restricted or distant access Progressive and powerful air jet 360° rotation <p>354 Nl/min 82 dBA 21°</p> <p>OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours</p>								

Nozzles for Polymer Blowguns









0690 06 Safety Angled Nozzle (Short)

	C						G	L	L1	kg
	M12x1.25	2.5	0690 06 00				15	94	70	0.033
							<ul style="list-style-type: none">• Restricted Access• Air screen effect and 360° directional jet• Safety: avoids the nozzle becoming completely blocked			
	 350 Nl/min			 86 dBA			 21°			
							 OSHA 1910.242 (b)/ OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours			










0690 06 01 Angled Nozzle (Short)

	Nickel-plated brass	C			G	L	L1	kg	
		M12x1.25	2.5	0690 06 01		15	94	70	0.033
						<ul style="list-style-type: none">• Difficult access• Progressive and powerful air jet, 360° rotation			
		 524 Nl/min	 86 dBA	 21°	 OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours				








0690 07 Nozzle with LF 3000® Push-In Connection

	Nickel-plated brass								
		ØD	C		G	L	L1	kg	
		4	M12x1.25	0690 07 00	15	35	13	0.024	
		<ul style="list-style-type: none">• Restricted Access• Progressive air jet							
	 340 Nl/min (with 2.7x4 tube) 200 Nl/min (with 2x4 tube)	 86 dBA		 21°		 OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours			

0690 09 Air Screen Safety Nozzle


















































































































































































	Nickel-plated brass								
		C			G	L	L1	kg	
		M12x1.25	2	0690 09 00	30	40.5	18.5	0.021	
		Deflector: technical polymer				<ul style="list-style-type: none">• High flow for blowing large surfaces• Air screen and deflector to avoid particles being blown back• Safety: avoids the nozzle becoming completely blocked			
						 660 Nl/min  86 dBA  24° nozzle 140° screen  OSHA 1910.242 (b)/ OSHA 1910.95 (b) 2003/10/EC directive: Requirement to use ear protection if exposure > 8 hours			


0690 08 COANDA Nozzle

Nickel-plated brass		C		L	L1	kg	
		M12x1.25	0690 08 00		47.5	26	0.033
					<ul style="list-style-type: none">• Directional air jet• Very quiet, energy-saving• Safety: avoids the nozzle becoming completely blocked		
		 240 Nl/min	 73 dBA	 20°	 OSHA 1910.242 (b)/ OSHA 1910.95 (b) 2003/10/EC directive: No ear defenders necessary		

Nozzles for Polymer Blowguns

0690 10 Safety Booster Nozzle

		C	DN		G	L	L1	kg	
	Nickel-plated brass	M12x1.25	2.5	0690 10 00	15	64	42	0.038	
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									
									



Metal Blowguns and Water Pistols

This range of robust blowguns guarantees a **longer service life** under **severe conditions** (crushing, impact, shock and corrosion). It includes two versions **to meet all requirements** for blowing and spraying in industrial applications.

Product Advantages

Workshop Blowgun

Compact for easy incorporation into compressed air ring mains
Nickel-plated forged brass for increased corrosion resistance

Water Pistol

Intended for the transmission of water and fluids
Designed for precise flow control and optimisation of the power and shape of the jet
Optimum use of industrial fluids
Excellent ergonomics and service life




Manufacturing Workshops
Assembly machines
Robotics
Ejection
Cooling
Packaging
Automotive Process

Applications

Technical Characteristics

Model	Metal Blowgun	Water Pistol
Compatible Fluids	Compressed air, industrial fluids	Water, oil, industrial fluids
Working Pressure	0 to 10 bar	0 to 20 bar
Working Temperature	Air: -15°C to +50°C Dry air: -20°C to +80°C	-20°C to +100°C
Tubes	Recoil tubes and hose	Braided hose with Parker Legris couplers

Component Materials



Silicone-free

Regulations

Compliance for all blowguns:





DI: 97/23/EC (PED)

DI: 2002/95/EC (RoHS), 2011/65/EC





DI: 1907/2006 (REACH)

Metal Blowguns and Water Pistols







0623 Lever-Operated Blowgun, Female BSPP Thread

	Nickel-plated brass, NBR		C			G	H min	H max	H1	L	L1	L2	kg
			G1/4	2	0623 10 35	18	19	37	21	64	28	60	0.119
			This blowgun has a hardened steel nozzle.										




0622 Button-Operated Blowgun, Female BSPP Thread

	Nickel-plated brass, NBR		C			G	H	H1	L	L1	ØT	kg
			G1/4	2	0622 26 73	18	17.5	20.5	82	29	7	0.196
			This blowgun has a hardened steel nozzle.									

2299 Water Pistol

	Zamak, nickel-plated brass, NBR			H	L	kg
			12		2299 12 01	140 126 0.471
This pistol allows independent control of:						
- the flow rate (trigger)						
- type of jet (adjustable to a fine mist) by the adjustable nozzle						
 1440 NI/min (air)  16.2 NI/min (water)  Adjustable						

2299 Adjustable Nozzle

	Nickel-plated brass, NBR			L	kg		
				12	2299 12 20	77.4	0.137
				This nozzle allows adjustment of the spray.			

Associated Products

For optimum connection and usage of the pistol and adjustable nozzle, you will find a full range of quick-acting couplers, in the Midi and Maxi Series, in Chapter 8.

Midi P. 8-43



Maxi P. 8-46



Blowgun Kits

Ready for use, **simple** and **ergonomic**, the Parker Legris blowgun kit remains an essential item of equipment for any blowing or spraying operation in the industrial environment.

Product Advantages

Ready for Use

Kit contents:

- one blowgun
- a 4 metre recoil tube
- one R1/4 threaded fitting, external diameter 8 mm

Easy to install and comfortable to use
Wide range of models and nozzles for optimum flow
Lower or upper connection
Labelling and colours can be customised
Packaging designed to facilitate self-service sales

Safety & Performance

Safe operation with the Safety or OSHA models
Durable, shock-resistant materials
100% leak and flow-tested in production
Date coding to guarantee quality and traceability
Minimum pressure drop
Optimisation of your energy consumption with the Energy-Saving model



Manufacturing Workshops
Cleaning
Blowing
Mixing
Ejection
Cooling
Packaging

Applications

Technical Characteristics

Compatible Fluids	Compressed air Other fluids: contact us
Working Pressure	0 to 10 bar
Working Temperature	Air: -15°C to +50°C Dry air: -20°C to +80°C
Tubes	Recoil tubing

Regulations

Compliance for all blowguns:

DI: 97/23/EC (PED)
DI: 2002/95/EC (RoHS),
2011/65/EC
DI: 1907/2006 (REACH)


Protection of design

All designs and models of Parker Legris blowguns have been registered with the following numbers:
13224 / 13225 / 13226.

Compliance for specific blowguns:

DI: 1910.242 (b) [OSHA]
The static pressure must be less than 30 psi in case the nozzle becomes blocked.
DI: 1910.95 (b) [OSHA]
The noise level must be less than 90 dBA over 8 hours' exposure.
DI: 2003/10/EC
Regulation relating to exposure to noise, particularly with regard to risks to hearing. The noise level must be less than 87 dBA.

Component Materials



Silicone-free




Customisation on request

- Marking
- Kit contents adaptable to your applications
- Additional functions
- Colour






Blowgun Kits




0631..09 Blowgun Kit, Lower Connection, Male BSPT Thread

	<p>Technical polymer, nickel-plated brass, treated aluminium, NBR, polyurethane tubing</p> 	C		F	H	H1	L	kg
		R1/4	0631 00 09	16	192.5	139.5	152	0.441
		Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0659 00 13).						




0631..01 Safety Blowgun Kit, Lower Connection, Male BSPT Thread

	<p>Technical polymer, nickel-plated brass, NBR, polyurethane tubing</p> 	C		F	H	H1	L	kg
		R1/4	0631 00 01	16	198.5	148.5	154	0.575
		Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0654 00 13).						

0631..23 Energy Saving Blowgun Kit with Angled Nozzle, Male BSPT Thread




	<p>Technical polymer, nickel-plated brass, NBR, polyurethane tubing</p> 	C		F	H	H1	L	kg
		R1/4	0631 00 23	16	195	148.5	154	0.458
		Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0653 66 13). External diameter of tube 6 mm						

0631..03 Blowgun Kit, Lower Connection with Standard Nozzle, Male BSPT Thread




	<p>Technical polymer, nickel-plated brass, NBR, polyurethane tubing</p> 	C		F	H	H1	L	kg
		R1/4	0631 00 03	16	165	148.5	99	0.528
		Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0651 66 13).						

Blowgun Kits




0631..02 Blowgun Kit, Upper Connection with Standard Nozzle, Male BSPT Thread

	Technical polymer, nickel-plated brass, NBR, polyurethane tubing 	C		F	H	H1	L	kg
		R1/4	0631 00 02	16	163	148.5	101	0.524
		Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0658 66 13).						




0631..05 Blowgun Kit Lower Connection with Short Angled Nozzle, Male BSPT Thread

	Technical polymer, nickel-plated brass, NBR, polyurethane tubing 	C		F	H	H1	L	kg
		R1/4	0631 00 05	16	195,5	148,5	163	0.536
		Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0656 66 13).						

0631..04 Blowgun Kit, Lower Connection with Short Angled Nozzle, Male BSPT Thread



	Technical polymer, nickel-plated brass, NBR, polyurethane tubing 	C		F	H	H1	L	kg
		R1/4	0631 00 04	16	195	148.5	163.5	0.536
		Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0656 66 13).						

0631..07 Blowgun Kit, Lower Connection with Interchangeable Nozzle, Male BSPT Thread

	Technical polymer, nickel-plated brass, NBR, polyurethane tubing 	C		F	H	H1	L	kg
		R1/4	0631 00 07	16	163	148.5	91	0.617
		Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0656 66 13). Delivered without nozzle.						



Blowgun Kits

0631..06 Blowgun Kit, Upper Connection with Interchangeable Nozzle, Male BSPT Thread

	Technical polymer, nickel-plated brass, NBR, polyurethane tubing 	<div> <div>C</div> <div></div> </div>					
		<div> <div>R1/4</div> <div>0631 00 06</div> </div>					
		<div> <div>16</div> <div>161.5</div> <div>148.5</div> <div>93</div> <div>0.501</div> </div>					

Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0655 66 13).
 Delivered without nozzle.

0631..08 Energy Saving Blowgun Kit, Lower Connection, Interchangeable Nozzle, Male BSPT Thread


	Technical polymer, nickel-plated brass, NBR, polyurethane tubing 	<div> <div>C</div> <div></div> </div>					
		<div> <div>R1/4</div> <div>0631 00 08</div> </div>					
		<div> <div>16</div> <div>163</div> <div>148.5</div> <div>91</div> <div>0.496</div> </div>					

Flow characteristics, noise level and norm compliance are identical to those of our blowguns (0653 66 13).
 Delivered without nozzle.

Quick-Acting Couplers

Polymer Safety, C 9000

Metal: Nickel-Plated Brass and Stainless Steel



Quick-Acting Couplers

C 9000 Polymer Quick-Acting Safety Couplers (P. 8-7)



Fluids: compressed air

Materials: reinforced technical polymer, nickel-plated brass

Pressure: 16 bar

Temperature: -20°C to +60°C

DN : 5.5 mm to 8 mm

Metal Quick-Acting Couplers (P. 8-18)



Fluids: compressed air, water, industrial fluids

Materials: nickel-plated brass or stainless steel

Pressure: 35 bar (stainless steel), 20 bar (brass)

Temperature: -15°C to +200°C (stainless steel), -20°C to +100°C (brass)

DN : 2 mm to 19 mm

Metal Quick-Acting Mould Couplers (P. 8-50)



Fluids: heat transfer fluids

Materials: nickel-plated brass

Pressure: 10 bar

Temperature: -15°C to +90°C

DN : 8 mm to 12 mm

3 Shut-Off Functions

Straight-Through

These couplers work without shut-off, meaning they offer maximum flow. Straight-Through couplers are designed to carry fluids such as water, coolants, etc. Before disconnection, the fluid flow must be shut off using a valve located upstream of the coupler.



Single Shut-Off (with or without vent)

On our single shut-off couplers, the male probe is straight-through. The fluid flow can be stopped in the female coupler when disconnected. The circuit can be vented upstream to avoid any risk of whiplash.











Double Shut-Off

On our double shut-off couplers, after disconnection, flow is prevented both upstream of the female coupler and downstream of the probe. Both sides of the circuit remain under pressure.




Technology and Flow Rates

The profiles of the Parker Legris quick-acting couplers are manufactured to conform to international standards and are interchangeable with other manufacturers' products meeting these standards.

Profile Description	Profile	Interchangeability	Flow (NI/min)	Bore Diameter (mm)
ISO B Standard		C 9000 Rectus 23 Rectus 24	1250 900 550	5.5
		C 9000 Rectus 30	2400 890	8 8.5
European Standard		C 9000 Rectus 26 Rectus 25	2000 1000 1800	7.2 7.2 7.4
		Rectus 27	2400	10
ARO Standard		C 9000 Rectus 14 Rectus 22	1250 560 800	5.5
ISO C Standard		Rectus 18	970	5.5
Asian Standard		Rectus 13	1150	7.5
UK Standard		Rectus 17	870	5
		Rectus 19	660	5.5
German Standard		Rectus 20	165	2.7
		Rectus 21	560	5

Quick-Acting Coupler Part Numbers

Standard Product



C 9000 Polymer Quick-Acting Safety Coupler Range

C 9000 Polymer Quick-Acting Safety Couplers

ISO B Profile



European Profile



ARO Profile



C 9000 Polymer Quick-Acting Safety Couplers

This range of ergonomic polymer couplers has been designed for **the safety of operators and machinery** while giving very high **energy efficiency performance**. Available in three profile standards, it is perfectly suited for any type of installation.

Product Advantages

Safety & Reliability

- Prevents risk of whiplash
- Quick-acting vent allowing disconnection to be carried out in total safety
- Rotating sleeve to avoid risk of accidental disconnection
- Low connection/disconnection force even under pressure
- Polymer sleeve protects equipment from scratching
- Protective spiral over the tube prevents kinking

Performance

- Very high flow and low pressure drop
- 100% leak-tested in production
- Date coding to guarantee quality and traceability
- Robust impact-resistant material
- Optimum energy efficiency
- Long-term reliability

Easy-to-Use

- Immediate identification by clear marking on each model showing:
 - profile of the compatible male probe
 - type part number
- Compatible with male probes conforming to:
 - ISO B profile
 - European profile
 - ARO profile



Applications

- Workshops
- Cleaning
- Blowing
- Pneumatics
- Air-Operated Tools
- Ring Main Circuits
- Packaging


Technical Characteristics

Compatible Fluids	Compressed air
Working Pressure	0 to 16 bar
Working Temperature	-20°C to +60°C

Regulations

DI: 97/23/EC (PED)
 DI: 2002/95/EC (RoHS), 2011/65/EC
 DI: 1907/2006 (REACH)
 ISO 4414 Pneumatic Fluid Power: General Rules Relating to Systems
 DIN EN 983 Safety Standard for Pneumatics

Component Materials




Silicone-free



C 9000 Polymer Quick-Acting Safety Couplers

C 9000 Technology and Flow Rates

"Typical" quick-acting coupler
Standard "poppet" technology
Flow: 1400 NI/min




C 9000 quick-acting coupler
"Optimal flow" technology
Flow: 2400 NI/min



Measurements carried out in accordance with ISO 6358 at a pressure of 6 bar, pressure drop < 0.7 bar

Operation

Operation



Disconnecting the probe


Rotation, arrow 1: circuit vented on probe side.

Rotation, arrow 2: probe disconnected from the body.

Connecting the probe

The sleeve does not need to be rotated to connect the probe.

Venting



ISO B6 profile, recoil tubing (I.D. 6 mm, length 6 m)

Venting time = 350 ms (transition from 6 bar to 0.2 bar)

ISO B8 profile, PVC tubing (I.D. 10 mm, length 25 m)

Venting time = 860 ms (transition from 6 bar to 0.2 bar)

Even with longer lengths of tubing, the vent time of the C 9000 coupler can be less than 1 second.

ISO B Profile



9401U Coupler, Male BSPP Thread

Technical polymer, nickel-plated
brass, NBR

C

E F G L kg


5.5	G1/4	9401U06 13	7.5	17	31.5	74	0.075
	G3/8	9401U06 17	8.5	21	31.5	76.5	0.095
	G1/2	9401U06 21	10.5	25	31.5	80	0.115
8	G1/4	9401U08 13	6.5	22	36.5	81.5	0.120
	G3/8	9401U08 17	7.5	22	36.5	82.5	0.133
	G1/2	9401U08 21	9	25	36.5	85.5	0.140

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min

C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9405U Coupler, Male BSPT Thread

Technical polymer, nickel-plated
brass, NBR

DN	C		F	G	L	kg
5.5	R1/4	9405U06 13	17	31.5	75	0.075
	R3/8	9405U06 17	19	31.5	76.5	0.095
	R1/2	9405U06 21	22	31.5	81.5	0.110
8	R1/4	9405U08 13	22	36.5	84	0.120
	R3/8	9405U08 17	22	36.5	84	0.120
	R1/2	9405U08 21	22	36.5	88	0.140

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min
C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9414U Coupler, Female BSPP Thread

Technical polymer valve, nickel-plated brass, NBR





C

E F G L kg

5.5	G1/4	9414U06 13	12	17	31.5	66.5	0.070
	G3/8	9414U06 17	12	22	31.5	72	0.085
8	G1/2	9414U06 21	15	27	31.5	78	0.115
	G1/4	9414U08 13	12	22	36.5	75	0.127
	G3/8	9414U08 17	12	22	36.5	75	0.144
	G1/2	9414U08 21	15	27	36.5	80	0.138

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min
C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9410U Coupler, LF 3000® Push-In Connection, Body Spiral Protection Spring

	<p>Technical polymer, nickel-plated brass, NBR</p> 		ØD			G	L	L1	kg
		5.5	8	9410U06 08		31.5	145	56	0.096
			10	9410U06 10		31.5	145	56	0.080
		8	10	9410U08 10		36.5	155	63	0.175
			12	9410U08 12		36.5	165	63	0.162

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min
C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9421U Coupler with Hosetail

Technical polymer, nickel-plated
brass, NBR

ØD

F

G

L

L1

kg

6

5.5

9421U06 06

17

31.5

88.5

26

0.070

8

8

9421U06 08

17

31.5

88.5

26

0.070

10

10

9421U06 10

17

31.5

88.5

26

0.070

6

8

9421U08 06

22

36.5

95

26

0.110

8

8

9421U08 08

22

36.5

95

26

0.100

10

10

9421U08 10

22

36.5

95

26

0.124

13

13

9421U08 13

22

36.5

99


30

0.125




C 9000 Series ISO B (DN 5.5): single shut-off flow = 1250 NI/min

C 9000 Series ISO B (DN 8): single shut-off flow = 2400 NI/min

ISO B Profile






9416U Coupler, Bulkhead Mountable, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR 	DN	C		E	F	G	K_{max}	L1	L2	ØT_{min}	kg
		5.5	G1/4	9416U06 13	12	22	31.5	6	12.5	68.5	18.5	0.105
		8	G3/8	9416U08 17	12	24	36.5	7	14.5	76	22.5	0.150




C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min
C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9440U Y Coupler, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR 	DN	C		E	F	F1	G	H	H1	kg
		5.5	G3/8	9440U06 17	11.5	19	20	31.5	70	16	0.207
		8	G1/2	9440U08 21	14	22	25	36.5	80	19	0.352




C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min
C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9087U Probe, Straight-Through, Male BSPP Thread

	Nickel-plated steel, technical polymer 	DN	C		E	F	L	L1	kg
		5.5	G1/4	9087U06 13	9	17	38	24	0.025
			G3/8	9087U06 17	9	19	38	24	0.032
			G1/2	9087U06 21	12	22	42	24	0.048
		8	G1/4	9087U08 13	9	17	38	24	0.030
			G3/8	9087U08 17	9	19	39	24	0.036
			G1/2	9087U08 21	12	22	42	24	0.058




Probe without shut-off

9086U Probe, Straight-Through, Female BSPP Thread

	Nickel-plated steel 	DN	C		E	F	L	L1	kg
		5.5	G1/4	9086 23 13	9	17	36	24	0.025
			G3/8	9086 23 17	9	19	36	24	0.025
			G1/2	9086 23 21	12	24	39	24	0.039


Probe without shut-off

9086U Probe, Straight-Through, Female BSPP Thread





	Nickel-plated steel 	DN	C		E	F	L	L1	kg
		8.5	G1/4	9086 30 13	10	17	40	28	0.032
			G3/8	9086 30 17	10	19	42	28	0.035
			G1/2	9086 30 21	12	24	43	28	0.046

Probe without shut-off
30 Series probe (DN 8.5) compatible with ISO B series C 9000 couplers (DN 8)


ISO B Profile




9080U Probe, Straight-Through, LF 3000® Push-In Connection, with Spiral Protection Spring


	Nickel-plated steel, NBR			ØD		G	L	L1	kg
			5.5	8	9080U06 08	24	112	24	0.052
				10	9080U06 10	24	112	24	0.044
			8	10	9080U08 10	24	114	26	0.095
				12	9080U08 12	29.5	125	26	0.096
Probe without shut-off									

9094U Probe, Straight-Through, with Hosetail




Nickel-plated steel



DN	ØD		F	L	L1	L2	kg
5.5	6	9094U06 06	14	51	24	25	0.016
	8	9094U06 08	14	51	27	25	0.017
	10	9094U06 10	14	51	24	25	0.018
8	8	9094U08 08	17	51	24	25	0.027
	10	9094U08 10	17	51	27	25	0.028
	13	9094U08 13	17	51	24	25	0.031

Probe without shut-off

European Profile



9401E Coupler, Male BSPP Thread

	Technical polymer, nickel-plated brass, NBR 	$\overline{\text{DN}}$	C			E	F	G	L	kg
			G1/4	9401E07 13		6.5	22	36.5	80	0.124
		7.2	G3/8	9401E07 17		7.5	22	36.5	81	0.122
			G1/2	9401E07 21		9	25	36.5	83.5	0.136

C 9000 Series: single shut-off = 2000 NI/min

9414E Coupler, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR 	$\overline{\text{DN}}$	C			E	F	G	L	kg
			G1/4	9414E07 13		12	22	36.5	73	0.118
		7.2	G3/8	9414E07 17		12	22	36.5	73	0.109
			G1/2	9414E07 21		15	27	36.5	78	0.130

C 9000 Series: single shut-off = 2000 NI/min

9410E Coupler, LF 3000® Push-In Connection, with Spiral Protection Spring

	Technical polymer, nickel-plated brass, NBR 	$\overline{\text{DN}}$	ØD			G	L	L1	kg
			10	9410E07 10		36.5	151	63	0.175
		7.2	12	9410E07 12		36.5	151	63	0.180

C 9000 Series: single shut-off = 2000 NI/min

9421E Coupler with Hosetail

	Technical polymer, nickel-plated brass, NBR 	$\overline{\text{DN}}$	ØD			F	G	L	L1	kg
			8	9421E07 08		22	36.5	93	26	0.113
		7.2	10	9421E07 10		22	36.5	93	26	0.114
			13	9421E07 13		22	36.5	97	30	0.119


C 9000 Series: single shut-off = 2000 NI/min

9416E Coupler, Bulkhead Mountable, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR 	$\overline{\text{DN}}$	C			E	F	G	K max	L1	L2	ØT min	kg
		7.2	G3/8	9416E07 17		12	24	36.5	7	14.5	74	22.5	0.153

C 9000 Series: single shut-off = 2000 NI/min





European Profile







9440E Y Coupler, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR			C		E	F	F1	G	H	H1	kg
			7.2	G1/2	9440E07 21	14	25	25	36.5	78	19	0.335
			C 9000 Series: single shut-off = 2000 NI/min									





9087E Probe, Straight-Through, Male BSPP Thread

	<p>Nickel-plated steel, technical polymer</p> 	<p> C </p>	E	F	L	L1	kg			
			7.2	G1/4	9087E07 13	9	14	34	20	0.018
				G3/8	9087E07 17	9	17	34	20	0.025
				G1/2	9087E07 21	12	22	38	20	0.048
			Probe without shut-off							





9086E Probe, Straight-Through, Female BSPP Thread

	<p>Nickel-plated steel</p> 		C		E	F	L	L1	kg
		7.4	G1/8	9086 25 10	7	14	32	20	0.015
			G1/4	9086 25 13	9	17	38.5	20	0.027
			G3/8	9086 25 17	9	19	33	20	0.027
			G1/2	9086 25 21	12	24	36	20	0.050
Probe without shut-off									


9080E Probe, Straight-Through, LF 3000® Push-In Connection, with Spiral Protection Spring

	Nickel-plated steel, NBR			ØD		G	L	L1	kg
	7.2		10	9080E07 10	24	114	20	0.102	
			12	9080E07 12	29.5	125	20	0.088	
	Probe without shut-off								





9094E Probe, Straight-Through, with Hosetail

	<p>Nickel-plated steel</p> 		ØD		F	L	L1	L2	kg
			8	9094E07 08	17	48	20	25	0.014
7.2			10	9094E07 10	17	48	20	25	0.016
			13	9094E07 13	17	48	20	25	0.019
Probe without shut-off									





ARO Profile







9401A Coupler, Male BSPP Thread

	Technical polymer, nickel-plated brass, NBR 		C		E	F	G	L	kg
			G1/4	9401A06 13	6.5	17	31.5	70.5	0.105
		5.5	G3/8	9401A06 17	9	21	31.5	73.5	0.123
			G1/2	9401A06 21	9	25	31.5	70.5	0.150
		C 9000 series: single shut-off = 1250 NI/min							





9405A Coupler, Male BSPT Thread

	<p>Technical polymer, nickel-plated brass, NBR</p> 		C		F	G	L	kg
			R1/4	9405A06 13	17	31.5	73	0.105
		5.5	R3/8	9405A06 17	19	31.5	74.5	0.110
			R1/2	9405A06 21	22	31.5	79.5	0.140
		C 9000 series: single shut-off = 1250 NI/min						





9414A Coupler, Female BSPP Thread

	<p>Technical polymer, nickel-plated brass, NBR</p> 		C		E	F	G	L	kg
		G1/4	9414A06 13	12	17	31.5	64.5	0.095	
		5.5	G3/8	9414A06 17	12	22	31.5	70	0.115
		G1/2	9414A06 21	15	27	31.5	76	0.145	
		C 9000 series: single shut-off = 1250 NI/min							


9410A Coupler, LF 3000® Push-In Connection, with Spiral Protection Spring

	Technical polymer, nickel-plated brass, NBR 		ØD		G	L	L1	kg
			8	9410A06 08	31.5	143	54	0.140
		5.5	10	9410A06 10	31.5	143	54	0.175
		C 9000 series: single shut-off = 1250 NI/min						





9421A Coupler with Hosetail

	<p>Technical polymer, nickel-plated brass, NBR</p> 		ØD		F	G	L	L1	kg
			6	9421A06 06	17	31.5	86.5	26	0.110
		5.5	8	9421A06 08	17	31.5	86.5	26	0.100
			10	9421A06 10	17	31.5	86.5	26	0.100
		C 9000 series: single shut-off = 1250 NI/min							





ARO Profile







9416A Coupler, Bulkhead Mountable, Female BSPP Thread

	<p>Technical polymer, nickel-plated brass, NBR</p> 	<p> C </p>											E F G K L1 L2 ØT kg	
			<p>5.5 G1/4 9416A06 13</p>											12 22 31.5 6 12.5 66.5 18.5 0.135
			<p>C 9000 series: single shut-off = 1250 Nl/min</p>											





9440A Y Coupler, Female BSPP Thread

	<p>Technical polymer, nickel-plated brass, NBR</p> 	 C 											kg
			5.5	G3/8	9440A06 17	11.5	19	20	31.5	68	16		
			C 9000 series: single shut-off = 1250 NI/min										





9087A Probe, Straight-Through, Male BSPP Thread

	<p>Nickel-plated steel, technical polymer</p> 	 C 						kg			
			G1/4	9087A06 13	9	17	36		22	0.020	
			5.5	G3/8	9087A06 17	9	19		36	22	0.024
				G1/2	9087A06 21	12	24		40	22	0.039
			Probe without shut-off								


9086A Probe, Straight-Through, Female BSPP Thread

	<p>Nickel-plated steel</p> 		C							kg		
					G1/4	9086 22 13	9	17	35.5		22	
					5.5	G3/8	9086 22 17	10	19		35.5	22
						G1/2	9086 22 21	12	24		38	22
					Probe without shut-off							

9084A Probe, Straight-Through, Male BSPT Thread






	<p>Nickel-plated steel</p> 		C						kg			
					R1/4	9084 22 13	14	40.5		22	0.020	
					5.5	R3/8	9084 22 17	17		40.5	22	0.031
						R1/2	9084 22 21	22		46	22	0.048
					Probe without shut-off							

ARO Profile








9080A

Probe, Straight-Through, LF 3000® Push-In Connection, with Spiral Protection Spring

	Nickel-plated steel, NBR									
			5.5	8		9080A06 08	24	118	22	0.028
				10		9080A06 10	24	118	22	0.027
			Probe without shut-off							

9094A

Probe, Straight-Through, with Hosetail

	Nickel-plated steel						F	L	L1	L2	kg
			5.5	6	9094A06 06	14	48.5	22	25	0.012	
				8	9094A06 08	14	48.5	22	25	0.014	
				10	9094A06 10	14	48.5	22	25	0.016	
			Probe without shut-off								


Metal Quick-Acting Coupler Range

Nickel-Plated Brass Quick-Acting Couplers

ISO B Profile, 23, 24 and 30 Series



European Profile, 25, 26 and 27 Series



ARO Profile, 14 and 22 Series



ISO C Profile, 18 Series



Asian Profile, 13 Series




UK Profile, 17 and 19 Series



Metal Quick-Acting Coupler Range

Nickel-Plated Brass Quick-Acting Couplers

German Profile, 20 and 21 Series



Mini Series



Standard Series



Midi Series



Maxi Series







Metal Quick-Acting Coupler Range

Stainless Steel Quick-Acting Couplers


European Profile, X25 and X27 Series

9201 Page 8-47	9214 Page 8-47	9287 Page 8-47	9087 Page 8-47	9286 Page 8-47	9086 Page 8-47
					

German Profile, X20 Series

9201 Page 8-48	9214 Page 8-48	9287 Page 8-48	9087 Page 8-48	9286 Page 8-48	9086 Page 8-48
					

German Profile, X21 Series

9201 Page 8-49	9214 Page 8-49	9287 Page 8-49	9087 Page 8-49	9286 Page 8-49	9086 Page 8-49
					

Quick-Acting Mould Couplers

9020 Page 8-51	9040 Page 8-51	9075 Page 8-51
		

Metal Quick-Acting Coupler Accessories

9071 Page 8-53	0691 Page 8-53	0681 Page 8-53	0164 Page 8-53	0167 Page 8-53
				

Metal Quick-Acting Couplers

In order to fulfill the requirements of the **widest range of industrial applications**, Parker Legris offers a range of metal couplers compatible with a large selection of fluids.

Simple to install, with or without shut-off valves, these couplers offer a **high flow rate capability**.

Product Advantages

Easy-to-Use

- Coupler with sliding sleeve: automatic connection and disconnection
- Wide variety of male probes
- Extremely compact
- Single or double shut-off models for greater safety
- Special range designed for pneumatic applications: 13 Series to 27
- Special range designed for the transmission of water and fluids: Midi and Maxi series

Robust & Reliable

- 100% leak-tested in production
- Excellent shock and impact resistance
- Nickel-plated brass for corrosion resistance
- Stainless steel version for restrictive environments

Optimum Performance

- Very wide range of flow rates
- "UltraFlo" technology: 18, 22, 23, 25 and 27 series
- Low pressure drop
- Long service life
- Maximum energy efficiency



Applications


- Workshops
- Flushing
- Spraying
- Packaging
- Factory Automation
- Filling Systems
- Cleaning

Technical Characteristics

Compatible Fluids	Compressed air, water (see compatibility chart below)
Working Pressure	0 to 20 bar 0 to 35 bar (stainless steel series)
Working Temperature	-20°C to +100°C -15°C to +200°C (stainless steel series)

Guaranteed for use with a vacuum of 655 mm Hg (86% vacuum).

Component Materials




Silicone-free

Metal Quick-Acting Couplers


Metal Quick-Acting Coupler Technology and Flow Rates

Measurements carried out in accordance with ISO 6358
at a pressure of 6 bar, pressure drop < 0.7 bar (single shut-off flow)




"Typical" quick-acting coupler

Standard "poppet" technology
Flow: 1000 NI/min




UltraFlo quick-acting coupler

"Optimal flow" technology
Flow: 1700 NI/min





3 Shut-Off Functions

Straight-Through





Single Shut-Off



Single shut-off coupler
+ probe without shut-off
When disconnected, the fluid path is closed upstream (body side).

Double Shut-Off




Double shut-off coupler
+ probe with shut-off
When disconnected, the fluid path is closed upstream (body side) and downstream (probe side).

Operation



Installation Options



Chemical Compatibility Chart for Metal Couplers

Below are the fluids compatible with Parker Legris metal quick-acting couplers.
This list is not exhaustive: if your fluid is not shown here, please contact us.

Acetamide

Ammonium chloride
Ammonium in solution
Argon
ASTM no. 1 oil
ASTM no. 2 oil
ASTM no. 3 oil

Butyl alcohol

Calcium carbonate

Castor oil
Coconut oil
Cod liver oil
Cold ammonium
Corn oil
Cotton seed oil
Cyclohexane

Detergents

Diesel oil
Diethylene glycol

Engine oil

Ethane
Ethanol
Ethyl alcohol
Ethyl silicate
Ethylene glycol

Fuel oil

Gear oil

Glycerin
Glycerol triacetate
Glycol
Groundnut oil

Heating oil (petroleum-based)

Helium

Heptane N

Hexane N

Hexyl alcohol

Hydraulic liquids:

H group
H-L group
H-LP group
HSA group
HSB group
HSD c (T) group in accordance with
DIN 51524 and 51525

Isododecane

Isooctane

Lard

Linseed oil

Methanol

Mineral oil

Neatsfoot oil

N-Heptane

N-Hexane

Nitrogen

N-Pentane

Octadecane

Olive oil

Pentane N

Petroleum

Propyl alcohol

Propylene glycol

Seawater

Silicone grease
Soap solution
Sodium hydroxide
Sodium sulphate

Soya bean oil

Stearyl alcohol

Terebenthine

Trisodium phosphate

Vaseline

Vaseline oil
Vegetable oil

Water

Wood oil

Zinc chloride





The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.

ISO B Profile





23, 24 and 30 Series







9101 Coupler, Male BSPP Thread

	Nickel-plated brass, NBR				E	F	G	L	kg	
			C							
			G1/4	9101 23 13	9	19	23	57	0.091	
			G3/8	9101 23 17	9	19	23	57	0.093	





9101 Coupler, Male BSPP Thread

	Nickel-plated brass, NBR			C		E	F	G	L	kg
5.5	G1/4	9101 24 13	9	22	27	43	0.079			
	G3/8	9101 24 17	9	22	27	43	0.082			
	G1/2	9101 24 21	12	24	27	46	0.093			
8.5	G1/4	9101 30 13	9	22	29	49	0.097			
	G3/8	9101 30 17	9	22	29	49	0.099			
	G1/2	9101 30 21	12	22	29	52	0.110			
24 Series (DN 5.5): single shut-off = 550 NI/min 30 Series (DN 8.5) : single shut-off = 890 NI/min										





9114 Coupler, Female BSPP Thread

	Nickel-plated brass, NBR			C		E	F	G	L	kg
5.5				G1/4	9114 23 13	9	19	23	55	0.095
				G3/8	9114 23 17	9	19	23	55	0.087
				G1/2	9114 23 21	12	24	23	57	0.120
23 Series (DN 5.5): single shut-off = 900 NI/min										

9114 Coupler, Female BSPP Thread


	Nickel-plated brass, NBR			C		E	F	G	L	kg
5.5	G1/4	9114 24 13	9	22	27	43	0.096			
	G3/8	9114 24 17	9	22	27	43	0.091			
	G1/2	9114 24 21	12	24	27	46	0.098			
8.5	G1/4	9114 30 13	9	22	29	49	0.113			
	G3/8	9114 30 17	9	22	29	49	0.107			
	G1/2	9114 30 21	12	24	29	52	0.115			
24 Series (DN 5.5): single shut-off = 550 NI/min 30 Series (DN 8.5): single shut-off = 890 NI/min										

9123 Coupler with Barb Connection

	Nickel-plated brass, NBR			ØD		F	G	L	L1	kg
			5.5	6	9123 23 06	19	23	73	25	0.091
				8	9123 23 08	19	23	73	25	0.092
				10	9123 23 10	19	23	73	25	0.094
23 Series (DN 5.5): single shut-off = 900 NI/min										

ISO B Profile

23, 24 and 30 Series



9123 Coupler with Barb Connection

ØD	F	G	L	L1	kg
6	21	27	60	25	0.081
5.5	21	27	60	25	0.082
10	21	27	60	25	0.082
8	22	30	66	25	0.098
8.5	22	30	66	25	0.098
13	22	30	66	25	0.103

24 Series (DN 5.5): single shut-off = 550 Nl/min
30 Series (DN 8.5): single shut-off = 890 Nl/min

9087 Probe, Straight-Through, Male BSPP Thread

C	E	F	L	L1	kg
G1/8	9	13	39	24	0.017
5.5	9	17	38	24	0.025
G3/8	9	19	38	24	0.032
G1/2	12	22	42	24	0.048
G1/4	9	17	42	28	0.030
8.5	9	19	42	28	0.036
G3/8	12	24	46	28	0.058
G1/2	12	24	46	28	0.058

Probe without shut-off
23 Series probe (DN 5.5) compatible with 24 Series coupler (DN 5.5)

9086 Probe, Straight-Through, Female BSPP Thread

C	E	F	L	L1	kg
G1/8	9	17	36	24	0.021
5.5	9	17	36	24	0.025
G3/8	9	19	36	24	0.025
G1/2	12	24	39	24	0.039
G1/4	10	17	40	28	0.032
8.5	10	19	42	28	0.035
G3/8	12	24	43	28	0.046
G1/2	12	24	43	28	0.046

Probe without shut-off
23 Series probe (DN 5.5) compatible with 24 Series coupler (DN 5.5)

9085 Probe, Straight-Through, with Barb Connection

ØD	L	L1	L2	kg
6	51	24	25	0.016
5.5	51	27	25	0.017
10	51	24	25	0.018
8	55	28	25	0.027
8.5	55	28	25	0.028
13	55	28	25	0.031

Probe without shut-off
23 Series probe (DN 5.5) compatible with 24 Series coupler (DN 5.5)


9293 Probe, Valved, Anti-Whiplash, Female BSPP Thread

C	E	F	L	L1	kg
5.5 G1/4	10	22	47	24	0.058

Probe with shut-off





European Profile

25, 26 and 27 Series







9101

Coupler, Male BSPP Thread

	Nickel-plated brass, NBR			C		E	F	G	L	kg
7.2	G1/8	9101 26 10	9	22	27	43	0.073			
	G1/4	9101 26 13	9	22	27	43	0.073			
	G3/8	9101 26 17	9	22	27	13	0.075			
	G1/2	9101 26 21	12	22	27	46	0.087			
26 Series (DN 7.2): single shut-off = 1000 NL/min										





9201

Coupler, Male BSPP Thread

	Nickel-plated brass, NBR			C		E	F	G	L	kg
7.4	G1/4	9201 25 13	9	19	23	57	0.095			
	G3/8	9201 25 17	9	19	23	57	0.097			
	G1/2	9201 25 21	12	22	23	60	0.135			
10	G3/8	9201 27 17	9	24	27	65	0.160			
	G1/2	9201 27 21	12	24	27	70	0.166			
	G3/4	9201 27 27	16	27	27	74	0.239			
25 Series (DN 7.4): single shut-off = 1800 NL/min / 25 Series (DN 7.4): double shut-off = 710 NL/min 27 Series (DN 10): single shut-off = 2400 NL/min / 27 Series (DN 7.4): double shut-off = 900 NL/min										





9214

Coupler, Female BSPP Thread

	Nickel-plated brass, NBR			C		E	F	G	L	kg
7.4	G1/4	9214 25 13	9	19	23	55	0.098			
	G3/8	9214 25 17	9	19	23	55	0.092			
	G1/2	9214 25 21	12	24	23	57	0.124			
10	G3/8	9214 27 17	12	24	27	68	0.177			
	G1/2	9214 27 21	12	24	27	68	0.166			
	G3/4	9214 27 27	16	32	27	74	0.255			
25 Series (DN 7.4): single shut-off = 1800 NL/min / 25 Series (DN 7.4): double shut-off = 710 NL/min 27 Series (DN 10): single shut-off = 2400 NL/min / 27 Series (DN 7.4): double shut-off = 900 NL/min										





9114

Coupler, Female BSPP Thread

	<p>Nickel-plated brass, NBR</p> 		C		E	F	G	L	kg	
		7.2	G1/4	9114 26 13	9	22	27	43	0.089	
			G3/8	9114 26 17	9	22	27	43	0.084	
			G1/2	9114 26 21	12	24	27	46	0.090	
26 Series (DN 7.2): single shut-off = 1000 NL/min										

9223


Coupler with Barb Connection

	<p>Nickel-plated brass, NBR</p> 		ØD		F	G	L	L1	kg
		7.4	6	9223 25 06	19	23	73	25	0.095
			8	9223 25 08	19	23	73	25	0.097
			10	9223 25 10	19	23	73	25	0.097
			13	9223 25 13	19	23	73	25	0.099
		10	8	9223 27 08	24	27	80	21	0.146
			10	9223 27 10	24	27	80	21	0.162
			13	9223 27 13	24	27	80	21	0.164
			19	9223 27 19	24	27	80	21	0.168

25 Series (DN 7.4): single shut-off = 1800 NL/min / 25 Series (DN 7.4): double shut-off = 710 NL/min
27 Series (DN 10): single shut-off = 2400 NL/min / 27 Series (DN 7.4): double shut-off = 900 NL/min

European Profile

25, 26 and 27 Series



9087

Probe, Straight-Through, Male BSPP Thread

Nickel-plated steel, technical
polymer

C

E

F

L

L1

kg


7.4	G1/8	9087 25 10	7	13	31	20	0.018
	G1/4	9087 25 13	9	14	34	20	0.018
	G3/8	9087 25 17	9	17	34	20	0.025
10	G1/2	9087 25 21	12	22	38	20	0.047
	G3/8	9087 27 17	9	19	37	22	0.031
	G1/2	9087 27 21	12	22	40	22	0.046
	G3/4	9087 27 27	16	32	45	22	0.085

Probe without shut-off


25 Series probe (DN 7.4) compatible with 26 Series coupler (DN 7.2)



9086

Probe, Straight-Through, Female BSPP Thread



Nickel-plated steel



		C		E	F	L	L1	kg
7.4	G1/8	9086 25 10		7	14	32	20	0.015
	G1/4	9086 25 13		9	17	38.5	20	0.027
	G3/8	9086 25 17		9	19	33	20	0.027
10	G1/2	9086 25 21		12	24	36	20	0.050
	G3/8	9086 27 17		9	19	34	22	0.026
	G1/2	9086 27 21		12	24	38	22	0.041
	G3/4	9086 27 27		16	32	42	22	0.090

Probe without shut-off

25 Series probe (DN 7.4) compatible with 26 Series coupler (DN 7.2)

9085

Probe, Straight-Through, with Barb Connection

Nickel-plated steel





		ØD		L	L1	L2	kg
7.4		6	9085 25 06	48	20	25	0.013
		8	9085 25 08	48	20	25	0.015
		9	9085 25 09	48	20	25	0.015
		10	9085 25 10	48	20	25	0.016
		13	9085 25 13	48	20	25	0.020
10		8	9085 27 08	48	22	25	0.021
		10	9085 27 10	48	22	25	0.023
		13	9085 27 13	48	22	25	0.026
		19	9085 27 19	48	22	25	0.038

Probe without shut-off

25 Series probe (DN 7.4) compatible with 26 Series coupler (DN 7.2)

9287

Probe, Valved, Male BSPP Thread


		Nickel-plated brass, NBR									
			C		E	F	L	L1	kg		
7.4	G1/8	9287 25 10		7	22	41	20	0.046			
	G1/4	9287 25 13		9	22	43	20	0.046			
	G3/8	9287 25 17		9	22	43	20	0.049			
	G1/2	9287 25 21		12	22	46	20	0.060			
10	G3/8	9287 27 17		9	24	58	22	0.086			
	G1/2	9287 27 21		12	24	58	22	0.090			
	G3/4	9287 27 27		16	27	62	22	0.132			

Probe with shut-off

25 Series probe (DN 7.4) not compatible with 26 Series coupler (DN 7.2)

European Profile

25, 26 and 27 Series



9286

Probe, Valved, Female BSPP Thread

	Nickel-plated steel, NBR		DN	C		E	F	L	L1	kg
7.4				G1/8	9286 25 10	10	22	43	20	0.068
				G1/4	9286 25 13	10	22	43	20	0.062
				G3/8	9286 25 17	10	22	43	20	0.058
				G1/2	9286 25 21	12	24	46	20	0.064
10				G3/8	9286 27 17	9	24	55	22	0.096
				G1/2	9286 27 21	12	24	55	22	0.086
				G3/4	9286 27 27	16	32	58	22	0.149

Probe with shut-off
25 Series Probe (DN 7.4) not compatible with 26 Series coupler (DN 7.2)

9285

Probe, Valved, with Barb Connection

	Nickel-plated steel, NBR		DN	ØD		F	L	L1	L2	kg
7.4				6	9285 25 06	21	60	20	25	0.047
				8	9285 25 08	21	60	20	25	0.048
				10	9285 25 10	21	60	20	25	0.049
				13	9285 25 13	21	60	20	25	0.053
10				8	9285 27 08	24	75	22	25	0.097
				10	9285 27 10	24	75	22	25	0.099
				13	9285 27 13	24	75	22	25	0.103
				19	9285 27 19	24	75	22	25	0.105

Probe with shut-off
25 Series Probe (DN 7.4) not compatible with 26 Series coupler (DN 7.2)

9293


Probe, Valved, Anti-Whiplash, Female BSPP Thread

	Nickel-plated steel, NBR		DN	C		E	F	L	L1	kg
7.4				G3/8	9293 25 17	10	22	43	20	0.052

Probe with shut-off
25 Series Probe (DN 7.4) not compatible with 26 Series coupler (DN 7.2)

ARO Profile


14 and 22 Series



9101 Coupler, Male BSPP Thread



Nickel-plated brass, NBR




DN	C		E	F	G	L	kg
5.5	G1/4	9101 14 13	9	22	27	43	0.080
	G3/8	9101 14 17	9	22	27	43	0.081
	G1/2	9101 14 21	12	24	27	46	0.093

14 Series (DN 5.5): single shut-off = 560 Nl/min

9105 Coupler, Male BSPT Thread



Nickel-plated brass, NBR




DN	C		F	G	L	kg
5.5	R1/4	9105 22 13	19	23	61	0.098
	R3/8	9105 22 17	12	19	60	0.096
	R1/2	9105 22 21	22	23	61	0.114

22 Series (DN 5.5): single shut-off = 800 Nl/min

9114 Coupler, Female BSPP Thread



Nickel-plated brass, NBR




DN	C		E	F	G	L	kg
5.5	G1/4	9114 14 13	9	22	27	43	0.095
	G3/8	9114 14 17	9	22	27	43	0.091
	G1/2	9114 14 21	12	24	27	46	0.098

14 Series (DN 5.5): single shut-off = 560 Nl/min

9114 Coupler, Female BSPP Thread



Nickel-plated brass, NBR




DN	C		E	F	G	L	kg
5.5	G1/4	9114 22 13	9	19	23	56	0.098
	G3/8	9114 22 17	9	19	23	55	0.091
	G1/2	9114 22 21	12	24	23	58	0.123

22 Series (DN 5.5): single shut-off = 800 Nl/min

9123 Coupler with Barb Connection



Nickel-plated brass, NBR




DN	ØD		F	G	L	L1	kg
5.5	6	9123 14 06	21	27	60	25	0.080
	8	9123 14 08	21	27	60	25	0.081
	9	9123 14 09	21	27	60	25	0.082
	10	9123 14 10	21	27	60	25	0.082
	13	9123 14 13	21	27	60	25	0.094

14 Series (DN 5.5): single shut-off = 560 Nl/min

ARO Profile

14 and 22 Series



9123 Coupler with Barb Connection

	Nickel-plated brass, NBR 	$\overline{\text{DN}}$	$\emptyset D$			F	G	L	L1	kg
			6		9123 22 06	19	23	74	25	0.093
		5.5	8		9123 22 08	19	23	74	25	0.097
			10		9123 22 10	19	23	74	25	0.098

22 Series (DN 5.5): single shut-off = 800 NI/min

9084 Probe, Straight-Through, Male BSPT Thread

	Nickel-plated steel 	$\overline{\text{DN}}$	C			F	L	L1	kg
			R1/4		9084 22 13	14	40.5	22	0.020
		5.5	R3/8		9084 22 17	17	40.5	22	0.031
			R1/2		9084 22 21	22	46	22	0.048

Probe without shut-off
22 Series probe (DN 5.5) compatible with 14 Series coupler (DN 5.5)

9086 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated steel 	$\overline{\text{DN}}$	C			E	F	L	L1	kg
			G1/4		9086 22 13	9	17	35.5	22	0.024
		5.5	G3/8		9086 22 17	10	19	35.5	22	0.023
			G1/2		9086 22 21	12	24	38	22	0.039

Probe without shut-off
22 Series probe (DN 5.5) compatible with 14 Series coupler (DN 5.5)


9085 Probe, Straight-Through, with Barb Connection

	Nickel-plated steel 	$\overline{\text{DN}}$	$\emptyset D$			L	L1	L2	kg
			6		9085 22 06	48.5	22	25	0.012
			8		9085 22 08	48.5	22	25	0.014
		5.5	9		9085 22 09	48.5	22	25	0.014
			10		9085 22 10	48.5	22	25	0.016
			13		9085 22 13	48.5	22	25	0.022

Probe without shut-off
22 Series probe (DN 5.5) compatible with 14 Series coupler (DN 5.5)

ISO C Profile

18 Series



9101 Coupler, Male BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
			5.5	G1/4	9101 18 13	9	19	23	60	0.106
				G3/8	9101 18 17	9	19	23	60	0.108

18 Series (DN 5.5) : single shut-off = 970 NI/min

9114 Coupler, Female BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
			5.5	G1/4	9114 18 13	9	19	23	58	0.109
				G3/8	9114 18 17	9	19	23	58	0.101

18 Series (DN 5.5) : single shut-off = 970 NI/min

9123 Coupler with Barb Connection

	Nickel-plated brass, NBR		DN	ØD		F	G	L	L1	kg
			5.5	6	9123 18 06	19	23	76	25	0.104
				8	9123 18 08	19	23	76	25	0.106
				10	9123 18 10	19	23	76	25	0.108

18 Series (DN 5.5) : single shut-off = 970 NI/min

9087 Probe, Straight-Through, Male BSPP Thread

	Nickel-plated steel		DN	C		E	F	L	L1	kg
			5.5	G1/4	9087 18 13	9	17	41	28	0.025
				G3/8	9087 18 17	9	19	41	28	0.028

Probe without shut-off

9086 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated steel		DN	C		E	F	L	L1	kg
			5.5	G1/4	9086 18 13	9	17	40	28	0.022
				G3/8	9086 18 17	9	19	41	28	0.024

Probe without shut-off


9085 Probe, Straight-Through, with Barb Connection

	Nickel-plated steel		DN	ØD		L	L1	L2	kg
			5.5	6	9085 18 06	56	28	25	0.016
				8	9085 18 08	56	28	25	0.016
				10	9085 18 10	56	28	25	0.018





Probe without shut-off

Asian Profile





13 Series







9105 Coupler, Male BSPT Thread

	Nickel-plated brass, NBR						F	G	L	kg
			C							
			7.5							
			R1/4	9105 13 13		22	27	49	0.086	
			R3/8	9105 13 17		22	27	49	0.090	
			R1/2	9105 13 21		22	27	53	0.110	
13 Series (DN 7.5): single shut-off = 1150 NL/min										





9114 Coupler, Female BSPP Thread

	<p>Nickel-plated brass, NBR</p> 		C		E	F	G	L	kg	
		G1/4	9114 13 13	9	22	27	45	0.099		
		G3/8	9114 13 17	9	22	27	45	0.093		
		G1/2	9114 13 21	12	24	27	48	0.102		
13 Series (DN 7.5): single shut-off = 1150 NL/min										





9123 Coupler with Barb Connection

	Nickel-plated brass, NBR			ØD		F	G	L	L1	kg
			7.5	8	9123 13 08	21	27	62	25	0.084
				10	9123 13 10	21	27	62	25	0.086
				13	9123 13 13	21	27	62	25	0.089
13 Series (DN 7.5): single shut-off = 1150 NL/min										





9084 Probe, Straight-Through, Male BSPT Thread

	Nickel-plated steel			C		F	L	L1	kg
			7.5	R1/4	9084 13 13	14	37	12	0.022
				R3/8	9084 13 17	17	37	12	0.028
				R1/2	9084 13 21	22	44	17	0.050
Probe without shut-off									

9086 Probe, Straight-Through, Female BSPP Thread


	<p>Nickel-plated steel</p> 		C		E	F	L	L1	kg	
7.5	G1/4	9086 13 13	9	17	22	12	0.026			
	G3/8	9086 13 17	9	19	33	12	0.024			
	G1/2	9086 13 21	12	24	36	17	0.036			
Probe without shut-off										

9085 Probe, Straight-Through, with Barb Connection




	Nickel-plated steel			ØD		L	L1	kg
7.5				8	9085 13 08	48	25	0.020
				10	9085 13 10	48	25	0.021
				13	9085 13 13	48	25	0.026
Probe without shut-off								

UK Profile




17 Series



9105 Coupler, Male BSPT Thread




	Nickel-plated brass, NBR							
			DN	C	F	G	L	kg
	5	R1/4	19	23	63	0.109		
		R3/8	19	23	62	0.108		
		R1/2	22	23	63	0.124		
17 Series (DN 5) : Single shut-off = 870 NI/min								

9114 Coupler, Female BSPP Thread

	Nickel-plated brass, NBR										
				DN	C	E	F	G	L	kg	
				5	G1/4	9	19	23	58	0.110	
					G3/8	9	19	23	57	0.103	
				G1/2	12	24	23	60	0.135		





17 Series (DN 5) : Single shut-off = 870 NI/min

9123 Coupler with Barb Connection





	Nickel-plated brass, NBR									
				DN	ØD	F	G	L	L1	kg
				5	6	19	23	76	25	0.106
					8	19	23	76	25	0.108
				10	19	23	76	25	0.111	

17 Series (DN 5): single shut-off = 870 NI/min





9084 Probe, Straight-Through, Male BSPT Thread

	Nickel-plated steel			C		F	L	L1	kg
	5		R1/8	9084 17 10	11	37	9	0.016	
			R1/4	9084 17 13	14	42	12	0.021	
			R3/8	9084 17 17	17	42	12	0.014	
			R1/2	9084 17 21	22	48	17	0.048	
Probe without shut-off									

9086 Probe, Straight-Through, Female BSPP Thread


	<p>Nickel-plated steel</p> 		C		E	F	L	kg
		5	G1/8	9086 17 10	7	14	33	0.016
			G1/4	9086 17 13	9	17	33	0.022
			G3/8	9086 17 17	9	19	33	0.023
			G1/2	9086 17 21	12	24	36	0.030
		Probe without shut-off						

9085 Probe, Straight-Through, with Barb Connection



	Nickel-plated steel			ØD						
						L	L1	L2	kg	
	5	6				9085 17 06	58	25	33	0.015
		8				9085 17 08	52	25	27	0.016
		10				9085 17 10	52	25	27	0.018
Probe without shut-off										

UK Profile

19 Series





9105 Coupler, Male BSPT Thread

	Nickel-plated brass, NBR		DN	C		F	G	L	kg
				R1/4	9105 19 13	19	23	63	0.100
			5.5	R3/8	9105 19 17	19	23	62	0.099
				R1/2	9105 19 21	22	23	68	0.117



19 Series (DN 5.5): single shut-off = 660 NI/min

9114 Coupler, Female BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
				G1/4	9114 19 13	9	19	23	58	0.102
			5.5	G3/8	9114 19 17	9	19	23	58	0.095
				G1/2	9114 19 21	12	24	23	60	0.127



19 Series (DN 5.5): single shut-off = 660 NI/min

9123 Coupler with Barb Connection

	Nickel-plated brass, NBR		DN	ØD		F	G	L	L1	kg
				6	9123 19 06	19	23	76	25	0.097
			5.5	8	9123 19 08	19	23	76	25	0.099
				10	9123 19 10	24	23	76	25	0.100



19 Series (DN 5.5): single shut-off = 660 NI/min

9084 Probe, Straight-Through, Male BSPT Thread

	Nickel-plated steel		DN	C		F	L	L1	kg
				R1/4	9084 19 13	14	50	12	0.022
			5.5	R3/8	9084 19 17	17	50	12	0.026
				R1/2	9084 19 21	22	56	17	0.051



Probe without shut-off

9086 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated steel		DN	C		E	F	L	kg
				G1/4	9086 19 13	9	17	46	0.025
			5.5	G3/8	9086 19 17	9	19	47	0.026
				G1/2	9086 19 21	12	24	50	0.039

Probe without shut-off


9085 Probe, Straight-Through, with Barb Connection

	Nickel-plated steel		DN	ØD		L	L1	L2	kg
				6	9085 19 06	60	25	35	0.016
			5.5	8	9085 19 08	60	25	35	0.017
				10	9085 19 10	60	25	35	0.019





Probe without shut-off

German Profile




20 Series







9201 Coupler, Male BSPP and Metric Thread

	Nickel-plated brass, NBR		C		E	F	G	L	kg
		2.7	M5x0.8	9201 20 19	5	9	10	26	0.009
			G1/8	9201 20 10	7	11	10	28	0.012
20 Series (DN 2.7): single shut-off = 165 Nl/min 20 Series (DN 2.7): double shut-off = 130 Nl/min									





9214 Coupler, Female BSPP and Metric Thread

	Nickel-plated brass, NBR		C		E	F	G	L	kg
		2.7	M5x0.8	9214 20 19	5	9	10	25	0.010
			G1/8	9214 20 10	7	12	10	28	0.013
20 Series (DN 2.7): single shut-off = 165 Nl/min 20 Series (DN 2.7): double shut-off = 130 Nl/min									





9226 Coupler, Bulkhead Mountable, with Barb Connection

	<p>Nickel-plated brass, NBR</p> 		ØD		F1	F2	G	L	L1	L2	kg
		2.7	3	9226 20 03	12	11	10	51	17	13	0.015
			4	9226 20 04	12	11	10	51	17	13	0.016
<p>20 Series (DN 2.7): single shut-off = 165 Nl/min 20 Series (DN 2.7): double shut-off = 130 Nl/min</p>											

9087 Probe, Straight-Through, Male BSPP and Metric Thread


	Nickel-plated brass			C		E	F	L	L1	kg
	2.7		M5x0.8	9087 20 19		5	7	18	10	0.002
			G1/8	9087 20 10		7	11	18	10	0.005
Probe without shut-off										

9287 Probe, Valved, Male BSPP and Metric Thread

	<p>Nickel-plated brass, NBR</p> 		C		E	F	L	L1	kg
		2.7	M5x0.8	9287 20 19	5	7	28	10	0.006
			G1/8	9287 20 10	7	11	30	10	0.009
Probe with shut-off									





German Profile

20 Series







9086

Probe, Straight-Through, Female BSPP and Metric Thread

	<p>Nickel-plated brass</p> 		C		E	F	L	L1	kg	
2.7					M5x0.8	5	7	17	10	0.003
					G1/8	7	12	19	10	0.006
Probe without shut-off										





9286

Probe, Valved, Female BSPP and Metric Thread

	<p>Nickel-plated brass, NBR</p> 	 C 	E	F	L	L1	kg		
			M5x0.8	9286 20 19	5	7	27	10	0.007
			G1/8	9286 20 10	7	12	30	10	0.010
Probe with shut-off									





9085

Probe, Straight-Through, with Barb Connection

	<p>Nickel-plated brass</p> 		ØD		L	L1	L2	kg
		2.7	3	9085 20 03	24	10	13	0.002
			4	9085 20 04	24	10	13	0.002
			5	9085 20 05	24	9	13	0.003
Probe without shut-off								






9285

Probe, Valved, with Barb Connection

	<p>Nickel-plated brass, NBR</p> 		ØD		L	L1	L2	kg
		2.7	3	9285 20 03	37	10	13	0.007
			4	9285 20 04	37	10	13	0.007
			5	9285 20 05	37	10	13	0.007
Probe with shut-off								


9095

Probe, Straight-Through, Bulkhead Mountable, with Barb Connection





	<p>Nickel-plated brass</p> 				F	L	L1	L2	L3	kg
		2.7	3	9095 20 03	11	44	10	17	13	0.012
			4	9095 20 04	11	44	10	17	13	0.012
Probe without shut-off										

German Profile





21 Series



9201 Coupler, Male BSPP Thread

	<p>Nickel-plated brass, NBR</p> 		C		E	F	G	L	kg
		5	G1/8	9201 21 10	7	14	16	36	0.027
			G1/4	9201 21 13	9	17	16	38	0.036
<p>21 Series (DN 5): single shut-off = 560 NI/min 21 Series (DN 5): double shut-off = 310 NI/min</p>									





9214 Coupler, Female BSPP Thread

	<p>Nickel-plated brass, NBR</p> 		C		E	F	G	L	kg
		5	G1/8	9214 21 10	9	14	16	36	0.030
			G1/4	9214 21 13	7	17	16	38	0.040
<p>21 Series (DN 5): single shut-off = 560 NI/min 21 Series (DN 5): double shut-off = 310 NI/min</p>									





9223 Coupler with Barb Connection

	<p>Nickel-plated brass, NBR</p>		ØD							
		4	9223 21 04							
		5	6	9223 21 06						
		8	9223 21 08							
<p>21 Series (DN 5): single shut-off = 560 NI/min 21 Series (DN 5): double shut-off = 310 NI/min</p>										





9226 Coupler, Bulkhead Mountable, with Barb Connection

	<p>Nickel-plated brass, NBR</p> 		ØD		F1	F2	G	L	L1	L2	kg
		4	9226 21 04	14	14	16	60	14	17	0.034	
		5	6	9226 21 06	17	17	16	60	14	17	0.048
		8	9226 21 08	17	17	16	60	14	17	0.047	
<p>21 Series (DN 5): single shut-off = 560 NI/min 21 Series (DN 5): double shut-off = 310 NI/min</p>											

9087 Probe, Straight-Through, Male BSPP Thread


	<p>Nickel-plated brass</p> 		C		E	F	L	L1	kg
		5	G1/8	9087 21 10	7	14	25	14	0.012
			G1/4	9087 21 13	9	17	28	14	0.019
Probe without shut-off									

9287 Probe, Valved, Male BSPP Thread





	<p>Nickel-plated brass, NBR</p> 		C		E	F	L	L1	kg
		5	G1/8	9287 21 10	7	14	40	14	0.023
			G1/4	9287 21 13	9	17	42	14	0.031
Probe with shut-off									

German Profile





21 Series







9086 Probe, Straight-Through, Female BSPP Thread

	<p>Nickel-plated brass</p> 		C		E	F	L	L1	kg		
5					G1/8	9086 21 10	8	14	25	14	0.014
					G1/4	9086 21 13	9	17	26	14	0.018
Probe without shut-off											





9286 Probe, Valved, Female BSPP Thread

	<p>Nickel-plated brass, NBR</p> 		C		E	F	L	L1	kg
		5	G1/8	9286 21 10	8	14	40	14	0.025
			G1/4	9286 21 13	9	17	42	14	0.035
Probe with shut-off									





9085 Probe, Straight-Through, with Barb Connection

	Nickel-plated brass			ØD		L	L1	L2	kg
			5	4	9085 21 04	32	14	17	0.006
				6	9085 21 06	32	14	17	0.008
				8	9085 21 08	32	14	17	0.009
Probe without shut-off									

9285 Probe, Valved, with Barb Connection

	<p>Nickel-plated brass, NBR</p> 		ØD		F	L	L1	L2	kg
		5	4	9285 21 04	14	50	14	17	0.022
			6	9285 21 06	14	50	14	17	0.023
			8	9285 21 08	14	50	14	17	0.024
Probe with shut-off									

9095 Probe, Straight-Through, Bulkhead Mountable with Barb Connection

	<p>Nickel-plated brass</p> 		ØD		F1	F2	L	L1	L2	L3	kg
		5	4	9095 21 04	14	14	50	14	14	17	0.019
			6	9095 21 06	14	17	50	14	14	17	0.027
			8	9095 21 08	14	17	50	14	14	17	0.028
Probe without shut-off											

Mini Series

Single Shut-Off



Double Shut-Off



0171 Coupler, Male BSPT and Parallel Metric Thread

	Technical polymer, nickel-plated brass, NBR			Colour	F	L	kg
	DN	C					
2	M7x1	0171 02 55 01			10	21	0.007
	R1/8	0171 02 10 01			10	21	0.010
	R1/8	0171 02 10 02			10	21	0.010
	R1/8	0171 02 10 03			10	21	0.010
	R1/8	0171 02 10 04			10	21	0.010
	R1/8	0171 02 10 05			10	21	0.010

Single shut-off
Mini Series (DN 2): single shut-off = 165 NL/min

0171 Coupler, Straight-Through, Male BSPT Thread

	Technical polymer, nickel-plated brass, NBR			Colour	F	G	L	kg
	DN	C						
3	R1/8	0171 03 10 01			13	17	24.5	0.020
	R1/8	0171 03 10 02			13	17	24.5	0.020
	R1/8	0171 03 10 03			13	17	24.5	0.020
	R1/8	0171 03 10 04			13	17	24.5	0.020
	R1/8	0171 03 10 05			13	17	24.5	0.020

Straight-through

0183 Probe, Valved, Male BSPT Thread

	Nickel-plated brass, NBR			F	L	kg
	DN	C				
2	R1/8	0183 02 10		10	13	0.007

Probe with shut-off

0184 Probe, Straight-Through, Male BSPT Thread

	Nickel-plated brass			F	L	kg
	DN	C				
2	R1/8	0184 02 10		10	13	0.006

Probe without shut-off


0181 Probe without Shut-off, Male BSPT Thread

	Nickel-plated brass			L	L1	kg
	DN	ØD	ØD1			
2	3	3.3	0181 03 04	11.5	13.5	0.010


Probe without shut-off

Mini Series

Single Shut-Off







Double Shut-Off



0181 Probe, Straight-Through with Barb Connection for Polyamide (PA) Tubing

	Nickel-plated brass		$\overline{\text{DN}}$	ØD	ØD1		L	kg
			3	4	4.7	0181 04 06	19	0.005
			Probe without shut-off					

0180 Probe, Straight-Through with Barb Connection for Flexible Tubing


	<p>Nickel-plated brass</p> 		$\varnothing D$	$\varnothing D1$		L	kg
		3	4	6	0180 04 00	19	0.007
			5	6.5	0180 05 00	19	0.007
		Probe without shut-off					

3150 Probe, Straight-Through with LF 3000® Push-In Connection

	Nickel-plated brass, NBR		$\overline{\text{DN}}$	ØD		G	L	$L1$	kg
			3	4	3150 00 61	8.5	39	18	0.008
			Probe without shut-off						

Standard Series





Single Shut-Off



0172 Coupler, Female BSPP Thread

	Nickel-plated brass, NBR			C		E	F	G	L	kg
			5	G1/4	0172 05 13	11	19	21	47	0.085
			Standard series: single shut-off = 480 Nl/min							

0187 Probe, Straight-Through, Male BSPP Thread

	Zinc-plated steel			C		E	F	L	kg
			5	G1/8	0187 05 10	7	14	4	0.018
				G1/4	0187 05 13	9.5	17	5	0.027
Probe without shut-off									

0186 Probe, Straight-Through, Female BSPP Thread

	Zinc-plated steel			C		E	F	L	kg
			5	G1/4	0186 05 13	12	17	17	0.028
			Probe without shut-off						

0185 Probe, Straight-Through, with Barb Connection for Flexible Tubing

	Zinc-plated steel			ØD	ØD1		L	kg
				4	6	0185 04 00	22.5	0.014
			5	7	9	0185 07 00	22.5	0.017
				10	12.2	0185 10 00	22.5	0.014
			Probe without shut-off					

0189 Double Probe

	Zinc-plated steel				F	L	kg
			5	0189 05 00	12	4	0.026
			Probe without shut-off				

Midi Series

Without Shut-Off



Single Shut-Off




0172

Coupler, Female BSPP Thread



Nickel-plated brass, NBR



DN	C		E	F	G	L	kg
12	G3/8	0172 12 17	16	27	29	56	0.155
	G1/2	0172 12 21	16	27	29	56	0.142


Midi series: single shut-off = 2200 NI/min

2272

Coupler, Straight-Through, Female BSPP Thread



Nickel-plated brass, NBR




DN	C		E	F	G	L	kg
12	G1/2	2272 12 21	10	24	29	33	0.072
	G3/4	2272 12 27	10	30	29	34.5	0.074
	G1	2272 12 34	10	36	29	34.5	0.087

2511

Coupler with Barb Connection for Hose



Nickel-plated brass, NBR



DN	ØD	ØD1		G	L	L1	kg
12	12	13.5	2511 12 12	29	75	32	0.146
	15	16.5	2511 12 15	29	75	32	0.147
	19	20.5	2511 12 19	29	81	38	0.159


Midi series: single shut-off = 2200 NI/min

2297

Coupler, Straight-Through, with Barb Connection for Hose



Nickel-plated brass, NBR




DN	ØD	ØD1		G	L	L1	kg
12	12	13.5	2297 12 12	29	51	27	0.073
	15	16.5	2297 12 15	29	51	27	0.076
	19	20.5	2297 12 19	29	57	33	0.090

2294

Probe, Straight-Through, Male BSPP Thread



Nickel-plated brass



DN	C		E	F	L	kg
12	G3/8	2294 12 17	6	22	31.5	0.031
	G1/2	2294 12 21	9.5	22	37	0.044
	G3/4	2294 12 27	13.5	27	41	0.068
	G1	2294 12 34	10.5	34	36	0.072

Probe without shut-off

Midi Series





Without Shut-Off







Single Shut-Off







0196 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated brass			C						E	F	L	kg		
						G1/4	0196 12 13	12	17					16	0.027
						G3/8	0196 12 17	12	21					15	0.034
						G1/2	0196 12 21	14	26					17	0.050
Probe without shut-off															





2296 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated brass			C							
						G1/2	2296 12 21	11	24	31.5	0.031
						G3/4	2296 12 27	11	30	38	0.058
						G1	2296 12 34	11	36	36.5	0.058
Probe without shut-off											

0195 Probe, Straight-Through, with Barb Connection for Flexible Tubing

	Nickel-plated brass			ØD	ØD1			F	L	kg
12	7	9	0195 07 00	17	29.5	0.026				
	10	12.2	0195 10 00	17	29.5	0.028				
	13	15.2	0195 13 00	17	29.5	0.030				
	16	18.5	0195 16 00	21	36.5	0.048				
Probe without shut-off										

2295 Probe, Straight-Through, with Barb Connection for Flexible Hose

	Nickel-plated brass			ØD	ØD1			G	L	L1	kg
12	12	13.5	2295 12 12	17	48	27	0.026				
	15	16.5	2295 12 15	18	48	27	0.034				
	19	20.5	2295 12 19	24	57	33	0.053				
Probe without shut-off											

2293 Y Coupler, Straight-Through

	Nickel-plated brass, NBR		DN			G	H	kg
12					2293 12 00	29	27	0.139
Probe without shut-off Midi Series: straight-through = 2200 NI/min								

Midi Series





Without Shut-Off



Single Shut-Off



2270 Coupler with Tap, Male BSPP Thread

	<p>Nickel-plated brass, NBR</p> 		C		F	G	H	M	kg
		12	G1/2	2270 21 00	28	29	40.5	35	0.272
		Flow = 2200 NI/min							

2203 Plug

	Nickel-plated brass		$\overline{\text{DN}}$		G	L	kg
			12		20	34	0.042
			2203 12 00				

2292 Universal Coupler Adaptor

	Nickel-plated brass, NBR		$\overline{\text{DN}}$		G	L	kg
			12		29	40.5	0.083
			2292 12 00				

Without shut-off
This adaptor provides interchangeability with numerous components (especially watering accessories).

2398 Universal Probe Adaptor

	Nickel-plated brass, NBR		$\overline{\text{DN}}$		G	L	L1	L2	kg
			12		20	43	19	18.5	0.035
			2398 12 01						

This adaptor provides interchangeability with numerous components (especially watering accessories).

2299 Water Pistol

	Zamak, Nickel-plated brass, NBR		$\overline{\text{DN}}$		H	L	kg
			12		140	126	0.471
			2299 12 01				

This pistol allows independent control of:
- the flow rate (trigger)
- type of jet (adjustable to a fine mist) by the adjustable Probe

2299 Adjustable Nozzle

	Nickel-plated brass, NBR		$\overline{\text{DN}}$		L	kg
			12		77.4	0.137
			2299 12 20			

This nozzle allows adjustment of the spray.

Maxi Series

Without Shut-Off



2272 Coupler, Straight-Through, Female BSP Thread

	Nickel-plated brass, NBR			C		E	F	G	K	L	kg
			19	G1	2272 18 34	9	36	42	11	45	0.182
Maxi series: straight-through = 8500 NI/min											

2297 Coupler, Straight-Through with Barb Connection for Hose

	Nickel-plated brass, NBR			ØD	ØD1		G	L	L1	kg
			19	19	20.7	2297 18 20	39.5	69	37	0.163
Maxi series: straight-through = 8500 NI/min										

2294 Coupler, Straight-Through, Male BSP Thread


	Nickel-plated brass			C		E	F	L	kg
			19	G3/4	2294 18 27	10.5	27	42.5	0.071
				G1	2294 18 34	13	34	46	0.102
Probe without shut-off									

2295 Coupler, Straight-Through with Barb Connection for Flexible Hose

	Nickel-plated brass			ØD	ØD1		L	L1	kg
			19	19	21	2295 18 20	69	41	0.068
Probe without shut-off									

Stainless Steel European Profile

X25 and X27 Series



9201

Coupler, Male BSPP Thread

Stainless steel 316L, FKM		DN	C		E	F	G	L	kg
		7.4	G1/4	9201X25 13	10.5	19	23	59	0.095
			G3/8	9201X25 17	9	19	23	57.5	0.094
			G1/2	9201X25 21	12	24	23	60.5	0.131
		10	G3/8	9201X27 17	9	24	27	57.5	0.131
			G1/2	9201X27 21	12	24	27	59.5	0.134
			G3/4	9201X27 27	16	32	27	60.5	0.171

X25 Series (DN 7.4): single shut-off = 1800 NI/min / X25 Series (DN 7.4): double shut-off = 710 NI/min
X27 Series (DN 10): single shut-off = 2400 NI/min / X27 Series (DN 10): double shut-off = 900 NI/min

9214

Coupler, Female BSPP Thread

Stainless steel 316L, FKM		DN	C		E	F	G	L	kg
		7.4	G1/4	9214X25 13	10	19	23	56	0.096
			G3/8	9214X25 17	9	19	23	55	0.089
			G1/2	9214X25 21	12	24	23	58	0.119
		10	G3/8	9214X27 17	11	24	27	56	0.140
			G1/2	9214X27 21	12	24	27	56	0.127
			G3/4	9214X27 27	16	32	27	60	0.191

X25 Series (DN 7.4): single shut-off = 1800 NI/min / X25 Series (DN 7.4): double shut-off = 710 NI/min
X27 Series (DN 10): single shut-off = 2400 NI/min / X27 Series (DN 10): double shut-off = 900 NI/min

9287

Probe, Valved, Male BSPP Thread

Stainless steel 316L, FKM		DN	C		E	F	L	L1	kg
		7.4	G1/4	9287X25 13	10	19	43	20	0.052
			G3/8	9287X25 17	9	19	43	20	0.053
			G1/2	9287X25 21	12	24	46	20	0.089
		10	G3/8	9287X27 17	9	24	58	22	0.080
			G1/2	9287X27 21	12	24	58	22	0.084
			G3/4	9287X27 27	16	32	62	22	0.122

Probe with shut-off

9087

Probe, Straight-Through, Male BSPP Thread

Stainless steel 316L		DN	C		E	F	L	L1	kg
		7.4	G1/4	9087X25 13	9	17	34	20	0.018
			G3/8	9087X25 17	9	19	34	20	0.014
			G1/2	9087X25 21	12	24	36	20	0.047
		10	G3/8	9087X27 17	9	19	37	22	0.013
			G1/2	9087X27 21	12	24	40	22	0.052
			G3/4	9087X27 27	16	32	45	22	0.086

Probe without shut-off

9286

Probe, Valved, Female BSPP Thread

Stainless steel 316L, FKM		DN	C		E	F	L	L1	kg
		7.4	G1/4	9286X25 13	10	19	54	20	0.056
			G3/8	9286X25 17	9	19	53	20	0.049
			G1/2	9286X25 21	12	24	56	20	0.079
		10	G3/8	9286X27 17	9	24	55	22	0.090
			G1/2	9286X27 21	12	24	55	22	0.080
			G3/4	9286X27 27	16	24	58	22	0.140

Probe with shut-off

9086


Probe, Straight-Through, Female BSPP Thread

Stainless steel 316L		DN	C		E	F	L	L1	kg
		7.4	G1/4	9086X25 13	12	10	33	20	0.023
			G3/8	9086X25 17	12	10	33	20	0.022
			G1/2	9086X25 21	14	12	35	20	0.035
		10	G3/8	9086X27 17	9	19	33	22	0.026
			G1/2	9086X27 21	12	24	37	22	0.037
			G3/4	9086X27 27	16	32	42	22	0.091

Probe without shut-off

Stainless Steel German Profile

X20 Series




9201

Coupler, Male BSPP and Metric Thread



Stainless steel 316L, FKM



C



E F G L kg

2.7	M5x0.8	9201X20 19	5	9	10	26	0.008
	G1/8	9201X20 10	7	11	10	28	0.011


X20 Series (DN 2.7) : single shut-off = 165 NI/min
X20 Series (DN 2.7) : double shut-off = 130 NI/min

9214

Coupler, Female BSPP and Metric Thread



Stainless steel 316L, FKM



C



E F G L kg

2.7	M5x0.8	9214X20 19	5	9	10	26	0.009
	G1/8	9214X20 10	7	12	10	28	0.012


X20 Series (DN 2.7) : single shut-off = 165 NI/min
X20 Series (DN 2.7) : double shut-off = 130 NI/min

9287

Probe, Valved, Male BSPP and Metric Thread



Stainless steel 316L, FKM



C



E F L L1 kg

2.7	M5x0.8	9287X20 19	5	9	28	10	0.005
	G1/8	9287X20 10	7	11	30	10	0.009


Probe with shut-off

9087

Probe, Straight-Through, Male BSPP and Metric Thread



Stainless steel 316L



C



E F L L1 kg

2.7	M5x0.8	9087X20 19	5	7	18	10	0.010
	G1/8	9087X20 10	7	11	20	10	0.015


Probe without shut-off

9286

Probe, Valved, Female BSPP and Metric Thread



Stainless steel 316L, FKM



C



E F L L1 kg

2.7	M5x0.8	9286X20 19	5	9	26	10	0.010
	G1/8	9286X20 10	7	12	30	10	0.014


Probe with shut-off

9086

Probe, Straight-Through, Female BSPP and Metric Thread



Stainless steel 316L



C




E F L L1 kg

2.7	M5x0.8	9086X20 19	5	7	17	10	0.002
	G1/8	9086X20 10	7	12	19	10	0.005

Probe without shut-off

Stainless Steel German Profile

X21 Series




9201

Coupler, Male BSPP Thread



Stainless steel 316L, FKM



(DN)	C		E	F	G	L	kg
5	G1/8	9201X21 10	7	14	16	36	0.026
	G1/4	9201X21 13	9	17	16	38	0.034


X21 Series (DN 5): single shut-off = 560 NI/min
X21 Series (DN 5): double shut-off = 310 NI/min

9214

Coupler, Female BSPP Thread



Stainless steel 316L, FKM



(DN)	C		E	F	G	L	kg
5	G1/8	9214X21 10	9	14	16	36	0.027
	G1/4	9214X21 13	9	17	16	38	0.037


X21 Series (DN 5): single shut-off = 560 NI/min
X21 Series (DN 5): double shut-off = 310 NI/min

9287

Probe, Valved, Male BSPP Thread



Stainless steel 316L, FKM



(DN)	C		E	F	L	L1	kg
5	G1/8	9287X21 10	7	14	40	14	0.021
	G1/4	9287X21 13	9	17	42	14	0.030


Probe with shut-off

9087

Probe, Straight-Through, Male BSPP Thread



Stainless steel 316L



(DN)	C		E	F	L	L1	kg
5	G1/8	9087X21 10	7	14	25	14	0.011
	G1/4	9087X21 13	9	17	28	14	0.018


Probe without shut-off

9286

Probe, Valved, Female BSPP Thread



Stainless steel 316L, FKM



(DN)	C		E	F	L	L1	kg
5	G1/8	9286X21 10	7	14	40	14	0.024
	G1/4	9286X21 13	9	17	42	14	0.033


Probe with shut-off

9086

Probe, Straight-Through, Female BSPP Thread



Stainless steel 316L



(DN)	C		E	F	L	L1	kg
5	G1/8	9086X21 10	8	14	25	14	0.013
	G1/4	9086X21 13	9	17	25	14	0.017

Probe without shut-off

Quick-Acting Mould Couplers

These Parker Legris quick-acting couplers provide the **best compromise** between **technical performance and ease of use** while providing long-term, reliable temperature regulation.

Product Advantages

Ergonomic

Can be connected using one hand by simply pushing the coupler body into the socket
Knurled sleeve provides excellent grip
Compact

Performance

Direct and automatic sealing
Socket threads are pre-coated
Maximum flow rate




Plastic Injection Moulding
Cooling
Die-Casting
Rubber Overmoulding
Printing
Coating & Laminating

Applications

Technical Characteristics

Compatible Fluids	Cold water, coolants, hot water, oil
Working Pressure	0 to 10 bar
Working Temperature	-15°C to +90°C (water applications) <i>For temperatures above 90°C, please contact us.</i>


Component Materials



Installation

Cavity Dimensions

	G	G1	H	H1	H2
9075T08 10	21	22	33	24	22
9075T08 13	21	22	34	24	22
9075T08 17	21	22	25	13	11
9075T12 17	32	33	42	30	28
9075T12 21	32	33	45	30	28



Quick-Acting Mould Couplers

Without Shut-Off




9020

Coupler with Hosetail



Nickel-plated brass, HNBR




DN	ØD		G	L	L1	L2	kg
8	8	9020T08 08	21	60	44	28	0.050
	10	9020T08 10	21	60	44	28	0.054
	12	9020T08 12	21	65	48	32	0.063
12	13	9020T12 13	32	75	53	32	0.069
	16	9020T12 16	32	75.5	54	32.5	0.172

9040

Coupler, Female BSPP Thread



Nickel-plated brass, HNBR




DN	C		E	G	L	L1	kg
8	G1/4	9040T08 13	10.5	21	43	27	0.056
12	G1/2	9040T12 21	15	32	66	44	0.208

9075

Female Socket, Male BSPT Thread



Nickel-plated brass



DN	C		E	F	G	G1	L	L1	kg
8	R1/8	9075T08 10	10	6	21	17.5	32	21	0.028
	R1/4	9075T08 13	13	8	21	17.5	33	22	0.031
	R3/8	9075T08 17	13	8	21	-	24	-	0.023
12	R3/8	9075T12 17	13	10	32	25	41	27	0.073
	R1/2	9075T12 21	16	14	32	25	44	30	0.075


Other coupler shapes are available on request:

- 90° angled body, with hosetail
- 45° angled body, female BSPP
- 90° angled body, female BSPP




Socket Installation

Two types of installation can be used for moulds. Sockets are fitted into the cavities using an Allen key.




Recessed Socket

This type of installation is recommended for new moulds



Exposed Socket

This type of installation is suited to moulds with no existing cavity.



Metal Quick-Acting Coupler Accessories

Parker Legris has developed a range of accessories for quick-acting couplers which save time, **match the product** to the application and **increase the life** of the equipment.

Product Advantages

Performance

Interchangeability with ISO B probe profile
Avoids tube twisting
Facilitates use by following movements
Robust

Adaptable

Two models depending on the application:

Oscillating fittings:

- angled at 45° and fitted with a ball bearing
- effortless rotation through 360°

Flexible fittings:

- fitted with a ball joint mounted on a lubricated plastic seat
- single connection providing an angle of rotation of 70°
- multiple tees (three connections) providing an angle of rotation of 360°




Pneumatics
Water
Workshops
Industrial Machinery

Applications

Technical Characteristics

Compatible Fluids	Industrial fluids
Working Pressure	Oscillating fittings: 0 to 15 bar Flexible fittings: 0 to 10 bar Swivelling multiple tees: 0 to 20 bar
Working Temperature	-5°C to +60°C

Component Materials








Other accessories are available on request:

- ISO B rotary fitting, male BSPT
- ISO B jointed fitting, male BSPP
- multiple tee with 2 outlets, female male BSPP








Metal Quick-Acting Coupler Accessories

9071U Oscillating ISO B Probe, Male BSPP Thread






	Treated steel, NBR 		C		E	F	H	L	kg
									
		6 G1/4 9071U06 13 8 G1/4 9071U08 13							
					5.5	19	30	52	0.066
					5.5	19	30	52	0.077

0691 Flexible Fitting, Female/Male BSPP Thread





	Treated steel, NBR 		C		E	F	G	L	kg
									
		5.5 G1/4 0691 13 13							
					5.5	24	25.5	56	0.090

NBR sleeve

0681 Multiple Tee with 3 Female Outlets, Male/Female BSPP Thread





	Chrome-plated brass, NBR 		C1		E	H	H1	L	L1	kg
										
		G1/2 G1/4 0681 13 21								
					7.5	36	24	138.5	30	0.430

0164 Adaptor, Male NPT/Female BSPP Thread

	Brass 	C1	C2		E	F	L	kg
								
		NPT1/8 G1/8 0164 11 10 NPT1/4 G1/4 0164 14 13 NPT3/8 G3/8 0164 18 17 NPT1/2 G1/2 0164 22 21 NPT3/4 G3/4 0164 28 27						
					7.5	14	20	0.015
					11	17	27.5	0.028
					11.5	22	28.5	0.044
					15	27	36.5	0.082
					16.5	32	38.5	0.110

Adaptor for female socket of quick-acting mould couplers

0167 Adaptor, Male BSPT/Female NPT Thread

	Brass 	C1	C2		F	L	kg
							
		R1/8 NPT1/8 0167 10 11 R1/4 NPT1/4 0167 13 14 R3/8 NPT3/8 0167 17 18 R1/2 NPT1/2 0167 21 22 R3/4 NPT3/4 0167 27 28					
					14	21	0.016
					17	28.5	0.029
					22	29.5	0.047
					27	37.5	0.088
					32	39.5	0.120

Adaptor for female socket of quick-acting mould couplers

Adaptors and Manifolds





A Complete Range of Adaptors

Brass Adaptors

0143

BSPP
Page 9-7



0144

BSPT/BSPP
Page 9-7



0152

BSPT
Page 9-7



0145

BSPP
Page 9-7



0158

BSPT/BSPP
Page 9-7



0117

BSPP
Page 9-8



0155

BSPP
Page 9-8



0164

NPT/BSPP
Page 9-8



0167

BSPT/NPT
Page 9-8



0168

BSPP
Page 9-9



0163

BSPT/BSPP
Page 9-9



0169

BSPP
Page 9-9



0121

NPT/BSPT
Page 9-9



0121

BSPT
Page 9-9



0929

BSPT
Page 9-10



0123

BSPT
Page 9-10



0136

BSPT
Page 9-11



Nickel-Plated Brass Adaptors

0912

BSPP/Metric
Page 9-11



0921

Metric
Page 9-11



0913

BSPT/BSPP
Page 9-11



0922

Metric
Page 9-11



0914

BSPT
Page 9-11



0910

BSPP
Page 9-12



0911

BSPT/BSPP
Page 9-12



0915

BSPP/Metric
Page 9-12



0923

Metric
Page 9-12



0916

BSPT/BSPP
Page 9-12



0924

Metric
Page 9-13



0917

BSPT/BSPP
Page 9-14



0927

BSPT
Page 9-13



0928

BSPT/BSPP
Page 9-13



0932

BSPT/BSPP
Page 9-13



0908

BSPP
Page 9-14



0909

BSPT/BSPP
Page 9-14



0903

BSPP
Page 9-14



0904

BSPT/BSPP
Page 9-14



0905

BSPP/Metric
Page 9-14



0906

BSPP/Metric
Page 9-15



0907

BSPP
Page 9-15



0920

BSPP/Metric
Page 9-15



0900

BSPT
Page 9-17



0901

BSPP/Metric
Page 9-16



0192

BSPT/BSPP
Page 9-16



0902

BSPP/Metric
Page 9-16



0191

BSPP
Page 9-16



0931

BSPP
Page 9-17



Stainless Steel Adaptors

1844

BSPT/BSPP
Page 9-18



1843

BSPP
Page 9-18



1845

BSPP
Page 9-18



1817

BSPP
Page 9-18



1871

NPT
Page 9-18



1855

BSPP
Page 9-19



1870

NPT
Page 9-19



1862

BSPP
Page 9-19



1864

NPT/BSPP
Page 9-19



1867

BSPT/NPT
Page 9-19



1863

BSPT/BSPP
Page 9-20



1872

NPT
Page 9-20



1861

BSPT/BSPP
Page 9-20



1873

NPT
Page 9-20



1821

BSPT
Page 9-20



1821

NPT
Page 9-21



1823

BSPT
Page 9-21



1823

NPT
Page 9-21



A Complete Range of Manifolds, Plugs and Accessories

Brass and Aluminium Manifolds

0135

BSPP brass
Page 9-22



3310

Push-In
Page 9-23



3311

BSPP/Metric
Page 9-23



3312

BSPP/Metric
Page 9-23



3313

BSPP
Page 9-23



3301

Modular
Page 9-24



3302

Single, double
and triple
Page 9-24



3303

Elbow
Page 9-25



3303

Plug
Page 9-25



Brass Plugs

0205

BSPT
Page 9-26



0205

NPT
Page 9-26



0209

BSPT
Page 9-26



0220

BSPP/Metric
Page 9-26



0200

BSPP/Metric
Page 9-26



0201

BSPP/Metric
Page 9-27



0202

Metric
Page 9-27



Nickel-Plated Brass Hollow Hex Plug

0919

BSPP/Metric
Page 9-28



Steel Plugs

0206

BSPT
Page 9-29



0206

NPT
Page 9-29



0210

BSPP/Metric
Page 9-29



0216

BSPT
Page 9-29



0216

NPT
Page 9-29



Stainless Steel Plugs

0285

BSPT
Page 9-30



0285

NPT
Page 9-30



Sealing Accessories

0138

Page 9-31



0137

Page 9-31



0605

Page 9-32



0602

Page 9-32



0139

Page 9-32



Tube Supports

0127

Brass
Page 9-33



1827

Stainless Steel
Page 9-33



Adaptors, Plugs and Manifolds

Parker Legris offers a **wide range of adaptors and manifolds** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

Product Advantages

Large Range & Flexibility

A complete offer, from the simple adaptor to a modular manifold solution

Large selection of materials for excellent chemical compatibility: brass, steel, stainless steel, aluminium

Surface treatment for increased corrosion resistance: nickel-plated brass or anodised aluminium

Stainless steel for corrosive environments

BSPP, BSPT, NPT and metric threads

Performance

Robust design

Suitable for low to high pressure, depending on configuration and material

Forged shapes for mechanical strength



Packaging
Robotics
Textile
Pneumatics
Automotive Process
Food Process




Applications

Technical Characteristics




Products	Adaptors and Plugs				Manifolds
Component Materials	Brass	Nickel-plated brass	Stainless steel 316L	Steel	Anodised aluminium
Working Pressure	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	60 bar	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	1/8" to 1/2": 200 bar 3/4" and 1": 150 bar 1 1/4" to 2": 100 bar, without sealing washer	20 bar
Working Temperature	-40°C to +150°C without sealing washer -20°C to +80°C with sealing washer	-10°C to +80°C	-20°C to +180°C	-10°C to +80°C	-10°C to +80°C

Brass Adaptors




0143 Equal Threaded Elbow, Female BSPP Thread

	<p>Brass</p> 	C		E	G	J	L	kg
		G1/8	0143 10 10	7.5	16.5	12	22.5	0.044
		G1/4	0143 13 13	11	18.5	15	26.5	0.055
		G3/8	0143 17 17	11.5	23.5	19	31.5	0.100
		G1/2	0143 21 21	15	28	23	34.5	0.150
		G3/4	0143 27 27	16.5	34	27	43.5	0.242




0144 Equal Stud Elbow, Male BSPT/Female BSPP Thread

	<p>Brass</p> 	C1	C2		E	G	H	J	L	kg
		R1/8	G1/8	0144 10 10	7.5	16.5	23	12	22.5	0.036
		R1/4	G1/4	0144 13 13	11	18.5	26	15	26.5	0.054
		R3/8	G3/8	0144 17 17	11.5	23.5	30	19	31.5	0.088
		R1/2	G1/2	0144 21 21	15	28	35	23	34.5	0.140
		R3/4	G3/4	0144 27 27	16.5	34	40	27	43.5	0.228




0152 Equal Elbow, Male BSPT Thread

	<p>Brass</p> 	C		H	J	L	kg
		R1/8	0152 10 10	19.5	10	19.5	0.017
		R1/4	0152 13 13	25	15	25	0.045
		R3/8	0152 17 17	26.5	15	26.5	0.055
		R1/2	0152 21 21	31.5	19	31.5	0.088
		R3/4	0152 27 27	35.5	23	35.5	0.153

0145 Equal Tee, Female BSPP Thread




	Brass 	C			E	G	H	J	L/2	kg
		G1/8	0145 10 10		7.5	16.5	22.5	12	22.5	0.056
		G1/4	0145 13 13		11	18.5	26.5	15	26.5	0.083
		G3/8	0145 17 17		11.5	23.5	31	19	31	0.131
		G1/2	0145 21 21		15	28	38	23	38	0.242
		G3/4	0145 27 27		16.5	34	47.5	27	47.5	0.378

0158 Stud Branch Tee, Male BSPT/Female BSPP Thread




	Brass 	C1	C2		E	G	H	J	L/2	kg
		R1/8	G1/8	0158 10 10	7.5	16.5	21.5	12	21.5	0.046
		R1/4	G1/4	0158 13 13	11	18.5	26	15	26	0.074
		R3/8	G3/8	0158 17 17	11.5	23.5	30	19	30	0.120
		R1/2	G1/2	0158 21 21	15	28	36	23	36	0.205
		R3/4	G3/4	0158 27 27	16.5	34	44	27	44	0.310

Brass Adaptors




0117 Equal Bulkhead Coupling, Female BSPP and Metric Thread

	Brass		C		F	F1	K _{max}	L	L1	ØT	kg
			M5x0.8	0117 00 19	14	14	7	10.5	3.5	10.5	0.012
			G1/8	0117 00 10	19	22	9	14	4	16.5	0.033
			G1/4	0117 00 13	24	27	15	21	4	20.5	0.057
			G3/8	0117 00 17	30	32	14	21	5	26.5	0.096
			G1/2	0117 00 21	32	36	20	27	6	28.5	0.116
			G3/4	0117 00 27	41	41	22.5	30	6	34.5	0.161
			G1	0117 00 34	46	50	24.5	34	8	42.5	0.266
			G1 1/4	0117 00 42	55	55	29.5	39	8	49.5	0.299
			G1 1/2	0117 00 49	60	60	29.5	39	8	54.5	0.303




0155 Equal Connector, Female BSPP Thread

	Brass		C		F	L	kg
			G1/8	0155 10 10	14	17	0.014
			G1/4	0155 13 13	17	24	0.026
			G3/8	0155 17 17	22	25	0.046
			G1/2	0155 21 21	27	32	0.084
			G3/4	0155 27 27	32	35	0.109




0164 Adaptor, Male NPT/Female BSPP Thread

	Brass		C1	C2		E	F	L	kg
			NPT1/8	G1/8	0164 11 10	7.5	14	20	0.015
			NPT1/4	G1/4	0164 14 13	11	17	27.5	0.028
			NPT3/8	G3/8	0164 18 17	11.5	22	28.5	0.044
			NPT1/2	G1/2	0164 22 21	15	27	36.5	0.082
			NPT3/4	G3/4	0164 28 27	16.5	32	38.5	0.110

0167 Adaptor, Male BSPT/Female NPT Thread

	Brass		C1	C2		F	L	kg
			R1/8	NPT1/8	0167 10 11	14	21	0.016
			R1/4	NPT1/4	0167 13 14	17	28.5	0.029
			R3/8	NPT3/8	0167 17 18	22	29.5	0.047
			R1/2	NPT1/2	0167 21 22	27	37.5	0.088
			R3/4	NPT3/4	0167 27 28	32	39.5	0.120



0168 Reducer, Male BSPP/Female BSPP and Metric Thread

	Brass, technical polymer		C1	C2		E	F	H	kg
			G1/8	M5x0.8	0168 10 19	7	14	6	0.009
			G1/4	M5x0.8	0168 13 19	7	17	7	0.017
			G1/8	G1/8	0168 13 10	7	17	7	0.011
			G3/8	G1/8	0168 17 10	9	19	6	0.019
			G1/4	G1/4	0168 17 13	9	19	6	0.013
			G1/8	G1/8	0168 21 10	11	24	10	0.050
			G1/2	G1/4	0168 21 13	11	24	10	0.041
			G3/8	G3/8	0168 21 17	11	24	10	0.029
			G1/4	G1/4	0168 27 13	11	32	12	0.098
			G3/4	G3/8	0168 27 17	11	32	12	0.083
			G1/2	G1/2	0168 27 21	11	32	12	0.063



With fitted captive seal

Brass Adaptors

0163 Unequal Reducer, Male BSPT/Female BSPP Thread



	Brass	C1	C2		F	L	kg
		R1/4	G1/8	0163 13 10	14	16	0.009
		R3/8	G1/8	0163 17 10	17	16.5	0.020
			G1/4	0163 17 13	17	16.5	0.012
			G1/8	0163 21 10	22	21	0.048
		R1/2	G1/4	0163 21 13	22	21	0.038
			G3/8	0163 21 17	22	21	0.024
			G1/4	0163 27 13	27	24	0.084
		R3/4	G3/8	0163 27 17	27	24	0.069
			G1/2	0163 27 21	27	24	0.046

0169 Increaser, Male/Female BSPP Thread



	Brass, technical polymer	C1	C2		E1	E2	F	L	kg
		G1/8	G1/4	0169 10 13	5	11	17	16	0.019
			G3/8	0169 10 17	5	14	22	19.5	0.039
		G1/4	G3/8	0169 13 17	7	14	22	19.5	0.041
			G1/2	0169 13 21	7	14.5	27	20.5	0.062
		G3/8	G1/2	0169 17 21	8	14.5	27	20.5	0.062
			G3/4	0169 17 27	8	15.5	32	22	0.082
		G1/2	G3/4	0169 21 27	9.5	15.5	32	22.5	0.087

With fitted captive seal

0121 Straight Male Adaptor, Male BSPT Thread


	Brass	C1	C2		F	L	kg
		R1/8	R1/8	0121 10 10	11	19	0.009
		R1/4	R1/8	0121 13 10	14	23.5	0.017
			R1/4	0121 13 13	14	27	0.020
		R3/8	R1/8	0121 17 10	17	24	0.021
			R1/4	0121 17 13	17	27.5	0.025
			R3/8	0121 17 17	17	28	0.026
		R1/2	R1/8	0121 21 10	22	28.5	0.042
			R1/4	0121 21 13	22	32	0.045
			R3/8	0121 21 17	22	32.5	0.045
			R1/2	0121 21 21	22	36	0.052
		R3/4	R1/4	0121 27 13	27	35	0.078
			R3/8	0121 27 17	27	35.5	0.078
			R1/2	0121 27 21	27	39	0.085
			R3/4	0121 27 27	27	40	0.091
			R3/8	0121 34 17	36	38.5	0.127
		R1	R1/2	0121 34 21	36	42	0.134
			R3/4	0121 34 27	36	43	0.143
			R1	0121 34 34	36	46	0.154
			R1/2	0121 42 21	46	46.5	0.220
			R3/4	0121 42 27	46	47.5	0.224
		R1 1/4	R1	0121 42 34	46	50.5	0.239
			R1 1/4	0121 42 42	46	53	0.230

0121 Equal Adaptor, Male NPT/BSPT Thread


	Brass	C1	C2		F	L	kg
		NPT1/8	R1/8	0121 11 10	11	19	0.009
		NPT1/4	R1/4	0121 14 13	14	27	0.021
		NPT3/8	R3/8	0121 18 17	17	28	0.026
		NPT1/2	R1/2	0121 22 21	22	36	0.052
		NPT3/4	R3/4	0121 28 27	27	40	0.090

Brass Adaptors

0929 Equal 3-Piece Adaptor, Male BSPT Thread



Brass, NBR



C		F	F1	L	L1	L2	kg
R1/8	0929 01 10	15	5	27	9	8.5	0.017
R1/4	0929 01 13	19	6	33.5	11.5	9.5	0.035
R3/8	0929 01 17	22	8	36.5	13	10	0.054
R1/2	0929 01 21	27	12	45	15.5	12	0.088

This connection accessory makes assembly much easier thanks to its 3-piece design.

To join 2 threaded components, simply push together and tighten the sleeve nut, thus reducing installation time.


Maximum working pressure: 50 bar

Working temperature: -10° to +80°C

Supplied with seal


0123 Tailpiece Adaptor for Rubber Hose, Male BSPT Thread

Brass

ØD	ØD1	C		F	L	L1	ØT	kg
4	6	R1/8	0123 04 10	10	34	22.5	3.3	0.008
6	8	R1/8	0123 06 10	10	34	22.5	5	0.009
7	9	R1/8	0123 07 10	10	34	22.5	5	0.009
	9	R1/4	0123 07 13	14	38.5	22.5	6	0.018
10	9	R3/8	0123 07 17	17	39	22.5	6	0.023
	12.2	R1/8	0123 10 10	13	34	22.5	5	0.014
	12.2	R1/4	0123 10 13	14	38.5	22.5	7	0.020
12	12.2	R3/8	0123 10 17	17	39	22.5	9.5	0.023
	14	R3/8	0123 12 17	17	46	29.5	11	0.026
13	15	R1/4	0123 13 13	17	45.5	29.5	7	0.026
	15	R3/8	0123 13 17	17	46	29.5	11	0.027
	15	R1/2	0123 13 21	22	50.5	29.5	12	0.045
16	18.5	R3/8	0123 16 17	19	54.5	38	11	0.040
	18.5	R1/2	0123 16 21	22	59	38	14	0.054
	18.5	R3/4	0123 16 27	27	62	38	15	0.084
19	21.5	R3/8	0123 19 17	22	54.5	38	11	0.046
	21.5	R1/2	0123 19 21	22	59	38	14	0.056
	21.5	R3/4	0123 19 27	27	62	38	18	0.082
25	26.7	R3/4	0123 25 27	27	62	38	18	0.079
	27	R1	0123 25 34	36	65	38	24	0.124
32	34.5	R1	0123 32 34	36	70	43	24	0.141

0136 Tailpiece Adaptor for Flexible Tubing, Male BSPT Thread

Brass

ØD	ØD1	C		F	L	L1	ØT	kg
4	4.3	R1/8	0136 06 10	10	26.5	15	2	0.007
	4.3	R1/4	0136 06 13	14	31	15	2	0.015
	4.3	R3/8	0136 06 17	17	31.5	15	2	0.020
6	6.4	R1/8	0136 08 10	10	26.5	15	4	0.007
	6.4	R1/4	0136 08 13	14	31	15	4	0.015
	6.4	R3/8	0136 08 17	17	31.5	15	4	0.020
8	8.4	R1/4	0136 10 13	14	31	15	6	0.016
	8.4	R3/8	0136 10 17	17	31.5	15	6	0.020
	8.4	R1/2	0136 10 21	22	36	15	6	0.039
10	10.7	R1/4	0136 12 13	14	36	20	7	0.018
	10.7	R3/8	0136 12 17	17	36.5	20	8	0.023
	10.7	R1/2	0136 12 21	22	41	20	8	0.041
12	12.7	R1/4	0136 14 13	14	36	20	7	0.019
	12.7	R3/8	0136 14 17	17	36.5	20	10	0.023
	12.7	R1/2	0136 14 21	22	41	20	10	0.040
	12.7	R3/4	0136 14 27	27	44	20	10	0.071
13	13.7	R3/8	0136 16 17	17	36.5	20	11	0.023
	13.7	R1/2	0136 16 21	22	41	20	11	0.041
	13.7	R3/4	0136 16 27	27	44	20	11	0.070

Nickel-Plated Brass Adaptors

0912 Equal Stud Elbow, Female BSPP and Metric Thread

	Nickel-plated brass	C		E	G	J	L	kg
		M5x0.8	0912 00 19	4	8	9	11	0.006
		G1/8	0912 00 10	8	13	10	18.5	0.015
		G1/4	0912 00 13	11	17	12	22.5	0.028
		G3/8	0912 00 17	11.5	21	15	25.5	0.043
		G1/2	0912 00 21	14	26	19	30	0.073
		G3/4	0912 00 27	16.5	32	22	35.5	0.143
		G1	0912 00 34	18	38.5	28	40.5	0.166

0921 Equal Stud Elbow, Male/Female and Metric Thread

	Nickel-plated brass	C1	C2		E	G	H	J	L	kg
		M5x0.8	M5x0.8	0921 00 19	4	8	11	9	11	0.006

0913 Equal Stud Elbow, Male BSPT/ Female BSPP Thread

	Nickel-plated brass	C1	C2		E	G	H	J	L	kg
		R1/8	G1/8	0913 00 10	8	13	17	10	18.5	0.012
		R1/4	G1/4	0913 00 13	11	17	22.5	12	22.5	0.026
		R3/8	G3/8	0913 00 17	11.5	21	25.5	15	25.5	0.038
		R1/2	G1/2	0913 00 21	14	26	30	19	30	0.064
		R3/4	G3/4	0913 00 27	16.5	32	34.5	22	35.5	0.098
		R1	G1	0913 00 34	18	38.5	40.5	28	40.5	0.000

0922 Equal Stud Elbow, Male Metric Thread




	Nickel-plated brass	C		H	J	L	kg
		M5x0.8	0922 00 19	11	9	11	0.010

0914 Equal Stud Elbow, Male BSPT Thread




	Nickel-plated brass	C		H	J	L	kg
		R1/8	0914 00 10	17	10	17	0.012
		R1/4	0914 00 13	22.5	12	22.5	0.027
		R3/8	0914 00 17	25.5	15	25.5	0.035
		R1/2	0914 00 21	30	19	30	0.056
		R3/4	0914 00 27	34.5	22	34.5	0.104
		R1	0914 00 34	40.5	28	40.5	0.156

Nickel-Plated Brass Adaptors




0910 Equal Y, Female BSPP Thread

	Nickel-plated brass 	C		E	F	H	kg
		G1/8	0910 00 10	8	13	12	0.018
		G1/4	0910 00 13	11	17	14	0.033
		G3/8	0910 00 17	11.5	20	16	0.045
		G1/2	0910 00 21	14	25	19	0.083




0911 Equal Y, Male BSPT/Female BSPP Thread

	Nickel-plated brass 	C1	C2		E	F	H	kg
		R1/8	G1/8	0911 00 10	8	13	12	0.022
		R1/4	G1/4	0911 00 13	11	17	14	0.038
		R3/8	G3/8	0911 00 17	11.5	20	16	0.050
		R1/2	G1/2	0911 00 21	14	25	19	0.103




0915 Equal Tee, Female BSPP and Metric Thread

	Nickel-plated brass 	C		E	G	H	J	L/2	kg
		M5x0.8	0915 00 19	4	8	11	9	11	0.010
		G1/8	0915 00 10	8	13	18.5	10	18.5	0.021
		G1/4	0915 00 13	11	17	22.5	12	22.5	0.042
		G3/8	0915 00 17	11.5	21	25.5	15	25.5	0.062
		G1/2	0915 00 21	14	26	30	19	30	0.099
		G3/4	0915 00 27	16.5	32	35.5	22	35.5	0.143
		G1	0915 00 34	18	38.5	40	28	40	0.244

0923 Equal Stud Branch Tee, Female/Male Metric Thread




	Nickel-plated brass 	C1	C2		E	G	H	J	L/2	kg
		M5x0.8	M5x0.8	0923 00 19	4	8	11	9	11	0.009

0916 Equal Stud Branch Tee, Male BSPT/Female BSPP Thread









	Nickel-plated brass 	C1	C2		E	G	H	J	L/2	kg
		R1/8	G1/8	0916 00 10	8	13	17	10	18.5	0.019
		R1/4	G1/4	0916 00 13	11	17	23.5	13	22.5	0.038
		R3/8	G3/8	0916 00 17	11.5	21	25.5	15	25.5	0.076
		R1/2	G1/2	0916 00 21	14	26	30	19	30	0.091
		R3/4	G3/4	0916 00 27	16.5	32	34.5	22	35.5	0.140
		R1	G1	0916 00 34	18	38.5	40.5	28	40.5	0.237

Nickel-Plated Brass Adaptors









0924 Equal Stud Run Tee, Female/Male Metric Thread

	Nickel-plated brass	C1	C2		E	G	H	H1	J	L	kg
		M5x0.8	M5x0.8	 0924 00 19	4	8	11	11	9	11	0.009









0917 Equal Stud Run Tee, Male BSPT/Female BSPP Thread

	Nickel-plated brass	C1	C2		E	G	H	H1	J	L	kg
		R1/8	G1/8	 0917 00 10	8	13	17	18.5	10	18.5	0.025
		R1/4	G1/4	 0917 00 13	11	17	22.5	22.5	12	22.5	0.038
		R3/8	G3/8	 0917 00 17	11.5	21	25.5	25.5	15	25.5	0.058
		R1/2	G1/2	 0917 00 21	14	26	30	30	19	30	0.090
		R3/4	G3/4	 0917 00 27	16.5	32	34.5	35.5	22	35.5	0.177
		R1	G1	 0917 00 34	18	38.5	40.5	40.5	28	40.5	0.219









0927 Equal Tee, Male BSPT Thread

	Nickel-plated brass	C		H	J	L	kg
		R1/8	 0927 00 10	17	10	34	0.018
		R1/4	 0927 00 13	22.5	12	45	0.032
		R3/8	 0927 00 17	25.5	15	51	0.056
		R1/2	 0927 00 21	30	19	60	0.094
		R3/4	 0927 00 27	34.5	22	69	0.133
		R1	 0927 00 34	40.5	28	81	0.217

0928 Equal Stud Branch Tee, Male BSPT/Female BSPP Thread




	Nickel-plated brass	C1	C2		E	H	J	L	kg
		R1/8	G1/8	 0928 00 10	8	34	10	18.5	0.016
		R1/4	G1/4	 0928 00 13	11	45	12	22.5	0.044
		R3/8	G3/8	 0928 00 17	11.5	51	15	25.5	0.053
		R1/2	G1/2	 0928 00 21	14	60	19	30	0.111
		R3/4	G3/4	 0928 00 27	16.5	69	22	35.5	0.236
		R1	G1	 0928 00 34	18	81	28	40.5	0.225

0932 Equal Stud Run Tee, Male BSPT/Female BSPP Thread




	Nickel-plated brass	C1	C2		E	H	H1	J	L	kg
		R1/8	G1/8	 0932 00 10	8	17	18.5	10	17	0.016
		R1/4	G1/4	 0932 00 13	11	22.5	22.5	12	22.5	0.035
		R3/8	G3/8	 0932 00 17	11.5	25.5	25.5	15	25.5	0.055
		R1/2	G1/2	 0932 00 21	14	30	30	19	30	0.091
		R3/4	G3/4	 0932 00 27	16.5	34.5	35.5	22	34.5	0.080
		R1	G1	 0932 00 34	18	40.5	40.5	28	40.5	0.226

Nickel-Plated Brass Adaptors




0908 Equal Cross, Female BSPP Thread

	Nickel-plated brass		C		E	G	H	J	kg
			G1/8	0908 00 10	8	13	21	10	0.038
			G1/4	0908 00 13	11	17	25.5	13	0.073
			G3/8	0908 00 17	11.5	21	28	17	0.107
			G1/2	0908 00 21	14	26	33.5	21	0.189




0909 Equal Cross, Male BSPT/Female BSPP Thread

	<p>Nickel-plated brass</p> 	C1		C2		E		G	H	J	kg
		R1/8		G1/8		0909 00 10	8	13	18.5	10	0.034
		R1/4		G1/4		0909 00 13	11	17	23.5	13	0.068
		R3/8		G3/8		0909 00 17	11.5	21	26	17	0.099
		R1/2		G1/2		0909 00 21	14	26	31	21	0.168




0903 Reducer, Male/Female BSPP Thread

	Nickel-plated brass		C1	C2		E	F	kg
			G1/4	G1/8	0903 10 13	8	6	0.004
			G3/8	G1/4	0903 13 17	9	8	0.006
			G1/2	G3/8	0903 17 21	10	10	0.010
			G3/4	G1/2	0903 21 27	14	12	0.022
			G1	G3/4	0903 27 34	20	17	0.036

0904 Reducer, Male BSPT/Female BSPP Thread

	Nickel-plated brass		C1	C2		F	L	kg
			R1/4	G1/8	0904 10 13	14	16	0.010
			R3/8	G1/8	0904 10 17	17	16.5	0.020
				G1/4	0904 13 17	17	16.5	0.015
			R1/2	G1/4	0904 13 21	22	19.5	0.032
				G3/8	0904 17 21	22	19.5	0.025
			R3/4	G3/8	0904 17 27	27	23.5	0.057
				G1/2	0904 21 27	27	23.5	0.044

0905 Reducer, Male BSPP/Female BSPP and Metric Thread

	Nickel-plated brass		C1	C2		E	F	L	kg	
			G1/8	M5x0.8		0905 19 10*	6	14	4.5	0.008
			G1/4	G1/8		0905 10 13*	8	17	5	0.011
			G3/8	G1/8		0905 10 17*	9	19	5	0.019
				G1/4		0905 13 17	9	19	5	0.013
			G1/2	G1/4		0905 13 21	10	24	5.5	0.032
				G3/8		0905 17 21	10	24	5.5	0.022
			G3/4	G3/8		0905 17 27	12	30	5.5	0.053
				G1/2		0905 21 27*	12	30	5.5	0.041



*Please contact us for detailed drawings of threads.

*Please contact us for detailed drawings of threads.

Nickel-Plated Brass Adaptors



0906

Increaser, Male BSPP and Metric/Female BSPP Thread

	Nickel-plated brass	C1	C2		E1	E2	F	L	kg
		M5x0.8	G1/8	0906 10 19	4	8	14	10	0.009
			G1/8	0906 00 10	6	8	14	10	0.011
		G1/8	G1/4	0906 10 13	6	11	17	14	0.016
			G3/8	0906 10 17	6	11.5	22	14.5	0.029
		G1/4	G1/4	0906 00 13	8	11	17	14	0.020
			G3/8	0906 13 17	8	11.5	22	14.5	0.032
			G1/2	0906 13 21	8	15	27	18	0.037
		G3/8	G3/8	0906 00 17	9	11.5	22	14.5	0.034
			G1/2	0906 17 21	9	14	27	18	0.038
		G1/2	G1/2	0906 00 21	10	14	27	18	0.054



0907

Equal Extended Adaptor, Male/Female BSPP Thread

	Nickel-plated brass	C		E	F	L	kg
		G1/8	0907 00 10	6	14	16	0.015
			0907 00 10 01	6	14	36	0.029
		G1/4	0907 00 13	8	17	26	0.032
			0907 00 13 01	8	17	43	0.046



0920

Bulkhead Connector, Female BSPP and Metric Thread

	Nickel-plated brass	C	C1		F	F1	K _{max}	L	L1	ØT	kg
		M5x0.8	M10x1	0920 00 19	14	14	7	10.5	3.5	10.5	0.012
		G1/8	M16x1.5	0920 00 10	19	22	9	14	4	16.5	0.029
		G1/4	M20x1.5	0920 00 13	24	27	15	21	4	20.5	0.056
		G3/8	M26x1.5	0920 00 17	30	32	14	21	5	26.5	0.095
		G1/2	M28x1.5	0920 00 21	32	36	20	27	6	28.5	0.115

0900



Equal and Unequal Adaptor, Male BSPT Thread

	Nickel-plated brass	C1	C2		F	L	kg
			R1/8	0900 00 10	12	19.5	0.008
		R1/8	R1/4	0900 10 13	14	23.5	0.015
			R3/8	0900 10 17	17	24	0.020
		R1/4	R1/4	0900 00 13	14	27	0.017
			R3/8	0900 13 17	17	27.5	0.026
			R1/2	0900 13 21	22	30.5	0.044
		R3/8	R3/8	0900 00 17	17	28	0.026
			R1/2	0900 17 21	22	31	0.046
		R1/2	R1/2	0900 00 21	22	33.5	0.044
			R3/4	0900 21 27	27	37.5	0.084
		R3/4	R3/4	0900 00 27	27	40	0.079
			R1	0900 27 34	34	43	0.144
		R1	R1	0900 00 34	34	45.5	0.153

Nickel-Plated Brass Adaptors



0901

Equal and Unequal Adaptor, Male BSPP and Metric Thread

	Nickel-plated brass	C1	C2		E	E1	F	L	kg
		M5x0.8	M5x0.8	0901 00 19	4	4	8	11.5	0.002
		G1/8	G1/8	0901 19 10	4	6	14	14.5	0.008
		G1/8	G1/8	0901 00 10	6	6	14	16.5	0.009
		G1/4	G1/4	0901 10 13	6	8	17	19	0.016
		G1/4	G1/4	0901 00 13	8	8	17	21	0.019
		G3/8	G3/8	0901 13 17	8	9	19	22	0.023
		G3/8	G3/8	0901 00 17	9	9	19	23	0.025
		G1/2	G1/2	0901 17 21	9	10	24	24.5	0.038
		G1/2	G1/2	0901 00 21	10	10	24	25.5	0.041



0192

Unequal Straight Adaptor, Male BSPT/BSPP Thread

	Nickel-plated brass	C1	C2		E	F	L	kg
		R1/8	G1/4	0192 10 13	9.5	17	23.5	0.019
		G1/4	G1/4	0192 13 13	9.5	17	27.5	0.024
		G1/2	G1/2	0192 13 21	11	27	31.5	0.068
		G1/4	G1/4	0192 17 13	9.5	17	28	0.025
		G1/2	G1/2	0192 17 21	11	27	31.5	0.061
		G1/2	G1/2	0192 21 21	11	27	34	0.061



0902

Equal and Unequal Adaptor, Female BSPP and Metric Thread

	Nickel-plated brass	C1	C2		F	L	kg
		M5x0.8	M5x0.8	0902 00 19	8	11	0.003
		G1/8	G1/8	0902 19 10	14	13	0.009
		G1/8	G1/8	0902 00 10	14	15	0.010
		G1/4	G1/4	0902 10 13	17	19.5	0.017
		G3/8	G3/8	0902 10 17	22	20	0.028
		G1/4	G1/4	0902 00 13	17	22	0.019
		G3/8	G3/8	0902 13 17	22	23	0.031
		G1/2	G1/2	0902 13 21	27	27	0.033
		G3/8	G3/8	0902 00 17	22	24	0.034
		G1/2	G1/2	0902 17 21	27	27.5	0.037
		G1/2	G1/2	0902 00 21	27	30	0.050
		G3/4	G3/4	0902 21 27	30	30	0.077
		G3/4	G3/4	0902 00 27	30	32	0.080

0191


Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

	Nickel-plated brass	ØD	ØD1	C		E	F	K	L	kg
		4	6	G1/4	0191 04 13	9.5	17	5	22.5	0.019
		7	9	G1/4	0191 07 13	9.5	17	5	22.5	0.022
			9	G1/2	0191 07 21	11	27	7	29.5	0.065
		10	12.2	G1/4	0191 10 13	9.5	17	5	22.5	0.020
			12.2	G1/2	0191 10 21	11	27	7	29.5	0.061
		13	15.2	G1/4	0191 13 13	9.5	17	5	22.5	0.022
			15.2	G1/2	0191 13 21	11	27	7	29.5	0.058
		16	18.5	G1/2	0191 16 21	11	27	7	36.5	0.067

Nickel-Plated Brass Adaptors


0931

Tailpiece Adaptor for Rubber Hose, Male BSPP Thread


	Nickel-plated brass		<div> <div></div> <div></div> </div>						
	ØD	ØD1	C	E	F	K	L	kg	
	6	7	G1/8	0931 06 10	6	12	4	20	0.009
		7	G1/4	0931 06 13	8	14	5	20	0.013
7	8	G1/8	0931 07 10	6	12	4	20	0.009	
		G1/4	0931 07 13	8	14	5	20	0.013	
8	9	G3/8	0931 07 17	9	19	5	20	0.022	
		G1/8	0931 08 10	6	12	4	20	0.009	
9	12	G1/4	0931 08 13	8	14	5	20	0.014	
		G3/8	0931 08 17	9	19	5	20	0.022	
10	12	G1/4	0931 10 13	8	14	5	20	0.016	
		G3/8	0931 10 17	9	19	5	20	0.024	
15	17	G1/2	0931 10 21	10	22	6	22	0.031	
		G3/8	0931 15 17	9	19	6	24	0.030	
18	20	G1/2	0931 15 21	10	22	6	24	0.037	
		G1/2	0931 18 21	10	22	6	24	0.039	


Stainless Steel Adaptors

1844 Equal Stud Elbow, Male BSPT/Female BSPP Thread





Stainless steel 316L





C1	C2		E	G	H	J	L	kg
R1/8	G1/8	1844 10 10	7.5	15	20.5	10	22.5	0.022
R1/4	G1/4	1844 13 13	12	18.5	27.5	12	26.5	0.044
R3/8	G3/8	1844 17 17	12	23.5	28	14	30	0.067
R1/2	G1/2	1844 21 21	15	28	38	18	38	0.114
R3/4	G3/4	1844 27 27	16.5	33	41	22	44.5	0.154
R1	G1	1844 34 34	19	40	48	32	50	0.312



1843 Equal Elbow, Female BSPP Thread

	Stainless steel 316L		C		E G		J	L	kg
			G1/8	1843 10 10	7.5	17.5	12	22.5	0.041
			G1/4	1843 13 13	11	18.5	15	26.5	0.055
			G3/8	1843 17 17	11.5	23.5	18	29	0.076
			G1/2	1843 21 21	15	28	23	38	0.159
			G3/4	1843 27 27	16.5	33	22	43.5	0.232
			G1	1843 34 34	19	40	32	52	0.444



1845 Equal Tee, Female BSPP Thread

	Stainless steel 316L		C		E G		H	J	L/2	kg
			G1/8	1845 10 10	7.5	17.5	22.5	12	22.5	0.060
			G1/4	1845 13 13	11	18.5	26.5	15	26.5	0.078
			G3/8	1845 17 17	11.5	23.5	29	18	29	0.100
			G1/2	1845 21 21	15	28	38	23	38	0.221
			G3/4	1845 27 27	16.5	33	43.5	22	43.5	0.301
			G1	1845 34 34	19	40	50	32	50	0.457

1817 Equal Bulkhead Adaptor, Female BSPP Thread




	Stainless steel 316L		C		F F1		K _{max}	L	L1	ØT _{min}	kg
			G1/8	1817 00 10	19	22	9	14	4	16.5	0.030
			G1/4	1817 00 13	24	27	15	21	4	20.5	0.053
			G3/8	1817 00 17	30	32	14	21	5	26.5	0.091
			G1/2	1817 00 21	32	36	20	27	6	28.5	0.109
			G3/4	1817 00 27	41	41	22.5	30	6	34.5	0.152
			G1	1817 00 34	46	50	24.5	34	8	42.5	0.252

1871 Equal Bulkhead Adaptor, Female NPT Thread




	Stainless steel 316L		C		F F1		K _{max}	L	L1	ØT _{min}	kg
			NPT1/8	1871 00 11	19	22	9	14	5	16.5	0.032
			NPT1/4	1871 00 14	24	22	9	14	5	16.5	0.060
			NPT3/8	1871 00 18	30	32	18	23	5	26.5	0.096
			NPT1/2	1871 00 22	32	36	22	29	6	28.5	0.120

Stainless Steel Adaptors




1855 Equal Connector, Female BSPP Thread

	Stainless steel 316L		C 				F	L	kg
			G1/8	1855 10 10					
			G1/4	1855 13 13					
			G3/8	1855 17 17					
			G1/2	1855 21 21					
			G3/4	1855 27 27					
			G1	1855 34 34					




1870 Equal Connector, Female NPT Thread

	Stainless steel 316L		C 				F	L	kg
			NPT1/8	1870 11 11					
			NPT1/4	1870 14 14					
			NPT3/8	1870 18 18					
			NPT1/2	1870 22 22					




1862 Reducer Connector, Female BSPP Thread

	Stainless steel 316L		C1 C2 				F	L	kg
			G1/4	G1/8	1862 13 10				
			G1/8	G1/8	1862 17 10				
			G3/8	G1/4	1862 17 13				
			G1/2	G1/4	1862 21 13				
			G3/8	G3/8	1862 21 17				
			G3/4	G1/2	1862 27 21				
			G1	G3/4	1862 34 27				

1864 Adaptor, Male NPT/Female BSPP Thread




	Stainless steel 316L		C1 C2 				E	F	L	kg
			NPT1/8	G1/8	1864 11 10					
			NPT1/4	G1/4	1864 14 13					
			NPT3/8	G3/8	1864 18 17					
			NPT1/2	G1/2	1864 22 21					

1867 Adaptor, Male BSPT/Female NPT Thread




	Stainless steel 316L		C1 C2 				E	F	L	kg
			R1/8	NPT1/8	1867 10 11					
			R1/4	NPT1/4	1867 13 14					
			R3/8	NPT3/8	1867 17 18					
			R1/2	NPT1/2	1867 21 22					

Stainless Steel Adaptors




1863 Reducer, Male BSPT/Female BSPP Thread

	Stainless steel 316L			C1	C2					F	L	kg
				R1/4	G1/8		1863 13 10			14	16	0.008
				R3/8	G1/8		1863 17 10			17	16.5	0.019
					G1/4		1863 17 13			17	16.5	0.011
				R1/2	G1/4		1863 21 13			22	21	0.036
					G3/8		1863 21 17			22	21	0.023
				R3/4	G1/2		1863 27 21			27	25.5	0.045
				R1	G3/4		1863 34 27			36	28.5	0.083




1872 Reducer, Male/Female NPT Thread

	Stainless steel 316L			C1	C2					F	L	kg
				NPT1/4	NPT1/8		1872 14 11			14	16	0.010
				NPT3/8	NPT1/8		1872 18 11			19	16.5	0.023
					NPT1/4		1872 18 14			19	16.5	0.016
				NPT1/2	NPT1/4		1872 22 14			22	21	0.039
					NPT3/8		1872 22 18			22	21	0.028




1861 Increaser, Male BSPT/Female BSPP Thread

	Stainless steel 316L			C1	C2					E	F	L	kg
				R1/8	G1/4		1861 10 13			11	17	24	0.022
					G3/8		1861 10 17			11.5	22	25	0.038
				R1/4	G3/8		1861 13 17			11.5	22	28.5	0.042
					G1/2		1861 13 21			15	27	32.5	0.068
				R3/8	G1/2		1861 17 21			15	27	33	0.070
				R1/2	G3/4		1861 21 27			16.5	32	38	0.093
				R3/4	G1		1861 27 34			19	41	43.5	0.182

1873 Increaser, Male/Female NPT Thread




	Stainless steel 316L			C1	C2					E	F	L	kg
				NPT1/8	NPT1/4		1873 11 14			14	17	25	0.024
					NPT3/8		1873 11 18			14	22	25	0.039
				NPT1/4	NPT3/8		1873 14 18			14	22	28.5	0.042
					NPT1/2		1873 14 22			17.5	27	31	0.065
				NPT3/8	NPT1/2		1873 18 22			17.5	27	31.5	0.066

1821 Equal and Unequal Adaptor, Male BSPT Thread

	Stainless steel 316L			C1	C2					F	L	kg
				R1/8	R1/8		1821 10 10			12	19	0.009
				R1/4	R1/8		1821 13 10			14	23.5	0.016
					R1/4		1821 13 13			14	27	0.019
				R3/8	R1/4		1821 17 13			17	27.5	0.024
					R3/8		1821 17 17			17	28	0.024
				R1/2	R3/8		1821 21 17			22	32.5	0.042
					R1/2		1821 21 21			22	36	0.048
				R3/4	R1/2		1821 27 21			27	41	0.079
					R3/4		1821 27 27			27	42	0.088
				R1	R3/4		1821 34 27			36	46	0.141
					R1		1821 34 34			36	48	0.146


Stainless Steel Adaptors

1821 Equal Adaptor, Male NPT Thread


	Stainless steel 316L			C		F	L	kg
	NPT1/8	1821 11 11		12	23	0.011		
	NPT1/4	1821 14 14		14	32	0.023		
	NPT3/8	1821 18 18		19	33	0.031		
	NPT1/2	1821 22 22		22	42	0.057		
	NPT3/4	1821 28 28		27	40	0.082		
	NPT1	1821 35 35		36	46	0.138		

1823 Tailpipe Adaptor for Rubber Hose, Male BSPT Thread


Stainless steel 316L


ØD	ØD1	C		F	L	L1	ØT	kg
7	9	R1/8	1823 07 10	10	34	22.5	5	0.009
	9	R1/4	1823 07 13	14	38.5	22.5	6	0.016
10	12.2	R1/4	1823 10 13	14	38.5	22.5	7	0.018
	12.2	R3/8	1823 10 17	17	39	22.5	9.5	0.021
13	15	R3/8	1823 13 17	17	46	29.5	11	0.025
16	18.5	R1/2	1823 16 21	22	59	38	14	0.050

1823 Tailpipe Adaptor for Rubber Hose, Male NPT Thread



Stainless steel 316L




ØD	ØD1	C		F	L	L1	ØT	kg
1/4	8.3	NPT1/8	1823 56 11	12	34	22.5	5.3	0.010
	8.3	NPT1/4	1823 56 14	14	38.5	22.5	5.3	0.016
1/8	11.7	NPT1/4	1823 60 14	14	38.5	22.5	8.5	0.018
	11.7	NPT3/8	1823 60 18	19	39	22.5	8.5	0.026


Brass Manifolds

0135

Manifold Block, Female BSPP Thread



Brass



C



H H1 K L N N1 kg

G1/4	0135 06 13	30	13	25	70	37	17	0.329
	0135 09 13	30	13	25	87	54	17	0.409
G1/2	0135 06 21	40	16	35	86	45	27	0.714
	0135 09 21	40	16	35	109	68	27	0.899
G3/4	0135 10 27	45	21	40	122	78	32	1.232

This product is designed to distribute in several directions.

The number of ports can be increased by using tee pieces, cross pieces or double banjo couplings.

Installation Options

	F1				F2				F4			
	Number of Outlets	N°1	N°2	N°3	Number of Outlets	N°4	N°5	N°6	Number of Outlets	N°7	N°8	N°9
0135 06 13	1		G1/4		2	G1/8		G1/8	2	G1/8		G1/8
0135 09 13	2	G1/4		G1/4	3	G1/8	G1/8	G1/8	3	G1/8	G1/8	G1/8
0135 06 21	1		G1/2		2	G1/4		G1/4	2	G1/8		G1/8
0135 09 21	2	G1/2		G1/2	3	G1/4	G1/4	G1/4	3	G1/8	G1/8	G1/8
0135 10 27	3	G1/2	G1/8	G1/2	3	G1/8	G1/8	G1/8	3	G1/4	G1/8	G1/4

Anodised Aluminium Manifolds


3310

In-Line Manifold

A photograph of the 3310 In-Line Manifold, a white, rectangular component with six black ports on the top and a single black port on the side.

Treated aluminium, NBR


A technical drawing of the 3310 In-Line Manifold showing two views: a top view and a side view. The top view shows the manifold with six ports, labeled with dimensions L1, ØD, 5, S, H, and Ø 4,6. The side view shows the manifold with dimensions N, C, and L.

ØD	C		Number of Outlets	E	H	L	L1	N	kg
4	G1/4	3310 04 13	8	10	33	114	104	11.5	0.175
6	G1/4	3310 06 13	8	10	33	114	104	12.5	0.169
8	G3/8	3310 08 17	6	12	33	114	104	15	0.156
10	G1/2	3310 10 21	6	14	48	130	119.5	17	0.348
12	G1/2	3310 12 21	6	14	45	117	107	20.5	0.370

3311




Manifold, Female BSPP and Metric Thread

Treated aluminium

C1	C2		Number of Outlets	H	H1	H2	K	L	L1	N	ØT	kg
G1/8	M5x0.8	3311 19 10 07	7	3.5	20	8.5	15	95	80	11	4.4	0.067
		3311 10 13 02	2	4.5	30	15	20	61	50	30	5	0.079
		3311 10 13 03	3	4.5	30	15	20	91	30	30	5	0.121
G1/4		3311 10 13 04	4	4.5	30	15	20	121	60	30	5	0.165
		3311 10 13 05	5	4.5	30	15	20	151	90	30	5	0.209
		3311 10 13 06	6	4.5	30	15	20	181	120	30	5	0.244
		3311 13 17 02	2	5.5	30	11	20	74	61	36	6.5	0.076
		3311 13 17 03	3	6	30	11	20	110	36	36	6.5	0.121
G3/8		3311 13 17 04	4	6	30	11	20	146	72	36	6.5	0.144
		3311 13 17 05	5	6	30	11	20	182	108	36	6.5	0.212
		3311 13 17 06	6	6	30	11	20	218	144	36	6.5	0.265

3312


Cross Manifold, Female BSPP and Metric Thread

	Treated aluminium			H	K	L	L1	N	ØT	kg
	C									
	M5x0.8	3312 00 19								
	G1/8	3312 00 10								
	G1/4	3312 00 13								
	G3/8	3312 00 17								
	G1/2	3312 00 21								
										

3313

Double Manifold, Female BSPP Thread


Treated aluminium

C1	C2		Number of Outlets	H	H1	H2	K	L	L1	N	ØT	kg
G1/4	G1/8	3313 10 13 02	2x2	4.5	30	15	20	61	50	30	5	0.075
	G1/8	3313 10 13 03	2x3	4.5	30	15	20	91	30	30	5	0.115
	G1/8	3313 10 13 04	2x4	4.5	30	15	20	121	60	30	5	0.151
	G1/8	3313 10 13 05	2x5	4.5	30	15	20	151	90	30	5	0.194
G3/8	G1/4	3313 13 17 02	2x2	6	40	20	20	74	61	36	6.5	0.109
	G1/4	3313 13 17 03	2x3	6	40	20	20	110	36	36	6.5	0.179
	G1/4	3313 13 17 04	2x4	6	40	20	20	146	72	36	6.5	0.238
	G1/4	3313 13 17 05	2x5	6	40	20	20	182	108	36	6.5	0.286
G1/2	G1/4	3313 13 21 03	2x3	6	40	20	28	116	36	36	6.5	0.222
	G1/4	3313 13 21 04	2x4	6	40	20	28	152	72	36	6.5	0.295
	G1/4	3313 13 21 05	2x5	6	40	20	28	188	108	36	6.5	0.369

Anodised Aluminium Manifolds




3301 Modular Manifold

Treated aluminium, NBR




ØD		Number of Outlets	H	H1	H2	H3	L	L1	N	N1	kg
4	3301 04 00	8	25	10	4.5	16	73.5	25	35	17	0.105
6	3301 06 00	4	25	10	4.5	16	73.5	25	35	17	0.108

Fixing with screw M3x20




3301 Manifold, Female BSPP Thread

	Treated aluminium, NBR		C		Number of Outlets	H	H1	H2	H3	L	L1	N	N1	kg	
			G1/8		3301 07 10	4	25	10	4.5	16	73.5	25	35	17	0.097
			Fixing with screw M3x20 NPT available on request												




3302 Single Manifold, Female BSPP Thread

	Treated aluminium, NBR		C		H	L	L1	kg
			G1/4	3302 01 13	25	24.5	25	0.030
				3302 01 13 01	25	24.5	25	0.031
			3302 01 13: side entry thread 3302 01 13 01: rear entry thread NPT available on request					

3302 Double Manifold, Female BSPP Thread


	Treated aluminium, NBR		C		H	H1	H2	L	N	kg
			G3/8	3302 02 17	25	12.5	24.5	51	26	0.061
			Side entry thread NPT available on request							

3302 Triple Manifold, Female BSPP Thread




	Treated aluminium, NBR 	C		H	H1	H2	L	N	kg
		G3/8	3302 03 17	25	12.5	25	77	26	0.087
		Side entry thread NPT available on request							

Anodised Aluminium Manifolds

3303 End Plate for Manifold



	<p>Treated aluminium</p> 					
			H	H1	L	kg
			3303 00 01	9.5	3.5	25

3303 Angled Fixing Plate



	<p>Treated aluminium</p> 			
			kg	
			3303 00 02	0.027

Brass Plugs



0205 Internal Hexagon Head Plug, Male BSPT Thread

	Brass	C		E1	E2 min	E2 max	F	G	H	kg
		R1/8	0205 10 00	6	3.1	4.9	5	9.7	8	0.003
		R1/4	0205 13 00	8	4.7	7.3	6	13.2	10	0.007
		R3/8	0205 17 00	8	5.1	7.7	8	16.7	11	0.013
		R1/2	0205 21 00	8	6.4	10	10	21	13	0.026
		R3/4	0205 27 00	11	7.7	11.3	14	26.4	17	0.054
		R1	0205 34 00	13	8.1	12.7	17	33.2	19	0.094
		R1¼	0205 42 00	14	10.4	15	22	41.9	22	0.176
		R1½	0205 49 00	14	10.4	15	24	47.8	22	0.246
		R2	0205 48 00	16	13.6	18.2	30	59.6	25	0.431
		For BSPT plug from 1/2" - 1½" inclusive: Conforms to DIN 906 Thread: EN 10226-1								

0205 Internal Hexagon Head Plug, Male NPT Thread



	Brass	C		E1	E2 min	E2 max	F	G	H	kg
		NPT1/8	0205 11 00	6	3.2	5	5	10.2	8	0.003
		NPT1/4	0205 14 00	8	4.4	7.2	6	13.6	10	0.008
		NPT3/8	0205 18 00	8	4.7	7.5	8	17	11	0.014
		NPT1/2	0205 22 00	8	6.3	9.9	10	21.2	13	0.026
		NPT3/4	0205 28 00	11	6.8	10.4	14	26.6	17	0.052
		NPT1	0205 35 00	13	8	12.4	17	33.2	19	0.091

0209 Square Head Plug, Male BSPT Thread

	Brass	C		E1	E2 min	E2 max	G	H	J	kg
		R1/8	0209 10 00	6	3.1	4.9	9.7	16	6	0.007
		R1/4	0209 13 00	8	4.7	7.3	13.2	18	8	0.014
		R3/8	0209 17 00	10	5.1	7.7	16.7	20	10	0.025
		R1/2	0209 21 00	11	6.4	10	21	22	13	0.047
		R3/4	0209 27 00	15	7.7	11.3	26.4	28	17	0.097
		R1	0209 34 00	18	8.1	12.7	33.2	32	19	0.170



Conforms to DIN 906
Thread: EN 10226-1

0220 Hex Head Plug, Male BSPP and Metric Thread

	Brass, technical polymer	C		F	G	H1	kg
		M5x0.8	0220 19 00	8	8	5	0.002
		G1/8	0220 10 00	14	14	7.5	0.011
		G1/4	0220 13 00	17	17	7.5	0.019
		G3/8	0220 17 00	17	22	8.5	0.024
		G1/2	0220 21 00	22	27	10	0.040

Pre-assembled polyamide washer
M5: with screwdriver slot for tightening
Maximum allowable working pressure = 20 bar
Part number with suffix 99, maximum allowable working pressure = 250 bar, example: 0220 19 00 99
Conforms to BNA 229 (with the exception of M5 model), BSPP thread, ISO ISO 228-1,
Parallel, metric thread, ISO NFE 03-054



0200 Hex Head Plug, Male BSPP and Metric Thread

	Brass	C		E	F	G	H1	H2	kg
		M6x1	0200 52 00	6	10	10	4	3.5	0.004
		M8x1.25	0200 57 00	7	13	13	4	3.5	0.007
		M10x1	0200 60 00	8	14	14	5	4.5	0.011
		M12x1	0200 65 00	9	17	17	5	4.5	0.018
		M12x1.25	0200 66 00	9	17	17	5	4.5	0.017
		G1/8	0200 10 00	7	14	13.7	5.5	4	0.011
		G1/4	0200 13 00	8.5	17	16.7	5.5	4	0.019

Brass Plugs



0201

Hex Head Plug with Collar, Male BSPP and Metric Thread

	Brass	C		E	F	G	H1	H2	kg
		M16x1.5	0201 75 00	10	17	22	6.5	5	0.025
		M18x1.5	0201 78 00	10	17	24	7	5	0.026
		M20x1.5	0201 80 00	10	17	26	7.5	5	0.031
		M22x1.5	0201 82 00	10	22	30	7.5	5	0.044
		M24x1.5	0201 83 00	10	22	32	7.5	5	0.046
		M24x2	0201 92 00	10	22	32	7.5	5	0.046
		M30x2	0201 88 00	11	27	38	8.5	6	0.075
		G3/8	0201 17 00	10	17	21.7	6.5	4.5	0.024
		G1/2	0201 21 00	10	22	26.7	7.5	5	0.041
		G3/4	0201 27 00	11	22	31.7	8.5	6	0.057
		G1	0201 34 00	11	27	39.7	8.5	6	0.087
		G1¼	0201 42 00	12	30	49.7	10	7	0.142

0202

Internal Hexagon Head Plug with Collar, Male Metric Thread

	Brass	C		E	F	G	H	H1	kg
		M12x1	0202 65 00	9	6	17	11	8	0.009
		M12x1.25	0202 66 00	9	6	17	11	8	0.009
		M14x1.5	0202 71 00	10	6	19	13	10	0.015
		M16x1.5	0202 75 00	10	8	22	13	10	0.020
		M18x1.5	0202 78 00	10	10	24	13	10	0.022
		M20x1.5	0202 80 00	10	12	26	13	10	0.025
		M22x1.5	0202 82 00	10	12	30	13	10	0.034
		M27x2	0202 86 00	11	17	35	15	11	0.053
		M30x2	0202 88 00	11	19	38	15	11	0.062
		Parallel metric threads, ISO standard NFE 03-054							


Nickel-Plated Brass Plugs

0919

Internal Hexagon Head Plug, Male BSPP and Metric Thread





Nickel-plated brass



C		E	F	G	H	kg
M5x0.8	0919 00 19	4	2.5	8	7.5	0.001
G1/8	0919 00 10	6	3	15	10	0.007
G1/4	0919 00 13	8	6	18	12	0.013
G3/8	0919 00 17	9	8	21	13	0.021
G1/2	0919 00 21	10	10	25	14.5	0.036
G3/4	0919 00 27	11	30	-	17	0.050
G1	0919 00 34	13	38	-	19	0.076



Steel Plugs

0206 Internal Hexagon Head Plug, Male BSPT Thread



	Steel 	C		E1	E2 min	E2 max	F	G	H	kg
		R1/8	0206 10 00	6	3.1	4.9	5	9.7	8	0.003
		R1/4	0206 13 00	8	4.7	7.3	6	13.2	10	0.007
		R3/8	0206 17 00	8	5.1	7.7	8	16.7	11	0.012
		R1/2	0206 21 00	8	6.4	10	10	21	13	0.023
		R3/4	0206 27 00	11	7.7	11.3	14	26.4	17	0.048
		R1	0206 34 00	13	8.1	12.7	17	33.2	19	0.086
		R1¼	0206 42 00	14	10.4	15	22	41.9	22	0.166
		R1½	0206 49 00	14	10.4	15	24	47.8	22	0.222

For BSPT plugs, from 1/2" - 1½" inclusive
Conforms to DIN 906
Thread, conforms to EN 10226-1

0206 Internal Hexagon Head Plug, Male NPT Thread



	Steel 	C		E1	E2 min	E2 max	F	G	H	kg
		NPT1/16	0206 08 00	6	3.8	6.4	4	7.8	7	0.002
		NPT1/8	0206 11 00	6	3.2	5	5	10.2	8	0.003
		NPT1/4	0206 14 00	8	4.4	7.2	6	13.6	10	0.007
		NPT3/8	0206 18 00	8	4.7	7.5	8	17	11	0.012
		NPT1/2	0206 22 00	8	6.3	9.9	10	21.2	13	0.024
		NPT3/4	0206 28 00	11	6.8	10.4	14	26.6	17	0.047
		NPT1	0206 35 00	13	8	12.4	17	33.2	19	0.083

0210 Hex Head Plug, Male BSPP and Metric Thread

	Steel 	C		E	F	G	H	kg
		M8x1.25	0210 57 00	8	14	12	15	0.010
		M10x1	0210 60 00	8	14	14	15	0.013
		M12x1.25	0210 66 00	11	17	17	18	0.021
		G1/8	0210 10 00	8	14	14	15	0.012
		M14x1.25	0210 70 00	11	19	19	20	0.032
		G1/4	0210 13 00	12	19	18	21	0.031
		G3/8	0210 17 00	12	22	22	21	0.046
		G1/2	0210 21 00	14	27	26	24	0.078
		G3/4	0210 27 00	16	32	32	27	0.134
		G1	0210 34 00	18	41	39	33	0.269
		G1¼	0210 42 00	20	50	49	35	0.441



Profile of head undercut conforms to DIN 3852-1; form D/E
BSPP threads, ISO 228-1
Parallel metric threads, NFE 03-054

0216 Hex Head Plug, Male BSPT Thread

	Steel 	C		F	H	kg
		R1/8	0216 10 00	13	16	0.012
		R1/4	0216 13 00	17	19	0.023
		R3/8	0216 17 00	19	21	0.038
		R1/2	0216 21 00	22	23	0.060




BSPT thread conforms to EN 10226-1

0216 Hex Head Plug, Male NPT Thread




	Steel 	C		F	H	kg
		NPT1/8	0216 11 00	13	16	0.012
		NPT1/4	0216 14 00	17	19	0.024
		NPT3/8	0216 18 00	19	21	0.038
		NPT1/2	0216 22 00	22	23	0.060

Stainless Steel Plugs

0285 Internal Hexagon Head Plug, Male BSPT Thread

	Stainless steel 316L 	C		E1	E2 min	E2 max	F	G	H	kg
		R1/8	0285 10 00	6	3.1	4.9	5	9.7	8	0.003
		R1/4	0285 13 00	8	4.7	7.3	6	13.2	10	0.007
		R3/8	0285 17 00	8	5.1	7.7	8	16.7	11	0.013
		R1/2	0285 21 00	8	6.4	10	10	21	13	0.024
		R3/4	0285 27 00	11	7.7	11.3	14	26.4	17	0.051
		R1	0285 34 00	13	8.1	12.7	17	33.2	19	0.089


0285 Internal Hexagon Head Plug, Male NPT Thread

	Stainless steel 316L 	C		E1	E2 min	E2 max	F	G	H	kg
		NPT1/8	0285 11 00	6	3.2	5	5	10.2	8	0.003
		NPT1/4	0285 14 00	8	4.4	7.2	6	13.6	10	0.007
		NPT3/8	0285 18 00	8	4.7	7.5	8	17	11	0.013
		NPT1/2	0285 22 00	8	6.3	9.9	10	21.2	13	0.025


Sealing Accessories


0138

Copper Washer




Copper




C		G1	G2	K	kg
M6	0138 06 00	6.3	9	1	0.033
M8	0138 08 00	8.3	11	1	0.001
M12	0138 12 00	12.3	15.5	1.3	0.072
M14	0138 14 00	14.3	18	1.5	0.001
M16	0138 16 00	16.3	20	1.5	0.001
M18	0138 18 00	18.3	22	1.5	0.001
M20	0138 20 00	20.3	24	1.5	0.001
M22	0138 22 00	22.3	27	1.5	0.002
M24	0138 24 00	24.3	29	2	0.003
M26	0138 26 00	26.3	31	2	0.003
M30	0138 30 00	30.3	36	2	0.004
M36	0138 36 00	36.3	42	2	0.005
M39	0138 39 00	39.3	44	2	0.007
M45	0138 45 00	45.3	52	2	0.007
M52	0138 52 00	52.3	60	2	0.009
G1/8	0138 10 00	10.3	13.5	1	0.001
G1/4	0138 13 00	13.5	18	1.3	0.001
G3/8	0138 17 00	17.3	21	1.5	0.001
G1/2	0138 21 00	21.3	26	1.5	0.002
G3/4	0138 27 00	27.3	32	2	0.003
G1	0138 33 00	33.5	39	2	0.005
G1 1/4	0138 42 00	42.5	49	2	0.007
G1 1/2	0138 48 00	48.3	55	2	0.008
G2	0138 60 00	60	68	2.5	0.014
DIN 7603 ISO 65061					


0137

Bonded Seal



Zinc-plated steel with NBR seal



C		G1	G2	K	kg
M12	0137 12 00	12.7	19	1.5	0.001
M14	0137 14 00	14.7	21	1.5	0.001
M16	0137 16 00	16.7	23	1.5	0.002
M18	0137 18 00	18.7	27	2	0.004
M20	0137 20 00	20.7	29	2	0.004
M22	0137 22 00	22.7	31	2	0.005
M24	0137 24 00	24.7	33	2	0.005
M30	0137 30 00	30.7	39	2	0.071
M39	0137 39 00	40	51	2.5	0.012
M45	0137 45 00	46	57	2.5	0.014
G1/8	0137 10 00	10.7	17	1.5	0.001
G1/4	0137 13 00	13.7	20.6	2.1	0.002
G3/8	0137 17 00	17.4	23.7	1.5	0.002
G1/2	0137 21 00	21.5	28.6	2.5	0.004
G3/4	0137 27 00	27	35.3	2	0.007
G1	0137 33 00	33.7	42	2	0.007
G1 1/4	0137 42 00	43	54	2.5	0.013
G1 1/2	0137 48 00	49	60	2.5	0.015
G2	0137 60 00	60.7	73	3	0.027



Note: to use these bonded seals successfully it is necessary to spot face around the female thread to provide a sealing face.

The diameter should be 0.3 mm to 0.5 mm greater than the external diameter of the seal.


The surface finish of the spot face should not exceed 12 μ.

Sealing Accessories


0605 Fluoropolymer Tape


	FKM	 <p>0605 12 12</p> <p>Can be used for temperatures from - 250°C to +260°C. Chemically inert and resistant to gases, acids, solvents, hydrocarbons, oils, alkalines, steam etc. Non-toxic, waterproof, self-lubricating. In accordance with CFR21. Can be used on all materials. Used to facilitate the preparation of leak-free threaded joints. Supplied on a reel, length = 12 m; width = 12.7 mm; thickness 0.08 mm.</p>
		kg 0.012

0602 Captive Sealing Washer






Technical polymer



C		G1	G2	K	kg
M5x0.8	0602 29 93 15	5.2	7.8	1.5	0.001
G1/8	0602 23 10 20	10.3	14	2	0.001
G1/4	0602 23 11 20	13.7	17.5	2	0.001
G3/8	0602 23 12 20	17.2	21	2	0.001
G1/2	0602 23 13 20	21.5	25.5	2.5	0.002
G3/4	0602 27 32 20	27	32	2.5	0.001
G1	0602 30 60 20	33.8	39	3	0.001

Maximum allowable working pressure: 20 bar

0139 Bi-Material Captive Sealing Washer

	<p>Zinc-plated steel with NBR seal</p> 	C		G	K	K1	kg
		G1/8	0139 10 00	14	1	1.7	0.001
		G1/4	0139 13 00	17	1	1.7	0.001
		G3/8	0139 17 00	22	1.2	2.1	0.001
		G1/2	0139 21 00	26	1.6	2.5	0.002
		G3/4	0139 27 00	32	1.5	2.5	0.003
		G1	0139 34 00	39.6	1.7	2.6	0.003
Maximum allowable working pressure: 250 bar							

Technical characteristics of captive seals **0602**

Tightening torque





	M5x0.8	G1/8	G1/4	G3/8	G1/2	G3/4	G1
Min. Torque in daN.m	0.06	0.08	0.3	0.5	1	1.2	1.9
Max. Torque daN.m	0.16	0.8	1.2	3	3.5	6	9

Tube Supports

0127



Brass Tube Support for Polymer Tubing

	Brass	ØD1	ØD2		L	kg
		4	2	0127 04 00	11	0.001
			2.7	0127 04 27	11	0.001
		5	3	0127 05 03	11	0.001
			3.3	0127 05 00	11.5	0.009
		6	4	0127 06 00	11.5	0.001
		8	5.5	0127 08 55	14	0.001
			6	0127 08 00	14	0.001
		10	7	0127 10 07	18	0.001
			7.5	0127 10 75	18	0.001
			8	0127 10 00	18	0.002
			8	0127 12 08	18	0.002
		12	9	0127 12 09	18	0.002
			10	0127 12 00	18	0.001
		14	11	0127 14 11	18	0.002
			12	0127 14 00	18	0.002
		15	12	0127 15 12	18	0.002
		16	13	0127 16 13	18	0.003
		18	14	0127 18 14	19.5	0.003
		20	15	0127 20 15	20.5	0.003
		22	16	0127 22 16	21	0.004
		25	19	0127 25 19	25	0.007

This tube support guarantees good gripping, at high temperatures and pressures, by preventing collapsing of the tube.

1827

Stainless Steel Tube Support for Fluoropolymer Tubing

	Stainless steel 316L	ØD1	ØD2		L	kg
		6	4	1827 06 00	11.5	0.001
		8	6	1827 08 00	14	0.001
		10	8	1827 10 00	18	0.001
		12	9	1827 12 09	18	0.001
			10	1827 12 00	18	0.001
		16	14	1827 16 00	18	0.002

This tube support is necessary when using fluoropolymer FEP tubing at all temperatures compatible with the fitting/ tubing assembly.

Notes

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.



Together, we can connect you to the best in technology

Inventor of the push-in fitting with more than 40 years of experience, Parker Legris has the know-how necessary for providing fluid connectors adapted to a wide variety of environments, such as production automation, packaging, transport, food process and the medical industry. Our wide selection of fittings, tubing, ball valves and accessories, along with our capacity to develop specific products, allow our customers to find the very best connector solution. Parker Legris, the right partner to accompany you in product development.

aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



ENGINEERING YOUR SUCCESS.

www.parkerlegris.com

Index

Part Number	Page	0185	8-42	0631..01	7-17	0921	9-11	1802	5-36	3102	1-17
		0186	8-42	0631..02	7-18	0922	9-11	1804	5-36	3103	1-14
0101	5-10, 11	0187	8-42	0631..03	7-17	0923	9-12	1805	5-34	3104	1-18, 4-39
0101..39	5-10	0189	8-42	0631..04	7-18	0924	9-13	1806	5-36	3106	1-17
0102	5-16	0191	9-16	0631..05	7-18	0927	9-13	1809	5-35	3107	1-19
0103	5-13	0192	9-16	0631..06	7-19	0928	9-13	1810	5-39	3108	1-14
0104	5-17	0195	8-44	0631..07	7-18	0929	9-10	1814	5-34	3109	1-10, 11
0105	5-9	0196	8-44	0631..08	7-19	0931	9-17	1816	5-36	3110	1-37, 60
0106	5-15	0199	5-12	0631..09	7-17	0932	9-13	1817	9-18	3112	1-16
0107	5-17	0200	9-26	0631..23	7-17	1005T	3-29	1820	5-35	3113	1-13
0108	5-13	0201	9-27	0651	7-8	1010P..M	3-33	1821	9-20, 21	3114	1-9
0109	5-12	0202	9-27	0652	7-8	1010T..A	3-31	1822	5-39	3116	1-20
0110	5-22	0205	9-26	0653	7-7	1010T..P	3-31	1823	9-21	3118	1-27
0110..40	5-22	0205	9-26	0654	7-7	1015Y..F	3-27	1824	5-39	3119	1-27
0110..60	5-22	0206	9-29	0655	7-8	1025L	3-12	1827	3-47, 5-39, 9-33	3120	1-24
0110..70	5-22	0209	9-26	0656	7-9	1025P..R	3-15	1843	9-18	3121	1-9
0111	5-21	0210	9-29	0657	7-9	1025P	3-11	1844	9-18	3122	1-25
0112	5-28	0216	9-29	0658	7-9	1025P..V	3-17	1845	9-18	3124	1-27
0113	5-16	0220	5-27, 9-26	0659	7-7	1025T	3-29	1855	9-19	3126	1-25
0114	5-11	0220..39	5-27	0669	4-59	1025U..A	3-23	1861	9-20	3129	1-12
0116	5-16	0222	1-37	0670	4-63	1025U..K	3-25	1862	9-19	3130	1-37, 60, 6-35
0117	9-8	0285	9-30	0671	4-64	1025U..R	3-20	1863	9-20	3131	1-10
0118	5-14	0400	6-10	0672	4-64	1025U	3-19	1864	9-19	3132	1-16
0118..39	5-14	0401	6-10	0673	4-63	1025U..V	3-25	1866	5-39	3133	1-13
0119	5-15	0402	6-10	0674	4-63	1025V	3-43	1867	9-19	3136	1-20
0119..39	5-16	0411	6-10	0675	4-63	1025V..C	3-43	1870	9-19	3139	1-20
0120	5-28	0414	6-10	0676	4-63	1025Y	3-27	1871	9-18	3140	1-18
0121	9-9	0432	6-15	0677	4-64	1030Y..F	3-27	1872	9-20	3142	1-23
0122	5-26	0436	6-15	0681	8-53	1040H	3-45	1873	9-20	3143	1-23
0123	9-10	0437	6-15	0682	4-64	1050P..M	3-33	2003U..R	3-20	3144	1-21
0124	5-21	0438	6-15	0683	4-64	1050T..A	3-31	2003U	3-19	3146	1-20
0124..40	5-21	0439	6-15	0690 01	7-10	1050T..P	3-31	2005P..R	3-15	3148	1-15
0125	5-27	0446	6-11	0690 02	7-10	1050V	3-43	2005P	3-11	3149	1-27
0126	5-27	0448	6-12	0690 03	7-10	1050V..C	3-43	2005U..R	3-20	3150	8-41
0127	3-47, 5-30, 9-33	0449	6-13	0690 04	7-10	1075Y..F	3-27	2005U	3-19	3151	1-25
0128..39	5-29	0452	6-12	0690 05	7-10	1080H	3-45	2010P..R	3-15	3158	1-15
0132	5-25	0461	6-14	0690 06	7-11	1096Y..F	3-27	2010P	3-11	3159	1-35
0133..39	5-25	0462	6-14	0690 06 01	7-11	1098Y..F	3-27	2010U..R	3-20	3160	1-35
0134	5-25	0465	6-29	0690 07	7-11	1099Y..F	3-27	2010U	3-19	3166	1-24
0135	9-22	0469	6-13	0690 08	7-11	1100H	3-45	2203	8-45	3168	1-24
0136	9-10	0471	6-11	0690 09	7-11	1100P..R	3-15	2270	8-45	3169	1-13
0137	9-31	0472	6-11	0690 10	7-12	1100P	3-11	2272 Midi Series	8-43	3175	1-7, 8
0138	1-92, 9-31	0482	6-12	0690 11	7-12	1100P..V	3-17	2272 Maxi Series	8-46	3180	1-22
0139	9-32	0483	6-12	0691	8-53	1100T..P	3-31	2292	8-45	3181	1-8
0142	5-17	0489	6-13	0694	3-39, 46	1100U..A	3-23	2293	8-44	3182	1-22
0143	9-07	0490	6-17	0695	3-39, 46	1100U..K	3-25	2294 Midi Series	8-43	3183	1-23
0144	9-07	0491	6-17	0697	3-47	1100U ..R	3-20	2294 Maxi Series	8-46	3184	1-22
0145	9-07	0491..64	6-17	0900	9-15	1100U	3-19	2295 Midi Series	8-44	3188	1-23
0151..39	5-29	0492	6-17	0901	9-16	1100U..V	3-25	2295 Maxi Series	8-46	3189	1-35
0152	9-7	0492..64	6-17	0902	9-16	1100Y	3-27	2296	8-44	3192	1-12
0155	9-8	0494	6-18	0903	9-14	1420U	3-33	2297 Midi Series	8-43	3193	1-15
0158	9-7	0496	6-18	0904	9-14	1441U..R	3-38	2297 Maxi Series	8-46	3198	1-14
0163	9-9	0497	6-18	0905	9-14	1442U..E	3-41	2299	7-15, 8-45	3199	1-11
0164	8-53, 9-8	0501	6-39	0906	9-15	1442U..R	3-38	2398	8-45	3202	1-43
0165	5-26	0502	6-39	0907	9-15	1445U..E	3-41	2511	8-43	3204	1-43
0166	5-20	0510	6-39	0908	9-14	1445U..R	3-38	3000 70 00	1-37, 75, 87	3206	1-43
0167	8-53, 9-8	0531	6-39	0909	9-14	1447U..E	3-41	3000 71 00	3-46	3218	1-42
0168	9-8	0532	6-39	0910	9-12	1447U..R	3-38	3000 71 11	3-46	3226	1-43
0168..39	5-29	0562	6-40	0911	9-12	1460U	3-37	3018	1-27	3229	1-41
0169	9-9	0563	6-40	0912	9-11	1461U	3-37	3081	2-9	3266	1-43
0171	8-40	0591	6-41	0913	9-11	1462U	3-37	3082	2-8	3281	1-41
0172	8-42, 43	0602	9-32	0914	9-11	1470P	3-35	3086	2-8	3293	1-41
0178	1-37	0605	1-60, 75, 87, 9-32	0915	9-12	1470U	3-37	3088	2-9	3298	1-41
0180	8-41	0622	7-15	0916	9-12	1471P	3-35	3089	2-8	3299	1-41
0181	8-40	0623	7-15	0917	9-13	1471U	3-37	3091	1-35	3300	1-31
0183	8-40	0627	6-40	0919	9-28	1472P	3-35	3100	1-16, 2-8	3301	9-24
0184	8-40	0630	6-40	0920	9-15	1472U	3-37	3101	1-8	3302	9-24

Index

3303	9-25	3893/3993	1-83	7000	4-16, 55, 6-33	7899	4-61	9094A	8-17	9414A	8-15
3304	1-21	3898/3998	1-84	7010	4-10	7910	6-33	9094E	8-14	9414E	8-13
3306	1-21	3899/3999	1-81	7011	4-10	7911	6-33	9094U	8-12	9414U	8-10
3310	1-21, 9-23	4020	6-35	7012	4-10	7913	6-33	9095 Series 20	8-37	9416A	8-16
3311	9-23	4021	6-35	7020	4-17	7914	6-33	9095 Series 21	8-39	9416E	8-13
3312	9-23	4022	6-35	7030	4-18	7921	4-57	9101 Series 23/24/30	8-25	9416U	8-11
3313	9-23	4023	6-35	7031	4-18	7926	4-57	9101 Series 26	8-27	9421A	8-15
3320	1-31	4202...20	6-48	7040	4-14	7930	4-43	9101 Series 14	8-30	9421E	8-13
3321	1-31	4202...30	6-48	7041	4-14	7931	4-43	9101 Series 18	8-32	9421U	8-10
3329	1-31	4212...20	6-48	7045	4-14	7932	4-43	9105 Series 22	8-30	9440A	8-16
3379	1-32	4212...30	6-48	7060	4-11	7960	4-57	9105 Series 13	8-33	9440E	8-14
3381	1-32	4222...20	6-48	7061	4-11	7961	4-57	9105 Series 17	8-34	9440U	8-11
3391	1-35	4222...30	6-49	7062	4-12	7970	4-61	9105 Series 19	8-35	BPLM	5-46
3524	1-29	4298	6-49	7065	4-11	7971	4-61	9114 Series 23/24/30	8-25	BVG4-LOCK	6-24
3527	1-29	4299	6-49	7066	4-11	7984	4-41	9114 Series 26	8-27	BVG4-L	6-21
3528	1-29	4402	6-31	7067	4-12	7985	4-41	9114 Series 14/22	8-30	BVG4P-LOCK	6-24
3529	1-29	4602	6-43	7100	4-20	7992	4-45	9114 Series 18	8-32	BVGT4-C	6-23
3538	1-28	4810	6-29	7101	4-20	7994	4-41	9114 Series 13	8-33	BVGT4-L	6-21
3539	1-28	4812	6-29	7110	4-20	7995	4-41	9114 Series 17	8-34	C3BPL	5-44
3549	1-28	4832	6-29	7111	4-21	7996	4-41	9114 Series 19	8-35	C4BPL	5-44
3600	1-68, 2-13	4890	4-47	7130	4-19	9020	8-51	9123 Series 23/24/30	8-25	C8BPL	5-44
3601	1-67	4891	4-47	7140	4-19	9040	8-51	9123 Series 14/22	8-30	CBPL	5-44
3602	1-72	4892	4-47	7160	4-19	9071U	8-53	9123 Series 18	8-32	CLIP	1-37, 3-47
3603	1-70	4895	4-47	7170	4-21	9075	8-51	9123 Series 13	8-33	COR4BPL	5-45
3604	1-72	4902	6-23	7180	4-20	9080A	8-17	9123 Series 17	8-34	F3BPL	5-43
3606	1-72	4991	6-23	7190	4-21	9080E	8-14	9123 Series 19	8-35	F4BPL	5-43
3608	1-70	4992	6-23	7300	4-53	9080U	8-12	9201 Series 25/27	8-27	F8BPL	5-43
3609	1-69	6000 71 00	3-17, 25, 46	7316	4-55	9084 Series 14/22	8-31	9201 Series 20	8-36	FBPL	5-43
3610	1-75	6101	1-91	7318	4-55	9084 Series 13	8-33	9201 Series 21	8-38	HBPL	5-46
3614	1-68	6104	1-92	7416	4-55	9084 Series 17	8-34	9201 Series X25/27	8-48	JBPL	5-46
3616	1-73	6105	1-91	7471	4-55	9084 Series 19	8-35	9201 Series X20	8-48	R3BPL	5-45
3618	1-71	6106	1-92	7630	4-18	9084A	8-16	9201 Series X21	8-49	RBPL	5-45
3620	1-74	6114	1-91	7631	4-18	9085 Series 23/24/30	8-26	9214 Series 25/27	8-27	S3BPL	5-45
3621	1-68	6179	1-91	7640	4-15	9085 Series 25/26/27	8-28	9214 Series 20	8-36	SBPL	5-45
3622	1-74	6300	1-50, 2-10	7645	4-15	9085 Series 14/22	8-31	9214 Series 21	8-38	TL	2-13
3626	1-75	6302	1-54	7649	4-15	9085 Series 18	8-32	9214 Series X25/27	8-47	TLT	2-13
3629	1-69	6304	1-55	7660	4-13	9085 Series 13	8-33	9214 Series X20	8-48	WBPL	5-46
3631	1-68	6306	1-54	7662	4-14	9085 Series 17	8-34	9214 Series X21	8-49		
3636	1-73	6307	1-56	7665	4-13	9085 Series 19	8-35	9223 Series 25/27	8-27		
3639	1-73	6315	1-48, 49	7668	4-13	9085 Series 20	8-37	9223 Series 21	8-38		
3666	1-74	6316	1-56	7669	4-13	9085 Series 21	8-39	9226 Series 20	8-36		
3667	1-74	6322	1-59	7680	4-20	9086 Series 23/24/30	8-26	9226 Series 21	8-38		
3668	1-74	6325	1-49	7762	4-21	9086 Series 25/26/27	8-28	9285 Series 25/27	8-29		
3669	1-70	6326	1-58, 59	7770	4-16	9086 Series 14/22	8-31	9285 Series 20	8-37		
3675	1-67	6331	1-63	7771	4-16	9086 Series 18	8-32	9285 Series 21	8-39		
3681	1-67	6332	1-63	7772	4-16	9086 Series 13	8-33	9286 Series 25/27	8-29		
3693	1-71	6333	1-63	7776	4-16	9086 Series 17	8-34	9286 Series 20	8-37		
3699	1-69	6336	1-63	7800	4-59	9086 Series 19	8-35	9286 Series 21	8-39		
3800/3900	1-81, 87, 2-13	6340	1-55	7801	4-59	9086 Series 20	8-37	9286 Series X25/27	8-47		
3800...70	1-87	6351	1-59	7802	4-59	9086 Series 21	8-39	9286 Series X20	8-48		
3801/3901	1-79	6352	1-49	7810	4-23	9086 Series X25/27	8-47	9286 Series X21	8-49		
3802/3902	1-85	6353	1-49	7812	4-23	9086 Series X20	8-48	9287 Series 25/27	8-28		
3803/3903	1-83	6355	1-53	7818	4-51	9086 Series X21	8-49	9287 Series 20	8-36		
3804/3904	1-85, 86	6366	1-58	7820	4-23	9086A	8-16	9287 Series 21	8-38		
3805/3905	1-79	6368	1-58	7822	4-23	9086E	8-14	9287 Series X25/27	8-47		
3806/3906	1-85	6380	1-57	7828	4-51	9086U	8-11	9287 Series X20	8-48		
3808/3908	1-83, 84	6382	1-57	7860	4-49	9087 Series 23/24/30	8-26	9287 Series X21	8-49		
3809/3909	1-81	6383	1-57	7861	4-49	9087 Series 25/26/27	8-28	9293 Series 23/24	8-26		
3816/3916	1-86	6388	1-57, 58	7870	4-49	9087 Series 18	8-32	9293 Series 25/27	8-29		
3821	1-80	6401	6-11	7871	4-49	9087 Series 20	8-36	9401A	8-15		
3821/3921	1-80	6402	6-11	7880	4-37	9087 Series 21	8-38	9401E	8-13		
3826	1-87	6503	1-53	7881	4-37	9087 Series X25/27	8-47	9401U	8-10		
3831/3931	1-80	6505	1-48	7883	4-37	9087 Series X20	8-48	9405A	8-15		
3866/3966	1-87	6508	1-52, 53	7885	4-37	9087 Series X21	8-49	9405U	8-10		
3879/3979	1-82	6509	1-51, 52	7886	4-37	9087A	8-16	9410A	8-15		
3889	1-82	6521	1-50	7892	4-39	9087E	8-14	9410E	8-13		
3889/3989	1-82	6579	1-51	7894	4-39	9087U	8-11	9410U	8-10		

Parker Safety Guide

Selection and Use of Fittings, Function Fittings, Tubing and Related Products

WARNING: Failure or improper selection or improper use of fittings, function fittings, tubing or related products ("Products") can cause death, personal injury and property damage.

Possible consequences of failure or improper selection or improper use of these Products include but are not limited to:

- Fittings thrown off at high speed.
- High velocity fluid discharge.
- Explosion or burning of the conveyed fluid.
- Electrocution from high voltage electric power lines.
- Contact with suddenly moving or falling objects that are controlled by the conveyed fluid.
- Injections by high pressure fluid discharge.
- Dangerously whipping tubing.
- Contact with conveyed fluids that may be hot, cold, toxic or otherwise injurious.
- Sparking or explosion caused by static electricity build-up or other sources of electricity.
- Sparking or explosion while spraying paint or flammable liquids.
- Injuries resulting from inhalation, ingestion or exposure to fluids.
- Dynamic applications with strong oscillation

Parker Legris has a continuous product development policy and therefore reserves the right to modify products shown in this catalogue. Please treat all dimensions therefore as indicative.

Photography Credits:

Jochen Detscher

Introduction (pages 1, 2, 4, 5, 6, 7, 8, 17), chapter headings and pages 1-33, 2-11, 3-13, 3-21, 6-19

All other photography is the property of Parker Legris.

Graphic Design:

Sylvain Fromentin

Printing:

Zalsman BV

Parker's Motion & Control Technologies

At Parker, we're guided by a relentless drive to help our customers become more productive and achieve higher levels of profitability by engineering the best systems for their requirements. It means looking at customer applications from many angles to find new ways to create value. Whatever the motion and control technology need, Parker has the experience, breadth of product and global reach to consistently deliver. No company knows more about motion and control technology than Parker. For further information, call 00800 27 27 5374.



AEROSPACE

Key Markets

- Aircraft engines
- Business & general aviation
- Commercial transports
- Land-based weapons systems
- Military aircraft
- Missiles & launch vehicles
- Regional transports
- Unmanned aerial vehicles

Key Products

- Flight control systems & components
- Fluid conveyance systems
- Fluid metering delivery & atomization devices
- Fuel systems & components
- Hydraulic systems & components
- Inert nitrogen generating systems
- Pneumatic systems & components
- Wheels & brakes



CLIMATE CONTROL

Key Markets

- Agriculture
- Air conditioning
- Food, beverage & dairy
- Life sciences & medical
- Precision cooling
- Processing
- Transportation

Key Products

- CO₂ controls
- Electronic controllers
- Filter driers
- Hand shut-off valves
- Hose & fittings
- Pressure regulating valves
- Refrigerant distributors
- Safety relief valves
- Solenoid valves
- Thermostatic expansion valves



ELECTROMECHANICAL

Key Markets

- Aerospace
- Factory automation
- Food & beverage
- Life science & medical
- Machine tools
- Packaging machinery
- Paper machinery
- Plastics machinery & converting
- Primary metals
- Semiconductor & electronics
- Textile
- Wire & cable

Key Products

- AC/DC drives & systems
- Electric actuators
- Controllers
- Gantry robots
- Gearheads
- Human machine interfaces
- Industrial PCs
- Inverters
- Linear motors, slides and stages
- Precision stages
- Stepper motors
- Servo motors, drives & controls
- Structural extrusions



FILTRATION

Key Markets

- Food & beverage
- Industrial machinery
- Life sciences
- Marine
- Mobile equipment
- Oil & gas
- Power generation
- Process
- Transportation

Key Products

- Analytical gas generators
- Compressed air & gas filters
- Condition monitoring
- Engine air, fuel & oil filtration & systems
- Hydraulic, lubrication & coolant filters
- Process, chemical, water & microfiltration filters
- Nitrogen, hydrogen & zero air generators



FLUID & GAS HANDLING

Key Markets

- Aerospace
- Agriculture
- Bulk chemical handling
- Construction machinery
- Food & beverage
- Fuel & gas delivery
- Industrial machinery
- Mobile
- Oil & gas
- Transportation
- Welding

Key Products

- Brass fittings & valves
- Diagnostic equipment
- Fluid conveyance systems
- Industrial hose
- PTFE & PFA hose, tubing & plastic fittings
- Rubber & thermoplastic hose & couplings
- Tube fittings & adapters
- Quick disconnects



HYDRAULICS

Key Markets

- Aerospace
- Aerial lift
- Agriculture
- Construction machinery
- Forestry
- Industrial machinery
- Mining
- Oil & gas
- Power generation & energy
- Truck hydraulics

Key Products

- Diagnostic equipment
- Hydraulic cylinders & accumulators
- Hydraulic motors & pumps
- Hydraulic systems
- Hydraulic valves & controls
- Power take-offs
- Rubber & thermoplastic hose & couplings
- Tube fittings & adapters
- Quick disconnects



PNEUMATICS

Key Markets

- Aerospace
- Conveyor & material handling
- Factory automation
- Food & beverage
- Life science & medical
- Machine tools
- Packaging machinery
- Transportation & automotive

Key Products

- Air preparation
- Compact cylinders
- Field bus valve systems
- Grippers
- Guided cylinders
- Manifolds
- Miniature fluidics
- Pneumatic accessories
- Pneumatic actuators & grippers
- Pneumatic valves and controls
- Rodless cylinders
- Rotary actuators
- Tie rod cylinders
- Vacuum generators, cups & sensors



PROCESS CONTROL

Key Markets

- Chemical & refining
- Food, beverage & dairy
- Medical & dental
- Microelectronics
- Oil & gas
- Power generation

Key Products

- Analytical sample conditioning products & systems
- Fluoropolymer chemical delivery fittings, valves & pumps
- High purity gas delivery fittings, valves & regulators
- Instrumentation fittings, valves & regulators
- Medium pressure fittings & valves
- Process control manifolds



SEALING & SHIELDING

Key Markets

- Aerospace
- Chemical processing
- Consumer
- Energy, oil & gas
- Fluid power
- General industrial
- Information technology
- Life sciences
- Military
- Semiconductor
- Telecommunications
- Transportation

Key Products

- Dynamic seals
- Elastomeric o-rings
- EMI shielding
- Extruded & precision-cut, fabricated elastomeric seals
- Homogeneous & inserted elastomeric shapes
- High temperature metal seals
- Metal & plastic retained composite seals
- Thermal management



ENGINEERING YOUR SUCCESS.